



PROJECT REPORT · DATA STRUCTURES AND ALGORITHMS LABORATORY

CholoKUET

A KUET campus navigator built on stacks, queues, trees and graphs

Department: Computer Science and Engineering

Institution: Khulna University of Engineering & Technology (KUET)

Course: Data Structures and Algorithms Laboratory

Submitted to:

Subah Nawar, Lecturer, Department of CSE, KUET

Lamisa Bintee Mizan Deya, Lecturer, Department of CSE, KUET

Course teachers, Data Structures and Algorithms Laboratory

Date of submission: 5 October 2025

Source code: github.com/ettisafxrup/CholoKUET

SUBMITTED BY



Ettisaf Rup

Undergraduate, CSE, KUET
Roll: 2407109



Afia Anjum Broti

Undergraduate, CSE, KUET
Roll: 2407096

Contents

1. Introduction	3
1.1 The problem	3
1.2 Motivation.....	3
1.3 Objectives.....	3
1.4 Scope.....	3
2. How the Marking Scheme Is Covered	4
3. Where We Used What	6
3.1 Tools and technologies	6
3.2 Every source file and what it holds	6
4. How the Application Works	8
4.1 Starting up.....	8
4.2 Logging in	8
4.3 The main menu	8
4.4 "Take me somewhere", step by step	9
4.5 The other features	10
4.6 Saving and closing.....	10
5. System Design	11
5.1 Architecture	11
5.2 Data files	11
5.3 Where the map came from.....	11
6. Data Structures	13
6.1 Array: the place list	13
6.2 Linked list: searches, favorites and routes.....	13
6.3 Stack (hand-written)	13
6.4 Queue (hand-written, circular)	13
6.5 Tree: browsing by category.....	14
6.6 Graph: walkways.....	14
7. Algorithms.....	15
7.1 Breadth-first search	15
7.2 Rebuilding the route	15
7.3 From a route to directions	15
7.4 Depth-first search	15
7.5 Linear and binary search	16
7.6 Bubble sort and selection sort	16
7.7 Distance and direction	16
8. Complexity Analysis	17

9. Testing.....	18
Problems we found and fixed	18
10. A Walk Through the App	19
10.1 Starting up and signing in.....	19
10.2 Take me somewhere.....	20
10.3 What's near me and the place page	21
10.4 Explore the campus.....	21
10.5 Search and sort	22
10.6 Location, history and favorites	22
11. Limitations.....	24
12. How We Can Improve It	25
12.1 Better routes	25
12.2 Better data	25
12.3 Better experience.....	25
12.4 Better engineering	25
References	26
Appendix A. Data Structure Walkthroughs.....	27
A.1 Array	27
A.2 Linked list.....	27
A.3 Stack (hand-written, dsa/stack).....	27
A.4 Queue (hand-written circular queue, dsa/queue)	28
A.5 Tree	28
A.6 BFS from the main gate to the Central Library	29
A.7 Linear and binary search.....	31
A.8 Bubble sort and selection sort, pass by pass	31
Appendix B. Building and Running.....	33

1. Introduction

1.1 The problem

Every year a new batch arrives at KUET and spends its first few weeks getting lost. The campus covers about 117 acres and has more than forty buildings, many known only by short forms such as "ACA building", "ME building" or "Kodom Tola". Nothing on the ground tells you that CSE, ECE and IEM share one building, or that the quickest walk from the main gate to the library goes past the halls. Visitors have it harder still, and even students who have been here for years often can't say how far the medical centre is from Lalan Shah Hall.

We wanted to find out how far a small program could get with those everyday questions, using only the data structures from this course.

1.2 Motivation

Most lab work practises each data structure alone: push three numbers, pop two, print the stack. That works, but it never shows *why* a stack exists. Campus navigation turned out to need almost everything in the syllabus. Walkways between buildings form a **graph**. Finding a route is **BFS**. The Back button is a **stack**. Building categories form a **tree**. Finding a place by name is **searching**, and listing places by distance is **sorting**. Here, every structure has a job to do.

1.3 Objectives

- Build a working navigator for the KUET campus that runs offline on any Windows PC.
- Write the **stack** and the **queue** ourselves and use them where they matter: BFS, DFS, navigation history and route reversal.
- Use real campus coordinates that we can defend, not invented positions.
- Turn a route into directions a person can follow: which roads to take, where to turn, what you pass on the way, and how long it takes.
- Let the program show its own working (the BFS queue, the DFS stack), so each structure can be seen during the viva.

1.4 Scope

CholoKUET covers 44 places on the main campus (departments, halls, the library, the auditorium, the medical centre, landmarks such as Durbar Bangla and the Central Shaheed Minar) connected by 56 walkways on 15 named roads. It works at the level of buildings, not rooms, and it does not read live GPS: the user types a place or a pair of coordinates. The name CholoKUET comes from "Cholo Explore Kore Ashi" ("come on, let's go explore"), because the project started with a simple question: could we build a map of our own campus ourselves?

2. How the Marking Scheme Is Covered

This chapter maps each part of the tentative marks distribution to the feature and source file that covers it, so any part can be found quickly during the evaluation.

The lab required us to write the stack and queue by hand; the other containers could come from the STL. Every algorithm that runs on them (BFS, DFS, linear and binary search, bubble and selection sort) is our own code. Running `make check-manual` confirms that `std::stack`, `std::queue` and `std::sort` appear nowhere in the program.

Marking area	Marks	Where it is covered in the app	Where it is in the code
Array	5 (with LL, Stack, Queue)	The list of all 44 places, used by every search, sort and "nearest place" lookup	<code>Campus::locations</code> (<code>std::vector<Location></code>) in <code>include/Campus.h</code> , <code>src/Campus.cpp</code>
Linked list		Recent searches (newest first, last 10), favorites, and every BFS route	<code>std::list<int></code> in <code>include/Navigator.h</code> ; <code>Graph::findRoute()</code> returns <code>std::list<int></code>
Stack (hand-written)		DFS, the Back button in Trip history, turning the BFS route the right way round, removing a deleted place from history	<code>dsa/stack/Stack.h</code> , <code>dsa/stack/Stack.cpp</code> ; used in <code>src/Graph.cpp</code> , <code>src/Places.cpp</code> , <code>src/NavigatorAdmin.cpp</code>
Queue (hand-written, circular)		BFS for every route in "Take me somewhere" and "Take me here"	<code>dsa/queue/Queue.h</code> , <code>dsa/queue/Queue.cpp</code> ; used in <code>Graph::findRoute()</code>
Tree	5	Browse by category (menu 5): KUET → category → place; rebuilt after every admin change	<code>include/CampusTree.h</code> , <code>src/CampusTree.cpp</code> : <code>build</code> , <code>addChild</code> , <code>find</code> , <code>remove</code> , <code>print</code> , <code>countNodes</code> , <code>height</code>
BFS	3 (with DFS, Searching)	Take me somewhere (menu 1), "Take me here" on a place page, and the step-by-step "Show how BFS found this route"	<code>Graph::findRoute()</code> and <code>Graph::rebuildRoute()</code> in <code>src/Graph.cpp</code>
DFS		Explore the campus (menu 3), the connectivity check, the warning after an admin deletes a place or walkway	<code>Graph::depthFirstOrder()</code> , <code>Graph::isConnected()</code> in <code>src/Graph.cpp</code>
Searching		Search (menu 4), and every "which place?" prompt; binary search for exact names	<code>src/Search.cpp</code> : <code>linearSearchByName</code> , <code>linearSearchByCategory</code> , <code>linearSearchById</code> , <code>binarySearchByName</code>
Sorting	2	Sort places (menu 6); What's near me (menu 2); sorting a copy before binary search	<code>src/Sort.cpp</code> : <code>bubbleSortByName</code> , <code>selectionSortByName</code> , <code>selectionSortByCategory</code> , <code>bubbleSortByDistance</code>
Presentation	5	Slide deck with a recorded walkthrough of the app, a live demo plan, logo and generated campus map	<code>presentation/CholoKUET Presentation.pptx</code> , <code>assets/</code>

Marking area	Marks	Where it is covered in the app	Where it is in the code
Q&A and Report	5	This report, 55 viva questions with answers, the DSA mapping, 907 unit checks	<code>presentation/, docs/viva-questions.md, docs/dsa-mapping.md, tests/</code>

3. Where We Used What

3.1 Tools and technologies

What	Used for
C++17	The whole application
Standard library	<code>vector</code> (array), <code>list</code> (linked list), <code>map</code> and <code>set</code> (graph storage, visited sets), <code>deque</code> (last log lines), <code>string</code> , <code>function</code>
<code>termcolor</code> (third_party, BSD licence)	Coloured terminal output in KUET gold, wrapped in our own <code>Style</code> module
<code>g++ 16 (MSYS2 UCRT64)</code> , <code>GNU Make</code> , <code>CMake</code>	Building the program and the tests; static linking so the .exe runs on any PC
<code>windres</code>	Putting the CholoKUET logo and version details into <code>CholoKUET.exe</code>
<code>OpenStreetMap</code>	Surveyed coordinates for 38 of the 44 places and the campus outline
<code>KUET master plan</code>	The road layout, and the position of six buildings OSM does not have
<code>Node.js</code>	<code>tools/render-map.js</code> , which draws the campus map from our data files
<code>Git</code> and <code>GitHub</code>	Version control; the code is at github.com/ettisafxrup/CholoKUET

3.2 Every source file and what it holds

File	What it does	Structures / algorithms inside
<code>main.cpp</code>	Starts the app; can also build the whole program on its own	-
<code>dsa/stack/Stack.cpp</code>	Our array stack	Stack
<code>dsa/queue/Queue.cpp</code>	Our circular queue	Queue
<code>src/Graph.cpp</code>	Walkway graph, BFS, route rebuild, DFS, connectivity	Graph, BFS + Queue, DFS + Stack, linked list
<code>src/Trip.cpp</code>	Turns a BFS route into roads, turns, stops and time	Linear pass over the route list
<code>src/CampusTree.cpp</code>	The category tree	General tree, preorder traversal
<code>src/Campus.cpp</code>	Loads, checks and saves every data file	Array of places, graph
<code>src/Search.cpp</code>	Linear and binary search	Searching
<code>src/Sort.cpp</code>	Bubble and selection sort with counts	Sorting
<code>src/Distance.cpp</code>	Haversine distance and compass bearing	-
<code>src/Navigator.cpp</code>	Startup, login, main menu, "which place?" prompts	Linear search, history Stack, recent-search list
<code>src/Trips.cpp</code>	Take me somewhere, What's near me, Explore	BFS, DFS, bubble sort

File	What it does	Structures / algorithms inside
src/Places.cpp	Search, place pages, categories, sorting, history, favorites	Search, sort, tree, stack, lists
src/NavigatorAdmin.cpp	Adding, editing and deleting places and walkways	Array, graph, tree rebuild, stack rebuild
src/Authentication.cpp, Logger.cpp, Style.cpp, Utils.cpp	Accounts, activity log, colours, safe input	-
tests/*.cpp	Eight unit-test programs	Checks for every structure

4. How the Application Works

This chapter follows the program from start-up to shutdown, then walks through the main feature step by step.

4.1 Starting up

1. `main()` creates the `Navigator` object and calls `initialize()`.
2. The program looks for `data/locations.txt` in the current folder and up to three folders above it, so it works whether it is started from the project folder, from `bin/`, or from a CMake build folder.
3. It turns on UTF-8 output and colours, creates `data/` and `logs/` if they are missing, and opens the activity log.
4. `Campus` loads the **categories**, then the **places** into the array (each becomes a graph vertex), then the **walkways** into the graph. Broken or repeated lines are skipped and reported, and never stop the program.
5. The **category tree** is built from the loaded places.
6. `Authentication` loads the accounts. If there are none, it creates `admin / admin123` and `student1 / student123`.
7. A quick **DFS** checks that every place can be reached, and warns if not.

4.2 Logging in

The login screen offers *Log in*, *Create an account* and *Exit*. Passwords are hidden with `*` while typing. Usernames are checked (3–30 letters, digits, `_` or `.`), and passwords are stored as a 64-bit FNV-1a hash of "username:password". After a successful login the session starts fresh: an empty **history stack**, an empty **recent-search list**, no current location, and the user's saved **favorites** list loaded from `data/favorites.txt`.

4.3 The main menu

#	Menu item	What happens	Structure used
1	Take me somewhere	Asks where you are and where you want to go, then gives directions	Graph, BFS + Queue, Stack, linked list
2	What's near me	The 10 closest places with distance, direction and walking time	Array, Haversine, bubble sort
3	Explore the campus	DFS order from a place, connectivity check, all roads	DFS + Stack
4	Search	One box for names, categories and numbers	Linear + binary search, linked list
5	Browse by category	KUET → category → place	Tree
6	Sort places	A–Z, Z–A, category, distance, with counts	Bubble + selection sort

#	Menu item	What happens	Structure used
7	Where am I?	Set your location by place or coordinates; copy it	Linear scan, Haversine
8	Trip history	Every place you have been; Back returns to the last	Stack
9	Recent searches	The last 10 places you searched for	Linked list
10	Favorites	Starred places, saved per user	Linked list
11	Help	How to use the app and how it works	-
12–15	Admin only	Manage places, manage walkways, users, activity log	Array, graph, tree

Everywhere in the app, pressing Enter on its own goes back, and a place can be typed as part of its name (**lib**), its number from the campus map (**3**), or coordinates (**22.8992**, **89.5016**).

4.4 "Take me somewhere", step by step

How a "Take me somewhere" request flows through CholoKUET




Figure 1. How a trip request travels through the code.

- 1. Where are you?** The answer goes to `resolvePlace()`. Coordinates are matched to the closest place by computing the Haversine distance to all 44 places. A number is looked up by ID. Text is matched by **linear search** on names, then on categories. If several places match, the user picks one from a numbered list. Pressing Enter uses the current location.
- 2. Where do you want to go?** The same process gives the destination.
- 3. BFS (`Graph::findRoute`)** starts at the start place, puts it in our **queue** and marks it visited. It repeatedly dequeues a place and enqueues every unvisited neighbour, recording `parent[neighbour] = current`. It stops when the destination is dequeued.
- 4. Rebuilding the route (`rebuildRoute`):** following `parent` from the destination gives the route backwards. Each place is pushed on our **stack**, and popping them all gives the route in forward order, stored in a **linked list**.
- 5. Planning the trip (`planTrip`):** walking along the route once, walkways on the same road are merged into one step, and the places in between become "places you pass". Where the road

changes, the compass bearings of the two walkways decide *turn left*, *turn right* or *continue straight*. Each step gets a direction, a length and a walking time at 75 m a minute.

6. **Showing it** (`printTrip`): a summary line, directions by road, a table of every stop with leg and running distances, and the roads in order.
7. **Afterwards** the user can choose *I'm going*, which pushes the start and destination onto the **history stack** so *Back* can undo it, or *Show how BFS found this route*, which runs BFS again and prints the queue and `parent` at every step.

4.5 The other features

- **What's near me** works out the distance from a point to every place in the array, sorts them with **bubble sort**, and shows the nearest ten with a compass direction and walking time.
- **Explore the campus** runs **DFS** from a chosen place (optionally showing the stack at every step), checks whether every place can be reached, and lists every road with its walkways.
- **Search** runs **binary search** on a sorted copy to find an exact name first, then **linear search** for partial name and category matches. Opening a result adds it to the **recent-search list**.
- **Browse by category** walks the **tree**: pick a category (a child of the root), then a place (a leaf).
- **Trip history** shows the **stack** from top to bottom. *Back* pops the top and moves you to the new top.
- **Admin edits** keep every structure consistent. Adding a place adds it to the array and the graph. Deleting one removes it from the array, the graph (with its walkways), the favorites and recent lists, and the history stack (by popping everything onto a second stack and pushing the rest back). Every change rebuilds the tree and is saved to the data files straight away.


4.6 Saving and closing

Every change is written to disk as it happens: places to `locations.txt`, walkways to `paths.txt`, accounts to `users.txt`, favorites to `favorites.txt`. Every login, search, route, DFS and admin action is logged to `logs/application.log` with a timestamp, and passwords are never logged. On *Log out* the session state is cleared; on *Exit* the program says goodbye and closes.

5. System Design

5.1 Architecture

We split the program into three layers. The top layer is the menus (**Navigator**, split across four files), which only talk to the user. The middle layer is the campus model (**Campus**), which owns the places, the categories and the graph, and is the only code that reads or writes the data files. The bottom layer holds the data structures and algorithms, which know nothing about menus or files. Because of this split, the stack can be opened and explained on its own, and the same core could later sit under a graphical app.



5.2 Data files

File	One line looks like	Notes
<code>data/locations.txt</code>	<code>3 Central Library Facility 22.899247 89.501796 Central library of KUET</code>	ID, name, category, latitude, longitude, description
<code>data/paths.txt</code>	<code>4 3 Academic Walk</code>	From, to, meters (empty = straight line), road name
<code>data/categories.txt</code>	<code>Academic</code>	Order of categories in the tree
<code>data/users.txt</code>	<code>student1 445aff2fe080879e student</code>	Username, password hash, role
<code>data/favorites.txt</code>	<code>student1 3</code>	Username and place ID

5.3 Where the map came from

We started from the *Proposed Revised Master Plan of KUET Khulna Campus*, but a drawing has no coordinates. OpenStreetMap had the campus outline and about forty named buildings, all surveyed on the ground, so we used those coordinates for 38 of our places. For the six buildings OSM does not have yet (Fazlul Haque Hall, the Central Mosque, the Canteen, the Garage, the Dormitory and Kodom Tola), we measured 18 buildings that appear in both the plan and OSM and fitted a least-squares affine transform from plan pixels to latitude and longitude. The fit differs from OSM by **27 m on average**, about the width of one building, which also shows the plan's layout is accurate. The 56 walkways follow the roads on the plan. KUET Road and Khanjahan Ali Hall Road are OSM names; the other road names are our own descriptive labels.

KUET Campus Map

CholoKUET - Cholo Explore Kore Ashi - 44 places, 56 walkable paths




Figure 2. The campus as CholoKUET sees it, drawn from its own data files. The numbers are place IDs. Map data © OpenStreetMap contributors.

6. Data Structures

6.1 Array: the place list

All 44 places live in a `std::vector<Location>`. Reading by index is $O(1)$, which suits a list that is read constantly and changed only by an admin. We never assume a place's ID equals its index: after a delete everything shifts left, so every lookup goes by ID.

6.2 Linked list: searches, favorites and routes

Recent searches are a `std::list<int>`. A new search goes to the front; if the place is already there it is moved rather than duplicated; after ten, the oldest drops off the back. All of these are cheap on a linked list. The route that BFS returns is also a list, because its length is not known until the search ends and we only ever walk it front to back.

6.3 Stack (hand-written)

An array of 200 integers and one index, `top`. An empty stack has `top = -1`. `push` moves `top` up and writes; `pop` reads and moves it down. Both refuse instead of writing outside the array (overflow and underflow).

```
bool Stack::push(int value)
{
    if (isFull())
        return false;    // overflow

    data[++top] = value;
    return true;
}
```

Used for **DFS**, the **Back** button, **reversing the BFS route**, and removing a deleted place from the middle of the history.

6.4 Queue (hand-written, circular)

A plain array queue wastes every slot it has already dequeued. Ours wraps round with `% CAPACITY`, so the rear moves back to slot 0 once the front has moved on. A separate `count` tells a full queue from an empty one.

```
bool Queue::enqueue(int value)
{
    if (isFull())
        return false;    // overflow

    rear = (rear + 1) % CAPACITY;
    data[rear] = value;
    count++;
    return true;
}
```

Used for **BFS** in every route.

6.5 Tree: browsing by category

KUET is the root, each category is a child, and each place is a leaf. Each node keeps its children in a vector, so a category can hold any number of places (Academic has eleven, Medical has one); a binary tree would force artificial splits. Children are stored inside their parent, so removing a node removes its whole subtree. The campus tree has 55 nodes and a height of 3.

```
struct TreeNode
{
    std::string name;
    int locationId = -1;          // -1 for the root and category nodes
    std::vector<TreeNode> children;
};
```

6.6 Graph: walkways

Every place is a vertex and every walkway an undirected edge with a length in meters and a road name. We use an adjacency list, because the campus is sparse: 44 vertices and only 56 edges. A matrix would be mostly empty, and scanning a row would cost $O(V)$ even for a place with two neighbours.

```
struct Edge
{
    int to;
    int meters;
    std::string road;
};

std::map<int, std::vector<Edge>> adjacency;    // place ID -> its walkways
```

7. Algorithms

7.1 Breadth-first search

BFS explores outwards one ring of neighbours at a time using our queue. A neighbour is marked visited when it is *enqueued*, not when it is dequeued, which stops the same place from being queued twice. In an unweighted graph BFS gives the route with the **fewest stops**. Our walkways have different lengths, so that is not always the shortest walk in meters, and the app shows both the walking length and the straight-line distance.

```
while (!queue.isEmpty())
{
    int current;
    queue.dequeue(current);
    if (current == goal)
        break;

    for (const Edge& edge : neighbors(current))
    {
        if (visited.count(edge.to))
            continue;
        visited.insert(edge.to);
        parent[edge.to] = current;
        queue.enqueue(edge.to);
    }
}
```

7.2 Rebuilding the route

The **parent** map describes the route backwards. We follow it from the destination and push each place on our stack; popping gives the forward order. For the gate-to-library route, the library is pushed first and the gate last, so the gate ends up on top (see Appendix A.6).

7.3 From a route to directions

planTrip() walks the route once, so it costs $O(k)$ for a route of k stops:

- Consecutive walkways on the same road merge into one step; the places in between become "places you pass".
- Where the road changes, the bearing of the new walkway is compared with the old one: under 35° is *continue straight*, over 150° is *turn around*, anything else is *turn left* or *turn right*.
- Each step gets an overall compass direction, a length, and a walking time at 75 m a minute (about 4.5 km/h).

7.4 Depth-first search

Our DFS is iterative. The top of our stack is the place being explored, and for each place we remember how far we have scanned through its neighbours, so after backtracking we carry on from where we stopped. Each place is pushed only once, so the stack never holds more than the number of places. The fixed 200-slot stack therefore cannot overflow, even on a fully connected graph, and one of our tests checks exactly that.

7.5 Linear and binary search

Linear search lowercases both strings and checks whether one contains the other, so **lib** finds *Central Library*. Binary search only works on sorted data, so it runs on a copy sorted by name and answers "is there an exact match?". On our 44 places it finds the library in **6 comparisons**, where a linear scan checks all **44**.

```
while (low <= high)
{
    int mid = low + (high - low) / 2;
    int result = compareIgnoreCase(name, sorted[mid].name);
    comparisons++;
    if (result == 0) return mid;
    if (result < 0) high = mid - 1;
    else          low = mid + 1;
}
```

7.6 Bubble sort and selection sort

Bubble sort swaps neighbours that are out of order and stops early when a pass makes no swaps. Selection sort finds the smallest remaining item on each pass and swaps it into place. Sorting all 44 places by name, bubble sort made **880 comparisons and 367 swaps**; selection sort made **946 comparisons** (exactly $44 \times 43 / 2$) but only **39 swaps**. Bubble sort is stable and selection sort is not. "What's near me" sorts 44 distances with bubble sort (931 comparisons, 474 swaps from the main gate).

7.7 Distance and direction

Distances use the Haversine formula with an Earth radius of 6,371 km, accurate to well under a meter over campus distances. Directions use the initial compass bearing between two points (0° north, 90° east), named as one of eight compass points.

```
a = sin2(Δφ/2) + cos φ1 · cos φ2 · sin2(Δλ/2)
d = 2R · atan2(√a, √(1 - a))

bearing = atan2(sin Δλ · cos φ2, cos φ1 · sin φ2 - sin φ1 · cos φ2 · cos Δλ)
```

8. Complexity Analysis

Operation	Time	Note
Array access by index	$O(1)$	
Find a place by ID	$O(n)$	Linear scan
Delete a place	$O(n)$	Later items shift left
Linked list: insert at front, remove from back	$O(1)$	Recent searches
Stack push / pop / peek	$O(1)$	
Queue enqueue / dequeue	$O(1)$	Circular indexes
Tree traversal and search	$O(n)$	n = number of nodes
BFS, DFS	$O(V + E)$	Adjacency list; a matrix would make it $O(V^2)$
Turning a route into directions	$O(k)$	k = stops on the route
Linear search	$O(n)$	
Binary search	$O(\log n)$	Sorted data only
Bubble sort	$O(n^2)$	$O(n)$ when already sorted
Selection sort	$O(n^2)$	At most $n - 1$ swaps
What's near me	$O(n^2)$	n distances, then bubble sort

Memory is $O(V + E)$ for the graph and $O(n)$ for everything else. The stack and queue are fixed at 200 integers each, and the program never lets the campus grow past 200 places, so neither can overflow during BFS or DFS.

9. Testing

We wrote eight small test programs, one per module, with a tiny `CHECK` macro of our own. `make test` builds and runs them all, and any failure stops the run.

Suite	What it checks	Checks
Stack	Empty stack, LIFO order, peek, overflow at 200, underflow	213
Queue	Empty queue, FIFO order, overflow, wraparound past the end of the array	419
Graph, BFS, DFS	Reachable, same start and end, unreachable, fewest stops over a longer path, disconnected and connected DFS, deleting a place, a full 200-vertex graph	26
Tree	Building from data, empty categories, case-insensitive find, removing a subtree	15
Search	Found, not found, partial and case-insensitive matches, binary search on sorted data	22
Sort	Empty, one item, already sorted, reverse sorted, duplicates (stability), by category and distance	13
Trip	Legs merge along one road, left and right turns, compass names, walking time, the trip reversed	34
Campus data	The real data files load with no bad lines, every walkway has a road name, all places are connected and on campus	165
Total		907

We also drove the whole program with scripted input as both a student and an admin, through every menu: wrong passwords, letters where numbers were expected, out-of-range choices, mismatched passwords, and adding, editing and deleting places and walkways. The program never crashed, the log recorded every action, and no password showed up in it.

Problems we found and fixed

- **DFS could overflow the stack.** The textbook "pop, then push every unvisited neighbour" version can push the same place many times, which on a dense graph needs more than 200 slots. We switched to the version that pushes each place once. A test on a complete 200-vertex graph guards against the old behaviour.
- **On one PC the program crashed at startup.** It was loading an incompatible `libstdc++` DLL from another program on the PATH. Linking statically fixed it and made the .exe portable.
- **termcolor did not compile with g++ 16,** because it uses `uint8_t` without including `<stdint>`. We include it before the library instead of editing the library.

10. A Walk Through the App

The screens in this chapter come from one real session, captured in the order shown. A new student starts the program, makes an account, logs in and tries each menu before leaving. In the terminal, titles and menu numbers appear in KUET gold and hints in grey.

10.1 Starting up and signing in

`make run` builds the program and opens the welcome screen (Figure 3). A new user chooses *Create an account*. The rules are printed first, and the password shows as stars while it is typed (Figure 4). After logging in, the main menu greets the user by name and groups its eleven options under *Get around*, *Find* and *You* (Figure 5).



Figure 3. Starting the program with `make run` (left) and the welcome screen (right).



Figure 4. Creating an account: the form (left) and the confirmation (right).




Figure 5. Logging in (left) and the main menu (right).

10.2 Take me somewhere

We typed only *Main* and *Caf*, and the app completed them to KUET Main Gate and Cafeteria. **BFS** found a route of 411 m, about 6 minutes, and merged its four walkways into two steps, one for each road (Figure 6). Under the directions the app lists every stop with its leg and running total, and says plainly that BFS gives the fewest stops, which is not always the shortest walk. Choosing *I'm going* sets the Cafeteria as the current location and pushes the trip onto the history **stack** (Figure 7).



Figure 6. Take me somewhere: two partial names (left) become directions by road (right).




Figure 7. Every stop on the route (left), and the confirmation after choosing *I'm going* (right).

A longer trip reads the same way. From the Central Library to the main gate, nine stops are merged into three steps:

```
Central Library → KUET Main Gate
707 m walk · about 10 min · 9 places · 3 roads

DIRECTIONS
• Start at Central Library
1 Head south on Library Lane · 89 m, about 2 min
  | until you reach Fazlul Haque Hall
2 Turn left, heading east on Hall Road · 258 m, about 4 min
  | past Shaheed Smrity Hall, Dr. M. A. Rashid Hall and Cafeteria
  | until you reach Kodom Tola
3 Turn left, heading east on KUET Road · 360 m, about 5 min
  | past KUET Dighi and Khan Jahan Ali Hall
• Arrive at KUET Main Gate

STOPS
# Place Road Leg Total
1 Central Library - 0 m
2 Fazlul Haque Hall Library Lane 89 m 89 m
3 Shaheed Smrity Hall Hall Road 80 m 169 m
4 Dr. M. A. Rashid Hall Hall Road 58 m 227 m
5 Cafeteria Hall Road 69 m 296 m
6 Kodom Tola Hall Road 51 m 347 m
7 KUET Dighi KUET Road 77 m 424 m
8 Khan Jahan Ali Hall KUET Road 101 m 525 m
9 KUET Main Gate KUET Road 182 m 707 m

ROADS Library Lane → Hall Road → KUET Road
```

10.3 What's near me and the place page

What's near me measures the distance from where we stand, the Cafeteria, to all 44 places, sorts them with **bubble sort** and lists the nearest ten with a direction and a walking time. It also reports the work done: 946 comparisons and 473 swaps (Figure 8). Picking a number opens that place's page, with its category, coordinates and walkways. From there *Take me here* runs the same BFS without asking for a start: 90 m to the post office, about 2 minutes (Figure 9).

```
Where are you? (Enter = Cafeteria)
>

1 Cafeteria 0 m you're here
2 Kodom Tola 51 m south-east about 1 min
3 Dr. M. A. Rashid Hall 69 m west about 1 min
4 KUET Post Office 90 m south-east about 2 min
5 Departmental Store 91 m north-west about 2 min
6 KUET Auditorium 93 m north about 2 min
7 Janata Bank, KUET Branch 99 m north about 2 min
8 KUET Dighi 106 m east about 2 min
9 Shaheed Smrity Hall 110 m south-west about 2 min
10 Durbar Bangla 119 m north-west about 2 min

Sorted with bubble sort: 946 comparisons, 473 swaps.
Pick a number to open it, or press Enter to go back.
> |
```

Figure 8. What's near me, from the Cafeteria.

```
Pick a number to open it, or press Enter to go back.
> 4

KUET Post Office
Facility · number 21

Campus post office near Teligati Road

Coordinates 22.897679, 89.503624
From you 90 m straight line
Walkways Kodom Tola 39 m on KUET Road

1 Take me here
2 I'm here
3 Add to favorites
4 Copy coordinates
0 Back
> |

Cafeteria → KUET Post Office
90 m walk · about 2 min · 3 places · 2 roads

● Start at Cafeteria
1 Head south-east on Hall Road · 51 m, about 1 min
until you reach Kodom Tola
2 Continue south-east onto KUET Road · 39 m, about 1 min
until you reach KUET Post Office
● Arrive at KUET Post Office

STOPS
# Place Road Leg Total
1 Cafeteria - 0 m
2 Kodom Tola Hall Road 51 m 51 m
3 KUET Post Office KUET Road 39 m 90 m

ROADS Hall Road → KUET Road
Straight-line distance 90 m. BFS picks the route with the fewest stops, which isn't always the shortest walk.

1 I'm going, set KUET Post Office as my location
2 Show how BFS found this route
0 Back
>
```

Figure 9. The place page for KUET Post Office (left) and the route from Take me here (right).

10.4 Explore the campus

Explore the campus has three options. The first walks the campus depth first from a chosen place and can print our **stack** at every push. The second is the connectivity check: **DFS** from the main gate reached 44 of 44 places (Figure 10). The third prints the graph as the app stores it, each road followed by its walkways and their lengths (Figure 11).

```

Explore the campus
1 Walk everywhere from one place (DFS)
2 Can every place be reached?
3 All roads and walkways
0 Back

> 2

DFS from KUET Main Gate reached 44 of 44 places.
✓ Every place on campus can be reached from every other.

Press Enter to go back...|

```

```

push Teachers and Staff Quarters (visit #42)
stack: [bottom] KUET Post Office | Kodom Tola | KUET Dighi | Khan Jahan Ali Hall | Central Sha
19 Central Mosque
20 Department of IEM
21 Canteen
22 Department of ECE
23 Department of CSE
24 Architecture and URP Building
25 Leather Engineering Building
26 Mechanical Engineering Building
27 Science Building
28 Central Computer Centre
29 EEE Building
30 Civil Engineering Building
31 KUET Lake
32 Rokeya Hall
33 Administrative Building
34 Mechanical Workshop
35 Water Treatment Plant
36 Mechatronics Engineering Building
37 Medical Centre
38 Central Mosque
39 Department of IEM
40 Canteen
41 Department of ECE
42 Department of CSE
43 Architecture and URP Building
44 Leather Engineering Building
45 Mechanical Engineering Building
46 Science Building
47 Central Computer Centre
48 EEE Building
49 Civil Engineering Building
50 KUET Lake
51 Rokeya Hall
52 Administrative Building
53 Mechanical Workshop
54 Water Treatment Plant
55 Mechatronics Engineering Building
56 Medical Centre
57 Garage
58 IT Incubation Centre
59 IT Building
60 Dormitory
61 Teachers and Staff Quarters
62 Residential Area Playground
63 Tennis Court

Reached 44 of 44 places.
Press Enter to go back...|

```

Figure 10. The Explore menu with the connectivity check (left), and the end of a DFS walk with the stack shown (right).

```

Roads and walkways
56 walkways on 15 roads

Academic Walk - 205 m
Central Library + Department of CSE 23 m
Central Library + Durbar Bangla 58 m
Department of CSE + Department of ECE 26 m
Department of ECE + Department of IEM 27 m
KUET Auditorium + Janata Bank, KUET Branch 23 m
Janata Bank, KUET Branch + Departmental Store 11 m
Departmental Store + Durbar Bangla 37 m

Admin Road - 291 m
Administrative Building + Mechanical Workshop 89 m
Administrative Building + Mechanical Engineering Building 67 m
Administrative Building + Tennis Court 37 m
Administrative Building + Rokeya Hall 98 m

Auditorium Road - 166 m
EEE Building + KUET Auditorium 73 m
KUET Auditorium + Cafeteria 93 m

Canteen Lane - 113 m
Department of IEM + Canteen 66 m
Canteen + Fazlul Haque Hall 47 m

```

```

Playground Road - 486 m
Civil Engineering Building + KUET Lake 168 m
KUET Auditorium + Central Playground 141 m
Central Shaheed Minar + Central Playground 93 m
KUET Lake + Central Playground 84 m

Residential Area Road - 278 m
Mechanical Workshop + Dormitory 113 m
Dormitory + Teachers and Staff Quarters 120 m
Teachers and Staff Quarters + Residential Area Playground 45 m

Science Walk - 471 m
Central Library + Science Building 65 m
Department of IEM + Architecture and URP Building 53 m
Architecture and URP Building + Leather Engineering Building 56 m
Science Building + Central Computer Centre 65 m
Science Building + Mechanical Engineering Building 61 m
EEE Building + Central Computer Centre 72 m
Mechanical Engineering Building + Leather Engineering Building 63 m
Central Computer Centre + Durbar Bangla 36 m

Workshop Road - 297 m
Mechanical Engineering Building + Mechanical Workshop 53 m
Leather Engineering Building + Garage 27 m
Mechatronics Engineering Building + Medical Centre 42 m
Mechatronics Engineering Building + Water Treatment Plant 35 m
Mechanical Workshop + Water Treatment Plant 83 m
Medical Centre + Garage 57 m

Press Enter to go back...|

```

Figure 11. Part of the roads and walkways list, shown here in two columns.

10.5 Search and sort

Search is one box for names, categories and numbers. *caf* is not an exact name, so **linear search** checks all 44 places and finds the Cafeteria. *Sort places* offers four orderings and names the algorithm behind each one (Figure 12).

```

Search
Type part of a name ("lib"), a category ("hall"), or a place number.

> caf

Linear search checked 44 places

1 cafeteria Food

Pick a number to open it, or press Enter to go back.
> |

```

```

sort places
1 Name A-Z bubble sort
2 Name Z-A selection sort
3 Category selection sort
4 Distance from me bubble sort
0 Back

> 1

```

Figure 12. Searching for *caf* (left) and the Sort places menu (right).

10.6 Location, history and favorites

Where am I? shows the current place with its coordinates and lets the user set or copy them. *Trip history* is our **stack** on screen: the top is where we are now, and each *Back* pops it until the history is empty (Figures 13 and 14). *Add to favorites* on a place page saves the place for that user, so it is still

listed under *Favorites* the next time they log in. Back on the welcome screen, 0 closes the program (Figure 15).

```

> 7

Where am I?

You're at KUET Post Office
Coordinates 22.897679, 89.503624

1 I'm at a place (pick it)
2 I'm at these coordinates
3 Copy my coordinates
0 Back

```

```

Trip history
Kept on a stack: Back takes you to the last place you were.

> KUET Post office (you're here)
  Cafeteria
  KUET Main Gate

1 Back (pop the top)
2 Clear history
0 Return

```

Figure 13. Where am I? (left) and Trip history, kept on a stack (right).

```

Trip history
Kept on a stack: Back takes you to the last place you were.

> Cafeteria (you're here)
  KUET Main Gate

1 Back (pop the top)
2 Clear history
0 Return

> 1
✓ Back at KUET Main Gate.

Trip history
Kept on a stack: Back takes you to the last place you were.

> KUET Main Gate (you're here)

1 Back (pop the top)
2 Clear history
0 Return

> 1
✓ Left KUET Main Gate. History is empty now.

Trip history
Kept on a stack: Back takes you to the last place you were.

Empty. Places you go with "Take me somewhere" or "I'm here" show up here.
Press Enter to go back...

```

```

KUET Post Office
Facility · number 21

Campus post office near Teligati Road

Coordinates 22.897679, 89.503624
Walkways Kodom Tola 39 m on KUET Road

1 Take me here
2 I'm here
3 Add to favorites
4 Copy coordinates
0 Back

> 3

```

Figure 14. Back pressed twice, until the history is empty (left), and adding a place to favorites (right).

```

> 10

Favorites

1 KUET Post Office Facility
Pick a number to open it, or press Enter to go back.
>

```

```

CholoKUET

Cholo Explore Kore Ashi · KUET campus

1 Log in
2 Create an account
0 Exit

> 0

CholoKUET · Cholo Explore Kore Ashi. See you around campus!

```

Figure 15. The favorites list (left) and leaving the app (right).

11. Limitations

- **Fewest stops, not fewest meters.** BFS ignores walkway length, so the suggested route can be a little longer in meters than the best one.
- **Six positions are estimates.** Fazlul Haque Hall, the Central Mosque, the Canteen, the Garage, the Dormitory and Kodom Tola come from the master plan and are accurate to about 30 m.
- **Most road names are ours.** Only KUET Road and Khanjahan Ali Hall Road are official names from OSM.
- **Buildings only.** There are no floors, rooms or labs yet.
- **Walkways are simplified.** They follow the plan's roads; short cuts and newer paths are missing.
- **No live location.** The user types a place or coordinates instead of reading GPS.
- **Demo-level login.** FNV-1a is fast to brute-force; a real system would use bcrypt or Argon2.
- **Terminal only.** The map picture is generated separately, not shown inside the program.

12. How We Can Improve It

Each of these should be a contained change, because the data structures do not depend on the menus.

12.1 Better routes

- **Dijkstra's algorithm** for the shortest walk in meters. Every walkway already stores its length, so only a priority queue and a new `shortestRoute()` are needed. The app could show both routes side by side.
- **A* search** using the straight-line (Haversine) distance as the heuristic, to find the same shortest route while exploring fewer places.
- **Accessible routes** by giving walkways extra properties (stairs, ramp, unpaved) and skipping the ones a user wants to avoid.
- **Time-aware routes**, for example avoiding gates that close at night.

12.2 Better data

- Survey the six estimated buildings with a phone GPS and **add them to OpenStreetMap**, so the map improves for everyone.
- Add the **real names of internal roads** once confirmed by the university.
- Go one level deeper in the tree: **floors, rooms and labs** inside each building ("CSE Lab 3").
- Store data in **SQLite** instead of text files once many admins edit it at once.

12.3 Better experience

- A **graphical, clickable map** (Qt, SFML or a web front end) on top of the same C++ core.
- A **phone app** that reads live GPS and snaps it to the nearest building.
- A **Bangla interface**, and spoken turn-by-turn directions.
- Search that **tolerates typos** ("library" → Library) using edit distance.

12.4 Better engineering

- Replace the demo password hash with **bcrypt or Argon2**.
- Automatic builds and tests on every push with **GitHub Actions**.
- A packaged **Windows installer** with a Start-menu shortcut.

References

- T. H. Cormen, C. E. Leiserson, R. L. Rivest, C. Stein, *Introduction to Algorithms*, 3rd ed., MIT Press, 2009. Chapters on elementary data structures, BFS, DFS and sorting.
- OpenStreetMap contributors, KUET campus data, © OpenStreetMap contributors, Open Database Licence (ODbL).
- *Proposed Revised Master Plan of KUET Khulna Campus*.
- R. W. Sinnott, "Virtues of the Haversine", *Sky and Telescope*, 68(2), 1984.
- I. Kalnytskyi, *termcolor*: a header-only C++ library for printing coloured messages, BSD 3-Clause licence.

Appendix A. Data Structure Walkthroughs

These walkthroughs were recorded from the program, running our own Stack, Queue, Tree, BFS, search and sort code on the real campus data. They show the state of each structure after every operation.

A.1 Array

```
Insert four places at the end:
```

```
[0] CSE
[1] Library
[2] EEE
[3] Main Gate
Size = 4
```

```
Access array[1] directly: Library
```

```
Remove index 0 (everything after it shifts left):
```

```
[0] Library
[1] EEE
[2] Main Gate
```

```
The real location list is an array too: 44 of 200 slots used.
```

```
Complexity: access  $O(1)$ , append  $O(1)$ , delete/search  $O(n)$ 
```

A.2 Linked list

```
insertBack(CSE), insertBack(Library), insertBack(EEE)
```

```
HEAD → CSE → Library → EEE → NULL
```

```
insertFront(Main Gate)
```

```
HEAD → Main Gate → CSE → Library → EEE → NULL
```

```
remove(Library)
```

```
HEAD → Main Gate → CSE → EEE → NULL
```

```
contains(EEE)? yes
```

```
A real BFS route is stored the same way:
```

```
HEAD → KUET Main Gate → Khan Jahan Ali Hall → Central Shaheed Minar → Central Playground →
KUET Auditorium → Janata Bank, KUET Branch → Departmental Store → Durbar Bangla → Central
Library → NULL
```

```
Complexity: insert at head/tail  $O(1)$ , search/remove  $O(n)$ 
```

A.3 Stack (hand-written, dsa/stack)

```
PUSH 10
```

```
PUSH 20
```

```
PUSH 30
```

```
TOP (top = 2)
```

```
↓
```

```
30
```

```
20
```

```
10
```

```
POP → 30
```

```

TOP (top = 1)
↓
20
10

PEEK → 20 (not removed)

Popping an empty stack: underflow, refused

With campus places, like the navigation history:
TOP (top = 3)
↓
Central Library
Mechanical Engineering Building
Administrative Building
KUET Main Gate

Complexity: push  $O(1)$ , pop  $O(1)$ , peek  $O(1)$ 

```

A.4 Queue (hand-written circular queue, dsa/queue)

```

ENQUEUE 10
ENQUEUE 20
ENQUEUE 30

FRONT → 10 20 30 ← REAR

DEQUEUE → 10

FRONT → 20 30 ← REAR
front index = 1, rear index = 2

Wraparound: fill the queue, dequeue 2, enqueue 2 more.
front index = 2, rear index = 1 → the rear wrapped back to the start of the array
Enqueue on a full queue: overflow, refused

With campus places, the way BFS uses it:
FRONT → KUET Main Gate, Khan Jahan Ali Hall, KUET Auditorium ← REAR

Complexity: enqueue  $O(1)$ , dequeue  $O(1)$ 

```

After filling all 200 slots and dequeuing two, the next values go into slots 0 and 1: the rear wraps round to the start of the array while the front is still at slot 2.

A.5 Tree

A small general tree (any number of children per node):

```

KUET
├── Academic
│   ├── CSE
│   └── EEE
├── Facilities
│   ├── Library
│   └── Auditorium
└── Residential

```

Preorder traversal (node first, then its children):

1. KUET
2. Academic

3. CSE
4. EEE
5. Facilities
6. Library
7. Auditorium
8. Residential

Parent of CSE is Academic; CSE and EEE are siblings.
Nodes: 8, height: 3

The real campus tree has 55 nodes, 10 categories, height 3.

Complexity: traversal $O(n)$, search $O(n)$

A.6 BFS from the main gate to the Central Library

Each step dequeues one place and enqueues its unvisited neighbours, recording **parent**. When the library is dequeued, the parent chain is pushed on our stack and popped off in forward order.

Start at KUET Main Gate
FRONT $\rightarrow$ KUET Main Gate $\leftarrow$ REAR

Step 1: dequeue KUET Main Gate
enqueue Khan Jahan Ali Hall (parent: KUET Main Gate)
FRONT $\rightarrow$ Khan Jahan Ali Hall $\leftarrow$ REAR

Step 2: dequeue Khan Jahan Ali Hall
enqueue Central Shaheed Minar (parent: Khan Jahan Ali Hall)
enqueue KUET Dighi (parent: Khan Jahan Ali Hall)
FRONT $\rightarrow$ Central Shaheed Minar, KUET Dighi $\leftarrow$ REAR

Step 3: dequeue Central Shaheed Minar
enqueue Central Playground (parent: Central Shaheed Minar)
FRONT $\rightarrow$ KUET Dighi, Central Playground $\leftarrow$ REAR

Step 4: dequeue KUET Dighi
enqueue Kodom Tola (parent: KUET Dighi)
FRONT $\rightarrow$ Central Playground, Kodom Tola $\leftarrow$ REAR

Step 5: dequeue Central Playground
enqueue KUET Auditorium (parent: Central Playground)
enqueue KUET Lake (parent: Central Playground)
FRONT $\rightarrow$ Kodom Tola, KUET Auditorium, KUET Lake $\leftarrow$ REAR

Step 6: dequeue Kodom Tola
enqueue KUET Post Office (parent: Kodom Tola)
enqueue Cafeteria (parent: Kodom Tola)
FRONT $\rightarrow$ KUET Auditorium, KUET Lake, KUET Post Office, Cafeteria $\leftarrow$ REAR

Step 7: dequeue KUET Auditorium
enqueue Janata Bank, KUET Branch (parent: KUET Auditorium)
enqueue EEE Building (parent: KUET Auditorium)
FRONT $\rightarrow$ KUET Lake, KUET Post Office, Cafeteria, Janata Bank, KUET Branch, EEE Building $\leftarrow$ REAR

Step 8: dequeue KUET Lake
enqueue Civil Engineering Building (parent: KUET Lake)
FRONT $\rightarrow$ KUET Post Office, Cafeteria, Janata Bank, KUET Branch, EEE Building, Civil Engineering Building $\leftarrow$ REAR

Step 9: dequeue KUET Post Office

FRONT → Cafeteria, Janata Bank, KUET Branch, EEE Building, Civil Engineering Building ← REAR

Step 10: dequeue Cafeteria
 enqueue Dr. M. A. Rashid Hall (parent: Cafeteria)
 FRONT → Janata Bank, KUET Branch, EEE Building, Civil Engineering Building, Dr. M. A. Rashid Hall ← REAR

Step 11: dequeue Janata Bank, KUET Branch
 enqueue Departmental Store (parent: Janata Bank, KUET Branch)
 FRONT → EEE Building, Civil Engineering Building, Dr. M. A. Rashid Hall, Departmental Store ← REAR

Step 12: dequeue EEE Building
 enqueue Central Computer Centre (parent: EEE Building)
 FRONT → Civil Engineering Building, Dr. M. A. Rashid Hall, Departmental Store, Central Computer Centre ← REAR

Step 13: dequeue Civil Engineering Building
 enqueue Rokeya Hall (parent: Civil Engineering Building)
 FRONT → Dr. M. A. Rashid Hall, Departmental Store, Central Computer Centre, Rokeya Hall ← REAR

Step 14: dequeue Dr. M. A. Rashid Hall
 enqueue Shaheed Smrity Hall (parent: Dr. M. A. Rashid Hall)
 FRONT → Departmental Store, Central Computer Centre, Rokeya Hall, Shaheed Smrity Hall ← REAR

Step 15: dequeue Departmental Store
 enqueue Durbar Bangla (parent: Departmental Store)
 FRONT → Central Computer Centre, Rokeya Hall, Shaheed Smrity Hall, Durbar Bangla ← REAR

Step 16: dequeue Central Computer Centre
 enqueue Science Building (parent: Central Computer Centre)
 FRONT → Rokeya Hall, Shaheed Smrity Hall, Durbar Bangla, Science Building ← REAR

Step 17: dequeue Rokeya Hall
 enqueue Administrative Building (parent: Rokeya Hall)
 FRONT → Shaheed Smrity Hall, Durbar Bangla, Science Building, Administrative Building ← REAR

Step 18: dequeue Shaheed Smrity Hall
 enqueue Fazlul Haque Hall (parent: Shaheed Smrity Hall)
 enqueue Amar Ekushey Hall (parent: Shaheed Smrity Hall)
 FRONT → Durbar Bangla, Science Building, Administrative Building, Fazlul Haque Hall, Amar Ekushey Hall ← REAR

Step 19: dequeue Durbar Bangla
 enqueue Central Library (parent: Durbar Bangla)
 FRONT → Science Building, Administrative Building, Fazlul Haque Hall, Amar Ekushey Hall, Central Library ← REAR

Step 20: dequeue Science Building
 enqueue Mechanical Engineering Building (parent: Science Building)
 FRONT → Administrative Building, Fazlul Haque Hall, Amar Ekushey Hall, Central Library, Mechanical Engineering Building ← REAR

Step 21: dequeue Administrative Building
 enqueue Mechanical Workshop (parent: Administrative Building)
 enqueue Tennis Court (parent: Administrative Building)
 FRONT → Fazlul Haque Hall, Amar Ekushey Hall, Central Library, Mechanical Engineering Building, Mechanical Workshop, Tennis Court ← REAR

Step 22: dequeue Fazlul Haque Hall

```

    enqueue Canteen (parent: Fazlul Haque Hall)
    FRONT → Amar Ekushey Hall, Central Library, Mechanical Engineering Building, Mechanical
    Workshop, Tennis Court, Canteen ← REAR

    Step 23: dequeue Amar Ekushey Hall
        enqueue Lalan Shah Hall (parent: Amar Ekushey Hall)
        FRONT → Central Library, Mechanical Engineering Building, Mechanical Workshop, Tennis
        Court, Canteen, Lalan Shah Hall ← REAR

    Step 24: dequeue Central Library

    Walking back through parent[] from Central Library to KUET Main Gate and pushing each
    stop:
    TOP (top = 8)
    ↓
    KUET Main Gate
    Khan Jahan Ali Hall
    Central Shaheed Minar
    Central Playground
    KUET Auditorium
    Janata Bank, KUET Branch
    Departmental Store
    Durbar Bangla
    Central Library
    Popping the stack gives the route from the start.

    Route: KUET Main Gate → Khan Jahan Ali Hall → Central Shaheed Minar → Central Playground →
    KUET Auditorium → Janata Bank, KUET Branch → Departmental Store → Durbar Bangla → Central
    Library

    Complexity:  $O(V + E)$ ; gives the fewest stops in an unweighted graph

```

A.7 Linear and binary search

```

Linear search for "Central Library" in the unsorted list:
Result: Central Library (checked all 44 items)
Linear search for ID 30 stopped after 30 comparisons (found)

Binary search needs sorted data, so sort a copy by name first.

low=0 mid=21 high=43 "IT Building" → go left
low=0 mid=10 high=20 "Civil Engineering Building" → go left
low=0 mid=4 high=9 "Canteen" → go right
low=5 mid=7 high=9 "Central Mosque" → go left
low=5 mid=5 high=6 "Central Computer Centre" → go right
low=6 mid=6 high=6 "Central Library" → found

Result: Central Library (6 comparisons)

Complexity: linear  $O(n)$ , binary  $O(\log n)$  but only on sorted data

```

A.8 Bubble sort and selection sort, pass by pass

```

Before: KUET Main Gate; Department of ECE; EEE Building; Mechatronics Engineering
Building; Central Computer Centre; KUET Post Office

Bubble sort A-Z:
Pass 1: [Department of ECE, EEE Building, KUET Main Gate, Central Computer Centre, KUET
Post Office, Mechatronics Engineering Building]
Pass 2: [Department of ECE, EEE Building, Central Computer Centre, KUET Main Gate, KUET
Post Office, Mechatronics Engineering Building]
Pass 3: [Department of ECE, Central Computer Centre, EEE Building, KUET Main Gate, KUET
Post Office, Mechatronics Engineering Building]

```

Pass 4: [Central Computer Centre, Department of ECE, EEE Building, KUET Main Gate, KUET Post Office, Mechatronics Engineering Building]

Pass 5: [Central Computer Centre, Department of ECE, EEE Building, KUET Main Gate, KUET Post Office, Mechatronics Engineering Building]

Comparisons: 15, swaps: 7

Selection sort A-Z:

Pass 1: [Central Computer Centre, Department of ECE, EEE Building, Mechatronics Engineering Building, KUET Main Gate, KUET Post Office]

Pass 2: [Central Computer Centre, Department of ECE, EEE Building, Mechatronics Engineering Building, KUET Main Gate, KUET Post Office]

Pass 3: [Central Computer Centre, Department of ECE, EEE Building, Mechatronics Engineering Building, KUET Main Gate, KUET Post Office]

Pass 4: [Central Computer Centre, Department of ECE, EEE Building, KUET Main Gate, Mechatronics Engineering Building, KUET Post Office]

Pass 5: [Central Computer Centre, Department of ECE, EEE Building, KUET Main Gate, KUET Post Office, Mechatronics Engineering Building]

Comparisons: 15, swaps: 3

Bubble swaps neighbours many times; selection makes at most $n-1$ swaps.

Bubble sort is stable, selection sort is not.

Complexity: both $O(n^2)$; bubble sort is $O(n)$ when already sorted

Appendix B. Building and Running

1. Install `g++` through MSYS2 (`pacman -S mingw-w64-ucrt-x86_64-gcc`) and add `C:\msys64\ucrt64\bin` to PATH.
2. Open a terminal in the project folder and run `make run`. It builds `bin/CholoKUET.exe` with the logo icon and starts it. `make test` builds and runs all eight test programs.
3. Without `make`, `g++ -std=c++17 main.cpp -o CholoKUET` builds the whole program in one command, because `main.cpp` pulls in every other source file.
4. Log in as `student1 / student123`, or as `admin / admin123` for the admin menus.