MORULE 5 RESOURCE



TABLE OF CONTENT

- What is a Resource?
- Types of Resources
- String Resource
- Internationalization
- Webography



What is a Resource?

- ▶ Resources include text data, bitmaps, audio, videos, ...
- Better to define resources in external files
 - Easier to maintain
- XML files
 - In **res** directory
- Accessed in Java code through IDs assigned to them



What is a Resource?

- Apps applicable to diverse hardware systems
 - By creating several resources files supporting different hardwares
- Resources mainly divided into drawables, layouts and values



- Drawable Resources
 - Define various graphics with bitmaps or XML
 - Icons and graphics resources according to the screen resolutions
 - Saved in res/drawable/
 - drawable-xhdpi folder : for 320dpi
 - drawable-hdpi folder : for 240dpi
 - drawable-mdpi folder : for 160dpi
 - drawable-ldpi folder : for 120dpi
 - Accessed from the R.drawable class



- Layout Resource
 - Define the layout for application UI
 - Saved in res/layout/
 - Accessed from the R.layout class
- Menu Resource
 - Define the contents of application menus
 - Saved in res/menu/
 - Accessed from the R.menu class



- MipMap Resources
 - For placing the app icons only
 - Any other drawable assets are placed in drawable folders
 - Saved in res/mipmap/
 - Accessed from the R.mipmap class



- Values Resource: String Resources
 - Define strings, string arrays, and plurals (and include string formatting and styling)
 - Saved in res/values/
 - Accessed from the R.string, R.array and R.plurals classes
- Values Resource: Style Resources
 - Define the look and format for UI elements
 - Saved in res/values/
 - Accessed from the R.style class



- Animation Resources
 - Tween animations
 - Saved in res/anim/
 - Accessed from the R.anim class
 - Frame animations
 - Saved in res/drawable/
 - Accessed from the R.drawable class



- Color State List Resource
 - Define a color resources that changes based on the View state
 - Saved in res/color/
 - Accessed from the R.color class



More Resource Types

- Define values such
 - Bool: XML resource that carries a boolean value
 - Color: XML resource that carries a hexadecimal color value
 - Dimension : XML resource that carries a dimension value (with a unit of measure)
 - ID : XML resource that provides a unique identifier for application resources and components
 - Integer: XML resource that carries an integer value
 - Integer Array: XML resource that provides an array of integers
 - Typed Array : XML resource that provides a TypedArray
- Saved in res/values/



- More Resource Types (continued)
 - But each accessed from unique R sub-classes
 - Bool : Accessed from the R.bool class
 - Color : Accessed from the R.color class
 - Dimension : Accessed from the R.dimen class
 - ID : Accessed from the R.id class
 - Integer : Accessed from the R.integer class
 - Integer Array : Accessed from the R.array class
 - Typed Array : Accessed from the R.array class



String Resource


- Do not hardcode String values!
 - Better to define String resources in external file
 - Easier to maintain
 - E.g, for internationalization



Using String Resource

- Add new resource entry in strings.xml file
 - Through <string> tag
 - Attribute **name**: identifies resource

▶ E.g,





String Resource

- Use String resource
 - In XML files
 - Through @string/resourceIdentifier

```
• E.g, 

android:id="@+id/helloText"

android:layout_width="wrap_content"

android:layout_height="wrap_content"

android:text="@string/hello_world" />
```

- In Java
 - Through R.string
 - E.g,

```
String message = getString(R.string.hello_vorld);
```

```
Toast.makeText(MainActivity.this, R.string.hello_world, Toast.LENGTH_LONG).show();
```



- Put default language text in res/values/strings.xml
- To support additional languages:
 - Create additional values directories inside res/
 - Include a hyphen and the ISO language code at the end of the directory name
 - E.g, res/values-fr
 - Copy strings.xml files in those directories with values in right language
 - E.g, res/values-fr/strings.xml
- Android loads the appropriate resources according to the locale settings of the device at runtime



- The Iso language code is defined by
 - A two-letter ISO 639-1 language code
 - Optionally followed by a two letter ISO 3166-1-alpha-2 region code (preceded by lowercase "r")
 - E.g, en, fr, en-rUS, fr-rFR, fr-rCA




▶ E.g,

In Android studio: change to Package view

```
Packages
app
  android.support.v7.appcompat
com.henallux.myfirstapp
   drawable
  layout
   menu menu
   i mipmap-hdpi
   i mipmap-mdpi
   i mipmap-xhdpi
   mipmap-xxhdpi
   values
      💆 dimens.xml
        strings.xml
      styles.xml
  values-fr
      strings.xml
   values-nl
     strings.xml
```

```
<?xml version="1.0" encoding="utf-8"?>
<resources>
    <string name="app_name">Ma première application</string>
    <string name="hello_world">Bonjour à tous!</string>
</resources>
```







Webography

- http://developer.android.com/guide/topics/resources/index.html
- http://developer.android.com/guide/topics/resources/availableresources.html
- http://developer.android.com/guide/topics/resources/localization.html
- http://developer.android.com/training/basics/supportingdevices/languages.html

