One flight, one track across a reception gap

Version 4: a rule that keeps one track_id across a long ADS-B gap, what it gains, and why it should not be the default yet

EUROCONTROL Performance Review Unit · 09 November 2026

Superseded by the next version. This version proposed the rule and measured it, and recommended against making it the default until two detectors were fixed. The next version fixes them, audits the rule, re-measures on the final code and makes it the default. The numbers below are those this version published; its pipeline-day figures for the new rule were later found to rest on a stale candidate table, and the next version replaces them. This page is frozen: rendering it no longer re-runs the analysis.

What we found

Today a reception gap of over 30 minutes ends a track. A flight crossing the Atlantic therefore becomes two tracks and two rows in the flight list, and neither row has both airports. The new rule keeps one `track_id` across such a gap when the evidence at its two edges fits one continuous flight.

- **Flights crossing the European box in one track: 25.3% under the current rule, 80.7% under the new one** (6,450 flights over two days). "Crossing" means exactly one of the two airports lies inside the box.
- All flights in one track: 87.6% to 95.0%.
- **Two things took crossing flights from 68.8% to 80.7%.** Reading altitude, vertical rate and speed at a gap's edge past blank samples gives 79.1%. Letting a flight lost while still climbing link gives 80.7%. A flight that reappears descending stays split, because that case failed its own limit.
- **Wrong joins are rare where we can check them:** 3 of 5,773 checkable linked gaps (0.05%), and 6 of 123,949 artificial gaps hiding a real landing. But 74.9% of linked gaps cannot be checked at all, because our truth covers Europe only.
- **The climb part is provisional.** Gaps linked only because the flight was climbing show 0 false joins in 185 checkable cases, under the 300 we wanted. All 6 artificial gaps that joined have a climbing edge and the same or a blank callsign.
- In a real pipeline run on one airframe in ten, crossing flights with both airports right on one row went from 0 to 105, of 285.

We do not recommend making it the default yet. Two things computed along a track break across a gap, and neither is fixed. A level segment spans a gap on 88.0% of the linked tracks checked (169 of 192). Cumulative distance comes up short across a gap, by a median of 1,508 NM. Switching would also create another silent `track_id` boundary. The rule is in the code, and it is not the default. Its settings are provisional for climbing edges.

The problem

Take a flight from New York to Frankfurt. Receivers hear it leave New York, lose it over the ocean, and hear it again near Ireland hours later. The current rule sees a gap over 30 minutes and starts a new track. The flight list then says this (an illustration, not a record from the data):

Rule and row	Track	ADEP	ADES
Current rule, first row	first piece	KJFK	none
Current rule, second row	second piece	none	EDDF
New rule, the only row	one track	KJFK	EDDF

Anyone asking how many flights went from New York to Frankfurt counts none under the current rule. Over the two days studied, the 6,450 crossing flights made 12,403 tracks, or 1.92 per flight. In the pipeline sample, 0 of 285 crossing flights had both airports right on one row.

Below, a **hole** is a gap over 30 minutes, and its **edges** are the samples either side of it.

The rule in plain words

A hole stays inside one track only if all of these hold. If a value needed for a check is missing, the check fails and the hole splits, except where the table says otherwise.

Check	Setting	Why
Hole not too long	at most 600 min	Longer holes leave too much room for anything to have happened.
At cruise or climbing before the hole	lowest of the nearest 5 altitudes within 5 min before the hole at or above 18,000 ft; or, below that, climbing: the mean of the nearest 5 vertical rates above 500 ft/min, resting on at least 3 rates	An aircraft at altitude is not about to land, and one still climbing has just left. A blank rate does not count as climbing.
At cruise after the hole	lowest of the nearest 5 altitudes within 5 min after the hole at or above 18,000 ft	The same at the other side. A descending aircraft below the floor does not pass: see Results.
No descent then climb	not both descending faster than 500 ft/min before and climbing faster than that after; a blank vertical rate does not count against it	That is what a stop in the hole looks like.
Callsign agrees	the last callsign before (at most 60 min old) and the first after (within 10 min) are not both present and different; blank counts as agreeing	A different callsign is a different flight. A blank says nothing.
Implied speed not too slow	at least 400 kt: straight-line distance between the edge positions over the time between them	A stop uses up time, which lowers this speed.
Implied speed not impossible	at most 750 kt	Faster than this is two aircraft sharing an address, not wind.
Real address	`icao24` not `000000`, `000001` or `ffffff`	These placeholders are shared by many aircraft.

Every edge value is read past blank samples, within 5 min of the hole. ADS-B sends position and altitude separately from speed and vertical rate, so the sample right at an edge often lacks one or the other. So position uses the last value within 5 min before the hole and the first within 5 min after it. Altitude, vertical rate and speed each use their own nearest 5 values within the same 5 min. With no altitude in that span the check fails. With no vertical rate, the descent-then-climb check passes, and the climbing alternative does not.

Everything else stays as it is. A callsign change and a short gap at low altitude still split. No sample is invented: the hole stays empty and only the identity changes. In the code this is `cruise_linked`, also called A10: the current rule, A9 `debounced`, with this one change. A day's run must read 11 hours back rather than 3, or a track across midnight would publish samples twice, and the code enforces that.

What others do. Nobody publishes a tested method, as far as our literature review, "Link flight pieces only where stops cannot fit", could find. Public practice splits on a time gap of 10 to 30 minutes and mostly stops there. OpenSky's 2021 dataset paper rejoins pieces when a straight extrapolation fits within 0.5 degrees, and GAIA publishes rules for splitting; neither reports how

often it links wrongly. We found no study that tests linking against real landings hidden in withheld data, which may be a gap in our search rather than proof that none exists. So this study measures its own error rate.

How we tested it

A **false join** is two different flights of one airframe sharing a track. A landing and a take-off vanish, the flight list pairs an airport from one flight with an airport from another, and nothing in the data shows it. A split, by contrast, is visible and leaves two truthful pieces. So we treat a false join as worse, and unclear evidence means split. That weighting is a project decision, not a result.

The days are 2026-06-14 and 2025-06-14, the only worldwide full days with the tables needed. Truth is Network Manager, the European flight data.

Test	What it does	What should happen	Size
Real holes	Each linked hole against Network Manager, matched on airframe and time and never on callsign, since that would score the callsign check against itself. True link: the hole lies inside one flight. False join: a landing or take-off of that airframe falls inside the hole. Otherwise unknown.	No false joins	22,985 linked, of 228,655 holes
Hidden landing	Two consecutive flights of one airframe. Delete from a cruise point in the first to a cruise point in the second, so a real landing sits inside an artificial hole. A second kind starts the cut at the first flight's last climbing sample below the floor. The cruise side of the cuts that count sits 30 min or more into cruise, where speed alone cannot give it away.	No joins	123,949: 40,975 between cruise edges, 82,974 from a climbing edge
Cut flight	Delete the middle of one continuous flight, for 60 to 360 min.	Rejoined	49,518
Real pipeline day	2026-06-14, one airframe in ten, through the real pipeline under both rules, to the flight list and events.	More flights right, nothing else moved	285 crossing flights

A setting had to meet three limits, pooled over the two days: false joins at most 0.1% of checkable real holes; at most 1% of hidden landings joined, read as a 95% upper bound; and at most 5% where the two flights have the same or a blank callsign, the case the callsign check cannot reject. Among settings within those limits, we took the most crossing flights in one track.

An edge allowed below the floor also has to pass the same three on its own, so a good result elsewhere cannot hide a bad one: at most 1% of the hidden landings of that kind, at most 5% of those with the same or a blank callsign, and at most 0.1% false joins among checkable holes linked only that way. A rate over a limit fails however small the sample. A rate within it, on under 300 checkable holes, passes only provisionally.

Climbing and descending are separate settings because of these same two days. We split them after a read of the same data showed one clean and one not. So the limits confirm a pattern already seen in that data. They are not a test of a prediction.

Results

Flights	Number	In one track, current rule	In one track, new rule	Tracks per flight, current	Tracks per flight, new
Crossing the European box	6,450	1,633 (25.3%)	5,203 (80.7%)	1.92	1.18
All others	51,986	49,546 (95.3%)	50,311 (96.8%)	1.03	1.01
All	58,436	51,179 (87.6%)	55,514 (95.0%)	1.12	1.03

The counts include 931 flights with no track at all, which read as not in one track. "In one track" says the flight is not split. It does not say the track holds nothing else: the false-join tests below

answer that.

False joins.

Evidence	Result	Reading
Real holes that can be checked	3 false joins of 5,773 (0.05%)	Within the 0.1% limit. 2 on 2025-06-14, 1 on 2026-06-14; 0 had the event within 5 min of an edge, where a timing error could explain it.
Real holes that cannot be checked	17,212 of 22,985 (74.9%)	No evidence either way.
Real holes linked only because the old edge was climbing	0 false joins of 185 checkable, among 1,101 linked	Under the 300 wanted, so provisional. Zero of 185 still allows up to 1.6% at 95% confidence, well above the 0.1% limit, and 83.2% of these holes cannot be checked.
Hidden landing, cuts deep in cruise	6 of 123,949 joined, from 5 flight pairs	At most 0.010%, at 95% confidence.
The same, same or blank callsign only	6 of 3,820 joined	At most 0.31%. Every join is in this group.
The same, callsign check removed	13 of 123,949 joined	At most 0.017%. So the safety does not rest on the callsign check alone.
Hidden landing, shallow cuts	0 of 38,623 joined	Easy cases, near an airport. Reported, not counted toward the limit.

Hidden landings by kind of edge. The chosen rule allows the first two kinds. We also ran 110,495 tests of the last two. With the chosen settings a descending edge fails the altitude check by construction, so those are not counted above, and they appear here as what turning descent on would face.

Edges either side of the cut	Tests	Joined	At most, 95%	Same or blank callsign: tests	Joined	At most, 95%	In the chosen rule
Cruise, then cruise	40,975	0	0.007%	906	0	0.33%	yes
Climb, then cruise	82,974	6	0.014%	2,914	6	0.41%	yes
Cruise, then descent	79,343	0	0.004%	2,291	0	0.13%	no
Climb, then descent	31,152	0	0.010%	1,092	0	0.27%	no

Climbing and descending edges, decided separately. All four combinations, at the chosen settings otherwise.

Edges below the floor allowed	Crossing flights in one track	All flights in one track	Real false joins among holes linked only that way, of checkable	Real false joins overall, of checkable	Hidden landings joined	Within limits
Neither	79.1%	94.7%	none	3 of 5,588 (0.054%)	0 of 40,975	yes
Old edge climbing (chosen)	80.7%	95.0%	0 of 185	3 of 5,773 (0.052%)	6 of 123,949	yes, provisional
New edge descending	79.9%	94.9%	3 of 119	6 of 5,707 (0.105%)	0 of 120,318	no
Both	81.5%	95.2%	3 of 305	6 of 5,893 (0.102%)	6 of 234,444	no

These two results point in opposite directions, and each could be chance. They do not show that the two kinds of edge differ. On real holes, climbing has 0 false joins of 185 and descending 3 of 119 (2.5%). If those 3 fell at random among the 304 checkable holes, the chance of all of them landing on the descending side is 0.059. On hidden landings it is the reverse: 6 of

82,974 joined with a climbing edge and 0 of 79,343 with a descending one. If those 6 fell at random among the 162,317 tests, the chance of all of them landing on the climbing side is 0.018. Timing may also play a part: 2 of the 3 descent false joins have the landing or take-off within 5 min of an edge, where an error in the truth time could produce a false join by itself. In the chosen rule, 0 of the 3 are that close. We have not checked those cases one by one.

Climbing on is a judgement. It gains 1.6 points of crossing flights and adds a way for a hidden landing to get through. At this sample size, "within the limit" means only that no false join was observed: 0 of 185 still allows up to 1.6%, at 95% confidence.

Descending off applies the limit. It has not been shown worse. It rests on 3 of 119. With so few checkable holes, a single false join would already read as 0.84%, over the limit, so one or two cases decide it. Turning it on as well would give 81.5% of crossing flights, 53 flights more, with 6 false joins of 5,893 (0.102%) overall.

How settings trade off. All of these have the speed ratio and time-for-a-stop checks off, which the Choices section covers. The chosen setting is the first row. All of them have climbing edges on, so "yes" here carries the same provisional status.

Speed floor	Longest hole	Crossing flights in one track	All flights in one track	Real false joins, of checkable	Hidden landings joined	Cut flights not rejoined	Within limits
400 kt	600 min	80.7%	95.0%	3 of 5,773 (0.05%)	6 of 123,949	20.4%	yes
400 kt	480 min	80.1%	94.9%	3 of 5,732 (0.05%)	1 of 121,918	20.4%	yes
400 kt	360 min	75.6%	94.4%	2 of 5,410 (0.04%)	0 of 112,029	20.4%	yes
315 kt	600 min	81.1%	95.1%	15 of 5,829 (0.26%)	39 of 123,949	8.5%	no
315 kt	480 min	80.6%	95.0%	6 of 5,779 (0.10%)	19 of 121,918	8.5%	no
315 kt	360 min	76.0%	94.5%	4 of 5,456 (0.07%)	10 of 112,029	8.5%	yes

Hidden-landing counts differ because only holes the setting allows are counted. The longest hole allowed matters for coverage, and also for hidden landings: at 400 kt they go from 6 joined at 600 min to 1 at 480 min and 0 at 360 min. The speed floor hardly matters on real flights, but it matters for false joins and for cut flights.

What keeps the remaining holes split. These are holes inside the flights scored. On crossing flights, 4,809 are linked and 1,173 stay split. Each is listed under the first check it fails, in the order the code applies them.

First test failed	Crossing flights: holes	of which failed nothing else	Other flights: holes	of which failed nothing else
Below the floor after the hole	428	94	352	94
Implied speed too slow, or no position to compute it	425	33	192	14
Below the floor before the hole	302	16	274	3
Hole too long	8	8	5	2
Callsign differs	6	5	3	3
Implied speed impossible	4	4	0	0
All holes left split	**1,173**		**826**	

No one cause dominates on crossing flights. 428 holes (36.5% of those left split) fail below the floor after the hole, 425 (36.2%) on implied speed, and 302 (25.7%) below the floor before it. Most of them would fail another check too: nothing else fails for only 94 of the 428 and 33 of the 425. Length is not the problem: 8 holes are too long.

"Below the floor" here also includes an edge with no altitude at all within 5 min, and these files do not separate the two. **This corrects the earlier version of this report,** which read this group as aircraft reappearing on approach. That was a guess and it was wrong: most of that group then were simply blank altitudes, now read past. Turning on descending edges adds only 53 crossing flights in one track.

How the method got here

Each row explains a final choice. The comparisons come from earlier runs of the study, except the last row, and the second figure in each comparison of the row before it, which are final.

What we found	What it did	What we chose
A position is often blank right at a hole's edge, and the first version split those holes because it could not compute a speed. In the final data, 82,212 of all 228,655 holes (36.0%) use a position read past a blank.	At 25,000 ft, 400 kt and 360 min, crossing flights in one track went from 40.1% to 64.4%, and linked holes from 7,745 to 15,951.	Read positions past blank samples.
All flights moved little (87.6% to 89.6%) because short European flights dominate, while crossing flights went only from 25.3% to 40.1%.	The headline hid the flights this is for.	Choose settings by crossing flights first.
Lower floors and longer holes let more through, but floors made little difference.	Before altitude was read past blanks, at 400 kt and 600 min: 67.7% at 25,000 ft, 68.8% at 18,000 ft, 69.9% at 10,000 ft.	18,000 ft and 600 min. See Choices below.
Altitude is often blank right after a hole, as position is, and a blank altitude failed the check at any floor.	Reading altitude, vertical rate and speed past blanks, at the same settings: crossing flights 68.8% to 79.1%, linked holes 18,064 to 21,884, false joins 2 of 4,670 to 3 of 5,588.	Read them past blanks. We treat it as a bug fix, and it stayed within the limits. Its cost is under Limits of the evidence.
An edge below the floor may still fit one flight if its direction does: an old edge climbing or a new edge descending.	Climbing: crossing flights 79.1% to 80.7%, 1.6 points, with 0 false joins of 185 checkable and 6 of 2,914 hard hidden landings joined. Descending: 79.1% to 79.9%, 0.8 points, with 3 of 119.	Climbing on, provisional, since 185 is under 300. Descending off, since 2.5% is over its 0.1% limit. Each is one setting.

Two counts say how often a position is read past a blank, and they answer different questions. 82,212 of all 228,655 holes (36.0%) is how common it is among holes, whatever the rule decides, at every length and altitude. 13,669 of 22,985 linked holes (59.5%) is how often a link rests on such a position, among the holes the chosen settings keep. Both count a hole when either edge reads past a blank, and neither counts a hole with no position within 5 min, which cannot link. Of the 3 false joins, 1 used such a position. Altitude is counted in Limits of the evidence below.

Real pipeline day

2026-06-14, one airframe in ten, flights that take off and land on the day.

Flights	Number	Rows per flight, current	Rows per flight, new	On one row, current	On one row, new	Both airports right on one row, current	Both airports right on one row, new
Crossing the European box	285	1.81	1.27	86	210	0	105

Flights	Number	Rows per flight, current	Rows per flight, new	On one row, current	On one row, new	Both airports right on one row, current	Both airports right on one row, new
of which Europe to outside	156	1.83	1.32	47	108	0	63
of which outside to Europe	129	1.78	1.20	39	102	0	42
Inside Europe	2,672	1.06	1.05	2,531	2,547	1,945	1,952

Crossing flights on one row went from 30.2% to 73.7%. Both airports right on one row went from 0 to 105, which is 36.8% of them. The rule finds no new airports: across every row of the comparison, 0 answers went from none to right. It puts answers on one row that were already on two. The ceiling is detection: 149 of 285 crossing flights (52.3%) have no row naming the airport outside the box, matching flights by callsign. On crossing flights, a destination went from right to wrong on 1 and from wrong to right on 1. 1 crossing flight gained a row, which we did not look into.

A small loss inside Europe. Of 2,672 flights inside Europe, 14 gained both airports right and 7 lost them. Destination went from right to wrong on 8 and from wrong to right on 7. We do not know why, as these CSVs cannot say. Those 7 flights should be looked at one by one before any promotion.

Track boundaries moved only where they should. Re-segmenting the sample under both rules, over the whole window a day's run reads, gives 38,383 track boundaries under the current rule and 35,349 under the new one. All 3,034 removed sit at holes the rule links (3,034 there, 0 elsewhere), and 0 were added. The pipeline's 16,194 tracks for the day are exactly those re-segmented tracks. Of 3,493 airport take-offs and landings in APDF, the detector finds 2,913 under the current rule and 2,914 under the new one.

Events that changed, on airframes with a linked track, inside the flights scored:

Event type	Current rule	New rule	Change
`first_seen`	545	313	-232
`last_seen`	530	298	-232
`top-of-climb`	540	308	-232
`top-of-descent`	540	308	-232
`level-end`	1,334	1,128	-206
`level-start`	1,335	1,129	-206
`entry-taxiway`	2,239	2,222	-17
`exit-taxiway`	2,237	2,222	-15
`AIBT`	130	116	-14
`AOBT`	136	122	-14
`entry-apron`	147	146	-1
`entry-parking_position`	325	324	-1
`exit-apron`	147	146	-1
`exit-parking_position`	330	329	-1
`level-off-descent-end`	644	643	-1
`level-off-descent-start`	646	645	-1
`runway-vacated`	102	101	-1

Event type	Current rule	New rule	Change
xing-fl50	450	451	+1
xing-fl100	455	459	+4
xing-fl245	471	487	+16

Most of this is arithmetic. first_seen, last_seen, top-of-climb and top-of-descent each fall by one per joined hole, 232 of them inside the flights scored, out of 1,273 linked holes in the sample. The level events fall by 206, one per hole inside a level segment, covered in the next section. level-off-descent-start and level-off-descent-end change by -1 and -1. xing-fl245 changes by +16, xing-fl100 by +4 and xing-fl50 by +1. Our reading, not measured, is that when one edge sits below a level and the other above, the hole itself reads as a crossing: the floor allows that at FL245, and a climbing old edge, which can be at any altitude, allows it lower down.

Airport surface events are not arithmetic, and we have not traced them. entry-taxiway changes by -17, exit-taxiway by -15, entry-apron by -1, exit-apron by -1, entry-parking_position by -1, exit-parking_position by -1 and runway-vacated by -1. These events are only matched at airports named on the track's flight-list row, so a row whose airports change can lose them. That is our reading from the code, not a measurement. They should be looked at alongside the 7 flights above.

AOBT **and** AIBT **change by -14 and -14. This is not evidence of glued flights.** The block detector gives a track at most one of each, the first off-block and the last on-block, so two pieces that each had one now have one between them. That is the detector's logic; we did not trace each of these individually. Could an on-block on the older piece and an off-block on the newer one mean the aircraft parked in the hole? To check, all 1,273 linked holes in the sample were labelled against every Network Manager flight of the airframe, whatever its day. The labels use Network Manager times only. Detected events are counted beside them and never decide a label.

Label	Holes	With a landing or on-block event on the older piece	With a take-off or off-block event on the newer piece	With both
True link	376	76	55	10
False join	0	0	0	0
Unknown	293	33	31	5
Airframe not in Network Manager	604	103	79	21

0 holes are false joins. Such events on both sides of a hole occur on checked true links too (10 of 376), so block events there are not proof of a stop. The event columns are lower bounds: a later piece that starts after midnight is absent because the next day was not built, and an event is counted anywhere on a piece rather than near the hole, so they support nothing beyond that sentence. The 293 unknown and 604 not-in-truth holes stay unchecked, the same limit as in the two-day figures.

What this breaks, and is not fixed

Level segments span holes. On 169 of 192 linked tracks inside the flights scored (88.0%), a level start before a hole pairs with a level end after it: 176 segments containing 206 holes. A user computing level time, or how much of a flight is flown level, gets hours of "level flight" during which nothing was received. We set the condition before measuring that damage on most linked tracks withdraws the recommendation, and this meets it.

Cumulative distance is short across holes. On 231 of the 231 holes compared, the distance added differs from the straight-line distance between the edges by over 1 NM. The median shortfall is 1,508 NM, and 95% of holes are short by at least 310 NM. All 231 have a blank position on a sample next to the hole, and the distance function reads a blank as zero distance, so the hole

adds next to nothing. The stored measurement agrees with this calculation on 192 tracks checked, with 0 off, so this is what would be published. A user reading distance flown from a linked track, or comparing it with a route, sees a long-haul flight far too short, with no warning.

The detectors were not changed in this work, and any fix gets its own `version`.

Limits of the evidence

- **Truth is European, and most linked holes cannot be checked.** 74.9% are unknown. A stop outside Network Manager's area is invisible, so how the rule performs elsewhere is unmeasured.
- **Two days.** 3 false joins, 1 on one day and 2 on the other, are too few to say anything about variation.
- **The two-day measurements re-segment existing tracks, not raw data.** They take `opdi-world/osn_tracks` as given. Only the pipeline day starts from the state vectors.
- **The pipeline day is a 10% sample with few crossing flights,** 285 of them. Its one-row share under the current rule is 30.2%, against 25.3% in the two-day data, which shows how far a sample this size can sit from the larger figure.
- **Flights inside one day only.** Eastbound crossings leaving before midnight UTC drop out, so the sample leans westbound. A flight whose first part belongs to a track of the day before reads as fewer tracks than it has.
- **A flight that never reaches the floor is untested.** It cannot link, and no test covers it.
- **Climb evidence is thin.** 185 checkable holes, under the 300 wanted, and 83.2% of holes linked this way cannot be checked. The 6 hidden landings it let through all fall in the 2,914 tests with a climbing edge that the callsign check cannot reject. No cut-flight test measures climbing alone: the low-edge cut removes a flight's whole cruise, so it needs climbing and descending together, and rejoins 0 of 35,804 under the chosen rule against 26,377 with both on.
- **The hidden-landing test does not cover a low climbing edge.** It cuts at a flight's last climbing sample below the floor, so just under 18,000 ft, whereas the rule accepts an old edge at any altitude while it climbs. So its 6 of 82,974 covers the high-climb case only, and a low climbing edge is covered only by the 185 real holes. A departure lost low that lands outside Network Manager's area reads as unknown, and most climbing links are unknown (83.2%). There the 400 kt speed test does most of the protecting. That is our reading, not a measurement.
- **A reading can be up to 5 min old.** An edge's altitude may come from a sample 5 min from the hole, so an aircraft could really be below the floor at the edge itself. 12,370 linked holes (53.8%) read the new edge's altitude past a blank, with 1 false join among them, and 46 (0.2%) read the old edge's, with 0. These count every hole with no altitude in the edge's own second, not only those the fix newly lets through. We have no measure of how far the aircraft moved in those minutes.
- **Hard same-callsign cases are few.** There are 3,820, so the bound is 0.31% overall and much weaker in places: the smallest group (a climbing edge, holes of 120-240 min, cut 120 min into cruise) has 11 tests and a bound of 24%. The 123,949 tests come from at most 38,734 flight pairs, and cuts of one pair are not independent, so the bounds are somewhat too tight.
- **Artificial holes are cleaner than real ones,** and cut flights lean to well-covered flights.
- **Cut flights are often not rejoined: 20.4% at 400 kt, against 8.5% at 315 kt.** Implied speed is the first failed check on 8,293 of the 10,109 misses (82.0%). This barely shows on real flights: going from 315 to 400 kt loses 13.0% of rejoined cut flights but 1.8% of linked real

holes. We can only partly explain it. Cut-flight tests are not split by flight type, and 89.0% of flights do not cross the box, so most tests are on shorter flights, where a cut can sit in slower flying or on a less direct path. Tests of 360 min, which only long flights can host, miss 6.4%, which fits. But misses first rise with length, 18.8% at 60 min, 23.6% at 120 and 29.6% at 180, which does not. That explanation is ours and not measured, and the pattern remains unexplained.

Choices made, and what they cost

These are judgement calls, and someone could reasonably go the other way.

Choice	What it costs, and the alternative
Real-hole limit tightened from 1% to 0.1%, after seeing results. The first limit could not separate settings, and we want a wrong join to be rare.	Set after the fact, so it is not an independent test. At 1%, 315 kt and 600 min would pass, with 81.1% of crossing flights and 15 false joins of 5,829 (0.26%).
Floor 18,000 ft, chosen by judgement, not by the selection rule. Applied across floors in the earlier runs, the rule would have picked 10,000 ft.	**These floor figures predate reading altitude past blanks.** Lower floors barely helped then, and the reason was the same blanks: a blank altitude fails at every floor. In those runs, 10,000 ft and 400 kt stayed within the limits only with a speed ratio check of 0.85: 69.5% of crossing flights, 4 false joins of 4,773 (0.08%), against 68.8% and 2 of 4,670 at 18,000 ft. Without that check it gave 69.9% but 6 of 4,817 (0.12%), over the limit. We gave that up for half the false joins and, in our judgement, edges further from busy airspace near airports. 10,000 ft has not been run again since the fix, so what it would give now is unknown.
400 kt and 600 min. The selection rule's pick.	315 kt and 480 min comes within 5 flights, 5,198 crossing flights against 5,203, but with 6 false joins of 5,779 (0.104%) it is just over the limit, and it joins 19 hidden landings against 6. Within the limits the nearest is 315 kt and 600 min with a speed ratio check of 0.85: 5,188 crossing flights, 3 false joins, 36 hidden landings joined, and 10.3% of cut flights missed against 20.4%.
Time-for-a-stop check off. It asks whether the time left over at a fast ground speed is too short for a stop. A larger allowance is looser.	At 35 min, crossing flights fall to 42.1%, and at 20 min to 32.7%. The safety gain is real: false joins 3 to 1 and hidden landings 6 to 0. The coverage loss is far larger, which is why it stays off.
Speed ratio check off. It compares implied speed with the aircraft's own speed at the edge.	At 0.85, crossing flights 80.1% and false joins 2, against 80.7% and 3. A small trade either way, and we kept the simpler rule.
Climbing edges on, on evidence short of what we wanted.	Gains 1.6 points of crossing flights, and adds a way for a hidden landing to get through: 6 of 82,974. Off gives 79.1% and 0 of 40,975 joined.
Descending edges off.	Gives up 81.5% for 80.7% of crossing flights. They fail their own limit, on a small sample. See Results.
A blank callsign counted with same callsign in the hard case.	868 of 3,820 tests (22.7%) are blank. The check cannot reject them, so this is the cautious way, but the group is not purely same-callsign flights.
Any landing or take-off in a hole counts as a false join.	Overstates false joins, if anything.

What is not decided

- **Making it the default.** Not recommended now. The rule ships off and `standard` still points to `debounced`.
- **A new silent `track_id` boundary.** Promotion would add one after those at A8 and A9. A join across it returns nothing rather than an error, and nothing in the published data says which rule produced a row, as `osn_tracks` has no version column. Consumers would have to be told.

- **The two fixes needed first.** Level detection must not pair a start and an end across a hole. Cumulative distance must carry across one. Both are detector changes with their own `version`, and neither is designed yet. After them, the event comparison should be run again.
- **Whether climbing edges stay on.** More checkable holes would firm up or remove the provisional status. Holes from more days are the way to get them.
- **Whether descending edges should be tried again** on a larger sample, once the timing of the near-edge cases is understood.
- **What a lower floor gives now.** 10,000 ft has not been run with altitude read past blanks.
- **Whether to add an airport test,** asking if any airport the aircraft could have stopped at fits inside the hole. Not built here, because it needs a join outside the rule's current form. Our literature review calls it the most promising and least proven idea. Whether it is needed depends on the unknown holes above.

Reproducing this

Run from the `opdi` repository. `run_track_link_day.py` and the regeneration need the cluster, S3 and Network Manager truth. The pipeline day's tables go under `s3a://eurocontrol/opdi-world/research/a10/`.

```
export PYSPARK_DRIVER_PYTHON=$PWD/.venv310/bin/python
unset PYSPARK_PYTHON
python benchmarks/run_track_link_day.py --day 2026-06-14 --arm debounced --steps 01 02 02a 03 04 04b
python benchmarks/run_track_link_day.py --day 2026-06-14 --arm cruise_linked --steps 02 02a 03 04 04b
python benchmarks/regenerate_track_v4.py --check     # what is stale; no cluster needed
python benchmarks/regenerate_track_v4.py --force     # final_grid and final_edges over two days, and the pipeline scor
python benchmarks/build_track_v4_paper.py            # fills this report; no cluster needed
```

Data. All in `papers/track-construction-v4/data/`. `final_grid/` has the settings search and the headline, `final_edges/` the four combinations of climbing and descending edges at the chosen settings, `stage2/` the pipeline day. `round1`, `round2`, `round3_fl250`, `round3_fl180`, `round3_fl100` and `round4_fl180` are earlier runs, kept to explain the method. They came from earlier code and are not regenerated, and all of them predate reading altitude past blanks, so they are not comparable with the final figures except where this report says so.

Provenance. Each file's script, arguments and commit are in the `_manifest.json` beside it. The final files record commit `4e4ceeb`. They came from `regenerate_track_v4.py --force` on that commit, and `regenerate_track_v4.py --check` reports all three jobs as current. The pipeline day's temporary tables (state vectors and raw tracks under `research/a10`) were deleted afterwards to return bucket space, so re-scoring the pipeline day needs `run_track_link_day.py` run again first.

Render. `index.qmd` holds this text with literal numbers and the regeneration step, but has not been rendered, because Quarto and R are not available on the machine that built it. `index.html` and `track-construction-v4.pdf` are built from the same text and CSVs by `benchmarks/build_track_v4_paper.py` (the PDF with `--pdf`, using reportlab), not through Quarto.