

No-Audio Call Triage

AI triage notes for "no audio / one-way audio" tickets

Prototype on simulated data

THE PROBLEM



L1 cannot read SIP/SDP. Most audio tickets go to L2. Each team checks its own part; nobody checks the gap.

L2: 20-40 min if clear, hours if intermittent. Getting one exact failed call takes longest.

ESTIMATED VALUE

10-15 min

of first digging saved per ticket.
L2 engineer estimate.

L1 learns what to collect.
Everyone discusses the same failed call.

HOW IT WORKS

Trigger: audio ticket + identified call. Runs async. Not triggered by low MOS alone.

Call data: Homer SIP/SDP · FreeSWITCH logs · RTP stats · all call legs



Every timeline line has an **ID, call leg and capture point**. Code checks each quote against its named line.

Note: facts, cause labelled as a guess, owner, visibility limit, line ID + quote, next check, missing data and a confidence reason. Links to Homer and raw logs.

WHAT L2 RECEIVES · SAMPLE NOTE

Owner: customer side

Suspected cause: Guess: customer firewall drops return audio

Next check: customer IT checks firewall drops for media-node IP and UDP port during this call

Missing: customer-side capture or firewall logs

PROTOTYPE RESULTS

3 / 40

pass in saved runmade-up quotes

Real LLM, simulated calls. All evidence checks passed.

NAT owner was right, but NAT was still listed as a possible cause. Failed 1 in 5 across tuning + saved run.

Traps: firewall; already-fixed NAT; stale SDP after transfer; media bypassing FreeSWITCH.

LIMITS TO KEEP VISIBLE

- Quote checks catch invented evidence, not bad reasoning. Private IPs may lead to NAT blame.
- Customer-side data is missing. Mask IPs and phone numbers before the LLM call. Engineers may trust it too much.
- Biggest delay stays:** waiting for customer IT.

NEXT: TEST ON REAL TICKETS

- Closed tickets with a known cause: measure owner accuracy and time saved.
- Run each case 10+ times. Report pass rate.
- Show notes to real L2 engineers.