

ChargePoint® Express Plus

A flexible DC Fast Charging platform that grows with you.



ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Express Plus Specifications

Express Plus Power Module

Express Plus Power Module Output	
Max Output Power	40 kW
Max Output Current	100 A
Power Conversion Efficiency	Up to 96%
Power Factor	0.99 at full load

Express Plus Power Module Specifications	
Power Module Dimensions	430 mm (H) x 130 mm (W) x 760 mm (L) (1 ft 5 in x 5 ft x 2 ft 6 in)
Power Module Weight	45 kg (98.5 lb)
Power Module Cooling	Liquid Cooled Technology
Harmonics	iTHD < 5% (Complies with IEEE 519)

Express Plus Power Block

Express Plus Power Block Input	
Input Rating	3-phase, 400-480Y VAC, 310-260 A 50/60 Hz
Wiring	L1, L2, L3, Earth
Short Circuit Current Rating	65 kA

Express Plus Power Block Output	
Max Output Power	200kW
Output Voltage, Charging	100 to 1000 VDC
Max Current per Output	250 A, 330 A, 350 A, 500 A*
Number of Stations Served	One Power Block can serve up to 2 Power Link stations. Additional Power Blocks can be added to serve more stations or increase power output.
Max Power Modules per Power Block	5

* Subject to site configuration and installed stations

Express Plus Power Block Specifications	
Power Block Dimensions	2191 mm (H) x 988 mm (W) x 1039 mm (L) (7 ft 3 in x 3 ft 3 in x 3 ft 5 in)
Power Block Weight	455 kg (1000 lb) without Power Modules
Power Block Enclosure Rating	Type 3R, IP56

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Express Plus Power Link 2000

Express Plus Power Link Output	
Max Output Power	500 kW with Power Blocks
Output Voltage, Charging	100 to 1000 VDC
CCS1 Max Output Current	500 A continuous liquid cooled cable with Power Blocks
CCS2 Max Output Current	500 A continuous liquid cooled cable with Power Blocks
CHAdeMO Max Output Current	North American and Europe (optional): 200 A continuous with Power Blocks

Express Plus Power Link Specifications	
Station Dimensions	2400 mm (H) x 720 mm (W) x 280 mm (D) (7 ft 11 in x 2 ft 5 in x 11 in)
Station Footprint	965 mm (W) x 635 mm (D) (3 ft 2 in x 2 ft 1 in) with Cable Management Kit (CMK)
Station Weight	270 kg (596 lb)
Number of Connectors	Up to 2 connectors per station. Simultaneous or sequential
Supported Connector Types	CHAdeMO, CCS1 (SAE J1772™ Combo), CCS2 (IEC 61851-23)
Cable Length	Standard 4.5 m (15 ft) with Cable Management Kit (CMK)**
Station Enclosure Rating	Type 3R, IP56
Locking Holster	Optional on pedestal
Mounting Type	Ground

* **Horizontal reach to typical vehicle charging port: 3.76 m (12 ft 4 in)

Express Plus Specifications

Functional Interfaces	
Indicators	Multicolor LEDs
LCD Display	Optional: Full-color 200 mm (8 in) LCD display
Authentication	RFID: ISO 15693, ISO 14443, NEMA EVSE 1.2-2015 (UR) Tap to Charge (NFC on Apple & Android) Contactless credit card Remote: Mobile and in vehicle (if supported by vehicle) ISO 15118-2, Plug&Charge

Connectivity Features	
Local Area Network	2.4 GHz and 5 GHz WiFi (802.11 b/g/n)
Wide Area Network	4G LTE
Supported Communication Protocols	OCPP 2.0.1
Service and Maintenance	Remote system monitoring, diagnostic, and proactive maintenance

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Safety Ratings	
Vehicle Safety Communication	CHAdeMO: JEVS G104 over CAN CCS1: SAE J1772 over PLC CCS2: IEC 61851-23, ISO 15118
Plug-Out Detection	Power terminated per JEVS G104 (CHAdeMO), SAE J2931 (CCS1) and IEC 61851-23 (CCS2)
Safety Compliance	Except for version with liquid cooled cable (in process): cUL and UL listed. Complies with UL 2202, UL 2231-1, UL 2231-2, CSA 107.1 CE and UKCA marked. Complies with IEC 61851-1 and IEC 61851-23
Surge Protection	Tested to IEC 61000-4-5, Level 5 (6 kV @ 3,000 A)
EMC Compliance	North America: FCC part 15 Class B Europe: EN55011, EN55022, and IEC61000-6-3 Class B

Generic Specifications	
Operational Altitude	< 3,000 m (9,800 ft)
Operating Temperature	-40°C to 50°C (-40°F to 122°F) with derating
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	Up to 95% at 50°C (122°F) non-condensing
Metering	Eichrecht (in progress)
Buy America	Buy America (FTA & FHWA) options available upon request

Energy Management Features	
Dynamic Power Management	Allows a fixed maximum power output per station or lets the system dynamically manage the power distribution per station
Remote Energy Management	Manage output power via the ChargePoint Admin Portal, API, and Open ADR 2.0b VEN



ChargePoint, Inc.
240 East Hacienda Avenue
Campbell, CA 95008-6617 USA
+1 408.841.4500 or +1 877.370.3802
US and Canada toll-free

Contact Us
Visit chargepoint.com
Email sales@chargepoint.com

©2013-2023 ChargePoint, Inc. All rights reserved. This material is protected by the copyright laws of the United States and other countries. It may not be modified, reproduced, or distributed without the prior, express written consent of ChargePoint, Inc. CHARGEPOINT is a US, UK, and EU registered trademark and service mark of ChargePoint, Inc. and cannot be used without the prior written consent of ChargePoint.

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.