

---

## Table of contents

Optical Resolution (sharpness, blur)

spectral Resolution  $\mathcal{R} = \frac{\lambda}{\Delta\lambda}$

$$\begin{aligned} & - \textit{Prisma with } L \equiv \text{base length}(\text{angle} \equiv \varepsilon) : \\ & \frac{\lambda}{d\lambda} = -L \frac{d\eta}{d\lambda} \\ & - \text{Diffraction Lattice} : \frac{\lambda}{\delta\lambda} = nN \\ & - \text{Interferometer} : \frac{\lambda}{\Delta\lambda} = n \cdot \frac{\pi \cdot r}{1 - r^2} = nN_e \\ & - \text{Planparallel Plate} : \frac{\lambda}{d\lambda} = \frac{x}{2d \tan(\beta)} \left( n - \frac{2d}{\cos(\beta)} \frac{d\eta}{d\lambda} \right) \end{aligned} \tag{1}$$

a) object is self-luminescent, lightwaves are incoherent and resolution is restricted:

Tele) object far and big, min. size for resolution:

$$\Delta y_{min} = 1.22 \cdot f^{Obj} \cdot \frac{\lambda}{D} \tag{2}$$

where “Diameter stop”  $\equiv D$  and view angle min. for “tele” resolution (object far and big):

$$\Delta \varepsilon_{min} = \frac{\Delta y_{min}}{f^{Obj}} = 1.22 \cdot \frac{\lambda}{D} \tag{3}$$

$\Rightarrow$  optical resolution “Tele”:

$$\mathcal{R}_{Tel} = \frac{1}{\Delta y_{min}} = 0.82 \cdot \frac{1}{f^{Obj}} \cdot \frac{D}{\lambda} \tag{4}$$

Mikro) object close and small, min. size for resolution:

$$\Delta y_g^{min} = \frac{1.22}{2} \cdot \frac{\lambda}{\eta} \cdot \frac{1}{\sin(u_g^{max})} = \frac{1}{2} \cdot \frac{\Delta s}{\eta} \cdot \frac{1}{\sin(u_g^{max})} = 0.61 \frac{\lambda}{A} \tag{5}$$

where aperture angle from sender (source, “Obj”)  $\equiv u_g$ , opposed to view angle  $\equiv \varepsilon$  from receiver (observer, “Oku”) and “Path difference”  $\equiv \Delta s$  and “Aperture stop”  $\equiv A = \eta \cdot \sin(u_g^{max})$

$\Rightarrow$  optical resolution “Mikro endo-luminescent”:

---


$$\mathcal{R}_{Mik(endo)} = \frac{1}{y_g^{min}} \stackrel{backlit}{=} \frac{A}{\lambda} \stackrel{luminescent}{\approx} 0.82 \cdot 2 \frac{A}{\lambda} = 0.82 \cdot 2 \sin(u) \frac{\eta}{\lambda} \quad (6)$$

b) object has no self-luminosity and is illuminated externally, lightwaves interfere coherently after diffraction:

Mikro) object close and small, min. size for resolution:

$$\Delta y \cdot \sin(u_g) = n \cdot \lambda \quad n \in \mathbb{N} \quad (7)$$

$$\Delta y_{min} = \frac{\lambda}{A} = \frac{\lambda}{\sin(u_g)} = \frac{\lambda}{\frac{\lambda}{\Delta y}} \quad A \equiv Aperture \quad (8)$$

$\Rightarrow$  optical resolution “Mikro exo-illuminated”:

$$\mathcal{R}_{Mik(exo)} = \frac{1}{\Delta y_{min}} = \frac{A}{\lambda} = \frac{\sin(u_g)}{\lambda} \quad (9)$$