

Table of contents

Potential as “intrinsic energy of inertia”	1
elec. Potential structure:	2
magn. Potential structure:	2
Electric endogen energy $E_{pot} = mc^2$:	2
Electric induced energy (exogenous excitation) $E_{kin} = \frac{1}{2}mv^2 \hat{=} (pc)^2$:	3
Conductor (charge conductive element for energy transfer) condition:	3
Slow changing current (quasi-stationary, low frequencies) condition:	3
Energy conservation for (large extended) conductive medium:	3
Energy of thin conductor (concentrated conductive medium without electric charge in its surrounding), Voltage (potentialdifference, tension):	4
Low Frequency:	5
High Frequency:	5
Continuity at Rest: Electric Charge	5
Continuity at Movement: Magnetic Field	5
Continuity at Acceleration: Radiation Energy	5
Continuity in Vacuum	5
Continuity in Matter	5
Near Field	6
Far Field	6
Dissipation in Vacuum	6
Dissipation in Matter	6
Energy gain by excitation:	7

Potential as “intrinsic energy of inertia”

Electro-Magnetic Field (force caused by potential):

$$\mathcal{B} = \nabla \times U_m = \frac{1}{c} \left(\frac{r}{|r|} \times \mathcal{E} \right) \quad \begin{matrix} \text{Near Field} & \dots & \text{Far Field} \\ \approx & & \approx \end{matrix} \quad (1)$$

$$\mathcal{E} = -\nabla U_e - \frac{\partial}{\partial t} U_m \stackrel{\text{moving charge}}{=} \frac{1}{2} \frac{1}{2\pi} \frac{1}{\epsilon_0} \frac{1}{r} \frac{1}{\left(1 - \frac{r}{|r|} \cdot \frac{v}{c}\right)^3} q \left[\underbrace{\left(1 - \frac{v^2}{c^2}\right) \frac{\frac{r}{|r|} - \frac{v}{c}}{r}}_{\text{uniform movement}} + \underbrace{\frac{\frac{r}{|r|} \times \left[\left(\frac{r}{|r|} - \frac{v}{c}\right) \times \dot{v}\right]}{c^2}}_{\text{accelerated movement}} \right] \stackrel{\text{fast moving}}{=} \quad (2)$$

Electro-Magnetic slow movement interactions (Maxwell conditions):

$$\nabla \cdot \epsilon_0 \mathcal{E} = \varrho \quad \nabla \cdot \mathcal{B} = 0 \quad \nabla \times \mathcal{E} = -\frac{\partial}{\partial t} \mathcal{B} \quad \nabla \times \frac{1}{\mu_0} \mathcal{B} = j + \epsilon_0 \frac{\partial}{\partial t} \mathcal{E} \quad (3)$$

$\Rightarrow$ Wave equation for potential:

$$\Delta \cdot U - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} U = J \quad (4)$$

$\Rightarrow$ Potential caused by “ignition J” (inhomogeneity) from source at rest, $v = 0$:

$$U = -\frac{1}{4\pi} \int \frac{J}{|r|} dr' \quad (5)$$

elec. Potential structure:

$$J = -\frac{1}{\epsilon_0} \varrho$$

$$U_e := \Phi \stackrel{\text{elec. charge dens.}=\varrho}{=} \frac{1}{4\pi} \frac{1}{\epsilon_0} \int \frac{\varrho}{|r|} dr' \hat{=} \frac{1}{2} \frac{1}{2\pi} \frac{1}{|r|} \frac{1}{\epsilon_0} Q = \frac{1}{2} \frac{1}{2\pi} \frac{1}{|r|} \frac{1}{\epsilon_0} It \quad (6)$$

magn. Potential structure:

$$J = -\mu_0 j$$

$$U_m := A \stackrel{\text{elec. current dens.}=j}{=} \frac{\mu_0}{4\pi} \int \frac{j}{|r|} dr' \hat{=} \frac{1}{2} \frac{1}{2\pi} \frac{1}{|r|} \mu_0 I = \frac{1}{2} \frac{1}{2\pi} \frac{1}{|r|} \frac{1}{c^2 \epsilon_0} I = \frac{1}{c^2} \frac{1}{t} U_e \stackrel{\text{source in uniformal movement, } v=\text{const.}}{=} \quad (7)$$

Electric endogen energy $E_{pot} = mc^2$:

$$e = \text{electron charge} \quad q = ne = \text{charge} \quad n \in \mathbb{N} \quad (8)$$

$$\text{Potential} \quad U = \frac{E_{pot}}{q} = \frac{(mc^2)^2}{ne} = \frac{m}{q} mc^4 = \kappa mc^4 \quad (9)$$

Electric induced energy (exogenous excitation) $E_{kin} = \frac{1}{2}mv^2 \hat{=} (pc)^2$:

E_{kin} Energy density electric:

$$w_e = \frac{1}{2}\epsilon_0\mathcal{E}^2 \quad (10)$$

E_{kin} Energy density magnetic:

$$w_m = \frac{1}{2}\frac{1}{\mu_0}\mathcal{B}^2 \quad (11)$$

E_{kin} Electric Energy:

$$W_e = \frac{1}{2}CU^2 \quad (12)$$

E_{kin} Magnetic Energy:

$$W_m = \frac{1}{2}LI^2 \quad (13)$$

Power:

$$P = VI = (U_1 - U_2)\frac{Q}{t} = \frac{E_1 - E_2}{t} = \frac{W}{t} = \frac{Fr}{t} = Fv \quad (14)$$

Conductor (charge conductive element for energy transfer) condition:

$$\sigma \cdot t \gg \epsilon_0 \quad (15)$$

Slow changing current (quasi-stationary, low frequencies) condition:

$$\frac{v}{c} \ll \frac{1}{c} \frac{\mathcal{E}}{\mathcal{B}} \ll \frac{c}{v} \quad (16)$$

Energy conservation for (large extended) conductive medium:

$$\int \left(\frac{\partial}{\partial t} (we + w_m) + \cdot \mathcal{S} + j \cdot \mathcal{E} \right) dr = \frac{d}{dt} W_e + \frac{d}{dt} W_m + D_S + \int (j \cdot \mathcal{E}) dr \stackrel{\text{low frequency}}{=} \frac{1}{2} \frac{d}{dt} (LI^2) + \frac{1}{2} \frac{d}{dt} \left(\frac{Q^2}{C} \right) \quad (17)$$

Energy of thin conductor (concentrated conductive medium without electric charge in its surrounding), Voltage (potential difference, tension):

$$V = U_1 - U_2 = r\mathcal{E} = \dot{\Psi} + RI + \frac{I}{C}t = L\dot{I} + RI + \frac{Q}{C} \quad (18)$$

$$\Delta \cdot := \text{div grad} = \text{Laplacian}$$

$$J = \text{"ignition of inhomogeneity, cause"} \quad j = \text{Current density} \quad \varrho = \text{Charge density}$$

$$V = \text{Potential difference} \quad I = \text{Current} \quad R = \text{Resistance}$$

$$L = \text{Inductance} \quad C = \text{Capacitance} \quad Q = \text{charge (ion)} \quad \Psi = LI = \text{mag. Flux}$$

$$\mathcal{S} = \mathcal{E} \times \mathcal{H} = \text{Poynting-Vector} = \text{radiation intensity}$$

$$D_S = \int (\cdot \mathcal{S}) dr = \int \text{div}(\mathcal{E} \times \mathcal{H}) dr = \text{dissipation energy lost from radiation} \approx 0 \text{ for low frequencies } \omega$$

$$d = \sqrt{\frac{1}{\mu\sigma} \frac{2}{\omega}} = \text{skin depth (surface) of conductor} \quad r = \frac{d}{\sqrt{2i}}\rho = \frac{d}{1+i}\rho = \text{radius (extension) of conductor}$$

$$\rho = kr = \text{"radius of curvature } k\text{"}$$

$$\omega = \dot{\rho} = \frac{v}{r} = 2\pi\nu = k\lambda \frac{1}{T} = \sqrt{\frac{k}{m}} \hat{=} kc \hat{=} \frac{1}{\sqrt{LC}} \hat{=} \sqrt{\frac{g}{r}} = \text{frequency}$$

$$\mu = \text{permeability of conductor} \quad \sigma = \text{conductivity of conductor (dielectricum)}$$

Low Frequency:

$$\omega \ll \frac{1}{\mu\sigma} \frac{2}{r^2} \iff r \ll d \iff \rho \ll 1 \quad (19)$$
$$L \approx \text{const.} \quad C \approx \text{const.} \quad D_S \approx 0$$

High Frequency:

$$\omega \gg \frac{1}{\mu\sigma} \frac{2}{r^2} \iff r \gg d \iff \rho \gg 1 \quad (20)$$
$$L(t) \neq \text{const.} \quad C(t) \neq \text{const.} \quad \text{for Dipol: } D_S \propto \omega^4 \gg 0$$

Continuity at Rest: Electric Charge

no Dissipation, no velocity, charge (ion) causes Electric Field

Continuity at Movement: Magnetic Field

no Dissipation, Velocity constant, moved charge (ion) causes emergence of Magnetic Field

Continuity at Acceleration: Radiation Energy

no Dissipation, Velocity changing, acceleration of charge (ion) causes emergence of Radiation

Continuity in Vacuum

Continuity in Matter

Refraction index emerges

Near Field

$$r \ll \lambda = \frac{2\pi}{k} \stackrel{\text{vacuum}}{=} \frac{2\pi}{\frac{\omega}{c}}$$

$$\frac{w_m}{w_e} \sim \frac{\frac{\vec{p}^2}{\epsilon_0 r^6}}{\frac{k^2 \mu_0 c^2 \vec{p}^2}{r^4}} \sim (kr)^2 \ll 1$$

$\vec{p}$ = elec. Dipol

Far Field

accelerated movement -> Radiation in Far Field of charge source

$$r \gg \lambda = \frac{2\pi}{k} \stackrel{\text{vacuum}}{=} \frac{2\pi}{\frac{\omega}{c}}$$

$$\frac{w_m}{w_e} = \frac{\frac{\epsilon_0}{2} c^2 \left(\mathcal{B} \times \frac{r}{|r|} \right)^2}{\frac{\epsilon_0}{2} c^2 \left(\mathcal{B} \times \frac{r}{|r|} \right)^2} = 1$$

Dissipation in Vacuum

no Continuity of charge/matter, no Refraction index, Reflection

Dissipation in Matter

no Continuity of charge/matter with Dielectricum, Refraction merges, Reflection, Absorption

Energy gain by excitation:

Action Quantum, Planck Constant (Energy-Frequency-Slope)¹:

$$h = \tan(\alpha) = \frac{E_{kin}}{\nu_i - \nu_0} = \frac{eV_{0i}}{\nu_i - \nu_0} \equiv \frac{E_1 - E_2}{\nu_0} = \frac{W}{\nu_0} = \frac{F_{EM} \cdot x}{\nu_0} = \hbar k \lambda \quad (21)$$

$$\hbar = \frac{E_1 - E_2}{\omega} = \quad (22)$$

$$E_{kin}^{max} = eV_0 = e \frac{Q}{C} = h(\nu - \nu_0) \quad (23)$$

V_0 = Opposing Potential ($I = 0$)

$\alpha = \angle(E_{kin}, \nu)$ e = electron charge Q = ion charge

$$C = \text{Capacitance} \quad \nu = \frac{1}{2\pi} \frac{1}{\sqrt{LC}} \sqrt{1 - \frac{C}{L} R^2}$$

$$\Rightarrow \text{Inductance } L = \frac{4\pi^2}{C} \left(\frac{e}{h} Q + \nu_0 \right)^2$$

$\Rightarrow$ Ionisation Energy of chemical element $E_i = h\nu = h \frac{\lambda}{c} = \hbar \omega = \frac{h}{k\lambda} \omega$

$\Rightarrow$ Energy released (gained) $E_{gain} = E_{pot} - E_i = mc^2 - h\nu$

¹Wirkungsquantum