

Project Guide

Tracking of an Autonomous Robot

Muhammad Emzir, Sakira Hassan

Department of Electrical Engineering and Automation
Aalto University, Finland

October 30, 2020

Contents

1	Introduction	2
2	Part I: Sensor modeling	3
2.1	Sensor model	3
2.1.1	Inertial measurement unit	3
2.1.2	Static IMU experiment	3
2.1.3	IMU calibration	4
2.1.4	Camera module calibration	4
2.1.5	Motor control	7
3	Part II: Localization	7
4	Part III: Tracking	9
4.1	Using IMU only	9
4.2	Tracking with both IMU and Camera	10
5	Reporting	10
6	Appendix	11
6.1	Connecting to the robot	11
6.2	Modules	12
6.2.1	IMU	12
6.2.2	Camera module	12
6.2.3	Motor control	13
6.2.4	Line sensor	13
6.2.5	Data & experiment checklist	14




Figure 1: DiddyBorg robot with camera module and IR detector.

1 Introduction

The aim of this project is to develop an algorithm for tracking an autonomous robot by using a set of sensors. The robot, a DiddyBorg rover-type robot, is programmed to follow a black line inside a closed area surrounded by walls. The robot is equipped with an inertial measurement unit (IMU), which is a combination of accelerometer, gyroscope, and magnetometer. In addition to the IMU, the robot is also equipped with an infra red detector, a motor controller, and a camera module. The IMU will measure the acceleration as well as the angular rate of the robot from three orthogonal body axis. The accelerometer measurements and the gyroscope measurements (angular velocity) from IMU are combined to obtain the acceleration in the inertial frame. The velocity and the position of the robot are then readily obtained by integration of the acceleration. However, as time increasing, the error will be accumulated, and hence the deviation from the actual position grows. The camera system will detect several predefined rectangles which contain unique QR codes with known position attached in the wall. This measurements can be used to correct the position estimate obtained by twice integration.

The sensors are connected to the main computer which is a Raspberry Pi. The Raspberry Pi system is responsible to handle all sensor measurement preprocessing and logging. It can also be used to transfer the recorded measurements data to other means.

The project consists of two parts. In the first part, we develop and verify the sensor model for the IMU and camera system. This includes the following steps:

- Derivation of the sensor model,
- Estimation of the model parameters.

In the second part of the project, we combine the sensor model developed in the first part with a dynamic model and a sequential estimation algorithm to obtain our final robot tracking system.

The project contains both theoretical and practical parts. In the practical part, you will be given measurement data (record log files) from different sensors. **You can find the information of log file for each task separately in Appendix 6.2.5.** You

also need to write two reports: one intermediate report on the first part and a final report which includes the results from both parts as well as improvements of the first part. The final grade of the project work will be based on the final report. On the course homepage, you can find more information about the peer review, deadlines, and the grading criteria ¹.

2 Part I: Sensor modeling

2.1 Sensor model

The robot is equipped by IMU, IR detection, camera systems, and motor control. The IR detection is used to detect a line pattern in the floor for tracking purposes, and it comes with built in calibration.

2.1.1 Inertial measurement unit

In this section, we will describe the sensor model of IMU. Inside an IMU, each individual sensor has the following linear equation; see for example [1, 2, 3].

$$\mathbf{y} = \mathbf{G}\mathbf{x} + \mathbf{b} + \mathbf{r}$$

The acceleration measurement in the body axis is can be written as:

$$\begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} k_x & 0 & 0 \\ 0 & k_y & 0 \\ 0 & 0 & k_z \end{bmatrix}^{-1} \begin{bmatrix} a_x \\ a_y \\ a_z \end{bmatrix} + \begin{bmatrix} b_x \\ b_y \\ b_z \end{bmatrix}, \quad (1)$$

where k_i, b_i, r_i , are the gain, bias, and noise, respectively in $i = \{x, y, z\}$ axis.

As the case of the accelerometers, the gyroscope also experiences the earth angular velocity, which may be used as a reference for calibration. However, for the case of MEMS gyroscope, the earth angular velocity is so small that it is buried in the sensor noise.

From the IMU measurement record log, we can determine the variance matrix of the IMU measurement noise. This matrix will be used later for tracking purpose.

2.1.2 Static IMU experiment

We can measure the IMU reading of a static robot using the python script provided in Appendix 6.2.1. We can obtain the bias of the gyroscope by placing the robot in a static position for a period of time. Then, we average the gyroscope readings to obtain the bias.

Task 1a. From the measurement record log file visualize the data. Read the Appendix 6.2.1 in order to understand what each column represents. What do you observe? Summarize what you have understood and write it down in your report.

Task 1b. Determine the bias of the gyroscope and write down the result in your report.

Task 1c. Determine the variance matrix of the IMU measurement noise and write down the result in your report.

¹Part of this guide is based on the previous year guide written by Dr. Roland Hostettler.

2.1.3 IMU calibration

To calibrate the accelerometer, we can depend on the assumption that the earth gravitational is fixed on a static object and we use the following simple procedure for every robot body axis:

- Turn on the robot, and run the python script for IMU (see Appendix).
- Place the robot in a firm horizontal support.
- Use a timer to record the log reading at each body axis, For example, 30s or 60s.
- Record the acceleration reading for the robot in up position, a_u in that direction.
- Rotate the robot 180° in the selected axis, and record the acceleration reading for the robot in up position, a_d .
- Calculate the gain for the selected axis as

$$k_i = \frac{a_u - a_d}{2g}.$$

Here, g is the gravity.

- Calculate the bias b_i for the selected axis By

$$b_i = \frac{a_u + a_d}{2}.$$

Task 2a. Plot the data from the measurement record log file. What did you observe? Is there any difference? Why it is so? Determine the gain k_i and bias b_i for each body axis $i = \{x, y, z\}$. Write down the results in your report.

Task 2b. Implement a static linear and nonlinear regression procedure as given in [1] or other scientifically based method. Write down the implemented method in your report. What is the reason behind choosing the method?

2.1.4 Camera module calibration

In this section, we will use a simple method to determine the distance of the robot relative to a specific wall. Assuming that the geometry of the confined area and the QR-code rectangles to be detected are fixed. Using additional measurement from the IMU, we can use the distance measurements we obtained from the camera to adjust the position estimate using the IMU only.

To determine the distance and attitude of the QR-codes to the camera, we can use the pinhole projection rule, which was first proposed by Brunelleschi at the early of the fifteenth century. It is a simplified mathematical model that describes the relationship between the coordinates of an object in a three dimensional space and its projection, assuming that the camera aperture is so tiny and there are no lenses used to focus the light; see Figure 3. Under this assumption, we have the following relation [4, Section 1.1.1]:

$$\begin{bmatrix} y_1 \\ y_2 \end{bmatrix} = -\frac{f}{x_3} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \quad (2)$$




Figure 2: Illustration of the robot and camera coordinate systems given by the right hand axis rule. Notice the camera coordinate system is parallel to the robot coordinate system




Figure 3: Illustration of a pinhole projection.




Figure 4: Relation between distance of QR-codes from the camera and detected height.

The image coordinate point (y_1, y_2) is given in pixel unit. At the sensor measurement logs, you will receive y_1 and y_2 in pixel units, as well as the unique number associated to each QR-code. We can convert these values into the position of the robot in the inertial frame. To do this, we need to estimate the focal length of the camera in pixel unit.

- Turn on the robot and run the python script for camera module (see Appendix).
- Wait until camera module ready.
- Prepare one QR-code only for the calibration.
- Place tape measure below the robot facing perpendicular to the wall with QR-code as close as possible until the QR-code is detected, and printed in the terminal. Write down the actual distance of the camera lens to the wall. You do not need to write the terminal QR code reading as they are stored in log file.
- Increase one or two cm, and hold for several seconds. Repeat this step until the QR-code cannot be read by the robot.
- Using the log file reading and Equation (2), we can determine the focal length f .

To get an insight of the focal length, plot one over the height against the recorded distance; you should get nearly linear relation; see Fig 4 . Then you can use the standard linear least-square regression to obtain the gradient and bias. Notice that the gradient k that you get is a multiplication of the QR-code length (cm) and the “actual” focal length in pixel.⁴

For each QR code detected, you can estimate the horizontal distance x_3 and direction ϕ from the QR-code center point to the robot using (2). Let y_1, y_2 are the center point of the QR-code, and h is the detected height of QR-code, all given in pixels. If the actual height of QR-code is given by h_0 , then we can measure the robot distance x_3 and heading ϕ using

$$x_3 = \frac{h_0 f}{h} + b, \quad (3)$$

where b is a bias and

$$\phi = \arctan\left(\frac{y_1}{f}\right). \quad (4)$$

Task 3a. There are two columns in the measurement record log file. The first represents the measured distance (in cm) and the second column represents the height (in pixel) measured from the terminal. You need to plot the data as described above and determine the gradient and bias. Write down the results in your report. Note that, you also need to consider the distance of the camera from the surface of the robot.

Task 3b. Determine the focal length in pixel from the Equation (3), given that the height h_0 of the QR-code is 11.5 cm.

2.1.5 Motor control

We can determine the speed of the robot. For this, we will use the script in Appendix 6.2.3. First, take a measuring tape to measure the distance and a stopwatch or timer to record each time lapse. Then, prepare the measuring tape in the floor in any direction, for example, 200cm. Now, place the robot at the beginning of the measuring tape. Start the script and record the time at every 30cm, for example, as the robot moves forward.

Task 4 There are two columns in the measurement record log file. The first represents the measured time (in s) and the second column represents the distance (in cm) measured from the measuring tape. You need to determine the speed of the robot. Write down the results in your report.

3 Part II: Localization

Now that you have both IMU and camera ready, you can use both of them to localize the robot position. This will serve as a validation to the measurement model of the camera derived before. Notice that although the camera axis is parallel to robot axis, the center position of the robot differs to the camera lens position. In the robot local axis, the camera lens position is fixed, but in global axis you will need to take account the direction of the robot in the global coordinate. The rotation matrix for a counterclockwise rotation of the 2×1 vector \mathbf{a} by an angle α around the z -axis is given by

$$\mathbf{R}(\alpha) = \begin{bmatrix} \cos(\alpha) & -\sin(\alpha) \\ \sin(\alpha) & \cos(\alpha) \end{bmatrix}$$

and thus, the rotated vector is

$$\mathbf{a}' = \mathbf{R}(\alpha)\mathbf{a}.$$

Place the robot with camera facing one of the walls. Make sure that the camera is able to detect as many as QR-codes possible (See Figure 5). You might need to use a smaller size QR-code if the camera does not able to detect more than one QR-code at the same




Figure 5: Detected QR-codes by CameraModule script.

time. Check the appendix on how to adjust the python script for this case. We measure the exact global position for a reference. Also, we measure the QR-codes position in global coordinate.

For each QR-code, the measurement model for camera is defined as

$$\begin{aligned} d_i &= \sqrt{(x_c - x_i)^2 + (y_c - y_i)^2} \\ \phi_i &= \arctan((x_c - x_i)/(y_c - y_i)) - \psi \end{aligned} \quad (5)$$

Now from Equation (3) and (4), we get

$$\begin{aligned} d_i &= \frac{h_0 f}{h_i} \\ \phi_i &= \arctan\left(\frac{C_{x,i}}{f}\right) \end{aligned} \quad (6)$$

Therefore, we have

$$\begin{aligned} h_i &= \frac{h_0 f}{\sqrt{(x_c - x_i)^2 + (y_c - y_i)^2}} \\ C_{x,i} &= f \tan(\arctan((x_c - x_i)/(y_c - y_i)) - \psi) \\ \mathbf{y} &= \mathbf{h}(\mathbf{x}). \end{aligned} \quad (7)$$

- Task 5a.** Describe the relation of these coordinates in your report; see Figure 6 as a reference.
What is the minimum number of different QR-codes that are needed to estimate the position and attitude of the robot in global coordinate?
- Task 5b.** Next, use nonlinear (weighted) least square technique to estimate the position and heading of the robot. To do this, you need to derive the Jacobian of measurement model that you choose and the measurement variance matrix for the camera module.




Figure 6: Illustration of the global coordinate system, QR-codes with known positions in global coordinate, and the robot local acceleration. When the robot camera heads to the y axis, the global angle of the robot equal to zero.

4 Part III: Tracking

In the first part of the project, we derived the sensor model, developed an estimator for the unknown model parameters, and verified that the model is indeed useful for tracking purposes. In this second part, we extend these results and develop the models and algorithm necessary for tracking the robot when moving. A prerequisite for this is that all the tasks in Part I have been completed successfully. In this part, the tasks are to:

- develop a dynamic model,
- adjust the sensor model,
- implement a filtering algorithm,
- validate the algorithm.

4.1 Using IMU only

In Section 2.1, the basic sensor model for the camera module was developed. Next, a dynamic model that describes the motion of the robot has to be chosen.

Task 6a. Choose a dynamic model to model the motion of the robot. The robot moves in two dimensions and hence, a two dimensional model is needed. Once you have chosen a suitable motion model, discretize it using an appropriate discretization method. The inputs to the motor in terms of pulse width modulation are recorded

which gives the velocity and the gyroscope gives the turning rate. You should use these inputs in your dynamic model.

Task 6b. Do dead-reckoning (i.e., prediction) based on speed measurements from motor control and turn rate measurements from gyroscope.

Task 6c. Take measurements and validate the tracking algorithm. Start by evaluating the method based on the simple test track provided and then move on to more complex scenarios if time permits. Since there is no ground truth available in this case (unless you devise a good strategy to find a ground truth), you have to make enough convincing experiments to show that the algorithm actually works. How accurate can you track the robot? How far from the sensor can the robot be tracked?

Hint:

- See the course slides for dynamic models. Also make sure that the sign of the gyroscope measurement is correct and that its units are converted to radians.

4.2 Tracking with both IMU and Camera

Now incorporate camera detection of QR-codes into the filtering algorithm. Make sure you place each QR-codes in known position on global coordinate, as it will be used inside the filtering algorithm. Notice that at each time-stamp, there could be more than one QR-code detected. Further, time-stamp from camera log files might differ totally with the timestamp you get from IMU.

Task 7. Use appropriate discretization to combine these two measurements.

Hint:

- The model and filtering algorithms may be quite sensitive to the tuning parameters (spectral density of the process noise and measurement noise). For the process noise, think about what it actually represents physically and relate it to the robots motion. For the measurement noise, you may estimate it based on the model parameter estimation data and possibly add some margin to account for modeling errors.

5 Reporting

To report the technical results of a project is an important skill. Reporting should be done using concise and accurate language, including enough detail such that someone with the same education and background can understand, interpret, and reproduce your work. Your derivations, results, and interpretations should be backed up by data, illustrations, and so forth. Furthermore, also make sure that you answer and discuss the questions raised in this guide.

Your project report should include at least the following²:

²You are free to use whatever structure you prefer, as long as it is consistent and logical.

- An abstract that briefly summarizes what you have done and what the results are,
- a brief introduction to the project and the problem that you are solving,
- derivation of the model,
- calibration procedures that are used (if any).
- description of the estimation method(s) used for parameter estimation, validation, and tracking,
- the results,
- conclusions and/or a summary,
- references (if applicable).

For the intermediate report, not all of the above items might apply yet. As a guide, you could include a brief description of the robot and sensor models, explanatory data analysis of the log file, and plans to implement localization algorithm and tracking.

6 Appendix

In this section we will describe how to connect to the robot platform via SSH, and how to run the simulation.

6.1 Connecting to the robot

To connect to the robot, you could use SSH connection either directly via terminal, or using VNC (preferred one).

- Turn on the robot using switch located at the bottom of the robot.
- Find the IP address of the robot. Check the MAC address written in the upper part of the robot. Then use an ip scanner to find the associated IP address. If you facing a difficulty to find the IP address, you could also connect a monitor to the robot via an HDMI port located behind the camera (unscrew top part of the robot first). Then connect usb keyboard to robot's USB ports. Then execute `ifconfig`.
- Once you found the IP address of the robot, you can connect to the robot via SSH, with user name:pi, password: pipipi. You can also automate this process as below:

```
ssh-keygen -t rsa -b 4096
ssh-copy-id pi@your_raspberry_ip_address
```

- The necessary files are located in

```
~/Git/DiddyBorg_Sensor_Fusion
```

We have also prepared a set of QR-codes in `~/Git/DiddyBorg_Sensor_Fusion/QR-codes` folder. Please pull from `Git` at least once when you just receive the robot to make sure that you have the unmodified version of program.

6.2 Modules

To run the module change the directory to `~/Git/DiddyBorg_Sensor_Fusion/data`. All log files will be stored in this folder. There are three files that you need to run the robot properly:

- `IMU.py`
- `CameraModule.py`
- `MotorControl.py`

These files stored in `~/Git/DiddyBorg_Sensor_Fusion/DiddyBorg_python`. To check options available for each of these files, execute:

```
python3 ./DiddyBorg_python/module_xxx.py --help
```

Pressing Escape button will immediately stop the python scripts, except on `CameraModule.py` while not showing any video output. Ideally, you should execute `IMU.py` command until it is ready, and then `CameraModule.py`. Once the camera is ready, then execute `MotorControl.py`.

You can modify (and encouraged!) these files to accomodate your need. Should you need to reset the configuration to default, you can always pull from Git.

```
git pull
```

6.2.1 IMU

After changing the directory to `~/Git/DiddyBorg_Sensor_Fusion/data`, to collect reading from IMU, you can run

```
python3 ./DiddyBorg_python/IMU.py
```

You can also specify the output file name using `--output=some_files.csv`. Default sampling times is 0.05, and you can modify it with `--sampling=0.1`.

The IMU log files column are, the Timestamp in ms, linear acceleration in x,y,z axis given in gravity unit, roll and pitch angle from accelerometer in degree, gyroscope x,y,z in degree/s, and magnetometer field strength in x,y,z axis in Gauss unit.

6.2.2 Camera module

To collect reading from IMU, you can execute the following command

```
python3 ./DiddyBorg_python/CameraModule.py
```

You can also specify the output file name using `--output=some_files.csv`. If you have access to X-server when connecting to the robot (using VNC, for example), you can also specify `--show` to show the video stream from the camera module. You can also specify the QR-code length in cm using `--qrlength=xx` where the input is given in cm. The IMU log files column are, the Timestamp in ms, QR-code number, center position (x,z) of QR-code in pixel, width and height of QR-code in pixel, raw distance from camera to QR-code in cm, raw attitude of the QR-code relative to the camera in deg.




Figure 7: IR Line Detector

6.2.3 Motor control

To run the motor

```
python3 ../Diddyborg_python/MotorControl.py
```

You can also specify the output file name using `--output=some_files.csv`. The IMU log files column are, the Timestamp in ms, first input from 0-1 as a percentage of pulse width modulation (PWM), and the second input.

6.2.4 Line sensor

Line Sensor has to be calibrated when its tried in a different material for every first time once its calibrated for the black line not necessary for following events. To calibrate it for the black line click the calibration button once and while the LEDs blink robot should be waved like the arrow showed in the following picture. Make sure all five sensors are exposed to both regions (black and white). The mode indicator lighting in the module stands for inverse detected region power on. Make sure the mode indicator is off for whole operation.

6.2.5 Data & experiment checklist

No.	Task	File location	Notes
Part I			
1	Static IMU experiment	data/task1/	To check the static bias and the covariance.
2	IMU calibration	data/task2/	To determine the gain and the bias of the accelerometers, gyroscope, etc.
3	Camera module calibration	data/task3/	To determine the focal length and bias.
4	Motor control	data/task4/	To determine the speed of the robot.
Part II			
5	Localization	data/task5/	To estimate the position and attitude of the robot.
Part III			
6	Tracking with IMU	data/task6/	To develop a tracking algorithm.
7	Tracking with IMU and camera	data/task6/	To develop a tracking algorithm.

References

- [1] U. Qureshi and F. Golnaraghi, “An algorithm for the in-field calibration of a MEMS IMU,” IEEE Sensors Journal, vol. 17, no. 22, pp. 7479–7486, nov 2017.
- [2] P. Patonis, P. Patias, I. N. Tziavos, D. Rossikopoulos, and K. G. Margaritis, “A fusion method for combining low-cost IMU/magnetometer outputs for use in applications on mobile devices,” Sensors, vol. 18, no. 8, p. 2616, aug 2018.
- [3] K. Papafotis and P. P. Sotiriadis, “MAG.i.c.AL. – a unified methodology for magnetic and inertial sensors calibration and alignment,” IEEE Sensors Journal, pp. 1–1, 2019.
- [4] D. A. Forsyth and J. Ponce, Computer Vision: A Modern Approach, 2nd ed. Pearson, 2011.