

MSDS 데이터 추출 검증 보고서

Document ID: MOCK_MSDS_006

데이터 검증 통계

섹션	DB 키워드 수	그대로 발견	매칭률
Section 1 (제품 정보)	2	2	100.0%
Section 2/3 (성분 정보)	10	10	100.0%
전체 합계	12	12	100.0%

출처별 상세 통계

Section 1 (제품 정보)

products.company_name: 1/1 (100.0%)

products.product_name: 1/1 (100.0%)

Section 2/3 (성분 정보)

ingredient_synonyms.synonym: 4/4 (100.0%)

ingredients.cas: 2/2 (100.0%)

- `ingredients.conc_raw`: 2/2 (100.0%)
- `ingredients.name`: 2/2 (100.0%)

데이터베이스 내용

Section 1 - 제품 정보

필드	값	출처
Product Name	CARADOL EP500-11	<code>products.product_name</code>
Company Name	Shell Chemical LP	<code>products.company_name</code>

Section 2/3 - 성분 정보

Name	CAS	EC Number	Concentration	Synonyms
Propoxylated Sorbitol	52625-13-5	None	50 - 60	D-Glucitol, propoxylated
Propoxylated glycerol	25791-96-2	None	40 - 50	Glycerol, propoxylated (MW 3000)

하이라이트 범례

- `ingredient_synonyms.synonym`
- `ingredients.cas`

- ingredients.conc_raw
- ingredients.name
- products.company_name
- products.product_name

슬라이싱된 구간

Extracted Section 1

Product name

:

CARADOL EP500-11

Product code

:

U1705

Synonyms

:

Polyol

****Manufacturer or supplier's details****

Company

: ****Shell Chemical LP****

PO Box 576

HOUSTON TX 77001

USA

SDS Request

: 1-800-240-6737

Customer Service

: 1-855-697-4355

****Emergency telephone number****

Chemtrec Domestic (24 hr)

: 1-800-424-9300

Chemtrec International (24

hr)

: 1-703-527-3887

****Recommended use of the chemical and restrictions on use****

Recommended use

: Use for the manufacture of polyurethane products.

Restrictions on use

:

This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information

: CARADOL is a registered trademark of Shell trademark Man-

agement BV.

Extracted Section 2/3

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Propoxylated Sorbitol	D-Glucitol, propoxylated	52625-13-5	50 - 60
Propoxylated glycerol	Glycerol, propoxylated (MW 3000)	25791-96-2	40 - 50

Chemical name

Synonyms

CAS-No.

Concentration (% w/w)

Propoxylated Sorbitol D-Glucitol,

52625-13-5

50 -60

propoxylated

Propoxylated glycerol Glycerol,

25791-96-2

40 -50

propoxylated

(MW 3000)

전체 원본 문서 (슬라이싱 구간 표시)

>>> page 1

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

****SECTION 1. IDENTIFICATION****

Extracted Section 1

Product name

:

CARADOL EP500-11

Product code

:

U1705

Synonyms

:

Polyol

****Manufacturer or supplier's details****

Company

: ****Shell Chemical LP****

PO Box 576

HOUSTON TX 77001

USA

SDS Request

: 1-800-240-6737

Customer Service

: 1-855-697-4355

****Emergency telephone number****

Chemtrec Domestic (24 hr)

: 1-800-424-9300

Chemtrec International (24

hr)

: 1-703-527-3887

****Recommended use of the chemical and restrictions on use****

Recommended use

: Use for the manufacture of polyurethane products.

Restrictions on use

:

This product must not be used in applications other than the above without first seeking the advice of the supplier.

Other information

: CARADOL is a registered trademark of Shell trademark Management BV.

****SECTION 2. HAZARDS IDENTIFICATION****

****GHS classification in accordance with 29 CFR 1910.1200****

Based on available data this substance / mixture does not meet the classification criteria.

****GHS label elements****

Hazard pictograms

: No Hazard Symbol required

Signal word

:

No signal word

Hazard statements

:

PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

1 / 16

>>> pend

>>> page 2

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

Precautionary statements

:

****Prevention:****

No precautionary phrases.

****Response:****

No precautionary phrases.

****Storage:****

No precautionary phrases.

****Disposal:****

No precautionary phrases.

****Other hazards which do not result in classification****

none

The classification of this material is based on OSHA HCS 2012 criteria.

****SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****

Substance / Mixture

: Mixture

****Hazardous components****

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Propoxylated Sorbitol	D-Glucitol, propoxylated	52625-13-5	50 - 60
Propoxylated glycerol	Glycerol, propoxylated (MW 3000)	25791-96-2	40 - 50

Chemical name

Synonyms

CAS-No.

Concentration (% w/w)

Propoxylated Sorbitol D-Glucitol,

52625-13-5

50 -60

propoxylated

Propoxylated glycerol Glycerol,

25791-96-2

40 -50

propoxylated

(MW 3000)

****SECTION 4. FIRST-AID MEASURES****

General advice

:

Not expected to be a health hazard when used under normal conditions.

If inhaled

:

No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact

:

Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact

:

Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed

:

In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms
and effects, both acute and
delayed

:

Does not pose an acute hazard under normal conditions of
use.

2 / 16

>>> pend

>>> page 3

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

Protection of first-aiders

:

When administering first aid, ensure that you are wearing the
appropriate personal protective equipment according to the
incident, injury and surroundings.

Indication of any immediate
medical attention and special
treatment needed

:

Treat symptomatically. Following cases of gross over-
exposure, investigation of liver, kidney and eye function may
be advisable. Records of such incidents should be maintained
for future reference.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

:

Large fires should only be fought by properly trained fire fight-
ers.

Alcohol-resistant foam, water spray or fog. Dry chemical pow-
der, carbon dioxide, sand or earth may be used for small fires
only.

Unsuitable extinguishing
media

:

Do not use water in a jet.

Specific hazards during fire-
fighting

:

Will only burn if enveloped in a pre-existing fire.

Hazardous combustion products may include:

Carbon dioxide

Unidentified organic and inorganic compounds.

Toxic gases

Carbon monoxide.

Specific extinguishing meth-

ods

:

Standard procedure for chemical fires.

Further information

:

Clear fire area of all non-emergency personnel.

All storage areas should be provided with adequate fire fighting facilities.

Keep adjacent containers cool by spraying with water.

Special protective equipment

for firefighters

:

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

****SECTION 6. ACCIDENTAL RELEASE MEASURES****

Personal precautions, protec-

tive equipment and emer-

gency procedures

:

Observe all relevant local and international regulations.

Avoid contact with skin, eyes and clothing.

Avoid inhaling vapour and/or mists.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Environmental precautions

:

Remove all possible sources of ignition in the surrounding

3 / 16

>>> pend

>>> page 4

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

area.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Use appropriate containment to avoid environmental contamination.

Ventilate contaminated area thoroughly.

Methods and materials for
containment and cleaning up

:

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely

For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Proper disposal should be evaluated based on regulatory status of this material (refer to Chapter 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

Additional advice

: For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

****SECTION 7. HANDLING AND STORAGE****

Technical measures

:

Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Advice on safe handling

:

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

Use local exhaust extraction over processing area.
Avoid unintentional contact with isocyanates to prevent uncontrolled polymerisation.
Avoid contact with skin, eyes and clothing.
Air-dry contaminated clothing in a well-ventilated area before laundering.
Do not empty into drains.
Handling Temperature:
4 / 16

>>> pend

>>> page 5

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

Ambient.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Avoidance of contact

:

Avoid contact with isocyanates, copper and copper alloys, zinc, strong oxidizing agents, and water.

Product Transfer

: Lines should be purged with nitrogen before and after product transfer. Keep containers closed when not in use.

Conditions for safe storage

:

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Storage period

: 24 Months

Further information on storage stability

: Prevent all contact with water and with moist atmosphere.

Tanks must be clean, dry and rust-free.

Prevent ingress of water.

Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat.

Nitrogen blanket recommended for large tanks (capacity 100 m³ or higher).

Drums should be stacked to a maximum of 3 high.

Storage Temperature:

Ambient.

Storage should be handled at temperatures such that viscosities are less than 500 cSt; typically at 25-50 °C.

Tanks should be fitted with heating coils in areas where the ambient temperatures are below the recommended product handling temperatures. Heating coil skin temperatures should not exceed 100 °C.

Packaging material

: Suitable material: Stainless steel., For container paints, use epoxy paint, zinc silicate paint.

Unsuitable material: Copper., Copper alloys.

Specific use(s)

: Not applicable

Ensure that all local regulations regarding handling and storage facilities are followed.

****SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION****

****Components with workplace control parameters****

Contains no substances with occupational exposure limit values.

5 / 16

>>> pend

>>> page 6

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**CARADOL EP500-11**

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

****Biological occupational exposure limits****

No biological limit allocated.

****Monitoring Methods****

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Meth-

ods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

****Engineering measures****

:

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

Adequate ventilation to control airborne concentrations.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

****Personal protective equipment****

Respiratory protection

:

No respiratory protection is ordinarily required under normal

6 / 16

>>> pend

>>> page 7

****SAFETY DATA SHEET****

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

Hand protection

Remarks

:

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye protection

:

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection

:

Skin protection is not ordinarily required beyond standard work clothes.

It is good practice to wear chemical resistant gloves.

Protective measures

:

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Hygiene measures

:

Wash hands before eating, drinking, smoking and using the toilet.

Launder contaminated clothing before re-use.

****Environmental exposure controls****

General advice

: Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

Information on accidental release measures are to be found in 7 / 16

>>> pend

>>> page 8

****SAFETY DATA SHEET****

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

section 6.

****SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****

Appearance

:

Viscous liquid.

Colour

: clear

Odour

: odourless

Odour Threshold

: Not relevant

pH

:

ca. 9

Melting point/freezing point

:

Data not available

Boiling point/boiling range

:

Data not available

Flash point

:

> 100 °C / 212 °F

Evaporation rate

: Data not available

Flammability (solid, gas)

:

Not applicable

Upper explosion limit / upper
flammability limit

:

Data not available

Lower explosion limit / Lower
flammability limit

:

Data not available

Vapour pressure

:

ca. 0.003 Pa (20 °C / 68 °F)

Relative vapour density

:

Data not available

Relative density

:

Data not available

Density

:

ca. 1,108 kg/m³ (20 °C / 68 °F)

Solubility(ies)

Water solubility

:

Miscible.

Partition coefficient: n-
octanol/water

:

log Pow: < 1

Auto-ignition temperature

:

> 300 °C / 572 °F

Decomposition temperature

: < 300 °C / 572 °F

Viscosity

Viscosity, dynamic

:

5.380 mPa.s (20 °C / 68 °F)

8 / 16

>>> pend

>>> page 9

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

Viscosity, kinematic

:

Data not available

Explosive properties

:

Not classified

Oxidizing properties

:

Not applicable

Surface tension

:

Data not available

Conductivity

: Electrical conductivity: > 10,000 pS/m, A number of factors,
for example liquid temperature, presence of contaminants,
and anti-static additives can greatly influence the conductivity
of a liquid, This material is not expected to be a static accumu-
lator.

Molecular weight

:

Data not available

****SECTION 10. STABILITY AND REACTIVITY****

Reactivity

: The product does not pose any further reactivity hazards in
addition to those listed in the following sub-paragraph.

Chemical stability

: No hazardous reaction is expected when handled and stored
according to provisions

Hygroscopic.

Possibility of hazardous reac-
tions

:

Polymerises exothermically with di-isocyanates at ambient
temperatures.

The reaction becomes progressively more vigorous and can
be violent at higher temperatures if the miscibility of reaction
partners is good or is supported by stirring or by the presence
of solvents.

Reacts with strong oxidising agents.

Conditions to avoid

:

Heat, flames, and sparks.

Product cannot ignite due to static electricity.

Incompatible materials

: Avoid contact with isocyanates, copper and copper alloys, zinc, strong oxidizing agents, and water.

Hazardous decomposition

products

: Unknown toxic products may be formed.

****SECTION 11. TOXICOLOGICAL INFORMATION****

Basis for assessment

: Information given is based on product testing, and/or similar products, and/or components.

****Information on likely routes of exposure****

Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

****Acute toxicity****

9 / 16

>>> pend

>>> page 10

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

****Product****:****

Acute oral toxicity

: LD50 : > 5000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity

: Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity

: LD50 : > 5000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

****Skin corrosion/irritation****

****Product****:****

Remarks: Not irritating to skin.

****Serious eye damage/eye irritation****

****Product****:****

Remarks: Not irritating to eye.

****Respiratory or skin sensitisation****

****Product****:****

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

****Germ cell mutagenicity****

****Product****:****

: Remarks: Not mutagenic.

****Carcinogenicity****

****Product****:****

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

****IARC****

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

****OSHA****

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

****NTP****

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

10 / 16

>>> pend

>>> page 11

****SAFETY DATA SHEET****

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

****Reproductive toxicity****

****Product****:****

:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

****STOT - single exposure****

****Product****:****

Remarks: Based on available data, the classification criteria are not met.

****STOT - repeated exposure****

****Product****:****

Remarks: Based on available data, the classification criteria are not met.

****Aspiration toxicity****

****Product****:****

Not an aspiration hazard.

****Further information****

****Product****:****

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

****SECTION 12. ECOLOGICAL INFORMATION****

Basis for assessment

: Incomplete ecotoxicological data are available for this product.

The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.

****Ecotoxicity****

****Product:****

Toxicity to fish (Acute toxicity)

: LC50: > 100 mg/l

Remarks: Practically non toxic:

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)

: EC50: > 100 mg/l

Remarks: Practically non toxic:

Toxicity to algae (Acute toxicity)

: EC50: > 100 mg/l

Remarks: Practically non toxic:

Toxicity to fish (Chronic toxicity):

Remarks: Data not available

11 / 16

>>> pend

>>> page 12

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**CARADOL EP500-11**

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

icity)

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

:

Remarks: Data not available

Toxicity to microorganisms
(Acute toxicity)

:

IC50: > 100 mg/l

Remarks: Practically non toxic:

Based on available data, the classification criteria are not met.

****Persistence and degradability****

****Product:****

Biodegradability

: Remarks: Not readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

****Bioaccumulative potential****

****Product:****

Bioaccumulation

: Remarks: Does not have the potential to bioaccumulate significantly.

****Mobility in soil****

****Product:****

Mobility

:

Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

****Other adverse effects****

no data available

****SECTION 13. DISPOSAL CONSIDERATIONS****

****Disposal methods****

Waste from residues

:

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or water.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

12 / 16

>>> pend

>>> page 13

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

Contaminated packaging

:

Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Send to drum recoverer or metal reclaimer.

Dispose in accordance with prevailing regulations, preferably
to a recognized collector or contractor. The competence of
the collector or contractor should be established beforehand.

****SECTION 14. TRANSPORT INFORMATION****

****National Regulations****

****US Department of Transportation Classification (49 CFR Parts 171-180)****

Not regulated as a dangerous good

****International Regulations****

****IATA-DGR****

Not regulated as a dangerous good

****IMDG-Code****

Not regulated as a dangerous good

****Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code****

Pollution category

: Not applicable

Ship type

: Not applicable

Product name

: Not applicable

****Special precautions for user****

Remarks

: Special Precautions: Refer to Chapter 7, Handling & Storage,
for special precautions which a user needs to be aware of or
needs to comply with in connection with transport.

****Additional Information****

****:**This product may be transported under nitrogen blanketing.**

Nitrogen is an odourless and invisible gas. Exposure to nitro-
gen may cause asphyxiation or death. Personnel must ob-
serve strict safety precautions when involved with a confined
space entry.

****SECTION 15. REGULATORY INFORMATION****

****EPCRA - Emergency Planning and Community Right-to-Know Act****

*: This material does not contain any components with a CERCLA RQ.

****SARA 304 Extremely Hazardous Substances Reportable Quantity****

This material does not contain any components with a section 304 EHS RQ.

****SARA 302 Extremely Hazardous Substances Threshold Planning Quantity****

This material does not contain any components with a section 302 EHS TPQ.

****SARA 311/312 Hazards****

: No SARA Hazards

13 / 16

>>> pend

>>> page 14

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

**CARADOL EP500-11**

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

****SARA 313****

: This material does not contain any chemical components with
known CAS numbers that exceed the threshold (De Minimis)
reporting levels established by SARA Title III, Section 313.

****Clean Water Act****

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act,
Section 311, Table 117.3.

****US State Regulations****

****California Prop. 65****

This product does not contain any chemicals known to State of California to cause cancer, birth
defects, or any other reproductive harm.

****Other regulations:****

The regulatory information is not intended to be comprehensive. Other regulations may apply
to this material.

****The components of this product are reported in the following inventories:****

AICS

:

Listed

DSL

:

Listed

IECSC

:

Listed

ENCS

:

Listed

KECI

:

Listed

NZIoC

:

Listed

PICCS

:

Listed

TSCA

:

Listed

TCSI

:

Listed

****SECTION 16. OTHER INFORMATION****

****Further information****

NFPA Rating (Health, Fire, Reactivity)

0, 1, 0

****Full text of other abbreviations****

Abbreviations and Acronyms

: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

14 / 16

>>> pend

>>> page 15

****SAFETY DATA SHEET****

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

****CARADOL EP500-11****

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling
COC = Cleveland Open-Cup
DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level
OE_HPV = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of Chemicals

15 / 16

>>> pend

>>> page 16

SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

CARADOL EP500-11

Version

2.1

Revision Date:

04/25/2018

SDS Number:

800001008935

Print Date: 09/03/2022

Date of last issue: 05/08/2015

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

Revision Date

: 04/25/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

16 / 16

>>> pend