Master's Thesis

Human-Guided Local Robotic Polishing via Joint Motion–Force Representation and Force-Conditioned Imitation Learning

인간의 영역 지정과 동작–힘 결합 표현 및 힘 조건부 모방학습을 활용한 국소 로봇 폴리싱

Eunseop Song

송은섭

The Graduate School

Sungkyunkwan University

Department of Intelligent Robotics

2027

Human-Guided Local Robotic Polishing via Joint Motion–Force Representation and Force-Conditioned Imitation Learning

Eunseop Song

A Master's Thesis Submitted to the
Department of Intelligent Robotics
and the Graduate School of Sungkyunkwan University
in partial fulfillment of the requirements
for the degree of Master of Science in Engineering

October 2026

Supervised by

Hyouk Ryeol Choi
Major Advisor

Thesis Examination

Eunseop Song

Committee Chair	Jachoon Koo
Committee Member	Hyung Pil Moon
Major Advisor	Hyouk Ryeol Choi

Scheduled submission	18 November 2026
Scheduled examination	25 November 2026
Expected degree award	February 2027

The Graduate School

Sungkyunkwan University

Contents

List of Tables **iv**

List of Figures **v**

Abstract **vi**

Notation and Terminology **viii**

1 Introduction **1**
1.1 Surface Rework and Local Polishing 1
1.2 What Remains after a Region Is Specified 2
1.3 Rules, Replay, and Learned Generation 3
1.4 Research Questions 3
1.5 Contributions 4
1.6 Scope and Organization 5

2 Related Work **6**
2.1 Robotic Polishing and Surface Coverage 6
2.2 Human Instruction and Local Task Specification 7
2.3 Rules and Demonstration Replay 7
2.4 Force in Demonstrations, Observations, and Actions 8
2.5 Observation-Conditioned Sequence Generation 9
2.6 Contact Regulation and Positioning of This Work 10

3 Problem Formulation and System Overview **11**
3.1 A Local Motion–Force Task 11
3.2 Human Guidance and the Region Interface 12
3.3 Module Responsibilities 13
3.4 Physical Platform and Observations 13
3.5 Stain-Centered Learning and Direction Transfer 16
3.6 Supported Conditions and Observable Success 18

4 Motion–Force Demonstration and Dataset Construction **20**
4.1 Teaching as a Source of Temporal Process Structure 20
4.2 VR Registration and Tracker-to-Tool Conversion 20
4.3 Synchronized Recording and the Meaning of Time 22
4.4 Signal Stages and Force Processing 23

4.5 Force Frames and Common-Axis Analysis . . . 24
4.6 Relative Coordinates, Episodes, and Data Partitions . . . 26
4.7 A Representative Motion–Force Pairing . . . 28

5 Force-Conditioned Motion–Force Skill Learning 30
5.1 Learning Objective and Observation Interface . . . 30
5.2 Implemented Observation Encoder . . . 31
5.3 Flow Matching Sample Construction . . . 31
5.4 Flow Integration and Physical Timing . . . 34
5.5 Separating Force Output from Force Observation . . . 35
5.6 Training Completion and Checkpoint Selection . . . 36

6 Robot Execution and Contact-Task Evaluation 39
6.1 From a Skill Sequence to Robot Commands . . . 39
6.2 Shared Pose Conditioning and Plan Connection . . . 40
6.3 Command Rates, Limits, and Force Gating . . . 40
6.4 Existing Lower-Level Contact Regulation . . . 42
6.5 Approach and Contact-Start Synchronization . . . 43
6.6 The Executed E1 Contact Procedure . . . 43
6.7 Completion, Observation Support, and Time Windows . . . 44
6.8 Execution Timing and Checks . . . 46
6.9 E3: Image-Based Stain-Area Evaluation . . . 46
6.10 Protocol Boundaries across E1–E3 . . . 47

7 Experimental Evaluation 48
7.1 Evaluation Questions and Recorded Cohorts . . . 48
7.2 Platform and Metric Boundaries . . . 49
7.3 E1: Strategy Comparison . . . 50
7.4 E2: Force-Information Ablation . . . 52
7.5 E3: Spatial Transfer of the Learned Skill . . . 54
7.6 Answers to the Research Questions . . . 59

8 Discussion and Extensions 60
8.1 What the Implemented Connection Establishes . . . 60
8.2 When Rules and Replay Are Sufficient . . . 61
8.3 Roles of Human Guidance and Relative Representation . . . 62
8.4 What Force Output and Observation Contribute . . . 62
8.5 Procedural Completion and Surface Quality . . . 63
8.6 Development Extensions . . . 64
8.7 Scope and Limitations . . . 64

9 Conclusions 66

Bibliography 68

A Coordinates, Signals, and Reproduction **70**
A.1 Pose and Force Signal Definitions 70
A.2 Learning and Temporal Parameters 70
A.3 Data and Analysis Reproducibility 71

B Experiment Versions and Provenance **73**
B.1 Selected Models and Dataset 73
B.2 Primary E1 Version and Membership 74
B.3 Historical E1 Development and Height-Only Replay 74
B.4 E2 Versions and the A4 Correction 76
B.5 Sources for Implemented Extensions 77

C Individual Outcomes and Evidence Boundaries **78**
C.1 E1 Primary Executions 78
C.2 E2 All Attempts 78
C.3 Cohort Membership and Interpretation 80
C.4 Original E1 Strategy Traces and Additional Cases 80
C.5 E2 Force Traces and Transition Cases 82
C.6 E1/E2 Qualitative Image Evidence 86

D Additional R Diagnostic and E3 Image Archive **89**
D.1 Additional R Executions and Source Precision 89
D.2 E3 Main-Run Pixel Areas 90
D.3 Occlusion, Interruption, and P2 Exclusion 90
D.4 Reused Segmentation Sensitivity and Procedure Diagnostics 92
D.5 Evidence Availability and Reproduction 94

E Development Extensions **95**
E.1 Execution-Derived Dose 95
E.2 Blending and Adaptive Execution Assets 97

국문요약 **98**

List of Tables

2.1 Force interfaces in related work 9
2.2 Task specification and evaluation scope 10

3.1 Module responsibilities 15

4.1 Teaching and learning signal stages 24

5.1 Architecture and training settings 33
5.2 E2 input, supervision, and external target 36
5.3 Selected checkpoint epochs 37

7.1 Strategy and information configurations 50
7.2 E1 strategy summary 50
7.3 Original R and additional R retiming 51
7.4 E2 corrected completion, timing, and peaks 53
7.5 E2 all-attempt force and travel 54
7.6 E3 actual registered placements 54
7.7 E3 image-based stain-area removal 56

A.1 Force signal definitions 71
A.2 Distinct clocks and sampling settings 72

B.1 Selected model identifiers 73
B.2 Historical 14 October E1 results 75
B.3 Historical E1 height-only replay 75

C.1 Individual primary E1 outcomes 79
C.2 Individual E2 corrected task outcomes 79
C.3 Original 15 October E1 comparison 80
C.4 Original C5 and additional diagnostic C6 81

D.1 Additional R diagnostic runs 89
D.2 Original additional-R run identifiers 90
D.3 Individual E3 main-run image areas 91
D.4 Executed P2 archive records 92
D.5 Archived E3 threshold sensitivity 92

E.1 Status of inherited extensions 97

List of Figures

3.1 Marked local region and registration 13
3.2 System overview and module interfaces 14
3.3 Archived robot apparatus photograph 15

4.1 Actual teaching-camera frames 21
4.2 Coordinate-processing and direction-transfer chain 22
4.3 Recorded force-processing stages 25
4.4 Episode lengths and dataset partition 27
4.5 Representative motion–force teaching 29

5.1 Implemented policy architecture 32
5.2 E2 force-information learning and execution 37

6.1 Command processing and contact execution 41

7.1 E1 completion and excess-force results 51
7.2 E2 timing, force peaks, and travel 53
7.3 E3 registered positions and directions 55
7.4 E3 individual image-area removal results 56
7.5 E3 N/P1 original RGB and ink masks 57
7.6 E3 D1/D2 original RGB and ink masks 58

B.1 E1 exit-height reference sensitivity 76

C.1 All E1 measured force traces 81
C.2 All E1 measured XY trajectories 82
C.3 Original E1 C5 and additional diagnostic C6 83
C.4 All E2 measured force traces 84
C.5 E2 A4 and B4 transition cases 85
C.6 First-run E1 initial and final snapshots 87
C.7 Frames from the first E2 C video 88

D.1 Lowest observed E3 removal, D2-3 91
D.2 D1-4 retained interruption and occlusion evidence 93
D.3 P2 retained final occlusion example 93

E.1 Uncalibrated execution heatmap 96

Abstract

Human-Guided Local Robotic Polishing via Joint Motion–Force Representation and Force-Conditioned Imitation Learning

Local surface rework requires coordinating tool motion, contact force, and time within a selected region. This thesis connects human region specification and demonstrations to an executable local robotic polishing skill. A joint motion–force representation temporally pairs Cartesian tool pose with teaching-derived target force. Conditional Flow Matching generates action sequences from RGB, pose, measured force, and force history. A shared executor conditions the references for an existing force-feedback controller. Center-relative position learning and an explicit planar direction adapter support reuse at registered placements.

Three evaluations address strategy, force information, and spatial reuse. E1 compares rules, force-inclusive demonstration replay (T), and the force-conditioned policy (C). Each strategy completes the prescribed contact–loaded-pass–exit procedure in five observed runs. A separate additional rule-retiming diagnostic (R^*) is kept distinct from the original rule cohort. Mean completion times $\pm$ sample SD are 24.840$\pm$1.321, 12.897$\pm$0.041, and 13.420$\pm$2.630 s for R^*/T/C. T has lower time dispersion and excess-force exposure than C. Retiming reduces the rule mean by 4.697 s (15.9%) without matching measured mean speed.

E2 separates pose-only learning with an external force target (A), motion–force learning with masked force observations (B), and motion–force learning with measured-force conditioning (C). A completes four of five attempts; B/C complete five each. Completed operator-based intervals are

17.65±1.20, 18.81±0.40, and 15.83±0.56 s, with $n = 4, 5, 5$. C's mean is 2.98 s (15.8%) shorter than B's. These descriptive intervals use a different completion protocol from E1.

E3 reuses the same C checkpoint without new teaching or retraining. Original RGB reprocessing with unchanged saved annotations, ROI, and gray threshold reproduces the board-marker ink-area measurements. N/P1/D1/D2 contain 20 selected runs and 19 evaluable pairs. Removal means ± sample SD are 100.00±0.00, 97.55±2.49, 98.12±3.75, and 93.67±6.60%, with $n = 5, 5, 4, 5$; final tool occlusion remains unquantified.

The results establish an executable human-guided skill, observed force-configuration differences, and reuse with registration and direction adaptation in the tested planar placements. Rules and replay remain effective fixed-task alternatives. Image-area reduction measures visible marker removal, separately from procedural completion; metal removal depth, mass, roughness, and micro-scratch restoration are not independently measured.

Keywords: Robotic Polishing, Human Guidance, Motion–Force Representation, Force-Conditioned Imitation Learning, Spatial Skill Transfer

Notation and Terminology

Symbol	Meaning
B, V, T, E	Robot-base, VR tracking, tracker, and calibrated tool/TCP frames.
${}^{B}T_{E}$	Homogeneous pose of frame E in frame B.
p, ρ, R	Position (mm), rotation vector (rad), and its rotation matrix.
$c \in \mathbb{R}^2$	Fixed task-origin XY coordinates in the robot base (mm).
$\theta_{\mathrm{live}}, \theta_{\mathrm{ref}}, \alpha$	Live stain-axis angle, teaching reference angle, and their wrapped alignment angle (rad).
$R_2(\alpha), u$	Planar rotation matrix and center-relative XY position aligned with the teaching direction (mm).
$q = [p^{\mathsf{T}}, \rho^{\mathsf{T}}]^{\mathsf{T}}$	Six-dimensional Cartesian pose; the code name `qpos` does not denote joint angles here.
$f^{\mathrm{demo}}, f^{\mathrm{meas}}$	Recorded teaching force and measured robot force (N). Superscripts identify their roles; frames are stated separately.
$f^{\pi}, f^{\mathrm{sent}}, f^{\mathrm{applied}}$	Policy-predicted, executor-transmitted, and controller-applied target forces (N). The last is not available as a synchronized recorded time series.
I_k, o_k	RGB observation and complete policy observation at physical sample k.
a_k, A_k	One action and a future action sequence.

Symbol	Meaning
H, L	Action horizon (128 samples) and force-history length (30 samples) for the evaluated checkpoints.
$t, k, \Delta t$	Physical elapsed time (s), sample index, and physical sample interval.
s, z_s, v_θ	Dimensionless flow time, noisy normalized action sequence, and learned vector field.
$g(t)$	Operational contact gate from measured robot-base F_z.
$Q_{95}, J_{\text{excess}}$	Common teaching base-force reference (N) and excess-force integral (N s).
R, T, C	E1 rule, teaching replay, and force-conditioned learned providers.
R^*	Additional five-run E1 rule diagnostic on 19 October, distinct from original R.
A, B, C	E2 motion-only, learned motion–force without force observation, and learned motion–force with force observation.
N, P1, D1, D2	Main E3 nominal, position, and direction conditions; P2 remains in the executed archive only.
$A_{\text{before}}, A_{\text{after}}$	Initial and residual target-ink pixel areas in the same E3 surface ROI.

Task specification identifies the local region and task setting. A *motion–force skill* is a temporally organized sequence of pose and target-force references. *Contact regulation* is the lower-level response to force feedback while executing those references. *Procedural completion* denotes the specified contact–traversal–exit sequence. It does not denote verified scratch removal or a roughness requirement. E3's image-based removal is a separate ink-area metric. The letter C names a condition within each experiment; E1, E2, and E3 executions are separate cohorts even where the same checkpoint is reused.

Chapter 1

Introduction

1.1 Surface Rework and Local Polishing

Surface finishing changes the condition of a component through controlled interaction between a tool and its surface. Robotic polishing therefore involves more than reaching a geometric pose: tool contact, feed motion, and processing duration jointly determine the operation. Research on curved-surface polishing combines tool-path planning with force-controlled processing, while coverage planning accounts for the contact region produced by the tool and workpiece geometry [1,2]. These studies establish an industrial and technical context for treating movement and contact as coupled process decisions.

Uniform processing of a whole surface and local rework around a selected region have different spatial objectives. A coverage operation seeks to treat a prescribed surface systematically. A local operation concentrates movement and loading around a limited target while retaining an approach and an exit. In the latter case, the relevant questions include where contact begins, which part of the region is traversed under load, how force changes during movement, and how the tool unloads and rises afterward. A path that reaches both endpoints can still omit one of these procedural requirements.

Interactive surface-treatment systems provide a practical precedent for combining human decisions, geometric planning, and robot execution [3]. The present thesis adopts a specific division of work. A person indicates the local region, and demonstrations provide examples of how the

tool moves and loads that region. The robot executes a generated or prescribed motion–force skill through an existing force-control system. This division is motivated by the equipment and task setting, rather than a general assertion that fine defects cannot be detected automatically.

The experimental surface contains visible markings that make the local task observable in the available RGB stream. Such board-marker markings supply a spatial processing cue. E1/E2 measure contact-task execution, and E3 additionally measures image-based stain-area reduction from saved before/after photographs. The markings are not calibrated models of metal scratch depth, and erasing a mark is not equivalent to restoring a measured metal surface profile.

1.2 What Remains after a Region Is Specified

An identified region is an incomplete processing instruction. It can supply an origin, extent, and visual context without specifying a force schedule or the time spent in each phase. For example, traversing a narrow region with a constant recipe force and replaying a recorded pass can share the same region but differ in approach timing, loaded motion, repeated movement, and exit. The region alone does not select between these strategies.

Human guidance enters through a marked region and task registration. Position is learned relative to the stain center; an implemented adapter aligns live XY and the policy image with the teaching direction and restores generated paths afterward. This supports reuse across planar placements and directions. The policy uses RGB and a fixed interaction ROI, with no external segmentation mask. E1 fixes the origin, and both E1/E2 disable direction alignment. E3 evaluates registered planar positions and directions, enabling alignment for its direction conditions.

The second source of human guidance is a temporally paired demonstration. A demonstrator supplies tool movement and interaction force together, so that approach, processing, and release have a common temporal organization. This supplies information that a geometric boundary does not encode. It does not provide labels for defect severity or an independent measurement of remaining material. Learning from those demonstrations is intended to generate an executable skill, not to infer an unobserved surface state by assumption.

1.3 Rules, Replay, and Learned Generation

Several valid methods can turn a spatial instruction into a polishing sequence. Rules can combine an approach, a prescribed path, a force recipe, and a departure. Replay can reuse the position, orientation, force, and timing of a successful teaching episode. A learned policy can instead generate a new sequence from the current image, pose, and force history. The existence of several legitimate choices makes a comparison necessary: the insufficiency of geometry alone does not imply that imitation learning is the only solution.

The lower-level controller also contributes feedback in every method. It regulates the physical interaction for the supplied target and operating mode. It does not independently choose the complete spatial and temporal strategy. Conversely, removing measured force from the learned policy does not remove the controller's force feedback. Distinguishing these two uses of force is necessary to interpret both baseline comparisons and ablations.

Generative sequence policies offer a way to model temporally related actions from demonstration. Action chunking and diffusion-based policies motivate predicting a sequence rather than an isolated next action [4, 5]. Here, conditional Flow Matching is the implemented generator. Its role is to produce normalized pose–force sequences; coordinate restoration and command conditioning remain explicit parts of execution. The thesis studies the combined representation and execution structure without proposing Flow Matching, force sensing, or a recurrent encoder as new algorithms.

1.4 Research Questions

Three questions organize the evaluation.

RQ1: For the same local task, how do rule-based planning, force-inclusive demonstration replay, and force-conditioned imitation learning differ in procedural completion, completion time, and force use?

RQ2: How do learning a target-force sequence and observing measured force at the policy input relate to completion, execution time, phase progression, and force use?

RQ3: What image-based stain-area removal is observed when the same policy is applied, without new teaching or retraining, to task regions at different planar positions and directions?

E1, *Strategy Comparison*, addresses RQ1 with the original five nominal runs per strategy on 15 October 2026 and a separately identified five-run R retiming diagnostic on 19 October, denoted R^*. E2, *Force-Information Ablation*, addresses RQ2 with five attempts per condition on 13 October and the corrected A4 outcome. E3, *Spatial Transfer of the Learned Skill*, addresses RQ3 through saved-image analysis of N/P1/D1/D2: 20 selected runs, of which 19 permit whole-stain image evaluation. P2's five executed runs remain in the 25-run archive but are excluded from the main removal evaluation because of final tool occlusion. Height-change robustness and independently measured metal surface-quality improvement remain outside the evaluated scope.

1.5 Contributions

The thesis makes three connected contributions at the system and experimental levels.

1. It formulates a local polishing task that links human region specification with time-aligned motion–force demonstrations. It realizes stain-centered position learning and an optional direction-alignment/inverse-restoration path, distinguishes force signal roles and frames, and states the procedural scope of the resulting skill.

2. It realizes observation-conditioned generation and execution of coupled pose–force sequences. The implemented policy, data construction, command conditioning, and existing contact controller form an explicit path from demonstration to robot action.

3. It connects strategy execution, force-information composition, and spatial reuse through three complementary evaluations. These quantify procedural completion, protocol-specific timing, force use, and E3 image-based ink-area reduction. Original trials, incomplete attempts, and image-unavailable cases remain traceable, with additional diagnostics separated from the original comparisons.

These contributions concern the connection between a particular task, representation, generator, and execution interface. They do not assert novelty for the individual encoder, relative-coordinate operation, controller, or logging state machine.

1.6 Scope and Organization

The implementation supports stain-centered learning and direction transfer for the marked-surface task. E1/E2 use a fixed tool, fixture, and region. E3 tests registered planar position/direction changes and quantifies board-marker area reduction, without establishing arbitrary-shape, curved-surface, or height robustness. Metal removal depth, mass, roughness, and micro-scratch restoration are not independently measured. There is no autonomous defect-completion detector or learned termination head.

Chapters 2 and 3 position and formulate the task. Chapters 4 and 5 explain teaching and learning; Chapter 6 distinguishes the execution and evaluation protocols. Chapter 7 reports E1–E3, Chapter 8 discusses findings and extensions, and Chapter 9 concludes.

Chapter 2

Related Work

2.1 Robotic Polishing and Surface Coverage

Surface-treatment planning and contact control address complementary aspects of a finishing operation. Mohsin et al. [1] combine tool-path planning, force-controlled contact, and process-parameter optimization for curved-surface polishing. Their evaluation includes an eyeglass-frame application and surface-quality measurements. This supports the practical importance of considering force and motion together, while also illustrating the additional measurements needed to make a claim about the finished surface.

Schneyer et al. [2] segment freeform geometries into regions with compatible machining strategies. Their method uses tool and workpiece geometry, varies the contact point on a finishing disk, and adapts path spacing to the contact area. The geometric region in that work organizes coverage of a known surface. The local region in the present study instead supplies a human-selected processing target, after which the choice of a temporal motion–force sequence remains.

These approaches make geometric planning a substantive baseline rather than a weak alternative. When geometry, material, and process requirements admit a stable recipe, explicit planning can directly express the intended treatment. The narrower question considered here is whether demonstrations and online observations add useful execution behavior in a specified local task. The current experiments do not compare surface finish against the published systems under matched tooling or materials.

2.2 Human Instruction and Local Task Specification

RoboGrind [3] integrates surface scanning, defect identification, interactive robot-program construction, planning, and force-controlled treatment. It also evaluates fiberglass wind-turbine-blade refurbishment. Its user interaction helps select and parameterize processing, while geometric planning and hybrid force–position control execute the resulting program. This is a useful example of human participation within an automated surface-treatment system.

The present work uses a simpler instruction channel: the person marks or specifies the local region and provides demonstrations. Region registration is separated from learning how to traverse and load it. This choice avoids requiring a fine-scratch detector in the available setup. It neither replaces the broader perception problem nor demonstrates that a marked region carries sufficient information for an optimal process strategy.

A task-relative origin also has a limited but clear purpose. It removes an absolute XY offset from the pose representation so that the local motion can be restored at a registered origin. An image-to-plane homography provides a registration mechanism, whereas rotation canonicalization is a separate transformation. Neither a task-origin subtraction nor a calibrated image mapping alone demonstrates orientation generalization. The experiments must establish that claim independently.

2.3 Rules and Demonstration Replay

Rules specify a finite program by composing a path, force schedule, and phase transitions. Replay preserves an example's motion–force association and timing without fitting a policy. In a repetitive, narrowly specified task, these methods can be sufficient and easier to inspect than a learned generator. Their adequacy is an empirical property of the task and execution environment.

The distinction between replay and learning is particularly relevant here because the replay baseline contains force as well as motion. A comparison against pose-only replay would mix the value of retaining force demonstrations with the value of generating from observations. E1 instead retains the selected demonstration's force sequence. Both rules and replay also retain contact-start

synchronization and lower-level force feedback. They are therefore fixed strategy providers with feedback during execution, rather than robots operating without contact sensing.

2.4 Force in Demonstrations, Observations, and Actions

DexForce [6] makes a particularly relevant distinction between observed motion and an action capable of producing the demonstrated force. It measures fingertip forces during kinesthetic demonstrations and constructs force-informed position targets using a quasi-static force–displacement relation. These targets are replayed through Cartesian impedance control to collect robot-only visual demonstrations. Its diffusion policy observes images and, in the force-enabled condition, measured forces and moments; it outputs force-informed positions rather than a separate desired-force vector. The paper also ablates force observations. This motivates treating force in supervision and force in observation as different design choices. Its dexterous-hand tasks and control interface differ from the tool-pose and target-force interface studied here.

ForceMimic [7] records motion and wrench with a handheld device. Its HybridIL method conditions trajectory generation on point-cloud features and TCP pose, predicts pose and wrench parameters, and executes them with position or orthogonal hybrid force–position primitives. The described policy input does not list measured-force history. Thus, its force-inclusive action interface should not automatically be interpreted as the same force-observation design used by condition C in this thesis. Its reported task is vegetable peeling, rather than a human-specified polishing region.

Admittance visuomotor policy learning [8] explicitly uses vision, proprioception, and contact force to generate action trajectories and desired contact forces, followed by admittance execution. FoAR [9] takes another route: force/torque information and a future-contact predictor guide reactive refinement of position actions. It evaluates wiping, peeling, and chopping with an end-effector position-control interface. These works illustrate that force can inform an observation, a learned reference, or a deployment correction. Those roles should be compared directly rather than grouped under a single force-aware label.

Table 2.1 compares these force interfaces.

Table 2.1: Force interfaces verified from the cited methods. "Not reported" denotes an input absent from the described policy interface, rather than proof that the broader system has no such signal.

Method	Policy force observation	Learned action interface	Execution interface
DexForce [6]	Forces and moments; ablated	Force-informed fingertip positions	Cartesian impedance
ForceMimic [7]	Not reported in described input	Pose and wrench	Position / hybrid force–position primitives
Admittance policy [8]	Contact force	Motion and desired force	Admittance controller
FoAR [9]	Force/torque	Position actions; future-contact prediction	Reactive position refinement
This thesis, C	Three force components and history	Tool pose and target force	Shared conditioner and existing force controller

2.5 Observation-Conditioned Sequence Generation

ACT [4] predicts action chunks to reduce the effective decision horizon in demonstration learning. Diffusion Policy [5] models a conditional distribution over action sequences and executes them with receding-horizon updates. Both provide methodological context for predicting temporally related actions. They do not, by themselves, define a polishing force recipe or prove an advantage over a suitable replay baseline.

Flow Matching [10] trains a vector field along a prescribed probability path and generates samples by numerical integration. The implementation in this project uses linear interpolation between Gaussian noise and a normalized demonstrated action chunk. Its vector-field loss and integration rule are specified in Chapter 5. Choosing this generator determines how sequences are learned and sampled; it does not determine how physical contact is regulated.

The image encoder uses the existing DINOv3 visual representation [11]. Global and fixed interaction-region features condition the generator together with pose and force history. A pretrained visual model is an implementation component, not evidence that the policy recognizes scratch depth or remaining material. The present experiments evaluate the assembled policy rather than isolating the backbone's contribution.

Table 2.2: Task specification and verified evaluation scope of representative work. These are descriptive comparisons of interfaces and tasks.

Work	Task/region specification	Demonstration or evaluation scope
Geometric coverage [2]	Tool and workpiece geometry	Segmentation and coverage of freeform geometry
RoboGrind [3]	Scanning and interactive program parameters	Laboratory and blade-refurbishment treatment
DexForce [6]	Task-specific object arrangements	Kinesthetic fingertip motion/force; dexterous manipulation
ForceMimic [7]	Visual scene and TCP state	Handheld motion/wrench capture; peeling
This thesis	Human-specified marked region; frozen origin	Tool pose/force/RGB; strategy and force-information comparisons; planar reuse with image-based ink-area evaluation

2.6 Contact Regulation and Positioning of This Work

Interaction control distinguishes the dynamic relation between motion and force from the selection of a task strategy. Impedance control describes how mechanical interaction should respond to motion [12]; admittance control uses measured interaction to alter a motion reference through virtual dynamics [13]. The deployed lower-level system is an existing element shared within the experimental comparisons. Its role is to execute the selected force and motion references.

This thesis occupies the connection between local human task specification, paired demonstrations, observation-conditioned sequence generation, and a common robot execution environment. Table 2.2 summarizes the task-level comparison. The evaluation asks whether the assembled choices change procedural execution, and which changes remain attributable to force output or force observation within the available design. It does not rank methods from different publications by their reported success rates.

Chapter 3

Problem Formulation and System Overview

3.1 A Local Motion–Force Task

The task formulation connects a spatial instruction to a physical operation. A region identifies the intended working area, while a skill supplies the temporally related references needed to approach, traverse under load, and exit. Keeping these descriptions separate makes it possible to compare different skill providers without changing the meaning of the task.

Let $\Omega \subset \mathbb{R}^2$ denote the selected local region in the robot-base XY plane and let $c = [c_x, c_y]^\mathsf{T}$ be a frozen task origin in millimeters. The region is specified by a person through the physical marking or the experiment's region parameters. A registered RGB image I_k, tool pose $q_k = [p_k^\mathsf{T}, \rho_k^\mathsf{T}]^\mathsf{T}$, and measured force f_k^{meas} describe the available execution context. Orientation is stored as a rotation vector in radians. The action representation is

$$a_{k+j} = \begin{bmatrix} p_{k+j}^{\mathrm{ref}} \\ \rho_{k+j}^{\mathrm{ref}} \\ f_{k+j}^{\mathrm{target}} \end{bmatrix} \in \mathbb{R}^9, \qquad j = 0, \ldots, H-1. \tag{3.1}$$

The reference describes a future tool pose and target force for the execution system. Pose6 denotes Cartesian tool position and orientation, including in fields named `qpos`; it does not denote six joint angles. Images and joint torques are not action outputs. The learned pose-only condition uses the first six components and obtains its force reference externally.

A *local polishing skill* is the sequence $A_k = (a_k, \ldots, a_{k+H-1})$, together with its physical sample timing and the task registration used to restore absolute coordinates. Pairing movement and force in this sequence represents when a target load accompanies a location or motion phase. It does not imply that the robot will realize the exact demonstrated velocity or force at every instant. Those quantities also depend on command conditioning, controller dynamics, and the physical contact.

3.2 Human Guidance and the Region Interface

Human guidance contributes both a spatial specification and examples of temporal behavior. The visible mark gives a practical cue for the local operation. The region-registration implementation can detect a dark marked region within a calibrated image area, map it to the working plane, and freeze its center and principal-axis direction. Figure 3.1 illustrates that interface using a genuine archived camera image.

The evaluated E1 comparison fixes $c = (457.4, 375.0)$ mm for all providers. Its evaluation band is specified independently by endpoints and width. The origin is a registration datum; it need not coincide with the midpoint of that band. In E2, the existing per-run origin interface is retained. Neither experiment uses a height-condition label as a policy input.

The policy's external stain-mask option is disabled for the evaluated checkpoints. Instead, the image encoder derives a fixed TCP interaction-region feature from RGB. The physical marking, the registered origin, the evaluator's spatial band, and the encoder's image ROI are therefore four different objects. Conflating them would incorrectly imply that the network is explicitly constrained to the evaluator's band or that it receives a segmentation of the complete processing strategy.




Figure 3.1: Archived camera view of a marked local region and its registration overlay. The colored outlines belong to the existing detection display. This is an example of spatial instruction and image registration, not a validated micro-scratch detector or the fixed-origin E1 trial image.

3.3 Module Responsibilities

Figure 3.2 shows the implemented path from human guidance to evaluation. A provider supplies a sequence, a common execution layer converts it into conditioned commands, and the lower-level controller produces the physical interaction. Measured robot pose and force provide feedback. Evaluation observes this interaction through its own procedural criteria.

Table 3.1 assigns the component responsibilities.

3.4 Physical Platform and Observations

The robot interface is the UR10 system identified by the deployed `ur10skku` topics and Cartesian command services. The teaching side uses a Vive tracker, calibrated tool pose, force/torque sensing, and a RealSense RGB stream. Robot execution records TCP pose from robot feedback and a processed six-axis wrench. The policy uses only the three force components. Torques remain useful logged diagnostics but are not policy inputs or actions for these checkpoints. Figure 3.3 shows the archived physical apparatus.




Figure 3.2: Implemented system overview. Solid arrows show data or execution flow. The dashed completion-to-executor arrow applies to E1's automatic finish/hold request; it does not synthesize an exit motion. E2 uses operator termination, and E3 removal is evaluated offline from saved photographs. The diagram is conceptual and editable.

Table 3.1: Responsibilities of the human and system components.

Component	Responsibility
Human operator	Specify the local task, demonstrate motion and loading, set up the specimen, and provide recorded field observations.
Teaching system	Register tracked tool pose and record paired RGB, pose, force, and receipt-time evidence.
Skill provider	Supply a time-related reference sequence using a rule, a fixed demonstration, or a conditioned generator.
Common executor	Restore coordinates, interpolate references, connect plans, condition commands, and manage the existing finish/hold procedure.
Lower-level controller	Regulate physical contact using the supplied target force and measured state.
Task evaluator	Recognize E1's contact procedure, retain E2's operator outcome, or quantify E3's saved-image ink-area reduction under their separate definitions.




Figure 3.3: Genuine archived apparatus photograph dated 7 August 2026, showing the robot-mounted processing tool and fixture. Only image rotation and proportional resizing were applied. It illustrates the local experimental platform; it is not presented as a photograph taken during the October E1 or E2 runs.

The available records support a description of a robot-mounted local processing tool acting on a marked plate. They do not specify a complete process qualification, including measured spindle speed, material alloy, abrasive grade, or pre/post roughness. The experiments use measured robot interaction to answer procedural questions and E3 saved photographs to evaluate ink-area reduction. These limits do not prevent reproducing the learning and execution interfaces, but they restrict claims about manufacturing outcomes.

3.5 Stain-Centered Learning and Direction Transfer

The representation separates the local movement pattern from its placement on the plate. Its training-data transformation expresses observation and action positions relative to a frozen stain center:

$$\widetilde{p}_k = [p_{k,x} - c_x,\ p_{k,y} - c_y,\ p_{k,z}]^{\mathsf{T}}, \qquad \widetilde{\rho}_k = \rho_k. \tag{3.2}$$

This transformation retains the base-axis orientation and absolute Z coordinate. A single-direction demonstration consequently teaches a center-relative movement pattern in its original reference direction. The implementation additionally supports transferring that learned pattern to another in-plane stain direction through coordinated observation and action transformations. Training on centered positions and aligning directions at inference are two connected parts of the transfer mechanism; the dataset converter itself does not rotate the training episodes.

3.5.1 Center and Axis from the Specified Region

The reference-free registration path detects dark pixels within a configured plate area, excludes the tool area, and maps the retained pixels to robot-base XY coordinates using each image's pose-dependent planar homography. It pools these mapped points across the registration frames. Starting from their coordinate-wise median, four iterations retain the nearest 85% of points and update the center by their mean. A singular-value decomposition of the trimmed, centered point cloud supplies the dominant strip axis. Its angle $\theta_{\mathrm{live}} \in [0, \pi)$ is measured in base-plane radians. The

axis is unoriented: the same strip has directions differing by π, rather than an identified stroke-start endpoint.

The resulting center and optional angle are frozen together for the episode. An operator-supplied live angle is also supported. The direction therefore enters through explicit task registration rather than a learned output head. A center recovered from the visible mark identifies the intended task; it does not estimate defect depth or determine the desired force schedule.

3.5.2 Observation Alignment and Path Restoration

Let θ_{ref} denote the base-plane axis associated with the teaching reference direction. The implemented alignment angle and planar rotation are

$$\alpha = \mathrm{wrap}_{\pi}(\theta_{\mathrm{ref}} - \theta_{\mathrm{live}}), \qquad \mathrm{wrap}_{\pi}(\delta) = ((\delta + \pi/2) \bmod \pi) - \pi/2, \tag{3.3}$$

$$R_2(\alpha) = \begin{bmatrix} \cos\alpha & -\sin\alpha \\ \sin\alpha & \cos\alpha \end{bmatrix}.$$

The wrapped angle lies in $[-\pi/2, \pi/2)$. For an absolute measured XY position $p_{k,xy}$, the policy-side position is

$$u_k = R_2(\alpha)(p_{k,xy} - c). \tag{3.4}$$

Center subtraction is applied first, followed by alignment to the teaching direction, and then by the checkpoint's numerical normalization. After the policy generates a sequence and the action bounds are inverted, each predicted XY position $\widehat{u}_{k+j}$ is restored as

$$p^{\mathrm{ref}}_{k+j,xy} = c + R_2(-\alpha)\widehat{u}_{k+j}. \tag{3.5}$$

The same inverse operation restores the stored demonstration-start XY pose before initial alignment. Thus both the live observation and generated path use the same frozen center and angle. Disabling direction alignment gives $\alpha = 0$ and reduces these equations to the translation-relative path used in E1/E2.

The single-camera policy image can also be rotated in plane about the configured TCP-ROI center, using the alignment angle and a configurable image-coordinate sign. The implementation uses bilinear image interpolation and reflected borders. This operation changes the image supplied to the policy while retaining the original view for recording and display. It adapts the visible direction to the reference view; a planar image rotation does not establish complete perspective or lighting invariance.

Only XY position is rotated by this adapter. Z, tool rotation-vector channels, target-force channels, and measured-force history retain their existing conventions. The method transfers a planar stroke direction while preserving the learned tool-posture and force interfaces; it is not a full rigid-frame transformation of pose and wrench. Its spatial role is distinct from observation-conditioned generation of the local motion–force sequence.

The current launch defaults leave direction alignment disabled. When enabled, the declared reference angle is 132°, image rotation is enabled, and the maximum accepted alignment magnitude is 65°. These are configurable reference and operating values, not a measured generalization range; the dataset name containing "90deg" is not used to infer the base-axis reference angle. If no live angle is available or the configured magnitude is exceeded, the implementation retains translation-only operation. Chapter 4 distinguishes these implemented transfer operations from the particular dataset and settings used in the measured comparisons.

3.6 Supported Conditions and Observable Success

The E1/E2 datasets and runtime settings use center-relative XY coordinates with direction alignment disabled. E3 reuses the same C checkpoint and normalizer at registered planar placements, with observation XY/image alignment and generated XY inverse restoration enabled for D1/D2. Its position and direction changes are listed in Chapter 7; they describe task registration rather than independent precision surface metrology.

E1 defines observable success as contact formation, a continuous loaded ordered traversal of the fixed band, and a simultaneous unloaded upward exit. E2 uses the documented operator-based completion interpretation, corrected for the interrupted A4 attempt. E3 measures segmented

board-marker ink-area reduction; image evaluability is independent of the automatic procedure label. These quantities are not pooled into one success statistic.

There is no learned termination output in the evaluated policy. A generated upward movement may reflect the demonstration's temporal structure. Recognition that the procedural exit has occurred belongs to the evaluator in E1 or to the operator's stopping decision in E2. Neither establishes that all defects have been removed. This distinction maintains a clear boundary between the generated skill and the state of the physical surface.

Chapter 4

Motion–Force Demonstration and Dataset Construction

4.1 Teaching as a Source of Temporal Process Structure

The purpose of teaching is to supply the motion and loading that remain unspecified by a local region. A demonstration records a tool's approach, motion through the working region, and departure together with the interaction force. This pairing supplies a temporal example for either direct replay or policy supervision. It does not include an independently measured defect-depth trajectory or a label that certifies material-removal completion.

The teaching system combines Vive tracking, a calibrated tool-pose publisher, force/torque sensing, and a RealSense RGB stream. The archived collection interface records six pose components and the first three force components. The paired data used by the evaluated models have a single RGB camera. Figure 4.1 shows actual frames from the selected replay episode's source, rather than a rendered apparatus or a substitute robot.

4.2 VR Registration and Tracker-to-Tool Conversion

The recorded pose must refer to the tool rather than the tracker housing. Let V be the tracking frame, T the tracked rigid body, E the tool/TCP frame, and B the robot base. The nominal rigid




Figure 4.1: Actual teaching-camera RGB frames associated with episode 29 at stored indices 0, 85, 150, and 400. The corresponding source is merged episode `ep_0003`, recorded on 19 August 2026. The view shows the tool and marked plate during the recorded operation. It does not show the full tracker or sensor assembly.

coordinate chain is

$$^{B}T_{E}(t) = {}^{B}T_{V}\,{}^{V}T_{T}(t)\,{}^{T}T_{E}. \tag{4.1}$$

Figure 4.2 summarizes the coordinate-processing chain. The fixed transforms identify the tracking world with the robot base and remove the tracker-to-tool offset. Translation is expressed in millimeters, while the final orientation is converted to a rotation vector in radians.

The implementation includes more than one rigid transform. Its calibration utilities solve the registration and tool offset, project rotations to valid rotation matrices, and support a planar correction and a bounded XY-dependent position residual. The tracker publisher converts OpenVR translation from meters to millimeters before applying the downstream calibration chain. It right-multiplies the configured spatial-angle alignment and applies the selected tool-offset convention. The published `calibrated_pose` is the final tool pose used by the recorder; the raw tracker rotation is not substituted for it in force-axis reconstruction.

The available calibration YAML records a 47-sample fit, planar correction, and a quadratic XY residual. Its stored residual RMS changes from 4.809 to 3.179 mm for that fit. These are




Figure 4.2: Implemented coordinate-processing roles, shown as an editable conceptual diagram. Calibration establishes the tool pose; center-relative learning and optional direction alignment register the local movement pattern. The last two boxes show the inference transfer in Equations (3.4) and (3.5), disabled in E1/E2 and enabled for the E3 direction conditions. Only XY positions are rotated; tool orientation and force channels retain their conventions.

calibration-fit diagnostics, not an independent accuracy test of every demonstration or October execution. The source also contains a configurable final constant offset. Consequently, a single conceptual frame-chain diagram is useful for understanding the registration, while the archived parameter file remains necessary for reproducing its numerical convention.

4.3 Synchronized Recording and the Meaning of Time

The source merged HDF5 identifies its schema as multimodal synchronized recording, its master as camera 0, and its clock as subscriber-receive Unix time. The camera observation supplies the common sample time. Pose and force are associated through receive-time buffers, with a recorded maximum synchronization error parameter of 0.05 s. The archive retains the source times, interpolation indicators, and pose/force synchronization errors for each paired sample.

These timestamps describe software receipt and pairing. They are not hardware exposure timestamps or the original force-sensor acquisition times. Their value is that the construction of a paired sample is explicit and can be inspected. Their limitation is that transport delay and sensor latency cannot be removed simply by assigning all signals to one image time.

The representative source episode records a nominal 30 Hz grid, 443 paired frames, and the original `sample_time_unix` array. The compact learning file retains the paired images and signals but not that full time array. For the replay baseline and the teaching plots, the source episode is recovered using the compact file's `source_h5` and `source_episode` attributes. This preserves the actual paired time axis instead of reconstructing it solely from the nominal rate.

4.4 Signal Stages and Force Processing

The word raw depends on where a signal enters the pipeline. The recorder's `raw_ft` is already a decoded and published measurement after the configured sign, startup-zero, and gravity-processing path. It is raw relative to the recorder's offline filter. It is not an uncorrected packet from the force sensor.

The teaching publisher applies its configured sensor decoding and sign convention, startup mean zeroing, selected publisher filtering, and delta-gravity compensation before publishing the wrench. The recorder then applies native-axis force filtering. In the representative archived episode, the force filter is an exponential moving average with $\alpha = 0.2$,

$$\bar{f}_k = \alpha f_k + (1 - \alpha)\bar{f}_{k-1}. \tag{4.2}$$

The stored pose is processed through the existing Hampel and difference-regularized smoothing pipeline. The archived episode reports no pose EMA, no approach slowdown, and retiming factor one. These are properties of the selected recorded episode; optional processing branches in the current recorder are not assumed to have been active.

Table 4.1 distinguishes the recording, cleanup, and normalization stages.

Table 4.1: Teaching and learning signal stages. Normalization changes scale for the network; it does not perform physical calibration.

Stage	Meaning and use
Published / recorder raw	Decoded and compensated force paired with calibrated pose; preserved as `raw_ft` and `raw_position`.
Filtered recording	Existing pose processing and force EMA; paired images and source-time mapping retained.
Learning cleanup	Derived force fields modified by the specified native-axis cleanup; pose and RGB preserved.
Normalized tensors	Training-split bounds map pose and force channels to the network scale. B then masks its force-conditioning tensors.

The 12 October force-cleanup dataset is a derived copy. It preserves the 42 episodes' images and pose fields, sets negative native F_z values to zero, and sets all three force components to zero where the associated stored $z > 175$ mm. Signed F_x, F_y remain unchanged in the other samples. The same rules apply to observation and action force fields. This height rule is an offline preprocessing convention tied to the stored coordinate system, not a new real-time contact detector or an estimate of material-removal depth.

Figure 4.3 shows these stages for the representative episode. Learning nonnegative targets does not impose a nonnegative output constraint on the generator. The archived model checks include negative unconditioned force predictions in some chunks; the runtime must therefore be described from its actual gating and command-processing code, rather than by assuming cleanup enforces a physical output bound.

4.5 Force Frames and Common-Axis Analysis

The existing force correspondence analysis supplies a resolved relation between teaching published axes and the calibrated tool frame:

$$R_{E\leftarrow\mathrm{pub}} = I, \qquad f_B(t) = R_{B\leftarrow E}(t)\, f_{\mathrm{pub,processed}}(t). \tag{4.3}$$




Figure 4.3: Actual force-processing stages for teaching episode 29. The upper panel compares post-publisher recorder raw force, offline EMA, and the learning cleanup in native axes. The lower panel rotates the complete cleanup force vector to robot-base axes using its paired tool orientation. These are different signal stages; none is a new physical calibration.

The second relation is posture dependent. All three force components are rotated using the calibrated tool rotation. Sign, zero, and gravity corrections are already present in the published vector and are not applied again. Translating the XY task origin does not rotate force.

Robot feedback follows a different processing chain: startup zeroing, the archived moving-average stage, a fixed sensor-to-TCP rotation, TCP gravity correction, and TCP-to-base rotation before publication and copying into the current-force topic. The executor's recorded force is therefore already in robot-base axes. Re-rotating that CSV would be incorrect.

Common-axis reconstruction makes the recorded teaching distribution and measured robot-base component comparable for an empirical force-exposure statistic. It does not recover an unlogged controller-applied target or establish a force-tracking error. It also does not imply that training tensors were retrospectively rotated. The evaluated dataset keeps native teaching force, while the inference adapter reads the selected robot-force components directly before normalization. This numerical input convention is retained when reporting the actual evaluated implementation. A common-frame policy-training ablation was not performed.

4.6 Relative Coordinates, Episodes, and Data Partitions

The compact representation subtracts the stored stain center from observation and action XY positions, leaving Z and orientation unchanged. Learning this local pattern removes absolute XY placement from the pose supervision. The selected dataset is labeled single-direction, 90-degree, and explicitly records `rotation_aligned=false`. This attribute describes the saved training data; it does not mean that the implementation lacks direction transfer. The separate inference adapter in Section 3.5 aligns live positions and images to a configured teaching direction and inversely restores generated XY. E1/E2 explicitly disable that adapter, so their results do not quantify its transfer performance. Some upstream files also record episode-specific XYZ corrections, which are preprocessing transformations rather than separate generalization tests.

The evaluated A/B/C models share 42 unique episodes. The optimization partition contains 38 episodes; validation contains episodes 35, 39, 22, and 37. The checkpoint normalizer files reproduce this episode-level partition. All windows from an episode remain in its assigned partition,




Figure 4.4: Stored lengths of all 42 episodes used by the force-cleanup models. Orange identifies the four validation episodes. The partition is made before window sampling; repeated windows are not independent demonstrations.

avoiding overlap of windows from one episode across optimization and validation. This does not establish independence by operator, material, specimen, or collection session. No separate held-out demonstration-test split is claimed.

Figure 4.4 shows the episode lengths and fixed partition.

The loader draws 50 start indices per episode and constructs a 128-step future sequence. End-of-episode padding repeats the final action and masks padded positions out of the loss. Force history includes the current sample and the preceding samples up to a length of 30; a short initial history is padded on the left with the first available value. Start sampling is resampled across training epochs. Its existing phase sampler upweights the one-second precontact period by five relative to free and contact periods, using the recorded force thresholds of 3.0 and 1.2 N. The offline sampler uses this force-derived phase information for all three conditions, including A. A's policy still receives no force observation or force target.

Normalization bounds are computed from optimization-training episodes only. For channel d, the implemented min–max mapping is

$$\mathcal{N}_d(x) = 2\frac{x - m_d}{\max(M_d - m_d, \epsilon)} - 1, \tag{4.4}$$

where m_d, M_d are the stored training bounds and ϵ is the numerical denominator floor. State and action bounds are stored separately; force history uses the state-force bounds. Normalization does not force all future online values to lie within the training range.

4.7 A Representative Motion–Force Pairing

Episode 29 is used to explain the temporal representation because it is the operator-selected replay source, rather than an episode chosen for low error. Figure 4.5 presents its actual position and force history. The transition from approach to loaded movement and then rising motion gives a structured association between location, loading, and time. Replay uses that association directly; learning uses many such future windows as supervision.

The force action derives from measured teaching interaction, not an independently recorded human command. Physical equivalence must be assessed from robot measurements because the mechanics and controller differ.




Figure 4.5: Teaching episode 29 on the original paired source-time axis. XY is task relative, Z remains in the stored absolute convention, and force is the native-axis cleanup signal. The 175 mm line is the offline cleanup boundary. The curves are not a desired-versus-measured robot force-tracking comparison.

Chapter 5

Force-Conditioned Motion–Force Skill Learning

5.1 Learning Objective and Observation Interface

The learning problem is to generate a future local skill from the execution context, while preserving a joint representation of movement and target loading. A conditioned sequence can change at a later inference call when the robot reaches a different pose or contact state. The policy is not asked to estimate scratch depth, choose an abrasive, or output a separate completion decision.

For the force-observing model, the physical observation at index k is

$$o_k = \left(I_k, \widetilde{q}_k, f_k^{\mathrm{meas}}, f_{k-L+1:k}^{\mathrm{meas}}\right), \qquad L = 30. \tag{5.1}$$

The numerical state has nine components: six Cartesian pose values and three current force values. History has shape 30×3. Only F_x, F_y, F_z enter this observation; the sensor's torque channels do not. The input image is the single 240×424 RGB view. Images are converted to floating-point tensors and normalized using the implemented RGB channel means and standard deviations.

The action target is a normalized 128×9 sequence of task-relative position, rotation vector, and teaching-derived target force. Position and orientation describe the tool reference, whereas force describes a controller-level target. Both appear in the same sequence so that their temporal

correspondence can be learned. The action horizon corresponds to approximately 4.27 s on the nominal 30 Hz action grid. Its last sample is at $127/30$ s relative to the first, which distinguishes a sample count from an endpoint-to-endpoint duration.

5.2 Implemented Observation Encoder

The active model is the Flow RGB policy in the archived training snapshot. It uses a frozen DINOv3 ViT-small patch-16 image backbone, a state MLP, a one-layer force-history GRU, and a fusion MLP. The separate encoder modules available elsewhere in the repository do not determine this checkpoint's architecture.

The visual branch combines the global image feature with a feature pooled from a fixed TCP interaction ROI. The ROI is constructed internally from reference image dimensions 424×240, center $(253, 120)$, and area-fraction parameter 0.25. The DINO patch features in that ROI are pooled by the configured attention mechanism. Global and ROI features are each projected to 512 components. The ROI is a calibrated interaction-region prior, not an external defect mask and not a prediction of surface damage.

The state MLP encodes all nine normalized state components into 256 components. A GRU with input dimension three and hidden dimension 64 encodes the force history, with its final hidden state contributing to fusion. The fused condition is 256-dimensional. Thus the current force appears both in the state vector and as the last history sample. There is no learned moment-history branch, LSTM comparison, or termination head in the evaluated configuration.

Figure 5.1 summarizes the force-observing architecture.

Table 5.1 lists the saved architecture and training parameters.

5.3 Flow Matching Sample Construction

Flow Matching learns a field that transports a simple noise distribution toward the demonstrated sequence distribution [10]. The following equations describe the particular implemented construction, rather than all possible flow-matching paths.




Figure 5.1: Actual force-observing policy configuration, shown conceptually. In B, the current-force and history tensors are zeroed after normalization while the history branch remains. A uses pose6 state/action and omits force history. The flow vector field has the same sequence shape as its action input.

Table 5.1: Architecture and training settings for the force-cleanup checkpoints used in E1–E3.

Item	Stored value
Backbone / trainable status	DINOv3 ViT-small, patch 16 / frozen
State / history / global condition	256 / 64 / 256 components
Temporal U-Net channel widths	256, 512, 1024
Convolution kernel / groups	5 / 8
Flow-time embedding	256 components
Action horizon / force-history length	128 / 30 samples
Loss / flow integration updates	Masked MSE / 10
Optimizer	AdamW, learning rate 10^{-4}
Weight decay / optimizer betas	10^{-5} / $(0.95, 0.999)$
Batch size / training seed	12 / 0
Training epochs / warmup	500 / 10 epochs
Learning-rate schedule	Cosine; minimum 10^{-6}
Gradient norm clip	1.0

Let $A \in \mathbb{R}^{H \times d_a}$ be a demonstrated action chunk after action normalization, with $d_a = 9$ for B/C and $d_a = 6$ for A. Independently sample a noise chunk $Z_0 \sim \mathcal{N}(0, I)$ with the same shape and a scalar flow time

$$s \sim \mathcal{U}(\varepsilon, 1 - \varepsilon), \qquad \varepsilon = 10^{-4}. \tag{5.2}$$

The source implementation uses

$$Z_s = (1 - s)Z_0 + sA, \qquad U = A - Z_0. \tag{5.3}$$

The vector-field network $v_\theta(Z_s, s, c_k)$ predicts U, conditioned on the encoded observation $c_k = E_\theta(o_k)$. The scalar s belongs to a dimensionless generative process. It is unrelated to the physical polishing time t or the future sample index j.

Let m_j equal one when future step j has actual episode support and zero when it is padded. The implemented per-batch objective is

$$\mathcal{L}_{\mathrm{FM}} = \frac{\sum_{b,j,d} m_{bj} \left[v_\theta(Z_{s_b}, s_b, c_b)_{jd} - (A_b - Z_{0,b})_{jd} \right]^2}{d_a \, \max\left(1, \sum_{b,j} m_{bj}\right)}. \tag{5.4}$$

Here b indexes batch elements, j future action steps, and d action coordinates. A new noise tensor and flow time are sampled for the training evaluation. All valid normalized coordinates contribute to the same MSE. There are no additional orientation-geodesic, target-force-tracking, material-removal, or completion losses in this configuration.

The conditional temporal U-Net operates along the action-sequence dimension. Its residual blocks combine temporal convolutions with the global observation and flow-time condition. The configured channel levels are 256, 512, and 1024; convolutional blocks use GroupNorm and Mish nonlinearities. These choices parameterize the field rather than creating a separate head for each physical objective. In particular, a lower force-related loss is not computed independently from the motion coordinates.

5.4 Flow Integration and Physical Timing

At inference, a fresh Gaussian chunk $Z^{(0)}$ is generated. With $M = 10$ and $h = 1/M$, the source applies

$$Z^{(m+1)} = Z^{(m)} + h\, v_\theta\Big(Z^{(m)}, (m + \tfrac{1}{2})h, c_k\Big), \quad m = 0, \ldots, M-1. \tag{5.5}$$

This is the exact explicit update with a midpoint flow-time argument used in the code. It is not a two-stage midpoint Runge–Kutta solver: no intermediate state evaluation is computed. The final sequence is denormalized using the stored action bounds, and its relative XY coordinates are restored before execution. When the implemented direction-transfer option is active, observation XY and the single-camera policy image are aligned before conditioning, and generated XY is inversely rotated before center addition, as defined in Section 3.5. This adapter surrounds the learned generator without changing its training objective or adding a predicted direction channel. It is disabled in E1/E2 and enabled for the E3 direction conditions.

Ten dimensionless flow updates generate one action chunk. Physical reference progression uses the separate 30 Hz action grid. The inference callback timer is configured at 5 Hz and generation is gated by plan age. The nominal stride of 120 action samples corresponds to 4.0 s. E3 additionally

uses a 0.5 s replanning lead, giving a configured plan-age threshold of $120/30 - 0.5 = 3.5$ s. The saved E3 execution configurations and runtime source snapshot implement this lead; it is not a measured interval between completed inference calls. Timer scheduling and inference latency can change the actual generation interval. The E3 lead does not replace the nominal stride reported for E1/E2. Command publication at 125 Hz is another distinct clock (Table A.2).

The force history also has two time interpretations. In the dataset, 30 samples on a nominal 30 Hz grid describe approximately one second of historical context. Online, the adapter retains the most recent 30 force callback values and left-pads an insufficient history; it does not resample them onto an exact one-second clock. A 20 Hz recording cap for diagnostic CSV files does not specify the policy callback rate. The history length is therefore reported as a sample count, with its nominal training duration stated separately.

5.5 Separating Force Output from Force Observation

The three E2 conditions implement different information contracts. A has a six-dimensional pose state and six-dimensional pose action, with no force-history encoder or force supervision. An external constant 23 N target is supplied by the execution interface; it is not an A policy output. B retains the nine-dimensional action and the same history architecture as C, but the current-force part of its normalized state and its normalized history tensor are replaced by zeros. C retains the measured-force inputs.

Masking occurs in the dataset/model conditioning path during training and again at the inference boundary. It does not alter the force-action target. Because masking is applied after normalization, a zero conditioning value is a neutral network input, not a declaration that physical measured force is zero newtons. B remains a separately trained model. It uses the same teaching episodes and retains their force-action targets, learning a target-force sequence conditioned on image and pose even though measured force is masked at its observation input. It is not C evaluated after an untrained removal of its inputs.

The title's two terms identify these separate roles. *Joint motion–force representation* pairs pose and teaching-derived target force on the same action time axis. *Force-conditioned imitation*

Table 5.2: Information contracts for three separately trained conditions using the same 42 episodes (38 training, four validation). Pose denotes tool position and orientation. All conditions retain actual force feedback in the lower-level controller.

Model	Policy observation	Action supervision	Force reference
A	I_t, pose_t	$\mathrm{pose}_{t:t+127}$	External 23 N
B	$I_t, \mathrm{pose}_t, 0, 0_{30\times3}$	$(\mathrm{pose}, f^{\mathrm{target}})_{t:t+127}$	Policy force output
C	$I_t, \mathrm{pose}_t, f_t^{\mathrm{meas}}, \mathcal{H}_t$	$(\mathrm{pose}, f^{\mathrm{target}})_{t:t+127}$	Policy force output

learning additionally uses current measured force and force history as observation conditioning. The force coordinates of a noisy action chunk in Equation (5.3) are part of the generative training path, not observed force inputs. Table 5.2 and Figure 5.2 make the distinction explicit.

Here $\mathcal{H}_t = f_{t-29:t}^{\mathrm{meas}}$; B's zeros replace normalized conditioning tensors and do not mean a physical reading of 0 N. At a selected training index, the current RGB/pose observation and supported force history condition the future 128-sample action chunk. Samples beyond the episode end are padded and excluded by the existing loss mask. This explanatory notation summarizes sample construction; the actual objective remains the masked flow-vector-field loss in Equation (5.4).

The force signal is still used by the common executor and lower-level controller in A and B. It is also used by the existing offline phase sampler. Thus "force observation OFF" refers specifically to the policy's conditioning channels. Chapter 7 uses this distinction to interpret the A/B comparison as a force-output comparison and B/C as a force-observation comparison, subject to the limitations of separate single-seed training.

5.6 Training Completion and Checkpoint Selection

The recorded training completed 500 epochs per condition, ending at zero-based epoch 499. The deployed best checkpoints are selected by minimum validation loss, as confirmed by both the model manifest and the checkpoint metadata. Table 5.3 distinguishes the configured duration from the selected epoch.

Validation evaluates the same flow-field objective using held-out episodes. Its minimum selects a generative model according to that objective, not according to robot task completion or measured finish quality. Since noise and flow time enter the loss evaluation, the numerical minimum also




Figure 5.2: Explanatory information-flow diagram. B/C have the same motion–force supervision and architecture; B masks only normalized force conditioning in training and inference. Each condition has its own trained checkpoint. The shared lower-level measured-force feedback is preserved.

Table 5.3: Selected checkpoints. Epoch values follow the stored zero-based convention. Validation losses have different action dimensions for A versus B/C and are not task-performance scores.

Model	State/action dim.	Best epoch	Final epoch	Best val. loss
A	6 / 6	39	499	0.049722
B	9 / 9	42	499	0.069948
C	9 / 9	42	499	0.066444

should not be interpreted as a deterministic physical optimum. There is one recorded training seed per condition. Five robot repetitions per condition evaluate execution of that trained model; they do not constitute five independently trained policies.

The resulting method offers a concrete mechanism for coupling motion and target loading under observations. Whether the mechanism improves a given local task remains an empirical question. Its demonstrated function is generation and deployment of the specified action representation; its broader value is assessed alongside rules and replay in the following chapters.

Chapter 6

Robot Execution and Contact-Task Evaluation

6.1 From a Skill Sequence to Robot Commands

Figure 6.1 summarizes the command-processing chain. The generated sequence is an upper-level reference. Its physical meaning depends on the execution system that samples it, connects new plans, gates force, and transmits commands to the existing controller. A common execution layer is therefore necessary for interpreting differences between providers.

The provider interface supplies a time array, pose–force values, a plan identifier, and whether the plan is finite. R supplies a prescribed finite path with a recipe force. T supplies a finite teaching sequence with its original time axis. C supplies successively generated chunks from observations. Relative XY positions are restored using the frozen task origin before commands are interpreted in robot-base position coordinates. In the optional direction-transfer path, inverse XY rotation precedes that addition; the evaluated E1/E2 configuration uses translation alone. This restoration occurs before downstream command conditioning. The accompanying force values remain controller targets, with their frame interpreted by the lower-level configuration.

The timed sampler uses elapsed reference time rather than selecting the closest spatial waypoint. It linearly interpolates position and force and interpolates orientation on $SO(3)$. This preserves

the association between a source time and its requested pose/force. It does not guarantee identical physical feed velocity, because downstream conditioning and contact dynamics can alter motion.

6.2 Shared Pose Conditioning and Plan Connection

The evaluated E1 configuration applies the same archived pose conditioner to R, T, and C. Earlier metadata within the profile still refers to its initial C-only introduction; the active shared R/T/C wrapper and recorded runtime establish the later comparison's actual scope. R/T are presented through a private 30 Hz, 128-point pose view with a 120-point stride, while their original finite force/time plans remain the source for force sampling and phase boundaries.

The conditioner smooths XYZ with a 35-point moving average and orientation with a quaternion mean. The latter avoids averaging rotation vectors through their branch cut near π. Edge padding is confined to the filter's window construction. A replacement plan is joined to the preceding reference and velocity over 0.5 s. Its quintic connection weight is

$$\beta(u) = 10u^3 - 15u^4 + 6u^5, \qquad u = \min(1, (t - t_b)/0.5), \tag{6.1}$$

where t_b is the connection start. Position connects from a velocity-extended anchor; orientation uses a bounded relative rotation. The conditioner also retains its velocity state across replacement plans and bounds the change in commanded velocity.

These operations alter the reference actually presented to the command loop. They are shared processing choices, rather than evidence that the generated raw chunks are intrinsically smooth. Likewise, T's time scaling of one describes its source-time replay, not equality between the demonstrator's and robot's measured instantaneous speed.

6.3 Command Rates, Limits, and Force Gating

The command loop uses a nominal 0.008 s period, corresponding to 125 Hz. The common proportional command-update gain is 15 s^{-1}, with per-axis position speed cap 10 mm/s and angular cap 40 degrees/s. The pose-conditioning acceleration settings are 25 mm/s^2 and 100 degrees/s^2. The




Figure 6.1: Execution interface and distinct command stages. The transmitted target is observable in executor logs; the controller-applied target is not available as a synchronized time series. This conceptual diagram describes command processing, not measured force-tracking performance.

force-command slew limit is 30 N/s. These are command-processing settings, not experimentally measured limits of physical tool speed or contact force.

For a scalar translational component, the shared update can be represented as

$$\delta x_i = \mathrm{clip}\big(\min(1, K\Delta t)(x_i^\star - x_i^{\mathrm{cmd}}), -v_i^{\max}\Delta t, v_i^{\max}\Delta t\big), \tag{6.2}$$

followed by the existing acceleration conditioning. $x_i^\star$ is the sampled conditioned reference, $K = 15$ s^{-1}, and Δt is bounded by the nominal control period. Orientation uses a relative-rotation increment instead of direct component-wise interpolation across a branch cut.

The operational gate reads measured robot-base F_z^B, enters contact at 3.0 N, and leaves at 1.2 N. While the gate is OFF, the requested normal target is suppressed. The command's tangential force components are set to zero in the evaluated common executor. Thus B/C learn a three-component force action, but the deployed comparison transmits only its normal-force component as a nonzero target. Their three-component measured-force observations can still inform generation.

The target's final approach to its requested value is affected by gain and slew conditioning. A nominal constant recipe is therefore distinct from the full transmitted force curve, particularly around contact onset and release. In E1, R uses 18 N. In E2, A uses an external 23 N target. The operator's approximate 20 N teaching intention, those recipe values, and the measured base-force distribution describe different quantities.

6.4 Existing Lower-Level Contact Regulation

The archived controller receives a Cartesian pose reference and a signed target-force vector. Its TCP-coordinate path rotates measured base vectors into the local frame, performs contact-control computation there, and restores the resulting motion to the robot frame. The stored controller configuration identifies TCP force coordinates and an existing mass/damping adaptation mode. This lower-level adaptation is a shared control asset; it is not the upper-level residual surface-repair policy proposed in the old thesis.

The underlying admittance implementation defines position error $e = x_d - x_c$ and force error $F_d - F_{\mathrm{ext}}$. Its scalar virtual dynamics can be written as

$$M\ddot{e} + D\dot{e} + Ke = F_d - F_{\mathrm{ext}}, \qquad x_c = x_d - e, \tag{6.3}$$

where x_d is the supplied motion reference, x_c the compliant motion output, and M, D, K the virtual mass, damping, and stiffness. This controller calculation converts position to meters internally; its translational parameter units are kg, N s/m, and N/m. The source discretizes the relation using the Tustin form and contains mode-dependent parameter updates. Equation (6.3) explains the interaction role; it does not replace the deployed switching and adaptation logic with a newly designed controller.

Teaching force, policy output, transmitted target, and measured force must remain distinct. The available axis correspondence permits rotating teaching measurements into robot-base coordinates for analysis. It does not provide the actual controller-applied reference after all internal processing.

For that reason, the thesis does not subtract published TCP target F_z directly from measured base F_z and call the result tracking RMSE.

6.5 Approach and Contact-Start Synchronization

R and T retain an existing one-time contact-start synchronization. Before confirmed contact, their approach reference continues to progress up to the prescribed processing boundary. Once distinct received force observations sustain the existing ON state for 0.2 s, the reference clock is aligned to that boundary. After the alignment, the finite strategy advances from its source timing; repeated synchronization is not applied.

This mechanism matters because the physical surface can be encountered before or after a nominal geometric boundary. It supplies feedback to fixed strategies without learning a policy. C instead generates its own approach and later chunks from observations. Common contact gating and lower-level force regulation remain active in all methods.

The normal departure is also provider dependent. R includes a planned zero-force upward segment, T contains the selected teaching exit, and C can generate an exit within its pose–force sequence. The evaluator recognizes the result of these actions. It does not insert a new retraction to make a deficient sequence satisfy the task.

6.6 The Executed E1 Contact Procedure

E1 uses a fixed 25 mm-wide XY band between $P_0 = (445, 395)$ mm and $P_1 = (487, 345)$ mm. Its length is 65.299 mm and it is divided into 14 longitudinal segments. The band concerns the TCP center; it is not a measurement of the contact footprint.

Let $d = (P_1 - P_0)/\ell$, $\ell = \|P_1 - P_0\|$, and let n be a unit vector perpendicular to d in the XY plane. For TCP XY position p_{xy}, define longitudinal and transverse coordinates

$$u = d^{\mathsf{T}}(p_{xy} - P_0), \qquad v = n^{\mathsf{T}}(p_{xy} - P_0). \tag{6.4}$$

Band occupancy requires $0 \le u \le \ell$ and $|v| \le 12.5$ mm. An ordered loaded candidate starts at an end segment and advances through adjacent first visits toward the opposite end. Contact OFF, missing support, or leaving the band breaks a candidate. Revisiting a previously visited segment does not create additional forward progress. Completion of the 14-segment sequence establishes the required pass. There is no per-segment 0.466 s dwell requirement in this primary criterion.

The primary E1 session uses `pass_height_ref_v2`. The evaluator first confirms contact for 0.2 s. Once the first continuous loaded ordered pass succeeds, it freezes the working-height reference $z_{\text{work_ref}}$. This is the time-weighted lower median of actual TCP Z over that successful candidate's jointly observed, in-band, contact-ON support $\mathcal{S}$:

$$z_{\text{work_ref}} = \inf\left\{ z : \int_{\mathcal{S}} \mathbf{1}[Z(t) \le z]\, dt \ge \tfrac{1}{2} \int_{\mathcal{S}} dt \right\}. \tag{6.5}$$

Here $Z(t)$ is linearly interpolated only within valid recorded pose support, in millimeters, and the integrals weight the supported physical duration. Failed candidates contribute no support to the frozen reference. Approach, exit, and recovery are outside $\mathcal{S}$. After the required pass, both the OFF state and

$$Z(t) \ge z_{\text{work_ref}} + 5 \text{ mm} \tag{6.6}$$

must hold simultaneously for 0.2 s. Contact formation, the ordered loaded pass, and this exit conjunction define `TASK_COMPLETED`. The criterion recognizes the specified contact procedure; it does not detect completed material removal.

The 14 October development evaluator instead referenced the first confirmed contact height. Its original results and height-only offline replay are retained as historical material in Appendix B.3, separate from the physically executed 15 October primary comparison.

6.7 Completion, Observation Support, and Time Windows

The primary E1 observer is `received_observations_v2`. Each new pose and wrench subscription receipt retains its sample identifier and host monotonic timestamp. The observer constructs supported intervals using pose brackets and zero-order-held force. Gaps longer than 0.2 s

remain unobserved. The consumed intervals record their source receipt identifiers, interval bounds, and decision times; repeated reads of the command loop's cached state are not counted as new observations.

Offline reproduction uses those exact consumed intervals and the original receipt records, with no post-stop bracket added to the decision evidence. The archived report confirms agreement of online and offline completion and height-reference fields for all 15 original executions. The 19 October additional R report records the same observer/evaluator versions and online/offline agreement in its five runs. The analysis retains those documented evaluator checks and uses the matching archived precision CSVs and frozen run identities. It does not rerun the evaluator with new thresholds or infer higher-rate samples from the lower-rate CSVs.

The E1 completion time is measured from `execution_start` to the first `TASK_COMPLETED`, including in the additional R^* cohort. Incomplete attempts have no completion time. The E1 force-analysis window begins at execution start and ends at first completion, or at the first stop if the procedure is incomplete. Subsequent return or hold is excluded. The same E1 window rule is applied to every provider and both R cohorts.

Within this window, excess-force exposure is

$$J_{\text{excess}} = \int_{t_0}^{t_1} \max\bigl(F_z^B(t) - Q_{95}, 0\bigr)\ dt, \qquad Q_{95} = 30.812396273\ \text{N}. \tag{6.7}$$

The reference is the existing episode-balanced, actual-time-weighted teaching cleanup distribution rotated to base axes, with the archived stored-Z candidate convention. It includes validation episodes because it describes the common teaching reference, not a fitted policy input. It is an empirical analysis upper reference, not a damage, safety, or effective-polishing limit. The lower quantile, approximately 0.4498 N, is not used as a contact threshold. Low or zero native-force samples can have nonzero projected base components and do not establish meaningful contact.

E2 has a different stopping protocol: the recorded window ends at the first operator finish request. A terminal software event labeled normal completion verifies the existing stop path rather than task achievement. A4 demonstrates why the two must be separated. The first request time is retained even when the later operator report identifies the task as incomplete.

6.8 Execution Timing and Checks

The action grid (30 Hz), inference callback timer (5 Hz), nominal stride (120 samples, 4.0 s), and command publication (125 Hz) describe different mechanisms. E3 applies a 0.5 s lead to the stride, yielding a configured 3.5 s plan-age threshold. This setting is verified from saved execution configurations and their runtime source snapshots; actual call-to-call generation intervals are not measured here. In the original E1 cohort, actual pose and force receipt-event records are approximately 125 Hz; the additional R report retains that observer configuration. E2 retains the earlier approximately 18 Hz archived feedback CSVs under a 20 Hz logging cap. Neither rate identifies the sensor's acquisition frequency or a policy replanning rate. Existing timing, freshness, workspace, and stop/hold checks remain common infrastructure.

6.9 E3: Image-Based Stain-Area Evaluation

E3 evaluates a different outcome: the reduction of visible board-marker ink area on a registered surface. The analysis uses stored before/after photographs and the frozen semiautomatic protocol documented in the 23 October image-removal report. Its primary metric is

$$\mathrm{Removal}(\%) = 100\,\frac{A_{\mathrm{before}} - A_{\mathrm{after}}}{A_{\mathrm{before}}}, \tag{6.8}$$

where A_{before} and A_{after} are segmented target-ink pixel areas in the same surface coordinates and fixed evaluation ROI. This denominator is the initial ink area, not the tool footprint, evaluator band, or full image. Residual ink and spreading within the ROI are included even outside the initial ink mask.

The established analysis combines a common OpenCV RGB-to-gray threshold, gray $\leq 45/255$, with saved manual annotations of visible ink boundaries in the original 424×240 RGB images. The initial visible stain outline receives a six-pixel margin to define the fixed ROI; the same surface region is compared afterward. This is semiautomatic segmentation. The annotations distinguish target ink from tool, cable reflections, and existing plate writing. The original RGB files are reprocessed with

the unchanged saved annotations, ROI construction, and threshold. No new boundary annotation, component-size deletion, or threshold optimization is introduced.

Reproduction of the saved alignment algorithm confirms identity registration for all 19 evaluable pairs, so their areas are counted in the original coordinates without resampling. For the six occluded pairs, its surface-feature homography indicates the shared ROI and occlusion; it does not reconstruct hidden ink. The normal pairs use executor pre-task and post-HOME photographs. P2's initial image is instead the first raw RGB frame of the same run before execution/contact. D1-4 has a pre-task photograph and an interruption-time diagnostic frame, with no post-HOME photograph. Its original stop reason is `manual_abort`. Whole-stain removal is unavailable because of final tool occlusion, not because interruption alone disqualifies an image.

The arithmetic mean and sample SD ($\mathrm{ddof} = 1$) are calculated over available run-level removal percentages. Pixels are not pooled across runs. P2 remains five executed archive records; it is excluded from the main N/P1/D1/D2 results. D1-4 remains among D1's five selected runs and is excluded only from the removal statistic, leaving image $n = 4$. Unavailable values are null. Automatic procedural completion is not an inclusion criterion, and image evaluability is not a success rate.

The archived gray-40/45/50 sensitivity aggregates use unchanged annotations and ROI (Appendix D); RGB-level reproduction uses the primary threshold 45. A 100% value means residual black-ink nondetection at this resolution and criterion. It does not establish physical ink absence or measure metal depth, mass, roughness, or micro-scratch restoration. No earliest removal-completion time, removal speed, or success threshold is defined.

6.10 Protocol Boundaries across E1–E3

E1's automatic completion, E2's operator interval, and E3's image-area change are separate outcomes. E3 first-stop diagnostics do not identify ink-removal time. N uses the existing Python HOME return; P1 uses controller PTP; D1/D2 additionally require commanded-release confirmation. These saved differences coexist with the common policy and contact-control structure.

Chapter 7

Experimental Evaluation

7.1 Evaluation Questions and Recorded Cohorts

Three evaluations connect the generated skill to its observed execution and processing result. E1 varies the strategy provider and includes an additional rule-feed diagnostic (RQ1). E2 separates learning target force from observing measured force (RQ2). E3 reuses the same C policy at registered positions and directions and measures saved-image ink-area reduction (RQ3). These are distinct cohorts and outcome definitions.

The original E1 cohort is the nominal development session

```
E1_CT_pass_height_v2_nominal_dev_20261015
```

The frozen configuration is `e1ct_46de718a23a2a7cf`. It uses evaluator `pass_height_ref_v2` and observer `received_observations_v2`. Each of its 15 original planned slots has one started execution, five per method, with no retry or exclusion. Five blocks each contain R/T/C in the recorded shuffled order (seed 20261014). C5 is preserved; later C6 is a separate diagnostic. The additional R^* consists of one 19 October diagnostic followed by four extension runs on the same date. It is not part of the original randomized blocks, and R and R^* are never pooled as $n = 10$.

E2 retains all 15 attempts from 13 October, five each in actual order A, B, then C. A4's task outcome follows the operator's field correction: contact release was not completed and the operator interrupted sustained contact. Its software events and stop time are preserved.

E3's image-report selection contains 25 runs, N/P1/P2/D1/D2 with five each. The main thesis evaluation uses N/P1/D1/D2, totaling 20 selected runs and 19 image-evaluable pairs. P2 remains five executed archive records, all occluded at the final image. D1-4 remains a selected D1 run but has no whole-stain removal value. These denominators describe inclusion and image support, not a common completion rate.

E1/E2 statistics are calculated from archived per-run precision CSVs matched to the frozen run lists. The additional R^* data include the original run identities and unrounded values. E3 integer areas are reproduced from the original RGB pairs with the saved annotations, ROI, and segmentation algorithm, and compared pixel by pixel with the stored masks. The supplied results manifest links each outcome to its cohort and source; Appendix D documents the reproduction level.

7.2 Platform and Metric Boundaries

The local task uses the UR10 platform, robot-mounted processing tool, and marked plate visible in RGB. The original E1 report identifies UR10 CB3 and an AIDIN AFT200-D80 force/torque sensor. E1/E2 share their respective archived command-processing and lower-level feedback configurations, while E3 retains condition-specific termination and return implementations. Measured spindle RPM, abrasive state, specimen alloy, scratch depth, mass loss, and roughness change are not independently supplied by these records.

E1 time is `execution_start` to the first `TASK_COMPLETED`, including approach and exit but excluding initial PTP and later HOME. Its J_{excess} uses the same whole execution window and the empirical teaching reference 30.812396273 N. E2 completed time is the operator-based interval, with A4 completion null and its interruption interval retained. E3's primary outcome is Equation (6.8); neither E1/E2 timing nor E3 automatic diagnostics supply a removal-completion timestamp. Means and sample SD use runs as the sample unit, not frames or pixels.

Table 7.1 summarizes the strategy and force interfaces.

Table 7.1: Strategy and force interfaces. All retain actual lower-level force feedback. Table 5.2 distinguishes E2 observations from supervision.

Study	Condition	Strategy and force interface
E1	R / R^*	Rule path, +18 N recipe; original / additional processing retiming.
	T	Episode 29 pose/force/source-time replay, scaling 1.0.
	C	Observation-conditioned Flow pose–force chunks.
E2	A	Pose learning; external 23 N target.
	B	Pose–force learning; normalized measured-force inputs masked.
	C	Pose–force learning with measured-force observation/history.
E3	C	Same checkpoint and normalizer; center-relative placement and D-condition direction adapter.

7.3 E1: Strategy Comparison

Figure 7.1 shows the individual E1 outcomes. Table 7.2 presents the R^*/T/C summary while explicitly retaining their collection dates. Each strategy completes the required procedure in its observed five runs. The original R also completes 5/5 and is preserved alongside R^* in Table 7.3 and the original R/T/C individual outcomes in Appendix C.

Table 7.2: E1 strategy summary: R^* is the separate additional five-run diagnostic on 19 October 2026; T/C are the original five each on 15 October. The 15 displayed runs were not randomized together in a new common block. Time and excess integral are mean $\pm$ sample SD, $n = 5$ per cell. Original R is retained separately; C5 remains included and C6 excluded.

Method	Date / cohort	Done/run	Time (s)	J_{excess} (N s)
R^*	19 Oct / additional	5/5	24.840 ± 1.321	0.000 ± 0.000
T	15 Oct / original	5/5	12.897 ± 0.041	0.125 ± 0.254
C	15 Oct / original	5/5	13.420 ± 2.630	1.440 ± 2.785

T has a shorter mean completion time and smaller time SD than C: 12.897$\pm$0.041 s versus 13.420$\pm$2.630 s. Their mean excess integrals are 0.125 and 1.440 N s, respectively; R^* and original R have zero observed excess. The common Q_{95} is a teaching-derived analysis reference, not a target force or safety/damage boundary. These outcomes establish procedure execution and different time–force characteristics. They do not measure ink-removal success or surface quality.




Figure 7.1: E1 individual runs and mean ± sample SD. Original R, additional R^*, original T, and original C are kept separate, with dates on the axis. Each colored point is one run; R*1 and C5 identify the retained short first additional run and high-exposure original C5. C6 is excluded. R^* points and summaries use the verified unrounded per-run CSV; displayed numbers are rounded only for presentation. Bars are dispersion, not confidence intervals.

7.3.1 Original R and Additional Processing Retiming

Table 7.3: Original R and separate additional R^*, five runs each. Peak feed is a source-path parameter; measured pass speed is calculated on the successful loaded-pass support. Values are mean ± sample SD where appropriate. The dates identify distinct collections.

Metric	Original R (15 Oct)	Additional R^* (19 Oct)
Completed / executed	5/5	5/5
Peak-feed parameter (mm/s)	10.000000	14.940779
Completion time (s)	29.537 ± 0.075	24.840 ± 1.321
Measured pass XY speed (mm/s)	7.918 ± 0.124	10.841 ± 0.088
J_{excess} (N s)	0.000 ± 0.000	0.000 ± 0.000

The additional feed reference is 14.940779233290927 mm/s, the summed XY distance divided by summed source time across the stored Z$\leq$ 175 mm work-candidate intervals of 42 unique teaching episodes, including four validation episodes. The report records 4299.093664 mm over 287.742265 s. This is a dataset-derived recipe reference, not an independent held-out setting or a verified physical-contact interval.

That value is applied to the existing rest-to-rest quintic path's *peak-feed parameter*. For the quintic scaling $10u^3 - 15u^4 + 6u^5$, the ratio of peak to source movement-average speed is

1.875; the new source processing average is therefore 7.968416 mm/s. The experiment does not match a constant or measured mean TCP speed to 14.941 mm/s. Actual successful-pass XY speed changes from 7.918±0.124 to 10.841±0.088 mm/s. Teaching candidates, full source processing, and successful robot-pass support have different interval definitions.

Only processing is retimed, from 12.243621 to 8.194767 s. The source approach, force ramps, normal-release paths and durations, +18 N target, common controller, and command limits remain as recorded. Later phase start times shift with the shorter processing phase. Source-plan duration is not actual first-completion time because contact synchronization and observed release/rise timing also contribute.

R^*'s mean completion time is 4.697 s (15.9%) shorter than original R. This is a descriptive comparison of separate-date additional diagnostics. The first added run was observed before extending to five, and its shorter release-confirmation interval is retained. R's time depends on path time parameterization and approach/exit as well as processing. The comparison does not attribute shorter learned execution to faster learning computation, or establish an IL advantage after matched measured speed. Original R/T/C tables, receipt traces, and the C5/C6 diagnostic remain in the appendices.

7.4 E2: Force-Information Ablation

E2 separates the two force roles by comparing A/B/C under the shared execution environment. A learns motion and uses an external constant force; B learns motion and force without policy force conditioning; C learns both with measured-force conditioning. The A/B comparison changes both the action dimension and the learned reference schedule. The B/C comparison retains the action and history architecture while changing force-conditioning information. All three are independently trained single-seed checkpoints.

Figure 7.2 displays all E2 attempts. Table 7.4 applies the corrected field outcome. A has four operator-reported completed attempts and one interrupted attempt. B and C have five operator-reported completed attempts each. A4 remains in the all-attempt statistics and has no successful completion time.




Figure 7.2: All E2 attempts. A4 is shown as a cross at its interruption time. The time summary marks use completed attempts only. Force peaks and XY travel include all five attempts in each condition. Axes retain the full observed ranges.

Table 7.4: E2 results with A4 corrected to incomplete release and operator interruption. Completed-time statistics use A $n = 4$, B/C $n = 5$. Mean observed peak is the mean of the five per-run peaks in every condition, including A4, not the whole-signal mean or pooled maximum. Values are mean $\pm$ sample SD.

Condition	Done/attempt	Time n	Time (s)	Mean peak (N)
A	4/5	4	17.65 ± 1.20	31.02 ± 1.46
B	5/5	5	18.81 ± 0.40	32.42 ± 0.76
C	5/5	5	15.83 ± 0.56	31.26 ± 1.66

The completed A intervals average 17.65±1.20 s ($n = 4$), whereas its all-attempt interval averages 19.87±5.07 s ($n = 5$). B and C both complete five attempts. Their completed intervals are 18.81±0.40 s and 15.83±0.56 s, respectively. A4's successful completion time remains null; its stop time is retained in the five-attempt interval, force, and travel statistics.

The B–C mean difference is 2.98 s. With $\bar{t}_B$ and $\bar{t}_C$ denoting the respective five completed operator-based intervals, the descriptive percentage is

$$r_t = \frac{\bar{t}_B - \bar{t}_C}{\bar{t}_B} 100 = 15.8\%. \tag{7.1}$$

It describes the recorded operator-based timing difference. It does not establish a causal productivity improvement, equal material removal, or a general benefit across every performance measure.

Table 7.5: E2 all-attempt force and motion statistics, $n = 5$ per condition. "Peak" is the mean of per-run measured peaks. Whole-window mean force includes approach and exit and is not a contact-only force-quality measure.

Condition	Mean F_z^B (N)	Peak F_z^B (N)	XY travel (mm)
A	12.09 ± 4.14	31.02 ± 1.46	229.68 ± 59.50
B	11.40 ± 1.17	32.42 ± 0.76	205.84 ± 4.80
C	9.36 ± 0.48	31.26 ± 1.66	189.22 ± 8.60

Table 7.5 reports the corresponding all-attempt force and travel statistics.

The mean measured peaks are similar in scale across A, B, and C; C is not below A in the group mean. Whole-window mean force and XY travel are lower for C in this cohort. The shorter contact interval and different approach/exit timing can explain part of those differences, so lower mean force is not interpreted as more accurate force regulation or more effective material processing.

The mean time with recorded $F_z^B \geq 3$ N is 11.49±7.31 s for A, 10.08±1.04 s for B, and 7.26±0.38 s for C. These existing contact diagnostics describe temporal organization on the observed window; they do not define a new threshold for effective polishing.

Full force traces and transition cases are retained in Appendix C.5, Figures C.4 and C.5.

7.5 E3: Spatial Transfer of the Learned Skill

E3 evaluates reuse of the same C checkpoint and normalizer without new teaching or retraining. N is nominal, P1 translates the registered region, and D1/D2 change its in-plane direction while also retaining their small center offsets. Figure 7.3 plots the registered positions and directions. Table 7.6 gives the actual registered values verified in the saved per-run registration and execution contexts. They are registration values rather than independent precision surface measurements.

Table 7.6: Main E3 conditions: registered offsets from nominal and direction change. D1/D2 include the listed center shifts. Each value is consistent across the five selected run contexts for its condition.

Condition	ΔX (mm)	ΔY (mm)	φ (deg)
N	0.00	0.00	0.00
P1	+29.55	+21.80	0.00
D1	-1.06	-1.36	+42.17
D2	-0.75	-3.53	-31.03




Figure 7.3: Registered center offsets and directions for N/P1/D1/D2. Left axes show the recorded registration offsets in millimeters. Right arrows show direction relative to nominal, with arbitrary display length; they are not measured stroke lengths or tool footprints. Small center shifts in D1/D2 are retained in the table.

Position transfer uses center-relative XY and restoration to the live center. D1/D2 additionally align observation XY and the policy image to the teaching reference, then inversely transform generated XY. Z, tool posture, force actions, and measured-force channels are not jointly rotated as a full $SE(3)$ transform. The result evaluates the policy together with its registration/direction adapter; it does not isolate spontaneous rotation generalization of the policy.

7.5.1 Selection and Image Evaluation

The image report preserves the original 25-run final selection rather than selecting new successful or latest runs. N is from 21 October and the selected P/D executions are from 23 October. P1 combines earlier repeats 2/4 with repeats 1/3/5; P2 includes retries of 1/2/3 and retained 4/5; D1/D2 include the final confirmed repeat-5 retries. The frozen selection manifests and original run identifiers define membership. D1-4 retains its original `manual_abort`. The experiment is a selected development collection, not a randomized controlled transfer study.

Table 7.7 reports the image-area results, and Figure 7.4 shows every evaluable run. The main removal comparison excludes P2 because every final P2 image is tool-occluded. P2 was executed and remains in the archive. In D1, all five selected runs remain, but D1-4's final tool occlusion prevents whole-stain measurement. Thus the main evaluation contains 20 selected runs and 19




Figure 7.4: All 19 evaluable main-run removal percentages with run numbers, condition means, and sample SD. D1-4 has no point and no imputed percentage. The full observed range includes D2-3 at 83.879%. Mean/SD are calculated over runs, without pooling pixels or defining a removal-success threshold.

evaluable image pairs. The semiautomatic gray-threshold and saved-boundary analysis is defined in Section 6.9. The established analysis is reproduced without changing its annotations or pixel criteria.

Table 7.7: Main E3 removal results, mean ± sample SD over image-evaluable runs. All conditions contain five selected executions. D1 image $n = 4$ means four evaluable pairs, not a 4/5 success rate; D1-4 is final-tool-occluded. P2's five occluded runs are archived outside this main table.

Condition	Selected n	Image n	Removal (%)	Unavailable
N	5	5	100.00 ± 0.00	0
P1	5	5	97.55 ± 2.49	0
D1	5	4	98.12 ± 3.75	1
D2	5	5	93.67 ± 6.60	0

Condition means range from 93.67% (D2) to 100.00% (N). This is a range of *condition means*, not a lower bound for individual runs. D2 includes the 83.879% observation, and D1-4 and P2 remain unquantified. A 100% value denotes no residual black ink detected at the original image resolution and established segmentation criterion.

Figures 7.5 and 7.6 show first-index original RGB and unchanged masks at identical scale. Appendix D retains the occluded D1-4/P2 records and lowest observed removal, D2-3.




Figure 7.5: N-1 and P1-1: original before/after RGB and enlarged binary ink masks. Black denotes counted ink; the dashed outline is the unchanged ROI. Mask axes are native pixel coordinates and use the same crop and scale in every example. No residual is detected in N-1; P1-1 retains 31 pixels. Original RGB resolution is 424×240; enlargement adds no image detail.




Figure 7.6: D1-1 and D2-1: original before/after RGB and saved binary masks, displayed with the same rules as Figure 7.5. The original remaining ink pixels are retained. Measured areas come from native images and masks, independently of the display enlargement.

7.6 Answers to the Research Questions

For RQ1, the original R/T/C and separate additional R^* each complete the defined procedure in their observed five runs. T has a shorter mean completion time and smaller time SD than C, while C has greater excess-force integral. R^* illustrates sensitivity to rule-path time parameterization without replacing the original experiment or establishing a matched-speed learning advantage.

For RQ2, B/C both complete five attempts and C has a 2.98 s (15.8%) shorter mean operator-based completion interval. A completes four of five, retaining A4 as an interrupted release transition. The separately trained single-seed configurations change target-force learning and/or force conditioning; they do not establish a general causal effect or a monotonic advantage across all metrics.

For RQ3, the same policy and task-registration/direction adapter yield observed condition-mean image-area removal of 93.67–100.00% across the evaluable N/P1/D1/D2 images. This supports reuse within the tested placements. It does not establish arbitrary-shape, curved-surface, or height robustness, superiority over R/T, or a causal spatial-transfer effect of force observation. E3 adds ink-area evidence without retrospectively measuring E1/E2 removal quality.

Chapter 8

Discussion and Extensions

8.1 What the Implemented Connection Establishes

The principal result is an implemented connection between a human-specified local task and an executable motion–force skill. The teaching representation supplies pose, loading, and timing together. The policy consumes observations and generates that same kind of sequence. The common executor and existing contact controller make the output actionable on the robot. E1 examines strategy execution, E2 separates target-force learning and force conditioning, and E3 measures image-based ink-area reduction after spatial reuse.

The primary E1 comparison establishes that this connection produces an executable local contact skill. Rules, replay, and the learned provider each complete contact, the required loaded traversal, and exit in all five planned runs. Their execution characteristics differ: T has a shorter mean completion time and smaller time dispersion than C, and C has greater mean excess-force exposure. E2 then shows a shorter operator-based completion interval for the force-observing configuration than for B, together with an incomplete release transition in A4. E3 adds condition-mean ink-area reductions of 93.67–100.00% in the evaluable registered placements. Together, the evaluations support an executable skill, observed force-configuration differences, and spatial reuse with its explicit adapter, while giving fixed strategies their observed value.

The comparison also clarifies what an execution-level result can establish. A generated rise can be learned as part of the demonstrated temporal structure. A gate can recognize unloading, and

an evaluator can confirm a displacement. None of those observations directly measures remaining defect depth. Maintaining that distinction allows the method to be described positively and precisely without assigning hidden process reasoning to the policy.

8.2 When Rules and Replay Are Sufficient

The nominal task is narrow: a specified region, a single demonstrated direction, a fixed setup, and an existing lower-level controller. Under those conditions, a prescribed strategy has a strong opportunity to work well. T reuses a full force-inclusive episode and its timing, making it a substantive alternative rather than a deliberately impoverished baseline. Its short completed intervals and low observed dispersion indicate that a stable demonstration can be valuable without policy learning.

R illustrates the same point from a process-recipe perspective. A finite rule can express approach, loading, traversal, and departure directly. Its longer interval reflects the constructed strategy and contact synchronization, not an intrinsic limitation that all rules must be slower. The executed additional R^* diagnostic makes this sensitivity concrete: processing-only retiming is associated with a 4.697 s (15.9%) shorter mean interval than original R. The dataset mean was used as a quintic peak-feed parameter, not matched actual average speed. The separate date and one-then-four collection history limit causal interpretation.

Imitation learning is used here to represent the demonstrated temporal relationship between motion and target force as an observation-conditioned generator. The specified region alone does not determine that relationship, but rules and replay can also supply it. E1 consequently evaluates learning alongside those alternatives rather than treating it as a necessary condition for completing the fixed task. T's strong nominal baseline and C's executable sequence are compatible findings: they characterize different ways to supply the local strategy.

8.3 Roles of Human Guidance and Relative Representation

Human guidance resolves where the local operation is intended to occur. Teaching supplies an example of how movement and loading can be organized. These are complementary contributions of the operator. A spatial mask, mark, or origin cannot be treated as a complete polishing strategy, and a demonstrated strategy cannot silently substitute for a new region specification.

The relative representation supports this division by learning position around a stain center and explicitly handling the stain direction at the policy boundary. A single-direction local movement pattern is reused by aligning live XY and the policy image with the teaching direction, then inversely rotating the generated XY path and adding the live center. This is an implemented spatial-generalization mechanism, rather than a future proposal. It addresses placement and in-plane direction through task registration while leaving observation-conditioned motion–force generation to the learned policy.

Its scope follows from the transformed channels. Z, tool orientation, and force are not rotated, and image adaptation is an in-plane warp about the interaction ROI. Thus the mechanism transfers the planar movement pattern without claiming complete pose–wrench equivariance or arbitrary-view invariance. E1/E2 disable direction alignment; E3 uses it for D1/D2 and evaluates the registered positions/directions in Table 7.6. Those observations characterize the combined policy and adapter in the tested planar arrangement.

The fixed image interaction ROI also has a specific function. It focuses part of the visual representation around the calibrated tool interaction area while retaining a global feature. It is not an explicit defect-state channel. The current experiments evaluate the resulting observation path as a whole; they do not isolate whether a mark's appearance, pose, or force carries most of the policy's decisions.

8.4 What Force Output and Observation Contribute

Target-force learning allows the reference sequence to express a changing load, including a departure from a constant recipe. Measured-force observation provides information about the

interaction that occurred rather than the load merely requested. Their roles are conceptually distinct and are separated by the E2 contracts.

The E2 observations identify differences in the organization of contact and release. C's mean operator-based completed interval is 2.98 s (15.8%) shorter than B's, with five completed attempts in each. This is a descriptive comparison of separately trained checkpoints, not the same weights tested with a channel switched off. A4 exposes an incomplete transition in the motion-only condition, but one interrupted attempt does not identify missing force output as the cause. The generated motion, external constant-force interface, mechanical state, and timing can all contribute.

The magnitude of force peaks also limits an uncomplicated advantage claim. C does not reduce the E2 mean peak below A, and it has greater E1 excess exposure than R and T. A lower whole-window force mean can follow from less time spent in contact. It is therefore inadequate to call that lower mean an improvement in force-control accuracy or surface finishing.

The force-frame convention is another practical boundary. The resolved teaching-to-base relation supports empirical common-axis analysis, while the evaluated training file and online adapter retain their actual numerical conventions. The force-conditioning path was not redefined for this thesis. Its present performance is an observation about that implementation; a future frame-consistent learning comparison would be a separate experiment. Similarly, the executor suppresses tangential force commands, so a nine-dimensional learned action should not be described as a physically demonstrated three-axis force-tracking capability.

8.5 Procedural Completion and Surface Quality

The contact procedure is a meaningful intermediate target for local polishing. A tool must establish contact, move through the relevant region under load, and leave the surface. E1 provides explicit observations for that sequence. E2 contributes an operator-based interpretation of task progression that preserves the interrupted attempt.

E3 adds a directly observed processing outcome: the percentage reduction of segmented board-marker ink area. N/P1/D1/D2 have means of 100.00, 97.55, 98.12, and 93.67% across 19 evaluable image pairs. These high condition means support practical reuse of the same policy with

task registration and direction alignment within the tested placements. The 83.879% D2-3 value remains an individual observation, while D1-4 and P2 remain image-unavailable; the range of means is not a minimum performance guarantee.

A completed traversal, operator completion, and a reduced image stain are complementary observations. E3 provides a quantitative ink-area outcome for its own spatial-transfer cohort. It cannot establish E1/E2 removal quality or productivity at equal removal. Neither marker disappearance nor an execution-derived heatmap independently measures metal depth, roughness, or micro-scratch restoration. This distinction preserves the positive result while stating its physical scope.

8.6 Development Extensions

Execution-derived dose heatmaps, finite blending paths, and adaptive reference-clock execution are implemented development assets. The heatmap remains an uncalibrated diagnostic; the blending and adaptive records do not provide a controlled E1–E3 surface-quality comparison. High-level residual reinforcement learning for curved-surface restoration remains planned. Appendix E preserves the diagnostic formulation, example heatmap, version distinctions, and implementation-status table. These extensions are separate from the three evaluated contributions.

8.7 Scope and Limitations

E1/E2 assess the nominal local task; E3 extends the evidence to the reported planar placements and directions. Arbitrary shapes, curved surfaces, height changes, and reference-Z robustness remain outside those observations. The tested direction transfer includes an explicit observation/image adapter and XY inverse transformation. It is not an isolated test of policy equivariance or of force observation's causal contribution to spatial transfer. The inherited blending/RL assets retain their separate implementation or planned status.

There is one recorded training seed per learned condition, distinct from the repeated robot executions. Original E1 shuffles R/T/C within five blocks, whereas R^* is a separate-date one-then-four diagnostic. E2 runs A, then B, then C, using separate checkpoints; A/B also changes action dimension

and force-target composition. Small cohorts and sample SDs establish neither statistical significance nor equivalence or population reliability. Setup, execution order, and operator timing remain possible contributors to the observed differences.

E3 is a selected development collection with retained retries and dates. N uses the existing HOME return, P1 uses PTP, and D1/D2 add commanded-release confirmation to PTP. These differences preclude treating duration or path length as a controlled removal-efficiency ranking. The image analysis is post hoc and semiautomatic, using stored photographs and saved visible-boundary annotations. D1's removal mean has $n = 4$; all five P2 final photographs and D1-4 are occluded. Hidden stain area is not estimated. The common 40/45/50 threshold sensitivity check describes segmentation dependence, not an uncertainty interval for future robot performance.

The numerical evidence is traceable to frozen run identities and archived analysis inputs. E1/E2 precision aggregates agree with their source CSVs; the additional R^* retains unrounded per-run values and template/configuration identifiers. E3 reprocessing from the original RGB, saved annotations, and fixed ROI reproduces all 25 initial areas, 19 evaluable final areas, and 75 stored mask/ROI arrays. This verifies computational reproduction of the established image analysis. It does not independently validate its manual semantic labels or calibrate physical material removal.

E1 automatic completion, E2 operator completion, and E3 image-area reduction remain distinct. A4's successful time is null; its 28.750 s interruption and all-attempt force/path values remain. C5 stays in the original C group; C6 is additional. Metal depth, mass, roughness, and micro-scratch restoration are not independently measured, and an unrecorded controller-applied target still prevents force-tracking-error claims.

Chapter 9

Conclusions

Local robotic polishing requires a strategy for movement, contact loading, and time within a selected region. Human region specification supplies the spatial task, but does not by itself determine that temporal strategy. This thesis has addressed the resulting skill-generation problem through paired motion–force teaching, observation-conditioned sequence learning, and a common robot execution interface.

Tool position is learned relative to a frozen stain center and paired with orientation and target force in one sequence. The Flow Matching policy uses RGB, Cartesian state, and three-axis force history. Its direction adapter aligns live XY and the policy image, then restores generated XY by inverse rotation and center addition; Z, orientation, and force keep their conventions. E1/E2 disable direction alignment; E3 reuses the same C checkpoint and normalizer for registered planar transfer. The interfaces separate skill generation, contact control, and completion recognition.

The first research question compares strategy providers for the fixed human-specified task. In the primary E1 cohort, rules, force-inclusive replay, and the conditioned policy each complete the required contact–loaded-pass–exit procedure in all five planned executions. Replay has a shorter mean completion time and smaller time dispersion than C, while C has greater mean excess-force exposure. The learned skill is therefore an executable strategy through the common robot interface, and rules and replay are also effective alternatives within this nominal task. C5 remains in the original C comparison and C6 is a separate diagnostic. The strategy summary distinguishes additional R^* from original T/C. Processing retiming is associated with a 4.697 s (15.9%) shorter mean than

original R while preserving +18 N and the common execution settings. This separate diagnostic uses a quintic peak-feed parameter and does not establish an IL advantage at matched measured speed.

The second research question compares the force-information configurations while retaining lower-level feedback. The force-observing motion–force policy C has a 2.98 s (15.8%) shorter mean operator-based completion interval than force-masked B, with five completed attempts in each. Motion-only A completes four of five attempts; A4 does not progress to release and is interrupted. It remains in all-attempt force, travel, and elapsed-interval statistics, while A's successful-time mean uses four completions. Timing, phase progression, and force exposure differ across the configurations, without a monotonic improvement from A through B to C or an identified cause for the single interrupted transition.

The third research question evaluates spatial reuse through an image-based processing outcome. In 20 selected N/P1/D1/D2 runs, 19 pairs permit whole-stain evaluation. Mean $\pm$ sample SD board-marker area reductions are 100.00 ± 0.00, 97.55 ± 2.49, 98.12 ± 3.75, and 93.67 ± 6.60%, respectively. D1-4 remains selected with an unavailable removal value due to tool occlusion. P2's five executed, occluded runs remain in the 25-run archive outside the main removal comparison. The results support reuse of the same policy together with task registration and the direction adapter within the tested planar placements, without new teaching or retraining.

The demonstrated scope combines contact-skill execution, observed force-information differences, and E3 image-based ink-area reduction. The latter neither establishes E1/E2 removal quality nor independently measures metal surface restoration, roughness, or micro-scratch removal. It also does not establish arbitrary geometry or height robustness. Existing dose, blending, and adaptive-execution assets remain separate extensions with their documented status.

Together, the three evaluations establish executable learned motion–force skills, observed force-information differences, and registered planar reuse with image-area evidence. Rules and replay retain their demonstrated value for the fixed task.

Bibliography

[1] I. Mohsin, K. He, Z. Li, and R. Du, "Path planning under force control in robotic polishing of the complex curved surfaces," *Applied Sciences*, vol. 9, no. 24, p. 5489, 2019.

[2] S. Schneyer, A. Sachtler, T. Eiband, and K. Nottensteiner, "Segmentation and coverage planning of freeform geometries for robotic surface finishing," *IEEE Robotics and Automation Letters*, vol. 8, no. 8, pp. 5267–5274, 2023. [Online]. Available: https://elib.dlr.de/196051/

[3] B. Alt, F. Stöckl, S. Müller, C. Braun, J. Raible, S. Alhasan, O. Rettig, L. Ringle, D. Katic, R. Jäkel, M. Beetz, M. Strand, and M. F. Huber, "RoboGrind: Intuitive and interactive surface treatment with industrial robots," in *2024 IEEE International Conference on Robotics and Automation (ICRA)*, 2024. [Online]. Available: https://arxiv.org/abs/2402.16542

[4] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn, "Learning fine-grained bimanual manipulation with low-cost hardware," in *Proceedings of Robotics: Science and Systems*, 2023.

[5] C. Chi, S. Feng, Y. Du, Z. Xu, E. Cousineau, B. Burchfiel, and S. Song, "Diffusion policy: Visuomotor policy learning via action diffusion," in *Proceedings of Robotics: Science and Systems*, 2023. [Online]. Available: https://diffusion-policy.cs.columbia.edu/

[6] C. Chen, Z. Yu, H. Choi, M. Cutkosky, and J. Bohg, "DexForce: Extracting force-informed actions from kinesthetic demonstrations for dexterous manipulation," *arXiv preprint arXiv:2501.10356*, 2025. [Online]. Available: https://arxiv.org/html/2501.10356v2

[7] W. Liu, J. Wang, Y. Wang, W. Wang, and C. Lu, "ForceMimic: Force-centric imitation learning with force-motion capture system for contact-rich manipulation," in *2025 IEEE*

International Conference on Robotics and Automation (ICRA), 2025. [Online]. Available: https://arxiv.org/html/2410.07554v3

[8] B. Zhou, R. Jiao, Y. Li, X. Yuan, F. Fang, and S. Li, "Admittance visuomotor policy learning for general-purpose contact-rich manipulations," *arXiv preprint arXiv:2409.14440*, 2024. [Online]. Available: https://arxiv.org/abs/2409.14440

[9] Z. He, H. Fang, J. Chen, H.-S. Fang, and C. Lu, "FoAR: Force-aware reactive policy for contact-rich robotic manipulation," *arXiv preprint arXiv:2411.15753*, 2025, version 2. [Online]. Available: https://arxiv.org/html/2411.15753v2

[10] Y. Lipman, R. T. Q. Chen, H. Ben-Hamu, M. Nickel, and M. Le, "Flow matching for generative modeling," in *International Conference on Learning Representations*, 2023. [Online]. Available: https://arxiv.org/abs/2210.02747

[11] O. Siméoni, H. V. Vo, M. Seitzer, F. Baldassarre, M. Oquab, C. Jose, V. Khalidov, M. Szafraniec, S. Yi, M. Ramamonjisoa, F. Massa, D. Haziza, L. Wehrstedt, J. Wang, T. Darcet, T. Moutakanni, L. Sentana, C. Roberts, A. Vedaldi, J. Tolan, J. Brandt, C. Couprie, J. Mairal, H. Jégou, P. Labatut, and P. Bojanowski, "DINOv3," *arXiv preprint arXiv:2508.10104*, 2025. [Online]. Available: https://arxiv.org/abs/2508.10104

[12] N. Hogan, "Impedance control: An approach to manipulation: Part i—theory," *Journal of Dynamic Systems, Measurement, and Control*, vol. 107, no. 1, pp. 1–7, 1985.

[13] A. Q. L. Keemink, H. van der Kooij, and A. H. A. Stienen, "Admittance control for physical human–robot interaction," *The International Journal of Robotics Research*, vol. 37, no. 11, pp. 1421–1444, 2018.

Appendix A

Coordinates, Signals, and Reproduction

A.1 Pose and Force Signal Definitions

The position vector is expressed in millimeters and orientation as a rotation vector in radians. The matrix $R = \mathrm{Exp}([\rho]_\times)$ maps a vector in the calibrated tool frame to the robot base when it represents $R_{B\leftarrow E}$. $[\rho]_\times$ is the skew-symmetric matrix associated with ρ. The saved dataset transformation subtracts only (c_x, c_y). The optional inference transformation additionally rotates center-relative XY by $R_2(\alpha)$, with inverse rotation followed by center addition on output (Section 3.5). Both retain Z, tool rotation vectors, and force channels. The evaluated E1/E2 settings use $\alpha = 0$.

Teaching force is a three-component post-publisher measurement. Its associated tool orientation supplies the base-axis rotation in Equation (4.3). Robot wrench feedback is already base expressed. A torque reference-point transformation would require a moment arm, but no torque transfer is needed for the three-force-component base projection used here. The available analysis does not infer a calibrated compliant contact point from a TCP-center trajectory.

Table A.1 distinguishes the force signal roles.

A.2 Learning and Temporal Parameters

The force-cleanup dataset contains 15,963 paired frames in 42 compact episodes. The optimization and validation sets contain 38 and four episodes. Validation episode identifiers are 35,

Table A.1: Force signal roles used throughout the thesis.

Signal	Interpretation
Teaching intention	Operator's approximate loading intention; not a numeric command trace.
Teaching recorded force	Measured interaction after the published processing path; used to construct learning supervision.
Policy force action	Denormalized output of the generator before executor gating and slew.
Executor transmitted target	Command-side force after shared processing; tangential target channels disabled in these comparisons.
Controller-applied reference	Target after internal controller processing; synchronized trace unavailable.
Robot measured force	Processed base-frame feedback used by the common gate, policy adapter, and recorded analysis.

39, 22, and 37. Each epoch's training window construction uses 50 starts per episode, a 128-step target, and the archived phase-sampling weights. The partition stored in each normalizer matches the dataset manifest.

The force-history dimension is three, its sample count is 30, and the selected recurrent layer is a one-layer GRU with hidden size 64. The state encoder receives pose and current force together in B/C. A removes the force state dimensions and history encoder. B retains the history architecture with zeroed conditioning. Physical force remains available to common execution in all conditions.

The training horizon, reference stride, inference timer, command period, and logging cap describe different mechanisms:

A.3 Data and Analysis Reproducibility

The run-level results retain the original identifiers, cohort membership, saved configurations, and analysis definitions. E1/E2 statistics use the archived precision CSVs matched to their frozen selections. E1's additional R^* cohort preserves its separate collection and unrounded values. The common result summary supplies the numerical tables and reported aggregates.

E3 reproduction uses the original before/after RGB hashes, saved visible-boundary annotations, fixed ROI construction, and archived segmentation algorithm. The reproduced initial/final ink masks and ROI arrays agree pixel by pixel with the stored analysis outputs. The displayed photographs and

Table A.2: Distinct clocks and sampling settings.

Mechanism	Value or meaning
Teaching paired sample grid	Nominal 30 Hz; original receipt times retained in merged HDF5.
Action sequence	128 samples, nominal 30 Hz.
Nominal new-plan stride	120 action samples at 30 Hz: 4.0 s.
E3 replanning lead / plan-age threshold	0.5 s / $4.0 - 0.5 = 3.5$ s, from saved configurations and runtime snapshot.
Actual plan-generation intervals	Not measured here; affected by callback scheduling and inference latency.
Inference callback timer	5 Hz, subject to plan-age gating.
Flow integration	10 dimensionless updates per generated chunk.
Command publication	Nominal 125 Hz (0.008 s).
E1 actual receipt-event recording	Approximately 125 Hz in the 15 October primary cohort; distinct subscription receipts.
E2 feedback CSV logging	20 Hz cap; approximately 18 Hz observed in the 13 October archive.
Analysis support	Receipt-time ZOH force and within-support pose interpolation; maximum gap 0.2 s.

binary masks remain distinct from conceptual diagrams and from uncalibrated execution heatmaps. Display cropping and enlargement never supply the measured areas.

The accompanying analysis manifests identify the source inputs, per-run configuration and image mapping, numerical precision, and software versions. Document construction uses the bundled figures, selected original photographs, bibliography, and LaTeX sources. Repeating the full image analysis additionally requires the original research archive. Both procedures preserve the recorded sample selection and unavailable measurements.

Appendix B

Experiment Versions and Provenance

B.1 Selected Models and Dataset

The dataset and models are the force-cleanup revision dated 12 October, with training completed on 13 October 2026. All three selected checkpoints have their own normalizer. The best epochs are 39, 42, and 42, while final epoch is 499. The stored checkpoint selection rule is minimum validation loss over 500 epochs. The model manifest preserves the original CPU metadata inspection. The E3 C checkpoint and normalizer files also match the hashes in every selected execution configuration; they are hashed without model loading or retraining.

Table B.1 lists the selected model identifiers.

The compact replay episode is linked to the source merged HDF5 recorded at 16:18 on 19 August 2026, source episode `ep_0003`. Its compact action and observation pose/force arrays contain 443 frames. The original source-time array is retained for T rather than replaced by an assumed

Table B.1: Short SHA-256 identifiers of the selected checkpoints and normalizers. Complete values are included in the supplied model manifest.

Model	Checkpoint prefix	Normalizer prefix
A	`2ea204ab65fb`	`ae7d07adf65a`
B	`080103e6c2ed`	`d7c917b8246c`
C	`60d55e7092cb`	`09111fa4acc3`

constant period. The exact source paths and extraction fields are recorded in the supplied episode metadata.

B.2 Primary E1 Version and Membership

The physically executed primary cohort is

`E1_CT_pass_height_v2_nominal_dev_20261015`

with configuration `e1ct_46de718a23a2a7cf`, evaluator `pass_height_ref_v2`, and observer `received_observations_v2`. The source report freezes the 15 planned run identifiers. Each planned slot has one started primary execution, and the original C5 remains the run ending in `230120_b45d2f021b`. Its full identifier and the additional C6 identifier are recorded in the cohort manifest.

C6 is the later execution ending in `233551_9021584d0a`. It retains repeat index 5 and the source retry link in the original archive, but is displayed as C6 for diagnostic interpretation. The subsequent session list therefore has 16 entries, while the primary E1 set remains the report-frozen 15. The explicit selection uses planned slots and original identifiers rather than the most recent record per repeated index. The same C checkpoint and frozen execution setting are retained.

The handoff `baseline_manifest.json` still contains preparation-era zero-attempt fields. The actual report, original execution evidence, and frozen report membership supersede those status fields for this thesis. The nominal placement is operator reported; the configured approximate surface Z is not a per-trial physical measurement. LOW/HIGH and reference-offset robustness are outside the completed evaluation scope.

B.3 Historical E1 Development and Height-Only Replay

The 14 October development session, `E1_CT_sync_confirm_dev_20261014`, uses configuration `e1ct_61a19f7d7337a82c` and the initial-contact height reference. Its started order is R, then T, then C. All 15 started runs show the required loaded pass, while the old exit criterion reports

Table B.2: Historical 14 October E1 development cohort with the initial-contact height reference. Completed-time means use $n = 3, 4, 5$ for R/T/C; excess-force summaries retain five started runs per method. These executions are not pooled with the primary cohort.

Method	Completed/started	Completed time (s)	J_{excess} (N s)
R	3/5	29.58 ± 0.03	0.000 ± 0.000
T	4/5	12.86 ± 0.01	0.005 ± 0.011
C	5/5	15.67 ± 3.60	2.323 ± 2.493

Table B.3: Height-only offline replay of the 14 October records. This secondary sensitivity analysis changes the release reference, retains the recorded trajectories, and adds no independent trials.

Method	Replay completed	Replay time (s)
R	5/5	27.24 ± 1.28
T	5/5	12.84 ± 0.02
C	5/5	15.64 ± 3.59

R 3/5, T 4/5, and C 5/5. Table B.2 preserves this historical comparison separately from the primary 15 October results.

The old release requirement was

$$Z(t) \geq z_{\mathrm{contact}} + 5\ \mathrm{mm}, \tag{B.1}$$

with OFF and rise sustained together for 0.2 s. R1, R3, and T4 were sensitive to the early height reference. The archived height-only replay changes that reference for the same observations and reports 5/5 for every method (Table B.3). It supplies no new physical executions and does not reconstruct the later receipt-event observer.

Figure B.1 compares the historical exit-height references.

An original 14 October R5 registration did not reach execution start and was followed by a started retry. Its source identifiers remain in the historical provenance. This bookkeeping does not apply to the 15 October primary cohort, whose original 15 slots contain no non-start or retry. Earlier prepared but unexecuted sessions are historical preparation records and are not incomplete requirements of the present thesis.




Figure B.1: Historical 14 October release thresholds using the initial-contact and successful-pass references. Both are derived from the same stored TCP traces. This diagnostic is distinct from the physically executed 15 October primary evaluator.

B.4 E2 Versions and the A4 Correction

The selected E2 cohort uses the force-cleanup revision of 13 October. Each actual `runtime.json` names its model revision, observation settings, and common executor. The run inventory orders the attempts A1–A5, B1–B5, and C1–C5. Preparation-only runtime files are not used as substitutes for these actual run files.

The old E2 report applied a common operator-confirmed completion interpretation to all 15 attempts. The later task instruction specifically corrects A4. This thesis adopts that field correction and stores it in `data/e2_operator_correction.json`. The original software event remains `operator_finish`, followed by the original normal-completion stop-path event. The derived task outcome is separately marked incomplete contact release. The original elapsed time 28.750087346 s remains the interruption interval.

The correction changes only the successful-time aggregation and task interpretation. A4 remains in all five-attempt statistics for force, travel, and elapsed interval. No surface image, raw force sample, event timestamp, or checkpoint is edited. The corrected table can be reconstructed from `data/e2_runs_corrected.csv`.

B.5 Sources for Implemented Extensions

The execution heatmap is generated by the existing polishing-removal recorder. The finite blending path and dose tools are in the local blending module and the 13 October extension package. The adaptive-velocity development records are versioned separately under the 14 October results directory. Their runtime metadata identifies them as adaptive-execution development rather than the primary E2 force ablation.

Appendix C

Individual Outcomes and Evidence Boundaries

C.1 E1 Primary Executions

Table C.1 lists all original primary E1 executions on 15 October. Every row completes the specified contact–pass–exit procedure, including C5. The recorded order identifies the shuffled blocks. C6 is reported separately in Table C.4 and is not a sixth observation in any primary C mean.

C.2 E2 All Attempts

Table C.2 distinguishes successful completion intervals from time to interruption. All original stop requests are retained. In particular, the missing A4 completion time is not a missing raw record.

The archived video inventory contains B/C videos but no A videos. The illustrated C1 WebM has an incomplete container ending; only decodable frames are used. It is not treated as a continuous independent proof of full task completion. Snapshot timing and varying tool viewpoint also limit before/after interpretation.

Table C.1: All 15 primary E1 executions under `pass_height_ref_v2`. All are procedurally completed. Full run identifiers, original labels, and source paths are preserved in the cohort manifest.

Run	Order	Completion (s)	J_{excess} (N s)	Peak F_z^B (N)
R1	2	29.424	0.000	22.81
R2	5	29.516	0.000	23.18
R3	7	29.546	0.000	22.90
R4	10	29.573	0.000	22.52
R5	13	29.625	0.000	22.02
T1	1	12.828	0.037	32.85
T2	4	12.908	0.001	30.96
T3	9	12.896	0.580	38.24
T4	11	12.920	0.010	31.91
T5	15	12.931	0.000	30.43
C1	3	11.694	0.048	32.89
C2	6	12.876	0.431	34.35
C3	8	12.740	0.237	33.43
C4	12	11.766	0.068	32.65
C5	14	18.024	6.413	40.21

Table C.2: Individual E2 task outcomes after the A4 field correction. "Operator completed" uses the recorded operator interpretation; it is not an automatic E1 evaluation.

Run	Task outcome	Completion (s)	Interval to stop (s)
A1	operator completed	16.787	16.787
A2	operator completed	16.445	16.445
A3	operator completed	18.581	18.581
A4	interrupted	—	28.750
A5	operator completed	18.777	18.777
B1	operator completed	18.690	18.690
B2	operator completed	18.511	18.511
B3	operator completed	19.508	19.508
B4	operator completed	18.693	18.693
B5	operator completed	18.671	18.671
C1	operator completed	15.902	15.902
C2	operator completed	15.297	15.297
C3	operator completed	15.597	15.597
C4	operator completed	16.751	16.751
C5	operator completed	15.618	15.618

Table C.3: Original R/T/C comparison on 15 October 2026; mean ± sample SD, $n = 5$. This table preserves the original cohort and is not pooled with additional R^*.

Method	Completed/started	Time (s)	J_{excess} (N s)
R	5/5	29.537 ± 0.075	0.000 ± 0.000
T	5/5	12.897 ± 0.041	0.125 ± 0.254
C	5/5	13.420 ± 2.630	1.440 ± 2.785

C.3 Cohort Membership and Interpretation

The original `data/cohort_manifest.csv` and JSON counterpart preserve the original E1 15, E2 15, and diagnostic C6. The current `results_manifest_20261108.csv` adds the five separate R^* executions and all 25 E3 records with their original run identifiers. It distinguishes main, additional-diagnostic, and archive-only roles, including incomplete and image-unavailable observations.

The precision summary, prose macros, tables, and affected plots use `data/results_summary_20261108.json`. The reported results use verified archived precision rows and reproduced E3 native-pixel counts. Original R and R^* are not pooled, and image evaluability remains distinct from procedural completion.

C.4 Original E1 Strategy Traces and Additional Cases

The original 15 October R/T/C summary is preserved here separately from the additional-R*/original-T/C table. Each method has five completed executions. Table C.3 and Figures C.1 and C.2 retain the original results and traces, including C5 and excluding C6 from group statistics.

C.4.1 Original C5 and Additional Diagnostic C6

The original primary C5 completes at 18.024 s, with $J_{\text{excess}} = 6.413$ N s and observed peak 40.21 N. Its required loaded pass completes at 16.488 s. These values remain in every primary C summary. The additional execution at 23:35 on the same date is displayed as C6. Its source retains repeat index 5 and a retry link to C5; those original fields are preserved in the manifest, while the analysis treats it as an additional post-comparison diagnostic rather than replacing the planned slot.




Figure C.1: Actual received robot-base F_z for all 15 original E1 runs, from execution start to first completion. Values use the archived ZOH display. The dashed teaching Q95 is an empirical analysis reference. C5 remains included.

Table C.4: Individual E1 executions with the same recorded evaluator. C5 belongs to the original primary five; C6 is additional diagnostic evidence. Times are relative to each execution start. Single-run values are shown without mean or SD.

Metric	Original C5 (primary)	C6 (diagnostic)
Completion time (s)	18.024	11.728
First confirmed contact (s)	4.464	4.420
Required pass complete (s)	16.488	10.980
Working reference Z (mm)	174.209	174.411
Required exit Z (mm)	179.209	179.411
Observed peak force (N)	40.211	35.006
J_{excess} (N s)	6.413	0.471
Time above reference (s)	1.829	0.260
Recorded contact losses	1	0




Figure C.2: All 15 original E1 TCP-center XY paths through first completion. The shaded region is the fixed 25 mm evaluation band, not a contact footprint or removal map.

C6 completes at 11.728 s, with $J_{\text{excess}} = 0.471$ N s and peak 35.006 N. The original outcome file and actual receipt events support these quantities. Figure C.3 shows that C5's first successful pass occurs later, while initial contact confirmation occurs at a similar elapsed time. C5 records one contact loss and C6 none. These stage observations describe the traces and do not establish a failure mechanism.

C5's longer execution and larger excess integral are not reproduced in C6. One additional execution does not show that the variability is resolved, that C5 was erroneous, or that the model improved. The original five-run comparison remains the basis for R/T/C conclusions.

C.5 E2 Force Traces and Transition Cases

C.5.1 Phase Transitions and Execution Cases

A4 is a direct counterexample to treating every normal-completion software event as task success. The operator reports that the tool remained in contact rather than progressing to release, and interrupted the attempt after 28.750 s. Its measured mean F_z^B is 19.456 N and its interval with recorded force at or above 3 N is 24.564 s. The trace is consistent with prolonged loading. The field report establishes the task interpretation; the trace does not independently establish why the transition failed.




Figure C.3: Separate traces for original C5 and additional C6. Top: received force with teaching Q95 dashed. Bottom: measured Z with required exit height dashed. Vertical dotted gray, dashed blue, and solid orange lines mark confirmed contact, required-pass completion, and first procedural completion. Full analysis windows are shown with a common time axis. C6 is not included in the primary mean.




Figure C.4: All measured E2 base-force traces from execution start to first operator stop request. A4 remains in A's five curves. Each curve uses native recorded values with ZOH; the plots do not infer a controller-applied force target.




Figure C.5: Two retained E2 transition cases. A4 is included because of the operator-confirmed release-transition failure. B4 is included because it has the maximum recorded contact-gate transition count, 38. Full force and Z traces are shown. Rapid gate transitions are a software contact diagnostic, not an independently counted number of physical impacts.

B4 illustrates a different phenomenon: the common instantaneous gate toggles repeatedly near contact transitions, with 38 recorded changes. The group mean gate-transition counts are 2.6 ± 0.9 for A, 12.4 ± 14.8 for B, and 3.6 ± 1.7 for C. B's dispersion is strongly influenced by B4; it is retained. Threshold crossings, baseline behavior, and transition timing can all affect these counts. They are not sufficient to diagnose an encoder failure or a physical contact-instability mechanism.

E2 C shows a relatively compact range of operator-based intervals and XY travel, but B's completed-time SD is smaller. Repeatability therefore depends on the quantity being considered. A leave-one-out deviation from other executions, where used in earlier diagnostics, would measure between-run repeatability rather than agreement with the teaching or controller force-tracking accuracy. The present primary comparisons use the explicitly reported timing, force, and travel quantities.

C.6 E1/E2 Qualitative Image Evidence

Figure C.6 shows the first started run of each E1 method, selected by run index without screening for the best image or result. The provider's initial and final snapshots have different viewpoints and times as the tool moves. They can illustrate the marked task and visible appearance but cannot quantify common-area removal. All-trial numerical results accompany these examples.

Figure C.7 presents uniformly sampled frames from the retained C1 video.




Figure C.6: Actual provider snapshots from the original E1 R1, T1, and C1 executions on 15 October 2026. Initial/final denote saved provider snapshots rather than matched metrology exposures; viewpoint, occlusion, and timing can differ. Visible marking changes do not measure scratch depth or surface restoration.




Figure C.7: Uniformly spaced camera-pane crops from the decodable portion of the first E2 C video. Only the adjacent diagnostic panel is omitted; camera overlays are retained. Times are video offsets, not synchronized stage-event times. The archived WebM ends prematurely and is not used to certify a complete exit sequence. A4 has no archived video.

Appendix D

Additional R Diagnostic and E3 Image Archive

D.1 Additional R Executions and Source Precision

Tables D.1 and D.2 report the five additional outcomes and original identifiers.

The original per-run precision CSV and 17-page additional-R report describe the same five executions. Their identities, session/configuration identifiers, and template hashes are verified against the stored run contexts and input manifest. The first run uses configuration `e1ct_6c29a198a24df7a2`; repeats 2–5 use `e1ct_c5c424abc45fac4c`. All share the frozen template with SHA-256 prefix `1616a9f1bbb68df6`, the recorded feed, +18 N target, and v2 evaluator/observer. These identifiers preserve the one-then-four collection history.

Table D.1: All five R^* executions on 19 October, calculated from unrounded source CSVs and displayed to three decimals. The first diagnostic precedes four extension runs. These do not replace the original R1–R5. Time is first automatic procedure completion; pass speed uses the successful loaded-pass support.

Run	Time (s)	J_{excess} (N s)	Peak (N)	Pass (mm/s)
R*1	22.481	0.000	21.488	10.696
R*2	25.319	0.000	22.000	10.887
R*3	25.520	0.000	20.541	10.886
R*4	25.458	0.000	22.727	10.822
R*5	25.420	0.000	20.944	10.915

Table D.2: Original identifiers for the additional R^* cohort. Full configuration and input hashes are supplied in the results manifest.

Run	Original run identifier
R*1	`E1_CT_NOMINAL_R_r1_20261019T140517_0921f1508b`
R*2	`E1_CT_NOMINAL_R_r2_20261019T141109_d8d222935d`
R*3	`E1_CT_NOMINAL_R_r3_20261019T141211_32499d64f6`
R*4	`E1_CT_NOMINAL_R_r4_20261019T141312_586a744e36`
R*5	`E1_CT_NOMINAL_R_r5_20261019T141415_bc2827864a`

Reaggregation of the unrounded times gives 24.839595 s and sample SD 1.320611 s, reproducing the displayed 24.840±1.321 s. The source-derived values and original identifiers are retained in `data/e1_rstar_source_runs.csv`. All five zero excess integrals and the shorter first run remain included.

D.2 E3 Main-Run Pixel Areas

Table D.3 lists the native-pixel areas for every main selected run.

The source-derived per-run identities and areas are captured in `data/e3_source_area_runs.csv`. Their ratios reproduce the reported main condition means and sample SDs. P1 ranges from 93.742 to 99.764%, evaluable D1 from 92.491 to 100.000%, and D2 from 83.879 to 98.250%. The eight 100% observations (five N and D1-2/3/5) mean black-ink nondetection under the established criterion. Figure D.1 preserves D2-3, the lowest observed individual removal, including all 128 residual pixels.

D.3 Occlusion, Interruption, and P2 Exclusion

Table D.4 preserves the five excluded P2 image records. Figures D.2 and D.3 show the retained interruption and occlusion evidence.

D1-4 retains `manual_abort`; its interruption-time diagnostic frame contains visible residual marking and final tool occlusion. The report identifies the frame as received 34.5 ms before the abort request (source stamp approximately 0.55 s before it). No post-HOME photograph is available. The visible region is not used to estimate hidden total residual area. P2's initial frames are same-run

Table D.3: All 20 main selected N/P1/D1/D2 runs. Native-pixel areas are reproduced from the original RGB and frozen annotations and agree with the stored masks, CSVs, and image report. Percentages use Equation (6.8). D1-4's final area and percentage remain null. Image evaluability is not procedure success.

Run	A_{before} (px)	A_{after} (px)	Removal (%)	Note
N-1	837	0	100.000	image evaluable
N-2	879	0	100.000	image evaluable
N-3	699	0	100.000	image evaluable
N-4	697	0	100.000	image evaluable
N-5	712	0	100.000	image evaluable
P1-1	858	31	96.387	image evaluable
P1-2	846	6	99.291	image evaluable
P1-3	772	11	98.575	image evaluable
P1-4	846	2	99.764	image evaluable
P1-5	799	50	93.742	image evaluable
D1-1	546	41	92.491	image evaluable
D1-2	676	0	100.000	image evaluable
D1-3	680	0	100.000	image evaluable
D1-4	700	—	—	tool occlusion
D1-5	798	0	100.000	image evaluable
D2-1	768	79	89.714	image evaluable
D2-2	738	13	98.238	image evaluable
D2-3	794	128	83.879	image evaluable
D2-4	743	13	98.250	image evaluable
D2-5	684	12	98.246	image evaluable




Figure D.1: D2-3: original RGB and unchanged masks. The 794 initial and 128 residual pixels give 83.879% removal. The common native-coordinate crop, dashed ROI, and black ink pixels follow the main evidence figures. This observed value is retained in D2's five-run mean.

Table D.4: P2 was executed five times and remains in the original 25-run selection. Every final photograph is tool-occluded. The initial areas are retained; whole-stain final areas and removal percentages are unavailable, not zero. P2 is outside the main four-condition removal evaluation.

Run	A_{before} (px)	Image result	Original stop
P2-1	777	unavailable	`operator_finish`
P2-2	773	unavailable	`operator_finish`
P2-3	652	unavailable	`operator_finish`
P2-4	717	unavailable	`operator_finish`
P2-5	778	unavailable	`operator_finish`

Table D.5: Existing sensitivity results from the image report, p.36. Values are condition-mean percentages; main gray threshold is 45. These are not sample SD or confidence intervals. D1 uses four images throughout.

Condition	gray ≤ 40	gray ≤ 45	gray ≤ 50
N	100.000	100.000	100.000
P1	97.912	97.552	96.914
D1	98.124	98.123	98.056
D2	94.659	93.665	92.932

pre-execution raw RGB, replacing initially occluded photographs; the final occlusion remains. These records are not removed or renamed in the archive.

D.4 Reused Segmentation Sensitivity and Procedure Diagnostics

The report's sensitivity check keeps annotations and ROI fixed and changes the gray threshold equally in before/after images. Table D.5 reproduces the published condition means at their printed precision; no new threshold or manual boundary is selected.

The archived v2 procedure outcomes are 8 completed and 17 `observation_unavailable` in the original 25-run selection, with 24/25 HOME returns. The 25-page execution report, its per-run metrics CSV, and the selected run contexts retain these same identities and diagnostic labels. They are auxiliary procedure records on that archive, not removal successes or outcomes for the main 20-run subset. Image inclusion is independent of them; the force/path evaluator is not rerun for the image analysis.




Figure D.2: D1-4 original pre-task RGB and interruption-time diagnostic frame, with the unchanged saved masks. Hatching denotes final tool occlusion in the initial-frame reference grid. Visible residual ink is retained; hidden residual area is not estimated and whole-stain removal remains null. The existing surface-feature alignment is used for the occlusion display only.




Figure D.3: P2-1 original pre-execution initial RGB and final image, with saved masks and occlusion hatching. The same-run initial replacement exposes the marking; final tool occlusion prevents whole-stain measurement. The mask display uses the established surface homography without reconstructing hidden image content. All five P2 records remain in the 25-run archive.

D.5 Evidence Availability and Reproduction

The 39-page image report's pp.10–34 contain one RGB/ROI/mask evidence panel per selected run. The original `image_pair_manifest.json` and CSV, `analysis_config.json`, `annotations.json`, and `occluded_runs.csv` are linked to the frozen 25-run selection. All 50 original RGB files match the recorded file hashes. The saved per-run contexts confirm the registered offsets, common C checkpoint/normalizer identifiers, and condition-specific termination implementations.

Reprocessing the original RGB with the unchanged algorithm, inclusive gray threshold 45, and saved polygon/ROI settings reproduces all 25 initial areas, 19 available final areas, and visible-residual diagnostics for the six occluded cases. The 25 initial ink masks, 25 final aligned masks, and 25 initial ROI arrays are pixel-identical to their archived counterparts. All 19 evaluable pairs use verified identity surface registration. The six occluded pairs retain their original surface-feature alignment and unavailable whole-stain values. This is RGB-level computational reproduction, in addition to CSV aggregation and mask comparison; it is not an independent reassessment of the manual semantic labels.

The native figure assets preserve the original 424×240 photographs. Binary-mask panels use the same $x = 175{:}325$, $y = 39{:}135$ crop and scale before/after and across displayed cases. Nearest-neighbor display preserves individual pixels; dashed vector ROI boundaries and occlusion hatching are annotations. No enhanced or generated photograph is used for measurement. The supplied display manifest records the selected original run IDs and hashes. Full source mapping, verification levels, software versions, and commands are supplied separately from the standalone document build.

Appendix E

Development Extensions

E.1 Execution-Derived Dose

The repository includes an execution-derived heatmap recorder. It integrates a Preston-style force–speed product along the measured path and optionally spreads it over a nominal tool kernel. Its diagnostic quantity can be expressed as

$$D(x, y) = \sum_k \kappa \, F_{n,k} \, v_k \, \Delta t_k \, K_{\mathrm{tool}}(x - x_k, y - y_k), \tag{E.1}$$

where (x_k, y_k) is the recorded path location, $F_{n,k}$ the implementation's selected force component or projection, v_k its selected speed, Δt_k the observation duration, and K_{tool} a spatial spreading kernel. Without a measured coefficient and tool-response calibration, κ defines relative scale and D has arbitrary units. Different recorder/extension versions also make different kernel and speed-model choices.

Figure E.1 illustrates this uncalibrated diagnostic quantity.

The implementation and generated artifact support calling this an implemented diagnostic extension. They do not support the older claim of a calibrated material-removal model. Its spatial distribution may help inspect where modeled processing exposure accumulated, but equal dose is not demonstrated equal removal on the actual specimen.




Figure E.1: Historical execution-derived heatmap from E1 C1 on 14 October 2026, reproduced with its original axes and colorbar. Values are an uncalibrated model diagnostic in arbitrary units. They are not measured removal depth, effective contact footprint, or surface-quality improvement. This historical illustration is separate from the 15 October primary E1 cohort.

Table E.1: Status of inherited extensions relative to the main thesis evidence.

Asset	Supported status
Execution heatmap	Implemented and generated from runs; uncalibrated arbitrary-unit diagnostic.
Finite blending planner	Implemented; archived offline planning and integration preparation. Surface-quality improvement not established by the main comparisons.
Adaptive reference-clock execution	Separate versioned development attempts and code; controlled ON/OFF outcome benefit not established.
High-level residual RL for curved-surface restoration	Planned extension; completed skill-level training and quality-grounded evaluation not established in the selected evidence.

E.2 Blending and Adaptive Execution Assets

The project also contains finite local blending-path generation from an existing dose map, construction of an additional spatial target, and time allocation along a path. The 13 October extension prepares a sequence in which an initial skill is followed by a separate blending pass and diagnostic displays. Its archived validation includes offline planning from an earlier execution. That is evidence of an implemented extension, not an E1–E3 surface-uniformity result.

Separate 14 October adaptive-velocity records provide development experience with reference-clock progression and replanning. The located runtime files contain five online-OFF development attempts across multiple versions. Their completion status does not establish a controlled adaptive ON/OFF process-quality comparison. A later source revision addresses a recorded stalled reference-clock case, but its README explicitly distinguishes offline checking from a new physical run. These records are therefore kept outside the nominal E2 A/B/C cohort.

Table E.1 distinguishes the supported status of each extension.

Residual adjustments to orientation and feed velocity based on residual removal demand remain a planned extension. Existing low-level learned mass/damping control is a different asset and does not validate that proposed high-level policy. The core motion–force skill in this thesis does not require a removal estimator, blending planner, or residual RL stage to count as an executable system.

국문요약

인간의 영역 지정과 동작–힘 결합 표현 및 힘 조건부 모방학습을 활용한 국소 로봇 폴리싱

송은섭

지능형로봇학과

성균관대학교

국소 표면 재작업에서는 지정된 영역 안에서 공구 동작, 접촉 힘, 작업 시간을 함께 구성해야 한다. 본 연구는 사람이 처리 영역을 지정하고 교시를 제공하는 국소 로봇 폴리싱 체계를 구현한다. 동작–힘 결합 표현은 Cartesian 공구 위치 · 자세와 교시 유래 목표 힘을 같은 시간축에 대응시킨다. Flow Matching 정책은 RGB, pose, 측정 힘 및 힘 이력에 조건화하여 동작–힘 시퀀스를 생성한다. 공통 실행 계층과 기존 하위 힘제어기가 이를 로봇 접촉 작업으로 연결한다. 영역 중심 상대위치와 명시적인 평면 방향 어댑터로 등록 위치 · 방향에서 스킬을 재사용한다.

E1은 규칙, 힘 포함 교시 재생 T, 힘 조건부 정책 C의 절차 수행을 비교한다. 세 전략은 관측된 각 5회에서 접촉–연속 부하 통과–이탈 절차를 완료했다. 별도 추가 규칙 시간매개화 진단 R^*를 원 규칙 시행과 구분하며, R^*/T/C의 완료시간 평균±표본 SD는 24.840±1.321, 12.897±0.041, 13.420±2.630초다. T는 C보다 시간 산포와 초과 힘 적분이 작았다. R^*는 원 규칙보다 평균 4.697초(15.9%) 짧았으며 실측 평균속도 정합 비교는 아니다.

E2는 외부 힘 목표를 쓰는 동작 전용 A, 힘 관측을 마스킹한 동작–힘 학습 B, 측정 힘에 조건화한 C를 비교한다. 완료는 4/5, 5/5, 5/5회이며, 작업자 기준 완료시간은 17.65±1.20, 18.81±0.40, 15.83±0.56초다($n = 4, 5, 5$). C의 평균은 B보다 2.98초(15.8%) 짧았다. 이는 E1의 자동 절차 완료시간과 구분되는 기술통계다.

E3는 동일 C 정책을 재교시 · 재학습 없이 다른 평면 위치 · 방향에 적용한다. 원 RGB와 저장된 주석 · ROI · 임계값을 그대로 사용하여 보드마카 잉크 면적 감소율을 재현했다. N/P1/D1/D2는 총 20회 중 19회의 영상 평가가 가능했고, 제거율 평균±표본 SD는 100.00±0.00, 97.55±2.49, 98.12±3.75, 93.67±6.60%다($n = 5, 5, 4, 5$). 최종 공구 가림은 결측으로 유지했다.

결과는 인간 지정 작업에서 학습 스킬의 실행 가능성, 힘 정보 구성별 실행 특성, 시험 배치 안에서 등록 · 방향 어댑터와 결합한 재사용을 뒷받침한다. 고정 작업에서는 규칙과 교시 재생도 유효했다. 영상 면적 감소와 절차 완료는 서로 다른 결과이며, 금속 제거 깊이 · 질량 · 거칠기 · 미세 스크래치 복원은 독립 계측하지 않았다.

주요어: 로봇 폴리싱, 인간 작업 지정, 동작–힘 표현, 힘 조건부 모방학습, 공간 스킬 전이