

Don't see what you're looking for? Log in for the full Help Center experience

Policy examples

Updated 3 months ago

Overview

Your company's unique activities, security, and regulatory needs may cause you to build your Policies differently than other Fireblocks customers. Below is a range of basic operational and approval flows for common use cases that you can benchmark or use as a template.

Trading and treasury management examples

Example 1

There are three Policy roles users can be assigned to in transaction flows: Initiator, Approver, and Signer. In this example, a company only wants specific users to have these operational roles. Their Policy could look like this:

#	Name	Initiator	Signer	Source	Destination	Amount	Asset	Action
01	Vault-to-vault	Traders	Management	Any	Any vault account	Unlimited USD per transaction	All	Require approval of: 1 of 1 group
02	Default transfer rule	Anyone	Initiator	Any	Any	Unlimited USD per transaction	All	Block

The Policy uses one basic rule to assign these functions.

1. Only members of a user group called Traders can *initiate* transactions.
2. Only users from a group called Management can *approve* the Trading group's transactions. Only one member of that group needs to approve the transactions before they can be signed.
3. Only the Head of Trading can *sign* the transaction to the blockchain after approval.

The second rule is the block-all rule, the mandatory rule at the bottom of every Policy that blocks any transaction that does not explicitly match a rule above it.

Creating this Policy example using the Policy Editor

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help Center

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Enter a name that makes the rule easily identifiable.

Vault-to-vault

Source

Choose an origin account.

 Any possible account 



Destination

Choose a destination account.

Any vault account 



☒ All addresses ☐ Whitelisted address ☐ One-time address only

Initiator

Choose the user or group that initiates the transaction.

Traders 



Funds

Define the type and amount of funds relevant to the rule.

- ☐ Non-fungible tokens (NFTs)
☒ Fungible tokens or coins

Asset

Choose the asset that this rule applies to.

Any



Value

Set the asset's minimum value.

Minimum

0

Currency

USD



Limitation

Add an extra layer of security to the rule.

- ☒ Limit to single transaction
☐ Limit to specific time

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks
/

⊗ Block
✓ Allow
✓ Request approval

Approval
Create a set of approvers using individual users, API keys, or groups.

☒ Transaction initiator can approve

Approver set

Management
x
v

+ Add approver set

Threshold

– 1 +

Designated signer
Assign the user required to sign the transaction.

☐ Initiator

☒ Single user

☐ Multiple users

Head of Trading

Your Policy will use more rules and parameters based on transaction values, Initiator types, and more. Example 2 below shows a more complete Policy for a trading business.

Example 2

Below are best practices to structure your workspace for trading and treasury management needs. To be competitive, you can set rules that enable your management team and traders to settle trades or rebalance quickly within limitations to manage risk.

In this example, the business needs both the Management and Trader user groups to transfer without approvals up to a certain value, requires custom approval flows for higher value transfers, and rejects all transfers if a pre-set aggregate limit exceeds an 8-hour window or per transaction.

Management group users also need less strict value thresholds and more flexibility than Traders group users regarding which types of accounts they can initiate transfers from.

Below are generic examples of Policy rules that meet these needs. Each rule is briefly explained beneath the image.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Fireblocks Help Center



06 Default transfer rule	Anyone	Initiator	Any	Any	Unlimited USD per transaction	All	Block
--------------------------	--------	-----------	-----	-----	-------------------------------	-----	-------

- Rules 1-3 are ordered by the highest Amount threshold to the lowest for transfers initiated by a Management group user. The most restrictive rules are listed first to ensure they're enforced based on the main principle called the [first-match principle](#). Rules 4-5 do the same for Traders.
 - For Rule 1, selecting **Per initiator** when defining the \$10 million within an 8-hour threshold ensures the rule will match only if the *same user* tries to transfer more than \$10 million within 8 hours. If they do, approval from two members of the Management user group is required.
- Rules 4-5 apply different amount thresholds for the Traders group, and only per transaction instead of over a fixed period. Rule 4 ensures that one Management group user must approve if they request a transfer worth over \$500,000. Rule 5 ensures that one Management group user must approve if they request a transfer worth over \$500,000. For Rules 4-5, you must create the Withdrawal vault account listed under Source and Source Name before you create this Policy.
- Finally, Rule 6 is the block-all rule, blocking any transfer not explicitly allowed by this Policy.

Submitting this Policy example using the Policy Editor

This is how you would submit Rule 1 above in the Policy Editor.

Don't see what you're looking for? Log in for the full Help Center experience

Don't see what you're looking for? Log in for the full Help Center experience

Rule for funding

Source

Choose an origin account.

 Any possible account 

Destination

Choose a destination account.

 Any possible account 

☐ All addresses ☒ Whitelisted address ☐ One-time address only

Initiator

Choose the user or group that initiates the transaction.

Management 

Funds

Define the type and amount of funds relevant to the rule.

☐ Non-fungible tokens (NFTs)

☒ Fungible tokens or coins

Asset

Choose the asset that this rule applies to.

Any

Value

Set the asset's minimum value.

Minimum

10000000

Currency

USD

Limitation

Add an extra layer of security to the rule.

☐ Limit to single transaction

☒ Limit to specific time

Hours

8

Initiator

Per initiator

Source

Per source

Destination

Per destination

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Fireblocks Help Center

/

Block

Allow

Request approval

Approval

Create a set of approvers using individual users, API keys, or groups.

☒ Transaction initiator can approve

Approver set

Admin x

▼

Threshold

1

–

+

+ Add approver set

Designated signer

Assign the user required to sign the transaction.

☒ Initiator

☐ Single user

☐ Multiple users

Web3 example

This example shows the basic best practices for structuring your workspace's Policy for decentralized finance (DeFi) and Web3 operations. If you use the [Fireblocks WalletConnect integration](#) or the [Fireblocks Chrome Extension](#), you can create specific rules for contract call transactions with different restrictions and approval flows than with other transfer types.

Use contract call rules to implement custom policies for DeFi operations in case you have different risk and compliance needs for DeFi. Below are generic examples of rules.

Option A

#	Initiator	Type	Source	Destination	Signer	Minimum	Asset	Action
01	Traders	Contract Call Approve & Typed	DeFi Trading	Any Whitelisted address	Initiator	N/A	All	Approved by: 1 groups
02	Management	Transfer	Any	Any Whitelisted address	Initiator	\$5M in 1 day	All	Block
03	Management	Transfer	Any	Any Whitelisted address	Initiator	\$500K for a transaction	All	Approved by: 1 groups
04	Management	Transfer	Any	Any Whitelisted address	Initiator	\$0 for a transaction	All	Allow
05	Anyone	Transfer	Any	Any	Initiator	\$0 for a transaction	All	Block

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Fireblocks Help Center



02	Traders	Raw	DeFi Trading	Any Whitelisted address	Initiator	N/A	All	Allow
03	Traders	Contract Call Approve	DeFi Trading	Any One-time address only	Initiator	N/A	All	Approved by: 1 groups
04	Traders	Raw	DeFi Trading	Any One-time address only	Initiator	N/A	All	Approved by: 1 groups
05	Management	Transfer	Any	Any Whitelisted address	Initiator	\$5M in 1 day	All	Block
06	Management	Transfer	Any	Any Whitelisted address	Initiator	\$500K for a transaction	All	Approved by: 1 groups
07	Management	Transfer	Any	Any Whitelisted address	Initiator	\$0 for a transaction	All	Allow
08	Anyone	Transfer	Any	Any	Initiator	\$0 for a transaction	All	Block

1. Rule 1 in Option A approves contract calls to enable DeFi operations in your workspace.

- Only Traders group users can initiate contract calls.
- Only the DeFi Trading vault account can be the Source.
- They can send contract calls to any contract address (Destination is set to Any, both Whitelisted+OTA). This allows maximum flexibility using Web3 protocols and liquidity pools, but is less secure. For maximum security, select Whitelisted Only to only allow contract calls with pre-whitelisted contracts.
- Amount is blank because you cannot set amount limits for contract calls in your Policy. Instead, you use the separate [Approve transactions - amount cap](#) setting.
- All contract call transactions to one-time addresses must be approved by one Management group user.

2. Alternatively, Rules 1-2* in Option B approve contract calls differently for Traders group users.

- Rule 1 in Option B is the same as Rule 1 in Option A, except Destination is set to Whitelisted Only, and Action is set to Allow. This allows Traders group users to send contract calls to whitelisted addresses without requiring approval.
- Rule 3 in Option B sets Destination to One-Time-Address Only. This allows Traders group users to send contract calls to one-time addresses with one Management group approval.
- Rules 2 and 4 in Option B relate to [Typed messaging signing](#) for smart contract transactions for Fireblocks Console users.

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help Center



Policy.

*Rules 2 and 4 in Option B enable [Typed messaging signing](#), which is the Fireblocks operation for signing standard off-chain messages (ETH Personal Sign and EIP-712). Signing an off-chain message that's not a transaction is often required by Web3 applications.

Submitting this Web3 Policy example using Policy Editor

This is how you would submit Rule 1 from Option A above using Policy Editor.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Enter a name that makes the rule easily identifiable.

Contract call rule

Source

Choose an origin account.

DeFi Trading ×



Destination

Choose a destination account.

 Any possible account ×



☐ All addresses ☒ Whitelisted address ☐ One-time address only

Contract call method

Choose a contract call method.

Any ×



Initiator

Choose the user or group that initiates the transaction.

Traders ×



Funds

Define the type and amount of funds relevant to the rule.

Asset

Choose the asset that this rule applies to.

Any



Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Fireblocks Help Center

/

Block

Allow

Request approval

Approval
Create a set of approvers using individual users, API keys, or groups.

☒ Transaction initiator can approve

Approver set

Traders x

Threshold

1

+ Add approver set

Designated signer
Assign the user required to sign the transaction.

☒ Initiator

☐ Single user

☐ Multiple users

Retail Policy example

Here we show basic best practices for structuring your Policy for retail operations. Retail businesses can use Fireblocks API to automate transfers to numerous retail users. With Policy, you can set limits and approval flows for API Signer user activity.

We recommend only giving certain users access to your omnibus treasury vault. You can apply Policy rules to an omnibus vault structure to streamline operations for your retail app by allowing instant transfers for API Signers. To tailor policies for high retail volumes, you can allow API Signers to sweep funds from your end client (intermediate) vault accounts to your Omnibus Deposits vault account and to withdraw from your Omnibus Withdrawals vault account.

You can also manage risk by setting custom approvals based on amount or time-based thresholds. An example of this structure is below, with custom rules for three user roles. Each rule is explained below. Note that if you use a two-withdrawal vault flow or a different vault structure than in this example, you should consider this when building your Policy.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center



07	Vault to vault topaz	Anyone	Management	 Vault - Withdrawals	 Vault - Treasury Whitelisted address	Unlimited USD per transaction	All	Require approval of: 1 of 1 group
08	Vault to vault peridot	Anyone	Management	 Vault - Treasury	 Vault - Withdrawals Whitelisted address	Unlimited USD per transaction	All	Require approval of: 1 of 1 group
09	Vault to vault amethyst	Anyone	FinOps	 Any	 Any Whitelisted address	\$1,000,000 per transaction	All	Block
10	Vault to vault gold	Kerry Gold	FinOps	 Any	 Any Whitelisted address	\$100,000 per transaction	All	Require approval of: 1 of 2 group
11	Vault to vault tanzanite	Anyone	FinOps	 Any	 Any Whitelisted address	\$50,000 per transaction	All	Require approval of: 1 of 1 group
12	Vault to vault pearl	Anyone	FinOps	 Any	 Any Whitelisted address	Unlimited USD per transaction	All	Require approval of: 1 of 1 group
13	Vault to vault silver	Anyone	Juniors	 Any vault account	 Any vault account	Unlimited USD per transaction	All	Allow
14	Default transfer rule	Anyone	Initiator	 Any	 Any	Unlimited USD per transaction	All	Block

- Rule 1 blocks API Signer users from withdrawing from the Any vault account. Only Management and FinOps groups users can access it.
- The most restrictive rules are listed first to ensure they are enforced based on the **first-match principle**.
 - Rule 2 requires any transfer between vault accounts by API Signers above \$50,000 to be approved by one FinOps group user. This rule, however, will get blocked by Rule 1 due to the first-match principle and because the parameters are the same.
 - Rule 3 allows API Signers to transfer any amount from \$0-\$50,000 between vault accounts without approval. This rule, however, will get blocked by Rule 1 due to the first-match principle and because the parameters are the same.
 - Rule 4 allows the API to transfer to the Fireblocks Gas Station without approval.
 - Rules 5-6 are similar to Rules 2-3, but more restrictive due to the Withdrawals Omnibus vault account being the source and external wallets the destination. Your user withdrawal wallets are often external wallets. It is up to you whether to whitelist them. In this example, some are not, but transfers are allowed because Destination is set to Whitelisted+OTA.
 - Rules 7-8 allow Management group users to transfer any amount between the Treasury and Withdrawals vault accounts with one other Management group user's approval. This allows them to rebalance their vault accounts.
 - Rule 9 blocks the FinOps group from collectively transferring over \$1 million within 24 hours by selecting Accumulate all under Accumulation.
 - Rules 10-12 allow FinOps group users to transfer certain amounts from any source to any destination with custom approval flows based on amount.
 - In Rule 10, transferring over \$100,000 requires approval from two FinOps users and one Management group user.
 - In Rule 11, transferring \$50,000 up -\$100,000 requires the approval of two FinOps group users or one Management group user.

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help Center



transactions, a Designated Signer is required.

- Finally, Rule 14 blocks any transfer that is not explicitly allowed by this Policy.

Submitting this Retail Policy example using Policy Editor

Below shows you how to submit Rule 1 from above using the Policy Editor.

Scope

Specify the extent of coverage for the rule.

Rule name
Enter a name that makes the rule easily identifiable.

Vault to vault diamond

Source
Choose an origin account.

Any possible account

Destination
Choose a destination account.

Any vault account

☒ All addresses ☐ Whitelisted address ☐ One-time address only

Initiator
Choose the user or group that initiates the transaction.

API Signer

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

☐ Non-fungible tokens (NFTs)

☒ Fungible tokens or coins

Asset

Choose the asset that this rule applies to.

Any

Value

Set the asset's minimum value.

Minimum

0

Currency

USD

Limitation

Add an extra layer of security to the rule.

☒ Limit to single transaction

☐ Limit to specific time

Action

Specify what happens when a transaction matches all criteria.

 Block

 Allow

 Request approval

Embedded Wallets example

Within the Embedded Wallets (EW) realm, you may build a Policy that meets your criteria. There is no best practice, as one example that fits one business may not meet the expectations of another.

You may limit volumes per end-user wallet, set a limit on which dApps the end-user can interact with, or block them from interacting with certain assets.

To apply any wanted logic, you may use the End User wallet venue, which can be used both as source and destination.

Don't see what you're looking for? Log in for the full Help Center experience



	ID	Policy Name	Transaction Type	From	To	Limit	Asset	Action		
↑ ↓	03	Anyone	↓↑ Transfer	Any end-user wallet	Any	Initiator	\$0 per transaction	 BTC_TEST	Allow	...
↑ ↓	04	Anyone	↓↑ Transfer	Any end-user wallet	Any end-user wallet	Initiator	\$0 per transaction	 SPARK23_B7FHMY5_6JP	Allow	...
↑ ↓	05	Anyone	 Contract Call Approve & Typed	Any end-user wallet	Contract Wallets - Test – Whitelisted address	Initiator	N/A	All	Allow	...
	06	Anyone	↓↑ Transfer	Any	Any	Initiator	\$0 per transaction	All	Block	

Although the above example is simple, it introduces different possibilities within the Policy for end-user wallets.

- 1. Rule 1 limits an end user to trade Solana no more than \$1,000 per day, regardless of the destination.
- 2. Rule 2 limits an end user to trade Ethereum (Sepolia) no more than \$2,000 per day, regardless of the destination.
- 3. Rule 3 allows end users to trade BTC, with no limits.
- 4. Rule 4 allows end users to trade with a special token only between themselves within the app ecosystem.
- 5. Rule 5 allows connecting to only a specific dApp, using Contract Whitelisting.

Note

Approval groups are not supported for Embedded Wallet transactions.

Was this article helpful?

Yes

No

ON THIS PAGE

- Overview
- Trading and treasury management examples
- Web3 example
- Retail Policy example
- Embedded Wallets example

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help Center



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)