

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

Search the Help Center /

Fireblocks Help Center

Identity & Compliance

Interacting with the TRUST platform

Interacting with the TRUST platform

Note: This feature is currently in Early Access. If you are interested in joining the Early Access phase, [contact your Fireblocks Customer Success Manager](#).

Important:

The TRUST platform is an external protocol. TRUST is not directly integrated with Fireblocks.

Overview

Fireblocks supports cryptographic Proof of Address signing for the TRUST (Travel Rule Universal Solution Technology) Network.

When interacting with TRUST for Travel Rule compliance, VASPs must prove ownership of blockchain addresses involved in a transaction. Fireblocks enables this by creating a secure typed message signing transaction using its MPC infrastructure.

This article explains:

- Why Proof of Address is required
- How the Fireblocks flow works
- Supported assets
- How to retrieve and submit the signature to TRUST

For full API implementation details, see the Developer Portal guide.

What is Proof of Address?

Don't see what you're looking for? Log in for the full Help Center experience

How the TRUST proof flow works

When a counterparty initiates a Travel Rule interaction through TRUST:

- 1. TRUST requests proof:** TRUST generates a UUID via its `CreateAddressOwnership` endpoint.
- 2. You create a signing transaction in Fireblocks:** Fireblocks generates a typed message signing transaction tied to:
 - Your vault account
 - The asset
 - Your TRUST prefix
 - The TRUST UUID
- 3. Approval and MPC signing:** The transaction follows your workspace approval policy. Once approved, Fireblocks signs the message using MPC.
- 4. Retrieve the signature:** You retrieve the TRUST-formatted signature via API.
- 5. Submit to TRUST:** You send the signature to TRUST’s Bulletin Board `/verify` endpoint.

The proof is successful once TRUST responds with `VALID`.

Supported assets

Proof of Address is supported for:

Asset	Chain	Signature Type
ETH	Ethereum	ETHEREUM_EOA
ETH_TEST	Goerli / Sepolia	ETHEREUM_EOA
BTC	Bitcoin	BITCOIN_P2WPKH
SOL	Solana	SOLANA_ED25519
TRX	Tron	TRON_EOA

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Only permanent addresses can be proven

Proof of Address applies only to the permanent address of a vault account. This is the address derived at derivation index 0. Other deposit addresses cannot be used for TRUST proof verification.

Transaction statuses

Proof transactions follow standard Fireblocks transaction states.

Status	Meaning
SUBMITTED	Transaction created
PENDING_AUTHORIZATION	Awaiting approval
PENDING_SIGNATURE	Awaiting MPC signing
COMPLETED	Signature ready
FAILED / REJECTED / CANCELLED / BLOCKED / TIMEOUT	Terminal failure state

In most cases, the proof transaction completes immediately after creation.

Security considerations

- Fireblocks uses Typed Message Signing, not Raw Signing.
- Typed signing mitigates the risk of signing unintended or malicious payloads.
- All signing operations follow your existing approval policy.
- No additional permissions are introduced.
- TRUST is an external protocol and is not operated by Fireblocks.

High-Level API flow

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/



```
{
  "transactionId": "uuid",
  "status": "COMPLETED"
}
```

2. Retrieve Signature

GET /v1/screening/travel_rule/trust/proof_of_address/{transactionId}

Returns:



```
{
  "transactionId": "uuid",
  "status": "COMPLETED",
  "signature": "encoded_signature"
}
```

3. Submit to TRUST

You must POST the signature to TRUST's verification endpoint:

POST /v1/verify

Example payload:



```
{
  "chain": "ETHEREUM",
  "type": "ETHEREUM_EOA",
  "signature": "0x...",
  "prefix": "yourcompany",
  "uuid": "trust-uuid",
  "address": "0x..."
}
```

Expected TRUST response:

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

```
    "trustProofOfAddress": {  
      "type": "string"  
    }  
  }  
}
```

Developer implementation

For full TypeScript SDK implementation examples, polling logic, and signature formatting details, see:

Developer Portal → TRUST Proof of Address API

The SDK method used is:

```
fireblocks.travelRule.createTrustProofOfAddress()
```

```
fireblocks.travelRule.getTrustProofOfAddress()
```

SDK package:

```
@fireblocks/ts-sdk (v14+)
```

Related resources

- [Fireblocks Transactions API](#)
- [Fireblocks Webhooks](#)
- [TRUST Network documentation](#)

Was this article helpful?

Yes

No

ON THIS PAGE

Overview

What is Proof of Address?

How the TRUST proof flow works

Supported assets

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

High-Level API flow

Related resources

fireblocks.com

fireblocks.com

Status

API Docs

Console

info@fireblocks.com



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)