

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Vault HD derivation paths

Updated 1 year ago

Fireblocks Vault is a BIP32-compatible Hierarchical Deterministic (HD) Wallet. If you're not familiar with the concept of HD wallets and BIP32, [start here](#).

Derivation paths

Fireblocks uses the following non-hardened BIP44 variant of derivation paths:

```
m / 44 / coin_type / account / change / address_index
```

- *coin_type* - value is based on [SLIP-44](#) standard.*
- *account* - value is the ID of the vault account. Account IDs are sequential and start with *index 0*.
- *change* - is always set to 0.
- *address_index* - is a sequential index starting from 0, where the permanent address of a wallet has index 0, and all other generated addresses (known in the UI as deposit addresses) start with *index 1* and go up.

For example, an ETH wallet under the vault account with ID 0 has an HD derivation path of *m/44/60/0/0/0*.

Note:

For most EVM wallets, the derivation is based on the ETH constant in the SLIP-44 standard, i.e. they use a coinType value of 60, same as Ethereum. The exceptions to this rule are:

- Ethereum Classic - coinType 61
- Flare - coinType 554
- Songbird (Legacy) - [coinType 554](#)

You can download the derivations paths of all wallets and addresses from your Console by selecting **Export Vault Balances & Addresses** at the top of your Vault account page, as

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Using [BIP32 tools](#), these derivation paths, combined with the Extended Private Key or the Extended Public Key, can derive a wallet's private key and public key/set of addresses, respectively.

Note:

The BIP32 standard uses 32-bit integers for the vault account index and deposit address index within a vault account, meaning you can create an approximate total of 2,147,483,647 vault accounts within a single Fireblocks workspace.

Fireblocks supports multiple deposit addresses for UTXO blockchains only. [See the deposit addresses article for more details](#). The BIP32 standard uses 32-bit integers, meaning you can have another 2,147,483,647 addresses per UTXO asset wallet in a single vault account.

Sandbox and Testnet workspace exception

There are specific points to note regarding Sandbox and Testnet workspaces. Go [here](#) for more information.

Was this article helpful?

Yes

No

ON THIS PAGE

Derivation paths

Related Articles

-  [Fireblocks Vault Key Derivation Tool](#)
-  [Troubleshooting incomplete user setup](#)
-  [MPC-CMP security enhancements \(version update, August 2023\)](#)
-  [MPC-CMP update for all Fireblocks users](#)

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center



Fireblocks

[fireblocks.com](#)

[Status](#)

[API Docs](#)

[Console](#)

[info@fireblocks.com](#)



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)