

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

Search the Help Center 

[Fireblocks Help Center](#)

[Tokenization](#)

Smart contract management

Roles in Fireblocks smart contracts

Note

Tokenization is a premium feature that requires an additional purchase. If you don't have access to this feature, contact your [Customer Success Manager](#) to discuss having it enabled in your Fireblocks workspace.

Overview

This article describes the roles contained within the Upgradeable ERC-20F, ERC-721F, and ERC-1155F token smart contract templates created by Fireblocks. Each role can perform a specific action and can be assigned to a specific address. Some roles can be assigned to multiple addresses.

Below is a list of roles and each role's hash you must use when assigning a role. To find a role's hash in the Fireblocks Console, go to **More Actions (...)** > **Manage contract**. View the Read functions, and expand the role to see its hash. While roles are defined by hashes, ERC-20F contracts can be managed directly via the Console UI without manually inputting these values.

BURNERROLE

`Ox3c11d16cbaffd01df69ce1c404f6340ee057498f5f00246190ea54220576a848`

Assigning roles

The method for assigning roles depends on your token standard and deployment method.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

2. Select **Manage contract**. *Note: If this option does not appear, your token may be an externally linked asset. Use Method 2 instead.*
3. Select the **Roles** tab.
4. Assign the desired role to an address via the interface. This method does not require role hashes.
5. Select **Submit**.

Method 2: Manual (For ERC-721F, ERC-1155F, and Linked Assets)

If the Roles tab is not available, you must grant roles manually:

1. Hover over the token and select **More Actions (...) > Manage contract**.
2. Go to **Read functions** to copy the specific **Role hash** (or find it in the table below).
3. Go to **Write functions** and locate the `grantRole` function.
4. Enter the **Role hash** and the target **Address**, then select **Submit**.

Role constants

Burner

This role has the ability to burn tokens. It is often granted to internal addresses within your organization. However, some use cases may benefit from assigning this role to external addresses. The burner address must hold the asset it will burn.

- Role hash:
0x3c11d16cbaffd01df69ce1c404f6340ee057498f5f00246190ea54220576a848

Contract Admin

This role can manage the contract's metadata, such as adding a link to the Terms of Service using the **contractURI** field. The Contract Admin role can also connect a token utility contract, such as the [Allowlist](#), to your already deployed token contract.

- Role hash:
0x2ce8d04a9c35987429af538825cd2438cc5c5bb5dc427955f84daaa3ea105016

Default Admin

△ Fireblocks Fireblocks Help C

Page 10 of 10

Minter

The Minter role is assigned when deploying your smart contract, but you can grant this role to additional addresses after deployment.

- ## Pauser

This role has the ability to pause and unpaue the smart contract and prevent addresses from interacting with it.

The Pauser role is assigned when deploying your smart contract, but you can grant this role to additional addresses after deployment.

- ## Recovery

This role has the ability to claw back tokens from a user. Often, this is used in conjunction with allowlists or denylists. If an address should not have access to the token based on the allowlist or denylist, the user with the Recovery role can force transfer the tokens back from that address.

- Role hash:
0x0acf805600123ef007091da3b3ffb39474074c656c127aa68cb0ffec232a8ff8

Salvage

This role can return tokens to an address in the scenario where the tokens were accidentally sent to a Fireblocks smart contract.

- Role hash:
0x75afe8d9fedb4699bf07dc7bcb33fe609a84a99adfab7076931f0d93228085bb

Upgrader

Don't see what you're looking for? Log in for the full Help Center experience

Role-based access tables

ERC-20F Contract

ERC-721F Contract

ERC-1155F Contract

Allowlist/Denylist Contracts

Was this article helpful?

Yes

No

ON THIS PAGE

- Overview
- Assigning roles
- Role constants
- Role-based access tables

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help C

