

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

Search the Help Center /

[Fireblocks Help Center](#)

[For Developers](#)

Fireblocks API

Fireblocks Smart Contract (DeFi) API

Note

You can also whitelist a smart contract address in the Fireblocks Console. Learn more about [whitelisting addresses](#).

Overview

Fireblocks Smart Contract API allows you to initiate special transactions that interact directly with any smart contract deployed on an Ethereum Virtual Machine (EVM) compatible network. This allows you to run contract operations not natively supported on the Fireblocks API, such as Decentralized Finance (DeFi) transactions and Non-Fungible Token (NFT) transfers.

Creating a smart contract transaction on EVM-compatible blockchains

If you already use libraries such as [Web3.js](#) or [Ethers.js](#), you can bridge between these libraries and the Fireblocks API using the [Fireblocks Web3 Provider and Hardhat Plugin](#).

Alternatively, you can call the [Create a new transaction](#) endpoint directly with the following parameters:

- **Operation:** Set to `CONTRACT_CALL`.
- **Source:** The vault account ID from which the transaction is initiated.
- **Destination:** The transaction destination should point to the smart contract you want to call. This can be either a [whitelisted address](#) or a [one-time address](#).
- **Asset:** The asset type should always be the base asset of the relevant EVM-compatible blockchain.

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Fireblocks Help Center

/

... , you can enter the contract address directly into the deploy...



```
fireblocksApiClient.createTransaction({
  operation: TransactionOperation.CONTRACT_CALL,
  assetId: "ETH",
  source: {
    type: PeerType.VAULT_ACCOUNT,
    id: "0" /* Source Vault Account ID */
  },
  destination: {
    type: PeerType.ONE_TIME_ADDRESS,
    oneTimeAddress: {
      id: "0x0"
    }
  },
  note: "Contract Call Transaction",
  amount: "0",
  extraParameters: {
    contractCallData: "<Deployment Transaction Payload>" /* Data Pay
  }
});
```

Visit our [Developer Portal](#) to see tutorials and examples in more languages we support, such as Python.

Managing NFTs with Fireblocks

The [Fireblocks Web3 Provider](#) and [Hardhat Plugin](#) also include the ability to interact with NFTs.

You can:

- Natively connect to base tokens in the ERC-721 and ERC-1155 formats.
- Connect to custom tokens by specifying your own ABI (Application Binary Interface) addresses.

Don't see what you're looking for? Log in for the full Help Center experience



Fireblocks Help Center



Setting Policy rules for contract calls

Learn more about using [Policies for EVM DeFi operations](#) on Fireblocks.

Was this article helpful?

Yes

No

ON THIS PAGE

Overview

Creating a smart contract transaction on EVM-compatible blockchains

Calculating the data payload

Contract deployment

Managing NFTs with Fireblocks

Setting Policy rules for contract calls

Related Articles

-  [Managing Vesting Smart Contracts](#)
-  [Managing smart contracts for tokenization](#)
-  [DeFi security best practices](#)
-  [Interacting with Web3 on Fireblocks](#)
-  [dApp Protection](#)
-  [Viewing asset and blockchain details](#)
-  [Transaction Simulation](#)
-  [API Co-Signer updates \(December 2021\)](#)

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center



fireblocks.com

fireblocks.com

Status

API Docs

Console

info@fireblocks.com



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)