

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

Search the Help Center 

Multi-destination UTXO transactions

Updated 5 months ago

Overview

Send a single transaction to multiple destinations with UTXO-based assets. You can execute several "sub-transactions" in a single blockchain transaction that divides the value you transfer across multiple destinations.

This helps you save on transaction fees and makes the operation more efficient. Send transfers to multiple destination types at the same time, and pay only a single transaction fee.

Multi-destination transactions can't use `TreatAsGrossAmount`

UTXO transactions with multiple destinations cannot use the **`TreatAsGrossAmount`** parameter, which automatically deducts fees from the transfer amount.

All destinations are logged in your workspace's [Transaction History](#).

Create multi-destination transactions

Send a single transaction to multiple destinations using the Fireblocks API:

1. [Create a new transaction via the Fireblocks API](#).
2. Use the **`destinations`** parameter instead of **`destination`**.
3. Specify each destination with its destination type and destination ID.

Destination type behavior

Default behavior

Multi-destination transactions use `DestType = MULTI_DESTINATION` by default.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help C

/

Changing your behavior

If your account currently uses `DestType = NONE` for multi-destination transactions, and you want to switch to the default `MULTI_DESTINATION` behavior, [submit a request to Fireblocks Support](#).

Policy enforcement

Each destination is treated as a separate sub-transaction according to your workspace's [Policies](#). Policy rules are checked for each sub-transaction, but apply to the whole transaction.

If different approval requirements apply to different sub-transactions, they must be approved separately. If any output is rejected, the entire transaction is blocked.

To create a policy rule based on the aggregated transaction amount, use time-based rules in your policy.

Example

A transaction has Vault A as the source, and three destinations: Addresses X, Y, and Z. The workspace policy has rules that match each destination separately:

1. Allow if transferring from Vault A to Address X
2. Require approval if transferring from Vault A to Address Y
3. Deny if transferring from Vault A to Address Z

Because rule 3 blocks any transaction from Vault A to Address Z, the entire transaction is denied to all destinations.

If the transaction is sent to only Address X and Y, then the approval request applies to the whole transaction.

Was this article helpful?

Yes

No

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Destination type behavior

Policy enforcement

Related Articles

-  Boost a stuck UTXO transaction
-  Multi-input transactions
-  Unknown Destination notice in multi-destination transactions
-  Doge-supported UTXOs



fireblocks.com

[Status](#)

[API Docs](#)

[Console](#)

info@fireblocks.com



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)