

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

Search the Help Center /

Tags & Protected Tags

Updated 2 months ago

Early Access feature

This feature is currently in Early Access. If you are interested in joining the Early Access phase, [contact your Fireblocks Customer Success Manager](#).

Overview

Use tags to organize and group vault accounts in your workspace. Tags help you structure large vault inventories, filter accounts, and support operational workflows.

When you create a tag with enforcement enabled, it becomes a protected tag. Protected tags can be used in Policy rules and require Admin Quorum approval for any changes.

Currently, you can attach tags only to vault accounts. Support for additional entity types, such as whitelisted addresses, is planned for future releases.

Before you begin

To work with tags, you need:

- **For tags:** Workspace access with vault account management permissions
- **For protected tags:** Admin or Owner role to create protected tags and approve changes
- **For Policy integration:** Understanding of your workspace's Policy configuration

Protected tags require Admin Quorum approval for modifications. Ensure your workspace has the appropriate approval quorum configured before creating protected tags.

Tags

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help C

/

Use cases

Use tags to:

- Group vaults by business unit, environment, geographic location, or customer segment
- Filter and search vault accounts in the Console
- Apply consistent structure across large vault inventories
- Support operational workflows and reporting

Protected tags

Protected tags are tags created with enforcement enabled. You can use protected tags as source and destination peers in Policy rules.

Changes to protected tags require Admin Quorum approval because Policy behavior can depend on them. This includes:

- Editing or deleting the tag
- Attaching or detaching the tag from vaults

Creating a protected tag does not require approval.

Protection state

The protection state of a tag is immutable after creation:

- You cannot convert a protected tag to a regular tag
- You cannot convert a regular tag to a protected tag

Tags in Policy rules must be protected tags

If you need to use a tag in Policy rules, you must create it as a protected tag. Plan your tag structure before creation.

Use protected tags in Policy

Select protected tags as source or destination peers when you define Policy rules.

Protected tags in Policy enable you to:

- Allow transactions only from vaults with a specific protected tag

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help C

/

Example. Geographic Routing

You can create protected tags for different geographic regions, such as US–East , EU–West , and APAC . Attach these tags to vault accounts based on their operational location.

In your Policy rules, you can:

- Require transactions from US–East vaults to be signed by US-based Co-signers
- Block transactions between EU–West and APAC vaults for compliance reasons
- Apply different approval thresholds based on the source vault's geographic tag

Manage tags in the Console

You can create, edit, delete, and attach tags to vault accounts in the Fireblocks Console.

Create a tag

To create a tag:

1. Go to **Settings > Tags**.
2. Select **Create Tag**.
3. Enter the tag details:
 - a. **Label:** Tag display name.
 - b. **Description:** Optional tag description.
 - c. **Color:** Tag color for visual identification.
 - d. **Enforcement:** Select this checkbox to create a protected tag
4. Select **Create**.

Edit a tag

To edit a tag:

1. Go to **Settings > Tags**.
2. Select the three-dot menu next to the tag you want to edit.
3. Select **Edit**.
4. Update the tag details.
5. Select **Save**.

If the tag is protected, this action requires Admin Quorum approval.

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

3. Select **Delete**.
4. Confirm the deletion.

If the tag is protected, this action requires Admin Quorum approval.

Attach tags to vault accounts

To attach tags to vault accounts:

1. Go to **Vaults > Accounts**.
2. Select one or more vault accounts.
3. Select **Attach Tags** from the bulk actions menu.
4. Select the tags to attach.
5. Select **Attach**.

If you attach a protected tag, this action requires Admin Quorum approval.

Detach tags from vault accounts

To detach tags from vault accounts:

1. Go to **Vaults > Accounts**.
2. Select one or more vault accounts.
3. Select **Detach Tags** from the bulk actions menu.
4. Select the tags to detach.
5. Select **Detach**.

If you detach a protected tag, this action requires Admin Quorum approval.

Filter vault accounts by tags

To filter vault accounts by tags:

1. Go to **Vaults > Accounts**.
2. Select the **Filter** button.
3. In the **Tags** section, select the tags to filter by.
4. The vault account list updates to show only accounts with the selected tags.

Manage tags with the API

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center



POST /tags

Creates a tag. You can enable enforcement at creation to make the tag protected.

Creating a protected tag does not require approval.

Request body



```
{
  "label": "US-East",
  "description": "Vault accounts in US East region",
  "enforcement": true,
  "color": "#FF5733"
}
```

Parameters

- **label (required, string):** Tag display name.
- **description (optional, string):** Tag description.
- **enforcement (optional, boolean):** Set to `true` to create a protected tag. Default is `false`.
- **color (optional, string):** Tag color in hex format.

Response



```
{
  "id": "tag-123",
  "label": "US-East",
  "description": "Vault accounts in US East region",
  "enforcement": true,
  "color": "#FF5733",
  "createdAt": "2025-01-13T10:30:00Z",
  "updatedAt": "2025-01-13T10:30:00Z"
}
```

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help C

/

Query parameters

- **page (optional, integer):** Page number for pagination. Default is 0.
- **pageSize (optional, integer):** Number of tags per page. Default is 50.
- **enforcement (optional, boolean):** Filter by enforcement state.

Response

```
{
  "tags": [
    {
      "id": "tag-123",
      "label": "US-East",
      "description": "Vault accounts in US East region",
      "enforcement": true,
      "color": "#FF5733",
      "createdAt": "2025-01-13T10:30:00Z",
      "updatedAt": "2025-01-13T10:30:00Z"
    }
  ],
  "page": 0,
  "pageSize": 50,
  "totalCount": 1
}
```

Get tag

GET /tags/{id}

Returns tag details, including enforcement state.

Path parameters

- **id (required, string):** Tag ID.

Response

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

```
{
  "label": "US East",
  "description": "Vault accounts in US East region",
  "enforcement": true,
  "color": "#FF5733",
  "createdAt": "2025-01-13T10:30:00Z",
  "updatedAt": "2025-01-13T10:30:00Z"
}
```

Update tag

PATCH /tags/{id}

Updates tag label, description, or color. You cannot change the enforcement state.

If the tag is protected, this operation requires Admin Quorum approval.

Path parameters

- **id (required, string):** Tag ID.

Request body

```
{
  "label": "US-East-Updated",
  "description": "Updated description",
  "color": "#00FF00"
}
```

Parameters

- **label (optional, string):** Updated tag display name.
- **description (optional, string):** Updated tag description.
- **color (optional, string):** Updated tag color in hex format.

Response (protected tag)

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Response (regular tag)



```
{
  "id": "tag-123",
  "label": "US-East-Updated",
  "description": "Updated description",
  "enforcement": true,
  "color": "#00FF00",
  "createdAt": "2025-01-13T10:30:00Z",
  "updatedAt": "2025-01-13T11:00:00Z"
}
```

Delete tag

DELETE /tags/{id}

Deletes a tag. If the tag is protected, this operation requires Admin Quorum approval.

Path parameters

- **id (required, string):** Tag ID.

Response (protected tag)



```
{
  "approvalRequestId": "req-789",
  "status": "PENDING"
}
```

Response (regular tag)



Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center



Attach or detach tags

POST /vaults/accounts/attached_tags

Attaches or detaches tags from vault accounts in bulk. If at least one tag in the request is protected, this operation requires Admin Quorum approval.

Request body



```
{
  "operation": "ATTACH",
  "vaultAccountIds": ["vault-1", "vault-2", "vault-3"],
  "tagIds": ["tag-123", "tag-456"]
}
```

Parameters

- **operation (required, string):** Either ATTACH or DETACH.
- **vaultAccountIds (required, array of strings):** Vault account IDs.
- **tagIds (required, array of strings):** Tag IDs.

Response (with protected tag)



```
{
  "approvalRequestId": "req-101",
  "status": "PENDING"
}
```

Response (without protected tag)



```
{
  "success": true,
}
```

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

GET /tags/approval_requests/{id}

Returns approval request details, including status, type, payload, and timestamps.

Path parameters

- **id (required, string):** Approval request ID.

Response

```
{
  "id": "req-456",
  "type": "UPDATE_TAG",
  "status": "PENDING",
  "payload": {
    "tagId": "tag-123",
    "updates": {
      "label": "US-East-Updated",
      "description": "Updated description"
    }
  },
  "createdAt": "2025-01-13T11:00:00Z",
  "updatedAt": "2025-01-13T11:00:00Z",
  "requiredApprovals": 2,
  "currentApprovals": 1
}
```

Cancel approval request

POST /tags/approval_requests/{id}/cancel

Cancels a pending approval request. You can only cancel requests with the `PENDING` status.

Path parameters

- **id (required, string):** Approval request ID.

Response

Don't see what you're looking for? Log in for the full Help Center experience

Fireblocks Fireblocks Help Center

/

```
}  
}
```

List vault accounts with tag filtering

GET /vault/accounts

Returns vault accounts. Supports tag filtering and includes tag attachments in the response.

Query parameters

- **includeTagIds (optional, array of strings):** Return only vault accounts with these tags.
- **excludeTagIds (optional, array of strings):** Exclude vault accounts with these tags.
- **includeTags (optional, boolean):** Include tag attachments in the response. Default is false.

Response

```
{  
  "accounts": [  
    {  
      "id": "vault-1",  
      "name": "Main Vault",  
      "tags": [  
        {  
          "id": "tag-123",  
          "label": "US-East",  
          "enforcement": true  
        }  
      ]  
    }  
  ]  
}
```

Get vault account with tags

GET /vault/accounts/{id}

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

Response



```
{
  "id": "vault-1",
  "name": "Main Vault",
  "tags": [
    {
      "id": "tag-123",
      "label": "US-East",
      "enforcement": true,
      "color": "#FF5733"
    },
    {
      "id": "tag-456",
      "label": "Production",
      "enforcement": false,
      "color": "#0000FF"
    }
  ],
  "assets": []
}
```

Protected tags and automations

Protected tags work with automation-based workflows. Because protected tags represent stable, approval-controlled groupings, you can use them as inputs to automated operational logic.

Using protected tags in automations allows you to define workflows that operate on dynamic sets of vaults without hard-coding vault IDs or manually updating automation rules as the vault set changes.

Automation use case: Deposit sweeping

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

- Monitor vaults with the `Deposit-Vaults` protected tag
- Automatically sweep incoming funds from those vaults
- Transfer the funds to a designated omnibus or treasury vault

As you add new deposit vaults, attaching the protected tag includes them in the automation workflow. You do not need to change the automation logic.

Because protected tags require approval for changes, modifications to the set of vaults participating in the automation are deliberate and auditable. This reduces the risk of accidental inclusion or removal of vaults from critical automated workflows.

Current limitations

Tags and protected tags are not currently supported as conditions or inputs in automation rules. This functionality is planned for release in H1 2026.

The automation use case described above represents the intended workflow once tag support in automations is available.

Was this article helpful?

Yes

No

ON THIS PAGE

Overview

Before you begin

Tags

Protected tags

Manage tags in the Console

Manage tags with the API

Protected tags and automations

Related Articles

Don't see what you're looking for? Log in for the full Help Center experience

 Fireblocks Help Center

/

 Naming Vault Accounts



[fireblocks.com](#)

[Status](#)

[API Docs](#)

[Console](#)

info@fireblocks.com



Fireblocks © 2026. All Rights Reserved. NMLS Registration Number: 2066055

[Privacy Policy](#)