



Module 4 Cheat Sheet: DataFrames and Spark SQL

| Package/Method | Description | Code Example |
|-------------------|---|--|
| appName() | A name for your job to display on the cluster web UI. | <pre>1. 1 2. 2 1. from pyspark.sql import SparkSession 2. spark = SparkSession.builder.appName("MyApp").getOrCreate()</pre> <div>Copied!</div> |
| createDataFrame() | Used to load the data into a Spark DataFrame. | <pre>1. 1 2. 2 3. 3 4. 4 1. from pyspark.sql import SparkSession 2. spark = SparkSession.builder.appName("MyApp").getOrCreate() 3. data = [("Jhon", 30), ("Peter", 25), ("Bob", 35)] 4. columns = ["name", "age"]</pre> <div>Copied!</div> <p>Creating a DataFrame</p> <pre>1. 1 1. df = spark.createDataFrame(data, columns)</pre> <div>Copied!</div> |
| createTempView() | Create a temporary view that can later be used to query the data. The only required parameter is the name of the view. | <pre>1. 1 1. df.createOrReplaceTempView("cust_tbl")</pre> <div>Copied!</div> |
| fillna() | Used to replace NULL/None values on all or selected multiple DataFrame columns with either zero (0), empty string, space, or any constant literal values. | <p>Replace NULL/None values in a DataFrame</p> <pre>1. 1 1. filled_df = df.fillna(0)</pre> <div>Copied!</div> <p>Replace with zero</p> |
| filter() | Returns an iterator where the items are filtered through a function to test if the item is accepted or not. | <pre>1. 1 1. filtered_df = df.filter(df['age'] > 30)</pre> <div>Copied!</div> |
| getOrCreate() | Get or instantiate a SparkContext and register it as | <pre>1. 1 1. spark = SparkSession.builder.getOrCreate()</pre> |

| Package/Method | Description | Code Example |
|----------------|---|---|
| groupby() | a singleton object. | <div>Copied!</div> |
| | Used to collect the identical data into groups on DataFrame and perform count, sum, avg, min, max functions on the grouped data. | <div>Grouping data and performing aggregation</div> <div>1. 1</div> <div>1. grouped_df = df.groupBy("age").agg({"age": "count"})</div> <div>Copied!</div> |
| | | <div>Returning the first 5 rows</div> <div>1. 1</div> <div>1. first_5_rows = df.head(5)</div> <div>Copied!</div> |
| head() | Returns the first <i>n</i> rows for the object based on position. | |
| import | Used to make code from one module accessible in another. Python imports are crucial for a successful code structure. You may reuse code and keep your projects manageable by using imports effectively, which can increase your productivity. | <div>1. 1</div> <div>1. from pyspark.sql import SparkSession</div> <div>Copied!</div> |
| | | <div>1. 1</div> <div>1. import pandas as pd</div> <div>Copied!</div> |
| pd.read_csv() | Required to access data from the CSV file from Pandas that retrieves data in the form of the data frame. | <div>1. 1</div> <div>1. df_from_csv = pd.read_csv("data.csv")</div> <div>Copied!</div> |
| pip | | <div>1. 1</div> <div>1. pip list</div> <div>Copied!</div> |
| | To ensure that requests will function, the pip program searches for the package in the Python Package Index (PyPI), resolves any dependencies, and installs everything in your current | |

| Package/Method | Description | Code Example |
|----------------|--|--|
| pip install | Python environment. The pip install <package> command looks for the latest version of the package and installs it. | 1. 1 1. pip install pyspark Copied! |
| | Used to print or display the schema of the DataFrame or data set in tree format along with the column name and data type. If you have a DataFrame or data set with a nested structure, it displays the schema in a nested tree format. | 1. 1 1. df.printSchema() Copied! |
| printSchema() | | 1. 1 1. import pandas as pd Copied! |
| | | Create a sample DataFrame 1. 1 2. 2 1. data = {'A': [1, 2, 3], 'B': [4, 5, 6]} 2. df = pd.DataFrame(data) Copied! |
| rename() | Used to change the row indexes and the column labels. | Rename columns 1. 1 1. df = df.rename(columns={'A': 'X', 'B': 'Y'}) Copied! |
| | | The columns 'A' and 'B' are now renamed to 'X' and 'Y' 1. 1 1. print(df) Copied! |
| select() | Used to select one or multiple columns, nested columns, column by index, all columns from the list, by regular | 1. 1 1. selected_df = df.select('name', 'age') Copied! |
| | | |

| Package/Method | Description | Code Example |
|----------------|---|--|
| show() | <p>expression from a DataFrame.</p> <p>select() is a transformation function in Spark and returns a new DataFrame with the selected columns.</p> <p>Spark DataFrame show() is used to display the contents of the DataFrame in a table row and column format.</p> <p>By default, it shows only twenty rows, and the column values are truncated at twenty characters.</p> | <pre>1. 1 1. df.show()</pre> <div>Copied!</div> |
| sort() | <p>Sorting DataFrame by a column in ascending order</p> <p>Used to sort DataFrame by ascending or descending order based on single or multiple columns.</p> | <pre>1. 1 1. sorted_df = df.sort("age")</pre> <div>Copied!</div> <p>Sorting DataFrame by multiple columns in descending order</p> <pre>1. 1 1. sorted_df_desc = df.sort(["age", "name"], ascending=[False, True])</pre> <div>Copied!</div> |
| SparkContext() | <p>It is an entry point to Spark and is defined in org.apache.spark package since version 1.x and used to programmatically create Spark RDD, accumulators, and broadcast variables on the cluster.</p> | <pre>1. 1 1. from pyspark import SparkContext</pre> <div>Copied!</div> <p>Creating a SparkContext</p> <pre>1. 1 1. sc = SparkContext("local", "MyApp")</pre> <div>Copied!</div> |
| SparkSession | <p>It is an entry point to Spark, and creating a SparkSession instance would be the first statement you would write to</p> | <pre>1. 1 1. from pyspark.sql import SparkSession</pre> <div>Copied!</div> <p>Creating a SparkSession</p> <pre>1. 1</pre> |

| Package/Method | Description | Code Example |
|----------------------|---|--|
| spark.read.json() | the program with RDD, DataFrame, and dataset | 1. spark = SparkSession.builder.appName("MyApp").getOrCreate() |
| | Spark SQL can automatically infer the schema of a JSON data set and load it as a DataFrame. | |
| spark.read.json() | The read.json() function loads data from a directory of JSON files where each line of the files is a JSON object. Note that the file offered as a JSON file is not a typical JSON file. | 1. 1 1. json_df = spark.read.json("customer.json") |
| | To issue any SQL query, use the sql() method on the SparkSession instance. All spark.sql queries executed in this manner return a DataFrame on which you may perform further Spark operations if required. | |
| spark.sql() | In PySpark DataFrame, it is used to register a user-defined function (UDF) with Spark, making it accessible for use in Spark SQL queries. This allows you to apply custom logic or operations to DataFrame columns using SQL expressions. | 1. 1 2. 2 1. result = spark.sql("SELECT name, age FROM cust_tbl WHERE age > 30") 2. result.show() |
| | Registering a UDF (User-defined Function) | |
| spark.udf.register() | function (UDF) with Spark, making it accessible for use in Spark SQL queries. This allows you to apply custom logic or operations to DataFrame columns using SQL expressions. | 1. 1 2. 2 3. 3 4. 4 5. 5 1. from pyspark.sql.functions import udf 2. from pyspark.sql.types import StringType 3. def my_udf(value): 4. return value.upper() 5. spark.udf.register("my_udf", my_udf, StringType()) |
| | Used to filter the rows from DataFrame based on the given condition. Both filter() and where() functions | 1. 1 1. filtered_df = df.where(df['age'] > 30) |
| where() | | |

| Package/Method | Description | Code Example |
|----------------|---|---|
| withColumn() | are used for the same purpose. Transformation function of DataFrame used to change the value, convert the data type of an existing column, create a new column, and many more. | Adding a new column and performing transformations <pre>1. 1 2. 2 1. from pyspark.sql.functions import col 2. new_df = df.withColumn("age_squared", col("age") ** 2)</pre> <div>Copied!</div> |
| | Returns a new DataFrame by renaming an existing column. | Renaming an existing column <pre>1. 1 1. renamed_df = df.withColumnRenamed("age", "years_old")</pre> <div>Copied!</div> |

Changelog

| Date | Version | Changed by | Change Description |
|------------|---------|-----------------|-------------------------|
| 2023-09-20 | 1.0 | Gagandeep Singh | Initial version created |
| 2023-09-21 | 2.0 | Pornima More | QA pass with edits |

IBM Corporation 2023. All rights reserved.