

## Power supply


TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 1/9



## Main microcontroller


TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 2/9



## Slave microcontroller


TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 3/9



Output laser type	Component values				
	RA	RB	RC	RD	CA
Voltaje	10K/1%	4K3/1%	NC	0R	1.5uF
Current	0R	187R/1%	1K1/1%	3K3/1%	56nF

Note: In voltaje type  $R_A = 2.33R_B$  and  $f_c = 661\text{Hz}$   
Note: In current type  $R_D = 3R_C$  and  $f_c = 567\text{Hz}$

## Analog sensors












TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 4/9



## Digital sensors







TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 5/9



## Servo motors


TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 6/9



## DC motors



TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 7/9



## Brushless motors

TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1




Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 8/9





## Bluetooth and RS232

TITLE: mainboard\_eurobotics2010\_r12\_patch\_r1

Document Number:

REV:

Date: 11/05/2011 19:11:39

Sheet: 9/9