

READY

02_Partitions



```
%sh
STATUS="$(service cassandra status)"

if [[ $STATUS == *"is running"* ]]; then
  echo "Cassandra is running"
else
  echo " Cassandra not running .... Starting"
  service cassandra restart > /dev/null 2>&1 &
  echo " Started"
fi
```

READY

Exercise 2 – Partitions

READY

In this exercise, you will:

- Experiment with partitions

1. NOTE: Be sure Apache Cassandra™ is running before doing these exercises. You can check by running nodetool on the command line:

READY

```
%sh
nodetool status
```

READY

2. Switch to the YooToob keyspace via the USE command:

READY

```
%cassandra
```

READY

3. Execute the following command to view the metadata for the videos table you created earlier.

READY



READY

- What is the partition key?

READY

02. Partitions

How many partitions are in this table?



READY

4. Execute the following query to view the partitioner token value for each video id. READY

```
SELECT token(video_id), video_id
FROM videos;
```

READY

5. Use the following command to inspect the file named /home/labwork/data-files/videos-by-tag.csv: READY

```
%sh
cat /home/labwork/data-files/videos-by-tag.csv
```

READY

6. Switch to the YooToob keyspace. READY



READY

7. Your mission, should you choose to accept it, is to write a CREATE TABLE statement that will store this data partitioned by tags. With this given data set, there should be two partitions, one for each tag. Call your table videos_by_tag. READY



READY

8. Execute the following command to insert the videos-by-tag.csv data. FINISHED

Took 0 sec. Last updated by anonymous at July 13 2020, 2:30:33 PM. (outdated)

```
INSERT INTO videos_by_tag(tag, video_id, added_date, title)
VALUES ('cassandra', 1645ea59-14bd-11e5-a993-8138354b7e31, '2014-01-29', 'Cassandra History');
```

READY

```
INSERT INTO videos_by_tag(tag, video_id, added_date, title)
```

```
VALUES ('cassandra',245e8024-14bd-11e5-9743-8238356b7e32, '2012-04-03', 'Cassandra & SSDs');
```

```
INSERT INTO videos_by_tag(tag, video_id, added_date, title)
VALUES ('cassandra',3452f7de-14bd-11e5-855e-8738355b7e3a, '2013-03-17', 'Cassandra Intro');
```

02_Partitions

```
INSERT INTO videos_by_tag(tag, video_id, added_date, title)
VALUES ('fenago',4845ed97-14bd-11e5-8a40-8338255b7e33, '2013-10-16', 'Apache Cassandra');
```

```
INSERT INTO videos_by_tag(tag, video_id, added_date, title)
VALUES ('fenago',5645f8bd-14bd-11e5-af1a-8638355b8e3a, '2013-04-16', 'What is Apache Cassandra?')
```

9. Verify CQL imported your data correctly by writing a SELECT * command.

READY



READY

10. Write a SELECT statement to retrieve all rows tagged with cassandra.

READY



READY

11. Now, find all videos tagged with fenago (similar to the previous query).

READY



READY

12. Finally, write a query to retrieve the video having a title of Cassandra Intro.

READY



READY

NOTE: Notice your query errors out. Apache Cassandra™ only allows queries on the partition key (and clustering columns shown in the next section). Since `title` is not the partition key, Apache Cassandra™ fails the query. If Apache Cassandra™ allowed querying on non-partition key columns, Apache Cassandra™ would have to scan all partitions on all nodes to produce a result set (which goes against the reason you would use Apache Cassandra™ in the first place).



READY

02_Partitions
