

Cheat Sheet: Python Data Structures Part-2

Dictionaries

Package/Method	Description	Code Example
Creating a Dictionary	A dictionary is a built-in data type that represents a collection of key-value pairs. Dictionaries are enclosed in curly braces {}.	Example: <pre>dict_name = {} #Creates an empty dictionary person = { "name": "John", "age": 30, "city": "New York" }</pre>
Accessing Values	You can access the values in a	Syntax: <pre>Value = dict_name["key_name"]</pre>

	dictionary using their corresponding keys.	<p>Example:</p> <pre>name = person["name"] age = person["age"]</pre>
Add or modify	Inserts a new key-value pair into the dictionary. If the key already exists, the value will be updated; otherwise, a new entry is created.	<p>Syntax:</p> <pre>dict_name[key] = value</pre> <p>Example:</p> <pre>person["Country"] = "USA" # A new entry will be created. person["city"] = "Chicago" # Update the existing value</pre>
del	Removes the specified key-value pair from the dictionary. Raises a <code>KeyError</code> if	<p>Syntax:</p> <pre>del dict_name[key]</pre> <p>Example:</p> <pre>del person["Country"]</pre>

	the key does not exist.	
update()	The update() method merges the provided dictionary into the existing dictionary, adding or updating key-value pairs.	<p>Syntax:</p> <pre>dict_name.update({key: value})</pre> <p>Example:</p> <pre>person.update({"Profession": "Doctor"})</pre>
clear()	The clear() method empties the dictionary, removing all key-value pairs within it. After this operation, the dictionary is still	<p>Syntax:</p> <pre>dict_name.clear()</pre> <p>Example:</p> <pre>grades.clear()</pre>

	accessible and can be used further.	
key existence	You can check for the existence of a key in a dictionary using the in keyword	<p>Example:</p> <pre>if "name" in person: print("Name exists in the dictionary.")</pre>
copy()	Creates a shallow copy of the dictionary. The new dictionary contains the same key-value pairs as the original, but they remain distinct	<p>Syntax:</p> <pre>new_dict = dict_name.copy()</pre> <p>Example:</p> <pre>new_person = person.copy() new_person = dict(person) # another way to create a copy</pre>

	objects in memory.	
keys()	Retrieves all keys from the dictionary and converts them into a list. Useful for iterating or processing keys using list methods.	<p>Syntax:</p> <pre>keys_list = list(dict_name.keys())</pre> <p>Example:</p> <pre>person_keys = list(person.keys())</pre>
values()	Extracts all values from the dictionary and converts them into a list. This list can be used for further processing or analysis.	<p>Syntax:</p> <pre>values_list = list(dict_name.values())</pre> <p>Example:</p> <pre>person_values = list(person.values())</pre>

items()	Retrieves all key-value pairs as tuples and converts them into a list of tuples. Each tuple consists of a key and its corresponding value.	<p>Syntax:</p> <pre>items_list = list(dict_name.items())</pre> <p>Example:</p> <pre>info = list(person.items())</pre>
---------	--	---

Sets


Package/Method	Description	Code Example
add()	Elements can be added to a set using the `add()` method. Duplicates are automatically removed, as sets only store unique values.	<p>Syntax:</p> <pre>set_name.add(element)</pre> <p>Example:</p> <pre>fruits.add("mango")</pre>

clear()	The <code>clear()</code> method removes all elements from the set, resulting in an empty set. It updates the set in-place.	<p>Syntax:</p> <pre>set_name.clear()</pre> <p>Example:</p> <pre>fruits.clear()</pre>
copy()	The <code>copy()</code> method creates a shallow copy of the set. Any modifications to the copy won't affect the original set.	<p>Syntax:</p> <pre>new_set = set_name.copy()</pre> <p>Example:</p> <pre>new_fruits = fruits.copy()</pre>
Defining Sets	A set is an unordered collection of unique elements. Sets are enclosed in curly braces <code>{}</code> . They are useful for storing distinct values and performing set operations.	<p>Example:</p> <pre>empty_set = set() #Creating an Empty Set fruits = {"apple", "banana", "orange"}</pre>

<code>discard()</code>	Use the <code>'discard()'</code> method to remove a specific element from the set. Ignores if the element is not found.	<p>Syntax:</p> <pre>set_name.discard(element)</pre> <p>Example:</p> <pre>fruits.discard("apple")</pre>
<code>issubset()</code>	The <code>'issubset()'</code> method checks if the current set is a subset of another set. It returns True if all elements of the current set are present in the other set, otherwise False.	<p>Syntax:</p> <pre>is_subset = set1.issubset(set2)</pre> <p>Example:</p> <pre>is_subset = fruits.issubset(colors)</pre>

issuperset()	The <code>issuperset()</code> method checks if the current set is a superset of another set. It returns True if all elements of the other set are present in the current set, otherwise False.	<p>Syntax:</p> <pre>is_superset = set1.issuperset(set2)</pre> <p>Example:</p> <pre>is_superset = colors.issuperset(fruits)</pre>
pop()	The <code>pop()</code> method removes and returns an arbitrary element from the set. It raises a <code>KeyError</code> if the set is empty. Use this method to remove elements when the order doesn't matter.	<p>Syntax:</p> <pre>removed_element = set_name.pop()</pre> <p>Example:</p> <pre>removed_fruit = fruits.pop()</pre>
remove()	Use the <code>remove()</code> method to remove a specific element from the set. Raises a	<p>Syntax:</p> <pre>set_name.remove(element)</pre> <p>Example:</p>

	<code>`KeyError`</code> if the element is not found.	<code>fruits.remove("banana")</code>
Set Operations	Perform various operations on sets: <code>`union`</code> , <code>`intersection`</code> , <code>`difference`</code> , <code>`symmetric difference`</code> .	<p>Syntax:</p> <pre>union_set = set1.union(set2) intersection_set = set1.intersection(set2) difference_set = set1.difference(set2) sym_diff_set = set1.symmetric_difference(set2)</pre> <p>Example:</p> <pre>combined = fruits.union(colors) common = fruits.intersection(colors) unique_to_fruits = fruits.difference(colors) sym_diff = fruits.symmetric_difference(colors)</pre>
<code>update()</code>	The <code>`update()`</code> method adds elements from another iterable into the set. It maintains the uniqueness of elements.	<p>Syntax:</p> <pre>set_name.update(iterable)</pre> <p>Example:</p> <pre>fruits.update(["kiwi", "grape"])</pre>



Skills Network

© IBM Corporation. All rights reserved.