

Home

Get started

- Quickstart
- Using GPT-5.6
- Key concepts

Core concepts

- Responses API
- Conversation state
- Background mode
- Streaming
- WebSocket mode
- Multi-agent
- Webhooks
- File inputs
- Compaction
- Counting tokens

SDKs and CLI

- OpenAI SDK
- OpenAI CLI

Resources

- Changelog
- Deprecations
- Supported countries
- OpenAI Crawlers
- Terms and policies

Legacy APIs

- Agent Builder
- Evals
- Fine-tuning
- Assistants API

Overview of OpenAI Crawlers

Copy Page

OpenAI uses web crawlers (“robots”) and user agents to perform actions for its products, either automatically or triggered by user request. OpenAI uses OAI-SearchBot and GPTBot robots.txt tags to enable webmasters to manage how their sites and content work with AI. Each setting is independent of the others – for example, a webmaster can allow OAI-SearchBot in order to appear in search results while disallowing GPTBot to indicate that crawled content should not be used for training OpenAI’s generative AI foundation models. If your site has allowed both bots, we may use the results from just one crawl for both use cases to avoid duplicative crawling. For search results, please note it can take ~24 hours from a site’s robots.txt update for our systems to adjust.

User agent	Description & details
OAI-SearchBot	OAI-SearchBot is for search. OAI-SearchBot is used to surface websites in search results in ChatGPT’s search features. Sites that are opted out of OAI-SearchBot will not be shown in ChatGPT search answers, though can still appear as navigational links. To help ensure your site appears in search results, we recommend allowing OAI-SearchBot in your site’s robots.txt file and allowing requests from our published IP ranges below. Example user-agent string (the version number may change): <code>Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/131.0.0.0 Safari/537.36; compatible; OAI-SearchBot/1.4; +https://openai.com/searchbot</code> When fetching robots.txt files, we may use a user-agent string with an additional <code>robots.txt</code> marker. The marker helps site owners more easily distinguish requests for the robots.txt file from requests for other resources, especially when their logs do not include paths: <code>Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/131.0.0.0 Safari/537.36; compatible; OAI-SearchBot/1.4; robots.txt; +https://openai.com/searchbot</code> Published IP addresses: https://openai.com/searchbot.json
OAI-AdsBot	OAI-AdsBot is used to validate the safety of web pages submitted as ads on ChatGPT. When you submit an ad, OpenAI may visit the landing page to ensure it complies with our policies. We may also use content from the landing page to determine when it’s most relevant to show the ad to users. OAI-AdsBot only visits pages submitted as ads, and the data collected by OAI-AdsBot is not used to train generative AI foundation models. Full user-agent string: <code>Mozilla/5.0 AppleWebKit/537.36 (KHTML, like Gecko); compatible; OAI-AdsBot/1.0; +https://openai.com/adsbot</code> Published IP addresses: https://openai.com/adsbot.json
GPTBot	GPTBot is used to make our generative AI foundation models more useful and safe. It is used to crawl content that may be used in training our generative AI foundation models. Disallowing GPTBot indicates a site’s content should not be used in training generative AI foundation models.

Ask AI