

Let AI agents search across workspace with the Universal Search MCP Server for Workspace

Developer Preview: Available as part of the [Google Workspace Developer Preview Program](https://developers.google.com/workspace/preview) (<https://developers.google.com/workspace/preview>), which grants early access to certain features.

The Universal Search MCP Server for Google Workspace uses the [Model Context Protocol \(MCP\)](https://modelcontextprotocol.io/introduction) (<https://modelcontextprotocol.io/introduction>) standard to allow AI agents to search your Workspace artifacts. This server provides a way to search across multiple Google Workspace products, including Gmail messages, Google Drive files, Google Calendar events, and Google Chat spaces and messages, using a single tool.

The Universal Search MCP Server provides a standardized way for AI agents to search for information across your entire Google Workspace account without needing to call individual product-specific tools.

Prerequisites

- A Google Cloud project. To create a project, see [Create a project](/workspace/guides/create-project) (</workspace/guides/create-project>).
- An MCP client, like [Google Antigravity](https://antigravity.google/) (<https://antigravity.google/>).
- To run the commands on this page, set up the gcloud CLI in one of the following development environments:

[Cloud Shell](#)Local shell (#local-shell)
(#cloud-shell)

To use an online terminal with the gcloud CLI already set up, activate Cloud Shell:

[Activate Cloud Shell](https://console.cloud.google.com/home/dashboard?cloudshell=true) (<https://console.cloud.google.com/home/dashboard?cloudshell=true>)

Configure the Universal Search MCP Server

To use the Universal Search MCP Server, you must enable it in your Google Cloud project and then configure your MCP client to connect to it.

Enable the APIs

To use the Universal Search MCP Server, enable the Google Workspace MCP API and the APIs for the products that you want to search in your Google Cloud project:

- Gmail API
- Google Drive API
- Google Calendar API
- Google Chat API
- Google Workspace MCP API

[CLI](#)Console (#console)
(#cli)

```
gcloud services enable gmail.googleapis.com \
drive.googleapis.com \
calendar-json.googleapis.com \
```

```
chat.googleapis.com \
workspacemcp.googleapis.com --project=PROJECT_ID 
```

Replace *PROJECT_ID* with your Google Cloud project ID.

Set up the OAuth consent screen

The Universal Search MCP Server uses OAuth 2.0 for authentication and authorization. You must configure the OAuth consent screen before you can create an OAuth client ID.

If you have already configured the OAuth consent screen for other MCP servers, ensure you have added the required scopes for the Universal Search MCP Server.

When you authenticate with the Universal Search MCP Server, you can choose to authenticate all requested scopes or only a subset of them. The server respects these choices and only searches across the products for which access has been granted.

For example, if you authenticate with all of the following scopes:

- `https://www.googleapis.com/auth/gmail.readonly`
- `https://www.googleapis.com/auth/drive.readonly`
- `https://www.googleapis.com/auth/calendar.readonly`
- `https://www.googleapis.com/auth/chat.messages.readonly`

Universal Search MCP Server will search across Gmail, Google Drive, Google Calendar, and Google Chat.

However, if you only grant access to `https://www.googleapis.com/auth/drive.readonly`, `https://www.googleapis.com/auth/calendar.readonly`, and `https://www.googleapis.com/auth/chat.messages.readonly` (and omit `https://www.googleapis.com/auth/gmail.readonly`), universal search only returns results from Google Drive, Google Calendar, and Google Chat. It doesn't search your email or return Gmail results.

1. In the Google Cloud console, go to **Google Auth Platform > Data Access**.
2. Click **Add or Remove Scopes**.
3. Add one or more of the following scopes:

- `https://www.googleapis.com/auth/gmail.readonly`
- `https://www.googleapis.com/auth/drive.readonly`
- `https://www.googleapis.com/auth/calendar.readonly`
- `https://www.googleapis.com/auth/chat.messages.readonly`

4. Click **Update** and then **Save**.

For detailed instructions on setting up the consent screen, see [Configure the Google Workspace MCP servers](#) (/workspace/guides/configure-mcp-servers#configure-consent-screen).

Configure your MCP client

To add the Universal Search MCP Server to your MCP client, follow the instructions for your client.

[Antigravity Claude](#) (#claude)
(#antigravity)

To add the Universal Search MCP Server to Antigravity, add the server configuration to your `mcp_config.json` file. These instructions support Antigravity 2.0, Antigravity IDE, and Antigravity CLI.

1. Create an OAuth 2.0 client ID and secret of type **Web application**. In the **Authorized redirect URIs** section, click **+ Add URI**, and then add `https://antigravity.google/oauth-callback` in the **URIs** field. For instructions, see [Configure the Google Workspace MCP servers](#) (/workspace/guides/configure-mcp-servers#configure-mcp-client).

2. Open or create the configuration file `~/.gemini/antigravity/mcp_config.json`.

3. Add the `workspace-universal` configuration to `mcp_config.json`:

```
{
  "mcpServers": {
    "workspace-universal": {
      "serverUrl": "https://workspacemcp.googleapis.com/mcp/v1",
      "oauth": {
        "clientId": "OAUTH_CLIENT_ID",
        "clientSecret": "OAUTH_CLIENT_SECRET"
      }
    }
  }
}
```

Replace the following:

- `OAUTH_CLIENT_ID`: The client ID you created.
- `OAUTH_CLIENT_SECRET`: The client secret you created.

4. Save `mcp_config.json`.

5. Authenticate the MCP server. You can authenticate using either the GUI settings or the CLI:

- **For Antigravity IDE or GUI (Antigravity 2.0):**

- Open your settings screen (e.g., click **Settings** at the bottom-left or open **Antigravity User Settings**).
- Navigate to **Customizations**.
- Under **Installed MCP Servers**, click **Refresh**.
- Find `workspace-universal` in the list, click **Authenticate**, sign in to your Google Account, copy the authorization code, paste it into the input dialog, and click **Submit**.

- **For Antigravity CLI:**

- Start Antigravity CLI:

```
agy
```

- Open the interactive MCP management panel by running:

```
/mcp
```

- Use the arrow keys to select `workspace-universal`, move to the **Authenticate** action, and press **Enter**. Complete the sign-in flow in your browser, copy the authorization code, paste it into the terminal prompt, and press **Enter**.

6. Verify that the server is correctly configured and running:

- **For Antigravity IDE or GUI:** A **Sign out** button is displayed next to `workspace-universal` under **Customizations > Installed MCP Servers**.
- **For Antigravity CLI:** Open the `/mcp` panel to view your configured MCP servers. Verified and authenticated servers display **Authed** next to their names inside the interactive TUI panel. You can select the `workspace-universal` server under the dashboard view to inspect its status and list all of its available tools.

Test the Universal Search MCP Server

Try asking your MCP client questions that require searching across different products:

- **"Find anything related to Project X across my email, docs, and chat messages."**
- **"When is my next meeting about the marketing plan, and what are the latest notes and chat messages on it?"**

If the tools execute successfully and you receive relevant responses from multiple products, your Universal Search MCP Server is correctly configured.

Supported tools

The Universal Search MCP Server offers the following tool:

- **search_corpus**: Performs a search across multiple Google Workspace products (Google Drive, Gmail, Google Calendar, and Google Chat) based on the provided query.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (<https://creativecommons.org/licenses/by/4.0/>), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (<https://www.apache.org/licenses/LICENSE-2.0>). For details, see the [Google Developers Site Policies](https://developers.google.com/site-policies) (<https://developers.google.com/site-policies>). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2026-07-22 UTC.