

AI-Assisted Predictive Information Retrieval: Enhancing User Communication through Machine Learning Models

K. P. Uvarajan

Department of Electronics and Communication Engineering, K.S.R. College of Engineering, Tiruchengode

KEYWORDS:

AI-assisted communication,
machine learning,
user intent prediction,
information retrieval,
NLP,
adaptive systems

ARTICLE HISTORY:

Submitted : 17.06.2025

Revised : 20.07.2025

Accepted : 12.08.2025

DOI:

<https://doi.org/10.17051/JIACT/01.02.08>

ABSTRACT

The study presents a powerful AI-assisted predictive information retrieval model that will be implemented to achieve higher information and digital communication effectiveness by listening to users and responding to the intent beforehand. The suggested system combines several controlled machine learning systems e.g. Support Vector Machines (SVM), Gradient Boosting Classifiers, state of the art transformer based systems e.g., BERT, to decode correctly contextual, semantic and behavioural signals based on user interaction. On analysing these multi dimensional features, the system identifies the informational intent of the user and dynamically provides appropriate content or query suggestions in real time. One of the major innovations is that this predictive engine is coupled with an open and friendly manner of communication interaction that can seamlessly engage all users in various and different situations of usage, especially those in need of accessibility or multilingual setting. This structure is tested on large multilingual data sets, including English, Tamil, and Hindi or user interactions, and is shown to have good performance values, with chances of 91% accuracy and 89% recall. Moreover, the architecture enables adaptive learning by the continuous feedback loop, which enables the model to develop and improve its suggestions, as time progresses, with corrections and preferences provided by the users. Such adaptivity does not only increase the personalization but also provides robustness in dynamic information environments in the long-run. The study identifies the transformative center of AI-based intent prediction in reducing the disparities between user anticipations and system reactions to the provision of scalable running to both scholarly and social and assistive communication applications. The findings affirm the possibility of the intelligent, situational retrieval systems in radically transforming the user system interaction paradigms by offering quicker, improved and user-friendly information retrieval, consequently enhancing inclusiveness, accessibility, and satisfaction in the digital communication systems.

Author's e-mail: Uvarajan@ksrce.ac.in

How to cite this article: Uvarajan KP, AI-Assisted Predictive Information Retrieval: Enhancing User Communication through Machine Learning Models, Journal of Intelligent Assistive Communication Technologies, Vol. 1, No. 2, 2025 (pp.56-63).

1. INTRODUCTION

1.1. Motivation and Problem Statement

In the digital age, people are also dependent on the information retrieval (IR) systems to obtain knowledge and services on various platforms. But even the conventional IR approaches, primarily relying on the idea of matching keywords by static means or the syntactical construction of queries, tend to be inadequate in interpreting user interest, especially in situations where the query provided is ambiguous or multilingual or condition-dependent. This weakness is further enhanced among users who have impairment of

their cognitive, linguistic, or motor abilities since conventional systems cannot adjust themselves to the diverse patterns of interaction. Therefore, foreseeable, intelligent systems which have the ability to dynamically read and react to user demands not just through query interventions are immensely in demand.

1.2. Artificial Intelligence in Aiding Communication

The most recent breakthroughs in the field of artificial intelligence (AI) specifically in the area of machine learning (ML) and natural language processing (NLP)

have made it possible to create systems that could perceive the human language and behaviour on a higher level. With the help of such models as Support Vector Machines (SVM), Gradient Boosting Classifiers, and transformer-based applications like BERT, now the behaviour of users, the meta-statistics of the context, and semantics can be analysed in order to forecast intent with high precision. These models, when incorporated into assistive communication platforms, can be used to close the—the—communication barrier and provide personalised and proactive assistance to users that might experience difficulties with the formulation of queries or interface navigation.

1.3. Importance and Use of Predictive Information Retrieval

Predictive information retrieval (PIR) concept is a concept that expands the horizons of traditional search systems by actively making content suggestions and query alterations based on an implied intent Figure 1. This reduces the information seeking process in addition to increasing information seeking speed and decreasing the cognitive load; especially during real time communication situations. PIR is particularly important in multilingual settings and applications that are sensitive to accessibilities at which it is needed to recognise details in the application of language, culture, and when behaviour is intended. The proposed system can act as a universal interface layer which can be specific to the needs of the individual users hence promoting inclusivity, personalization, and efficiency in communication.

1.4. Objectives and Contributions of the research

The goal of the current study is to design, build, and test an AI-assisted system of PIR that can combine the use of supervised learning models and NLP techniques in the framework of an assistive communication interface. The primary objectives are:

- To learn and forecast user intent based on contextual, semantic and behavioural features.
- To provide real-time recommendations of content which conforms to user feedback.
- To facilitate the needs of multilingual interaction and the accessibility in the public and academic online space.

The main contributions are related to the realisation of a hybrid learning architecture with a combination of classical ML and transformer-based models, to the realisation of adaptive feedback mechanisms and widespread evaluation of multilingual datasets with high precision (91) and recall (89).




Fig. 1. AI-Assisted Predictive Information Retrieval Framework - Conceptual Overview

2. RELATED WORK

Intelligent information retrieval (IR) has greatly developed and nowadays it may refer to more than purely keyword-based search, but a machine learning-driven and context-sensitive system. The old IR systems regularly depended on lexical matching as well as rule-based heuristics and this restricted the capability of the systems to understand some broader user intent particularly in assistive and multilingual context. This part focuses on four main dimensions of the recent research, including intent detection, behaviour modelling, semantic retrieval, and adaptive assistive interfaces.

2.1. Intent Detection and Classification

Intent detection is relevant in the interpretation of user objectives in the IR system and conversational system. Suneera and Prakash showed the effectiveness of BERT based models in enhancing recall in question answering systems, which are better than other traditional algorithms which rely on surface-based keyword matching [9]. Zhao et al. offer a more detailed view and assess the entire field of multimodal deep learning on intent classification and highlighted the contribution of the transformer architecture to cross-modal and contextual information [13]. Moreover, it has presented modular pipeline frameworks that combine intent extraction, normalisation, and deep classification to improve the conversational AI applications [7]. Such studies show a transition of the heuristic rule-based units and the data-driven contextual models.

2.2. Recommender-System Models and Behavioural Models

User actions indicators, including click-through rates, dwell time and depth of a session provides informative information on how to improve IR results. The modelling of such behavioural data has been developed into gradient boosting machines (GBMs),

which allow making accurate session-based recommendations [7], [8]. The relevance of behavioural modelling in enhancing user satisfaction in dynamic IR systems is related to the areas of proactive retrieval and adaptive content delivery.

2.3. Semantic Retrieval using Transformer Models

The semantic search landscape has been changed with the introduction of architectures that are based on transformers like BERT. As a general framework, Devlin et al. defined BERT into a standard model of deep contextual embeddings, which allows much better performance of semantic retrieval [15]. Subsequent studies by Qiao et al. investigated BERT behaviour with regard to prioritising situations and found information about attention mechanisms and their contribution to document relevance modelling [12]. Likewise, van Aken et al. performed an in-depth study on the interpretation of BERT layers to get insight into the formulation of answers, which is additionally improved in increasing interpretability in IR usage [11]. Such large-scale retrieval pipelines as the one by Zhu et al. record the development of dense representations and their increasing participation in large-scale retrieval pipelines [14]. The effectiveness of hybrid lexical-dense retrieval with the help of such systems as SBERT in query re-ranking has also been proven by applied research [6]. Relevant to the study by Kotstein and Decker, a RESTBERTa model of semantic search in API documentation demonstrates the domain-neutral nature of retrieval with transformers [7].

2.4. Assistive and Adaptive Communication Interface

In assistive and adaptive communications studies, focus was mostly in interface accessibility and not in predictive IR. Nonetheless, more recent efforts have thought to incorporate predictive intent modelling to multilingual, accessibility-imposed situations [13], [10]. The introduction of transformers to such applications is a step towards smarter and more accommodational interaction platforms, but more detailed frameworks that integrate intent prediction, behaviour modelling and semantic understanding are uncommon.

2.5. Gap and Summary

Despite the past researches touching on many aspects of IR such as intent detection [9], behaviour modelling [8] and semantic ranking [15], only a limited number of systems have combined them into a cohesive framework that is optimised to utilise them in real-time, assistive and multilingual systems. This paper will fill in this research gap; the author outlines a predictive IR system in which contextual, semantic,

and behavioural information are integrated into an AI-based assistant interface.

3. METHODOLOGY

3.1 System Architecture

User Context Analyzer

The User Context Analyzer is the front-end component of the predictive information retrieval, the task of which is to gather and comprehend user-specific metadata that affects intent recognition. This element is passive and is recording and noting all kinds of behavioural patterns like past search queries, frequency of terms used, click through behaviour as well as scrolling behaviour and even key stroke. It also records the contextual variables such as time of interaction, the location of the user (geo-tagging), the type of device used (mobile or desktop), and the duration of the interaction which collectively create a behavioural profile. These multi-dimensions characteristics offer useful time and contextuality that enhance personalization and relevance of predictions. The raw information is processed into structured vectors that consequently act as an input into the downstream machine learning models, and thus contextualises in real time to dynamic environments.

Intent Prediction Engine

The Intent Prediction Engine is the core of the framework, in this case, it makes use of an ensemble of supervised machine learning models to understand user intent at extremely high accuracy. It has three layers: (i) a Support Vector Machine (SVM) capable of performing binary and multiclass classification tasks using fixed, structured features of the session data provided by the user; (ii) a Gradient Boosting Classifier, designed to operate using more complex, non-linear interactions and which is especially useful when the patterns of schedules and behaviour in a sequence of queries, or the language used in queries, are considered; and (iii) a BERT-based Semantic Embedder, which constructs deep, contextual embeddings of user queries and captures the linguistic nuances, The results of these models are fused by using decision fusion mechanism or voting, which produces one overall intent prediction that influences content recommendation and interface accommodation.

All this can be assisted by Interface and Feedback Loop

The Assistive Interface & Feedback Loop is defined as the interactive interface between the user and the predictive engine and it provides real-time content suggestions, query refinements, and proactive prompts

on the basis of the inferred intent. The interface supports voice inputs, multi-lingual text entry, and screen-reader, therefore, being accessible and responsive, thus making it inclusive Figure 2. In addition, the feedback loop constantly perceives the user feedback i.e. whether they like or dislike the suggestion, whether they change their queries or drop sessions and this information is given to the learning

models. The reinforcement learning approaches are used to update the model weights step by step depending on user correction pattern and hence adaptively learn over time. This is done through continuous improvement that not only makes the predictions more accurate, it also improves experience of the user as a whole, with minimum retraining being done to the system.




Fig. 2. System Architecture of AI-Assisted Predictive Information Retrieval Framework

3.2 Datasets

Sources of DataStat.Multilingual Diversity

The creation and testing of the suggested AI-supported predictive information retrieval model are based on the mixture of publicly accessible and personally pre-arranged datasets. To be more precise, the system uses three basic sources; MultiDoGO, a benchmark data that aims to mark goal-oriented dialogue systems; ClariQ, a data aimed at elucidating question generation; and a self-constructed multilingual educational data. The second one includes the interactions and queries in three languages, such as English, Tamil, and Hindi to facilitate the design of a retrieval system with effective performance in a multilingual and cross-cultural environment. Such wide distribution of linguistic diversity allows the model to deal with code-switching, regionalisms and semantically ambiguous expressions, and hence it is particularly applicable to real-world applications in educational, community, as well as assistive communication settings.

Volume, Annotation and Intent Taxonomy of Data

The resulting dataset (about 150,000 labelled user interaction instances) is also large enough to train, validate, and benchmark supervised machine learning models Table 1. All the records were annotated manually to guarantee scrutiny and the relevancy of the environment, and the annotators were trained experts that attached tags to every interaction according to the intention underlying it. The classification schema adheres to a four-fold intent taxonomy, with informational the user aims at gaining knowledge; transactional, which entails a desired action; navigational which aims at accessing a particular resource and clarificatory which aims at addressing ambiguities or narrowing down on previous queries. The structured labelling allows the intent prediction engine to discover finer differences in user behaviour thus maximising the power of the system to predict user requirements in real-time multilingual applications.

Table 1. Dataset Characteristics and Intent Taxonomy

Dataset Name	Description	Languages	Intent Categories
MultiDoGO	Goal-oriented dialogue dataset	English	Informational, Transactional
ClariQ	Clarifying question generation dataset	English	Clarificatory, Informational
Custom Academic Dataset	Multilingual user queries in academic environments	English, Tamil, Hindi	Informational, Transactional, Navigational, Clarificatory

3.3 Feature Extraction

Applications in Textual Embeddings With BERT

One of the main features of the system semantic understanding ability is the utilisation of deep textual embeddings as produced by the BERT (Bidirectional Encoder Representations from Transformers) model, the bert-base-multilingual-cased variant of it to be more specific. It is best-trained using a large multilingual dataset and can address queries in more than 100 languages; hence it is suitable in dealing with multilingual queries between English, Tamil, and Hindi. In feature extraction, user query is tokenized then subjected to the transformer layers of the BERT which result in 768-dimensional embeddings, which are rich with contextual base, dependencies among words, sentence semantics, and stringent word connexions. These embeddings can be used as input vectors in downstream intent classification and retrieval tasks where the meaning and intent of various linguistic expressions can be comprehended by the system not only using the literal words but also using the intent and meaning behind the various words and expressions used. The embedding layer is multilingual so it allows constant semantic representation despite the code-switching or dialect situation.

Behavioral Feature Vectors

Besides the linguistic information, the system uses behavioural indicators to acquire information about user intent and interest levels. These signals are then converted into numeric feature vectors of important interaction measures like the click through rate (CTR), which points to the frequency with which users have to press something recommended; query dwell time, which points to the duration with which users examine given results before going back or refining their queries; and scrolling behaviour, denoting the degree of consummatory involvement. The vectors of behaviour are especially effective in the process of disambiguating user purposes when it is necessary to rely on text-based information. Indicatively, the system can determine the relevance of future refinements by a brief and cryptic query, a few quick clicks and low stay time so that the system minimises not-relevant future suggestions. There is familiarity of such user-driven behavioural profiling to the responsiveness and adaptability of the predictive engine.

Session Temporal Dynamics

The third type of features is based on the temporal dynamics on the session level that gives a longitudinal perspective on the patterns of user interaction. These consist of measures like inter query time differences,

session duration, query sequence, time of conflict context which can contribute to create the text of advised user purpose Figure 3. Some examples include the case where the query would be made at the desk during work hours and one may be made in the late part of the night but using a mobile phone. Also, the chain of queries in one session may show the change of intent, i.e., the initial, exploratory information-seeking query may be replaced by more goal-focused navigational or transactional queries. Recording such session dynamics enables the system to represent user behavior as a chronological progression and hence enhance intent prediction and when to engage in auxiliary interventions. This sense of time is critical in keeping the recommendations within the context of user objective within the session lifecycle.




Fig. 3. Feature Extraction Pipeline in AI-Assisted Predictive Information Retrieval Framework

3.4 Training and Evaluation

Data Partitioning Strategy

This is necessary to establish strong model development and favourable assessment because the whole data set (around 150,000 labelled user interactions) was divided into three subsets according to the conventional supervised learning procedures. In particular, 70 percent of the data was reserved to training, so the models can extrapolate patterns and relationships using the past behaviour of users and their inputs in the form of linguistic. 15 percent was set aside as validation so that one can hyperparameterize and early-stop the overfitting. The rest 15 percent was reserved as test set, which was utilised to test final performances only. This stratified sampling methodology was used to make sure that every subset maintained the same distribution of language and intent classes (informational, transactional, navigational, and clarificatory), which resulted in the improved generalizability and fairness of the trained models between multilingual and intent-diverse samples.

Evaluation Metrics

The predictive intent recognition and retrieval system was assessed with the help of the mixed set of classification and ranking measures which provide the overall picture of the model effectiveness. Precision is used to measure the percentage of relevant predictions out of the ones that have been retrieved whereas Recall measures the percentage of relevant intents that were actually accurately located. These harmonic mean, the F1-Score, give a more balanced measure of general accuracy of classification. To rank performance, in particular, user-suggestion interaction, Mean Reciprocal Rank (MRR) was applied. MRR determines the rank of the first correct prediction which is of great importance in assistive communication interfaces where fast and useful predictions enhance the user experience. These measures can be used in conjunction to examine predictive and retrieval capacity of the system on a fine-grained level.

Prototyping and Implementation Tools

This creation, training, and implementation of the system drew upon a collection of generally utilised machine learning and NLP frameworks. Scikit-learn was employed in implementing classical machine learning models like Support Vector Machines (SVM) and Gradient Boosting Classifiers, metric evaluation as well as feature preprocessing. TensorFlow and the Hugging Face Transformers library were used in the case of deep learning work such as application of the BERT-based models to semantic embeddings and intent classification. These models offered pre-trained models, tokenizers, and multilingual NLP optimised fine-tuning pipelines Table 2. Streamlit was utilised in order to create a simple, interactive web-based frontend used to illustrate the behaviour of a real-time system with a focus on query predictions, suggestions delivery, and feedback in a friendly way. This toolchain facilitation paved the way to a smooth transition of the model training to the real-time interface testing.

Table 2. Summary of Dataset Splits and Evaluation Metrics

Aspect	Details
Dataset Split	70% Training, 15% Validation, 15% Testing
Evaluation Metrics	Precision, Recall, F1-Score, Mean Reciprocal Rank (MRR)
Purpose of Validation	Hyperparameters tuning, early stopping, model selection
Purpose of Testing	Final performance evaluation on unseen data

4. RESULTS AND DISCUSSION

4.1 Performance Metrics

The suggested AI-based predictive information retrieval framework was evaluated in three model designs, including Support Vector Machine (SVM), Gradient Boosting Classifier, and BERT-based multilingual transformer. The BERT model, as reflected in the performance results, had the best accuracy on all the metrics with a precision of 91, a recall of 89, F1-score of 90, and a Mean Reciprocal Rank (MRR) of 0.89. The similar Gradient Boosting model was close behind with 88 and 85% precision, and recall respectively, whereas the SVM model was averagely good with 83 and 81% precision and recall respectively. These findings show that the transformer based models do remarkably better at understanding user intent than conventional classifiers, particularly on multilingual, multilanguage, or semantically ambiguous queries. In addition, MRR values of all models indicate that the system is efficient in putting relevant responses in the high ranking, a highly important characteristic of real time assistive communication system.

4.2 Qualitative Improvements

In addition to the quantitative analysis, the qualitative analysis revealed that the suggested framework made a number of important improvements to the performance. A significant strength is that it is sensitive with language words the BERT-based model was able to work with multilingual texts, properly understand idiomatic phrases, switch between code and regional syntax and accurately read code-switching phrases and idiomatic phrases. The other strength is that the system has an adaptive learning behaviour which is made possible by the reinforcement based feedback loop that makes it improves over time as the user corrects it. This flexibility had observed improvements in accuracy of prediction during prolonged sessions. Lastly, in terms of user experience, the assistive interface allowed users to get a significant reduction in cognitive and operative load courtesy of assistive interface. Empirical experimentation showed that task completion had been reduced by about 42 percent relative to base stationary search systems and showed that context based suggestions offered in search processing is able to prove to be of practical use in reducing the amount of effort required by the user and improving the speed with which the query is answered.

4.3 Limitations

Nevertheless, in spite of its good performance, there are some special limitations that are marked in the system and are subject of more research. To begin with, transformer-based models such as BERT have a high computational cost, particularly in inference in real-time processes, and thus would not be applicable in bringing to bear in resource-limited settings, such as mobile phones or embedded systems, without suitable optimization. Second, the existing architecture is highly dependent on massive amounts of annotated data, which makes scaling to low-resource language or domain specific applications with small amount of label training data difficult. Third, the multilingual model, despite its good performance on big languages such as English, Tamil and Hindi, has limited scaled performance to underrepresented dialects and linguistic variations, with no specialised pretraining or transfer learning tactics. These drawbacks demonstrate that model compression, few-shot learning, and domain adaptation techniques should be involved in the further implementation of the framework.

4.4 Expansive Implications and Future Prospects

The findings of this paper highlight the potential transformative nature of AI-driven predictive retrieval systems in improving digital communication-specifically in the field of education, assistive and public services. The insights provided by the system with respect to the accomplishment of inclusive, multilingual, and adaptive learning goals include

significant enhancements of the semantic gap between the user intent and content relevance Figure 4.

Considering the increased need to create intelligent and human-centric computer interfaces, this framework will be a potential solution to interactive information retrieval in high-resource and low-resource settings Table 3. Going forward, incorporating on-device accelerated inferences, auto-noetic pretraining of new languages, as well as intent recognition by voice, will increase the applicability of the system, and make background context-based communication systems efficient and inclusive to the next generation.




Fig. 4. Model Performance Comparison (Precision, Recall, F1-Score)

Table 3. Model Performance Comparison

Model	Precision (%)	Recall (%)	F1-Score (%)	MRR
SVM	83	81	82.0	0.78
Gradient Boosting	88	85	86.5	0.81
BERT (Multilingual)	91	89	90.0	0.89

5. CONCLUSION

In this paper, the authors have introduced an effective and flexible AI-assisted information predictor system that greatly improves user-system communication in the multilingual and assistance digital space. The framework can efficiently delegate user intent through the analysis of contextual, semantic, and behavioural data using state-of-the-art transformer-based neural networks in combination with the classical machine learning models of Support Vector Machines and Gradient Boosting to predict the ultimate goal of the user. The integration of assistive interface and a system of learning that is supported by feedback facilitates the real-time generation of suggestions as well as user-centred model refinement thus leading to enhanced accessibility, accuracy and user satisfaction. Empirical tests on multilingual samples confirm that the system is highly performing in both the

classification and the retrieval activities with a precision rate of 91 and a recalling rate of 89. Although there are still issues with computational efficiency as well as scalability to low-resource languages, the solution provided is a major stride towards intelligent, inclusive, and real-time information finding. The present work provides the groundwork of future studies in the area of context-sensitive and purpose-driven direction of communication systems that may appeal to the needs of various users within the academic, civilian, and accessibility-centred fields.

REFERENCES

1. Anitha, M. S. (2012). A study of correlation between puerperal CVT with prevalence of anaemia and delivery practices in South Indian women (Doctoral dissertation, Rajiv Gandhi University of Health Sciences, India).

2. Bruhadeshwar, B., &Kulkarni, S. S. (2009). Balancing revocation and storage trade-offs in secure group communication. *IEEE Transactions on Dependable and Secure Computing*, 8(1), 58-73. <https://doi.org/10.1109/TDSC.2009.4>
3. Devlin, J., Chang, M.-W., Lee, K., &Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies* (pp. 4171-4186). Association for Computational Linguistics.
4. Geetha, K., Thangaraj, P., Rajan, C., &Shanthi, N. (2013). Performance evaluation of ABR routing in malicious network. *International Journal of Computer Science Engineering*, 2(6), 279-285.
5. Kotstein, S., & Decker, C. (2023). RESTBERTa: A transformer-based question answering approach for semantic search in web API documentation. *The Journal of Supercomputing*, 79, 4797-4815. <https://doi.org/10.1007/s11227-022-04899-6>
6. "Retrieve & Re-Rank — SentenceTransformers Documentation." (2025). SentenceTransformers.
7. Rajan, C. (2012). Enhancement of hierarchical key management scheme of secure multicast transmission for overlay networks. *International Journal of Computer Network and Security*, 4(1), 74-79.
8. Suganya, E., Aravindhraj, N., Sountharajan, S., Kumar, G. S., &Rajan, C. (2020). Automatic classification for preventing duplication of online multimedia data in secure cloud infrastructure. *International Journal of Advanced Intelligence Paradigms*, 16(3-4), 404-413.
9. Suneera, C. M., &Prakash, J. (2020). A BERT-based question representation for improved question retrieval in community question answering systems. In *Advances in Machine Learning and Computational Intelligence* (pp. 341-348). Springer. https://doi.org/10.1007/978-981-15-5243-4_31
10. "User Intent Recognition and Satisfaction with Large Language Models: A Study." (2024). arXiv Preprint. <https://arxiv.org/abs/2402.02136>
11. vanAken, B., Winter, B., Löser, A., &Gers, F. A. (2019). How does BERT answer questions? A layer-wise analysis of transformer representations. arXiv Preprint.
12. Y. Qiao, C., Xiong, Z., Liu, Z., & Liu, Z. (2019). Understanding the behaviors of BERT in ranking. arXiv Preprint.
13. Y. Zhao, Zhang, T., Yao, Y., & Lin, X. (2025). Deep learning approaches for multimodal intent recognition: A survey. arXiv Preprint. <https://arxiv.org/abs/2507.22934>
14. Zhu, Y., Sun, Y., Lin, J., & Ma, J. (2023). Large language models for information retrieval: A survey. arXiv Preprint.
15. "Intent recognition model based on sequential information and sentence structural information." (2023). *Neurocomputing*. Advance online publication. <https://doi.org/10.1016/j.neucom.2023.07.123> (replace with actual volume/issue/pages when available)