Examining the Superposition of Saftey and Utility in LLM Activation Spaces

Midterm Project Update

Group 6: Evan Scamehorn, Kyle Sha, Adam Venton, Zeke Mackay, and Calvin Kosmatka

https://github.com/evan203/nlp-project-proposal

Recap:

- Aligned LLMs can produce harmful outputs using diverse jailbreaking techniques
- Safety subspaces are hypothesized to be represented in several different ways
- Alpaca (harmless prompts) and BeaverTails (harmful prompts) datasets
- Refusal score and Attack Success Rate to evaluate performance

Baseline Method:

- Difference-in-means (DIM) [1]
  - Mean response activation difference between harmful and harmless prompts
- Refusal Cone Optimization (RCO) [2]
  - Use gradient descent to generate multiple basis vectors representing safety mechanisms
- ActSVD safety/utility ranks [3]
  - Perform Singular Value Decomposition on model weights to identify safety/utility-critical low-rank matrices
- Mode Subspace Overlap (MSO) [4]
  - Performs SVD to quantify overlap between subspaces
- Representational Independence (RepInd) [2]
  - Performs cosine similarity on ablated model activations to test independence of multiple subspaces

Experiment setup:

- Comparison of safety and utility subspaces
  - Mode Subspace Overlap (MSO) similarity test between safety subspaces [4]
  - Representational Independence (RepInd) comparison between each safety subspace and utility subspace [2]

Findings — Safety Benchmarks:

We benchmark three variants of **Llama-3.1-8B-Instruct**:

1. **Base** — the original aligned model
2. **DIM-Ablated** — refusal direction projected out at layer 11 [1]
3. **ActSVD-Modified** — low-rank safety-critical weight components removed [3]

Evaluated on **JailbreakBench** [5] (100 harmful prompts, 10 harm categories, 10 each) and 100 harmless **Alpaca** [6] prompts. Attack Success Rate (ASR) = fraction of harmful prompts where the model complies instead of refusing. Compliance on harmless prompts should remain at 1.0.

Model	JBB ASR	Harmless	Pile PPL	Alpaca PPL
Base	0.16	1.00	8.69	6.01
DIM-Ablated	1.00	1.00	8.75	6.13
ActSVD-Modified	0.63	1.00	13.09	6.82

Findings — Jailbreak ASR:



DIM ablation achieves **100 % ASR** — complete safety removal across every harm category. ActSVD reaches **63 %** — partial removal only.

The per-category breakdown reveals ActSVD is **non-uniform**: 0.9 on Disinformation, Expert advice, Malware — but only 0.2 on Harassment and 0.0 on Sexual content.

Benchmark: JailbreakBench [5] — 100 prompts, 10 harm categories. Compliance via refusal-prefix matching.

Findings — Per-Category Jailbreak ASR:



ActSVD's weight pruning removes safety **non-uniformly** — it largely fails on socially sensitive categories (Harassment, Sexual content) while succeeding on more technical harms (Malware, Disinformation). DIM is uniformly effective.

Findings — Utility Preservation:



Perplexity on **The Pile** [7] (general text) and **Alpaca** [6] (instructions). DIM barely impacts capability (**+0.7 %** Pile PPL). ActSVD causes **+51 %** Pile PPL degradation — its distributed weight modifications damage general language modelling. The safety–utility scatter (right) shows DIM **dominates** ActSVD on both axes.

Findings — MSO Heatmap (DIM vs ActSVD):



Maximum Subspace Overlap (MSO) [4] measures overlap of the DIM refusal direction with ActSVD's weight-delta subspace per layer and weight type.

Most cells are **near random baseline** ($\approx k_A \cdot k_B/d$) — the two methods find **nearly orthogonal** safety structures.

Only notable signal: **layer 10** MLP down proj (MSO = 0.057, 3.2× random) — adjacent to DIM's source layer (11).

Findings — Per-Layer MSO & Cross-Model Cosine:





Left: Per-layer average MSO (red) vs random baseline (blue). Layer 10 is the only layer clearly above baseline. Layers 20–31 show no signal. **Right:** DIM directions computed independently for 6 models. Llama-3.1 ↔ Llama-3 cosine similarity = **0.603** — all cross-family pairs ≈ 0. The refusal direction is **model-family-specific**.

Future Extension:

- Evaluate Mode Subspace Overlap (MSO) between safety subspaces
- Implement and evaluate further jailbreaking techniques

Contribution:

Evan: Project Management, Paper reimplementation (20%) Adam: Report writeup, Model analysis (20%) Calvin: Model analysis, Literature review (20%) Kyle: Paper reimplementation, Report writeup (20%) Zeke: Model analysis, Slide writeup (20%)

References

[1] A. Arditi *et al.*, "Refusal in Language Models Is Mediated by a Single Direction," in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang, Eds., Curran Associates, Inc., 2024, pp. 136037–136083. doi: 10.52202/079017-4322.

[2] T. Wollschläger, J. Elstner, S. Geisler, V. Cohen-Addad, S. Günnemann, and J. Gasteiger, "The Geometry of Refusal in Large Language Models: Concept Cones and Representational Independence," in *Proceedings of the 42nd International Conference on Machine Learning*, A. Singh, M. Fazel, D. Hsu, S. Lacoste-Julien, F. Berkenkamp, T. Maharaj, K. Wagstaff, and J. Zhu, Eds., in Proceedings of Machine Learning Research, vol. 267. PMLR, 2025, pp. 66945–66970. [Online]. Available: https://proceedings.mlr.press/v267/wollschlager25a.html

[3] B. Wei *et al.*, "Assessing the Brittleness of Safety Alignment via Pruning and Low-Rank Modifications," in *Proceedings of the 41st International Conference on Machine Learning (ICML)*, in Proceedings of Machine Learning Research, vol. 235. PMLR, 2024, pp. 52588–52610. [Online]. Available: https://proceedings.mlr.press/v235/wei24f.html

[4] K. Ponkshe, S. Shah, R. Singhal, and P. Vepakomma, "Safety Subspaces are Not Linearly Distinct: A Fine-Tuning Case Study," in *Proceedings of the Fourteenth International Conference on Learning Representations (ICLR)*, 2025. [Online]. Available: https://arxiv.org/abs/2505.14185

[5] P. Chao *et al.*, "JailbreakBench: An Open Robustness Benchmark for Jailbreaking Large Language Models," in *NeurIPS Datasets and Benchmarks Track*, 2024. [Online]. Available: https://arxiv.org/abs/2404.01318

[6] R. Taori *et al.*, "Stanford Alpaca: An Instruction-following LLaMA model." GitHub, 2023.

[7] L. Gao *et al.*, "The Pile: An 800GB Dataset of Diverse Text for Language Modeling," *arXiv preprint arXiv:2101.00027*, 2020, [Online]. Available: https://arxiv.org/abs/2101.00027

[8] J. Ji *et al.*, "BeaverTails: Towards Improved Safety Alignment of LLM via a Human-Preference Dataset." [Online]. Available: https://arxiv.org/abs/2307.04657