GIT INSTRUCTION MANUAL

EVAN BERGERON FREDERICK LEE ZIYANG WANG SUNNY GAKHAR NISHAD GOTHOSKAR

Contents

Introduction
What is Git
Initializing Repository
Adding files to version control
Committing changes
Reverting changes
Branching
Merging Branches
Ignoring Files
Rebasing
Cherrypicking
Collaboration with Github
General workflows
Easily Reordering Commits
Adding partial files
Git aliases
Vim workflows
Installing vim-fugitive
Emacs workflows
Installing Magit

Introduction

This is a manual on how to set up Git on your computer and set up a basic Git workflow. The document covers installing and setting up Git and how to work with Git. The majority of this document is primarily intended for users who want to learn Git to use it in a fast-paced setting such as a hackathon, this document is also useful as a reference for experienced Git users who want to refer to some specific concept or command which they need.

What is Git

Initializing Repository

Adding files to version control

COMMITTING CHANGES

REVERTING CHANGES

Branching

MERGING BRANCHES

IGNORING FILES

Rebasing

CHERRYPICKING

Collaboration with Github

General Workflows

Easily Reordering Commits

Weve all been there. You pull from master, take several minutes to clean up the various merge conflicts, and then are ready to push. You pull one last time before pushing, and what do you know - someone has pushed again in the last couple minutes.

Previously, my workflow for this situation would look something like

- \$ git checkout -b tmp
- \$ git checkout master
- \$ git reset --hard HEAD~
- \$ git cherry-pick tmp

This works fine, but theres a much easier way – one that involves very little typing. We can simply say

git rebase -i HEAD 2

This will open an interactive git rebasing session (the -i stands for interactive). The window will display something along the lines of

```
pick 370e221 Commit one pick c342396 Commit two
```

In whichever text editor were in, we may simply reorder these lines to reorder the commits. Much shorter!

ADDING PARTIAL FILES

I just used this, actually. Suppose youve changed a single file foo.c in different sections, and each of these changes are logically different. For instance, maybe you refactor some function foo, while at the same time fixing a bug in function bar. Rather than create a separate branch and manaully edit the files, we can simply say

This will bring up an interactive prompt. It will automatically cycle through all the different areas of the diff, asking you if you want to stage each section. You may hit y or n for yes or no.

Once youre done adding the subset of changes you want to commit, you can double-check you have the right changes staged by saying

Once youre sure that youre good to go, just commit your changes as normal. You can repeat this process for the remaining changes. (Or just do a normal git add at this point).

GIT ALIASES

Git aliases are a good way to save yourself a lot of typing. I frequently want to see the git commit history, but dont especially care about the body of each commit. Heres the command Ive added to my configuration:

I can then just type git 1 to see a one line log of this commit history. If there are several long commands you use frequently, this can be a great way to save yourself some time.

VIM WORKFLOWS

At the time of writing, perhaps the most feature complete vim-git plugin is Tim Popes vim-fugitive. Consequently, we will assume usage of this plugin throughout the entire vim workflows tutorial.

Installing vim-fugitive

There are a number of ways to install vim-fugitive. The one suggested by Tim Pope is as follows:

```
$ cd ~/.vim/bundle
```

\$ git clone git://github.com/tpope/vim-fugitive.git

\$ vim -u NONE -c "helptags vim-fugitive/doc" -c q

Vundle is a great plugin manager for vim – if you use this, you may simply add the line

to your vimrc and run the PluginInstall command.

EASY GIT BLAME

Youre browsing some file and discover a horrible bug written by one of your coworkers. Youre about to storm over to someones desk and verbally abuse them for producing incorrect code. Before you deliver your diatribe, you need to know who to blame.

Before using vim-fugitive, you would have to exit vim, manually type git blame <filename>, and then search for the relevant line in the output. Now, you can simply type :Gblame in your vim prompt, and a vertical split will open up right next to the line in question. You could even establish a keybinding to do this for you! What was once several lines of typing is now a single keystroke away! Your coworkers have never been so scared...

EMACS WORKFLOWS

Similarly to vim-fugitive for vim, Magit is (at the time of writing), the most feature-complete git wrapper for emacs. We will thus assume usage of this package.

Installing Magit