产品规格书 PRODUCT SPECIFICATIONS

料 号Part NO		02-002				
产品名称Product Name		TRIMER-5PF; TRIMER-50PF; TRIMER-60PF				
型 号Model No		HK06-1				
			WL.C			
容量范围 (PF) Cop Honge		标称容量(PF) Nominal Copacitance(PF)	容量误差 Capacitance tolerance	电容温度系数 Camp coeff (ppa/°C)	Q值 Q VOLUE	备注 Remarks
最小值min	最大值max			XXX		
Less than 1.8	3	□ 06-3P	3+100% — 0%	Z-X \		Black
2.4	5	□ 06-5P	5+100% 0%	$\mathrm{NP0} \pm 250$	> 500	Blue
2.8	7	□ 06-7P	7+100% 0%	·. 0		Blue
3.8	10	□ 06-10P	10+100% 0%	$N450 \pm 300$		White
6. 5	20	□ 06-20P	20+100% 0%	N750±300		Red
9	30	□ 06-30P	30+100% 0%	N1000±500		Green
12	40	□ 06-40P	40+100% 0%	, ,	>300	Yellow
17	50	□ 06-50P	50+100% -0%			Brown
22	60	□ 06-60P	60+100%	$N2200 \pm 800$	>200	Brown
28	70	□ 06-70P	70+100% 0%			Brown
38	120	□ 06-120P	120+100% — 0%			Brown
额定电压Rated Voltage:			100V			
最大电压Max Voltage:			220V			
绝缘电阻Insulation Resistance:			10000M Ω			
工作环境温度 Operating Temperature:			-25~85°C			

