

PS/2 Keyboard for MSX And Legacy computers

Solution

Based on:

- . ARM Cortex M3 Blue Pill stm32f103c6t6**
- . ARM Cortex M4 Black Pill stm32f401ccu6**

Evandro Souza <evandro.r.souza@gmail.com>

Introduction

The main objective was to learn to use the ARM Core M3 and M4 Open Develop Enviroment (free)

To do so, I choose a critic mission challenge, with implementation features not commonly available in various smart solutions, as an example, update translation database tables not possible without full firmware recompilation and upload to hardware.

Show up a low cost solution.

Index

Enviroment characteristics and
considerations

About get the right MCU

Develop enviroment setup

The electronics

Firmware features

Firmware Technical Datasheets

Now

Enviroment characteristics and
considerations


About get the right MCU

Develop enviroment setup

The electronics

Firmware features

Firmware Technical Datasheets




		0	1	2	3	4	5	6	7	8
		Y=0	Y=1	Y=2	Y=3	Y=4	Y=5	Y=6	Y=7	Y=8
FE	X=0) 0	* 8	^ ~	C c	K k	S s	SHIFT	F4	Space
FD	X=1	 1	(9] [D d	L l	T t	CTRL	F5	CLS HOME
FB	X=2	@ 2	- -	; ,	E e	M m	U u	GRAPH	ESC	INS
F7	X=3	# 3	+ =	: :	F f	N n	V v	CAPS	TAB	DEL
EF	X=4	\$ 4	^ \	? /	G g	O o	W w	CODE/ KANJI	STOP	LEFT
DF	X=5	% 5	' ,	> <	H h	P p	X x	F1	BackSpace	UP
BF	X=6	" 6	' ,	A a	I i	Q q	Y y	F2	SLCT	DOWN
7F	X=7	& 7	Ç ç	B b	J j	R r	Z z	F3	RETURN	RIGHT


The MSX keyboard is a 8 lines (X) by up to 15 columns (Y) matrix, which can achieve a theoretical maximum of 120 keys – The HB8000 has 9 columns, as seen on the example (J25 is the keyboard connector and, on left, its key mapping table). A highend japanese MSX uses a 11 columns keyboard;

Firstly, the scan is done by writing on Y3:0 (PC3:0, address 0AAH), which goes to a decoder (up to 4x16 with open-collector outputs, and reading from X7:0 (through PPI 8255 PB7:0, port 0A9H);

The Caps Lock and Katakana states ("0" active) are sampled directly from MSX hardware and echoed on PS/2 keyboard LEDs.



MSX Keyboard Scanning timing



Detailed timing diagram of a MSX Keyboard read (OUT followed by an IN)

The available amount of time after the Y update (execution of OUT (0AAH), A) is 3,6μs;

- Obs.: In special circumstances, the keyboard reading (IN A, 0A9H) is not done just after OUT (eg: games), so, the converter must update X as soon as the PS/2 Keyboard events occur, according to respective Y of the moment. In other words, the converter must keep updating X even if the MSX is not doing the keyboard scan.


PS/2 Keyboard - Timmings

The PS/2 keyboard communicates to host computer through a *half duplex* synchronous serial line with 2 wires, in a unbalanced (gnd is the return path) communication mode. Two lines are used: Data and Clock;


- The clock rate is in range from 10K to 16,7KHz;

Observe the following timing diagrams of:

1) From PS/2 Keyboard to host (PC or converter):




2) From host to keyboard:



- (a) Host forces the clock line to low (0) for at least 100 μ s;
- (b) Is the time that keyboard requires to start to send clock to receive the frame, which can take up to 15ms;
- (c) Is the time to conclude the frame reception, after the keyboard has started the clock sending, and must be up to 2ms;

PS/2 Keyboard - Layout

- There are many exclusive MSX keys, like Graph, Code, Select and Stop. That though is also valid for a PC keyboard;
- The scan codes do not have any pairing (relationships) with keytops mark;
- The scan codes have different sizes: from 1 to 8 bytes;
- The PS/2 keyboard sends Type 2 codes (AT type) to the host and the auto-repeat is only on the last one pressed;
- The scan codes are not dependent of physical layout – For example: The codes 0x51 (key “/” on the left side of right Shift) and 0x6D (Key “.” of numeric keypad) are exclusive of ABNT2 (Id=275) keyboards;
- Here is the example of the base keyboard to todo this development (ABNT2 keyboard) with make scan codes:



Now

Environment characteristics and considerations

About getting the right MCU


Develop environment setup

The electronics

Firmware features


Firmware Technical Datasheets

Picking the MCU (Micro Controller Unit)



Features met

1. Low power consumption;
2. At least 16 pins must be 5V tolerant;
3. Output pins must support be configured as OD (Open Drain);
4. OD pins must allow to get their state read at any time;
5. At least 5 pins must be enabled as external interrupt;
6. The external interrupt pins connected to Y_SCAN must not share interrupt resources;
7. Its non volatile memory must be grather than 2560 bytes and must be writeable by software;
8. Plenty documentation available;
9. Open develop enviroment;
10. Low cost;
11. Easy to get.





Now

Enviroment characteristics and considerations

About get the right MCU

Develop enviroment setup

The electronics

Firmware features

Firmware Technical Datasheets

Develop Enviroment Setup

Linux Ubuntu 20.04

ARM GCC Tools

LibOpenCM3

OpenOCD

Visual Studio Code

The first steps was done with the orientation of this remarkable book:

Warren Gay, Beginning STM32 Developing with FreeRTOS, libopencm3 and GCC,
which was introduced me by Ismael Lopes da Silva, site
<https://www.embarcados.com.br/serie/programacao-com-a-placa-blue-pill/>, to
whom I am very grateful!

The background of the slide is a grayscale image of a computer keyboard. A single key, located in the lower right area, is highlighted in a vibrant red color. This red key has the word "Enter" printed on it in a white, sans-serif font. The other keys are in grayscale, creating a strong contrast with the red key. The overall composition is clean and modern, with a focus on the red key as a visual anchor.

Now

Environment characteristics and considerations

About get the right MCU

Develop environment setup

The electronics

Firmware features





Firmware Technical Datasheets

The Electronics


Modules usage comes with advantages:

- ARM 3.3V power is resolved from MSX 5V;
- All support circuitry (reset, crystal, SWD and status led) already up;
- 2.54mm DIP form feed, instead of SMD: Easier to match legacy.

- The EDA (Electronic Design Assitant) used to do the design is KiCad;
- Both Eeschema and Pcbnew.




- 100% of external electronics has the function of protecting the PS/2 Keyboard, ARM module and MSX host;
- Powers down the PS/2 interface when keyboard is not detected while booting-up;
- C2 and C3 (the capacitors in parallel with PS2Clk and PS2Data) absorb switching spikes, minimizing false detections of PS/2 changes;
- The measured consumption with black pill module was 28mA @ 5V;
- Dimension of single layer PCB: 65 x 55mm;
- BlackPill has USB capabilities as 5V tolerant, mitigating damages to connect to 5V data.



The electronics with Blue Pill module

- Blue Pill has the same basic specifications as Black Pill, but does not have USB implemented. This reduced the code size, so I choose a cheaper MCU: stm32f103c6t6 (32K Flash 10K RAM).
- Although BluePill has USB capabilities, there is no sufficient resources (5V tolerant pins) to feasible USB. Even to UART I have to use 3.3V pins (no 5V tolerant ones).



Now

Enviroment characteristics and
considerations

About get the right MCU

Develop enviroment setup

The electronics

Firmware features

Firmware Technical Datasheets

Firmware features

The Database (PS/2 to MSX translation) may be changed at any time: You have only to get a new Database, connect a tty terminal capable to send ASCII files and connect this terminal to the PS/2 to MSX Converter console, through an USB or a serial port. Unplug the keyboard and turn on the Converter.

The Database (an Intel Hex text file) is updated via console, with a help of a tty program (eg TIO) , that will guide you through the steps => A 15 seconds operation..

The Converter controls NumLock as PC does, CapsLock and Scroll Lock leds are sampled from MSX hardware, but Scroll Lock is mapped from Katakana led indicator (or Cyrillic or Korean).

It echoes real time the state of Caps and Kana (or Cyrillic or Korean) to Caps Lock and Scroll Lock, respectively. The user will be empowered to rebuild and upload anytime how this converter will act.

The valid PS/2 events for the Converter are Only make ad break Keys. As auto repeat has no sense for Converter firmware, the PS/2 is initalized as autorepeat 2CPS and 1,0s autorepeat delay.

The MSX puts column (Y_Scan) and the converter answers with line pointed (X_Scan) by Y_Scan. If there are no Y_Scan changes, this Converter will update X_Scan PS/2 Keyboard events related to that Y_Scan.

The background of the slide is a grayscale image of a computer keyboard. A single key, located in the lower right quadrant, is highlighted in a vibrant red color. This red key has the word "Alt" printed on it in a white, sans-serif font. The other keys are in grayscale, creating a strong contrast with the red key. The overall composition is clean and modern, with a focus on the red key as a visual anchor.

Now

Enviroment characteristics and considerations

About get the right MCU

Develop enviroment setup

The electronics

Firmware features

Firmware Technical Datasheets

Firmware Technical Data



The phylosofy used is to to a *Bare metal* programming, it means no use of any Operating System or RTOS.

The used languages are C++ and C, to make all firmware and TIO. The other language used was Excel VBA (to create/manage Database).

Task allocation here is used and implemented as interruptions:

- Hardware: MSX Y-Scan & PS/2 keyboard;
- Software: System timer, working at 30Hz & Timer2, with resolution of 1 μ s.

* The source code, excel Database compiler, schematics, pcb and its gerber files are all availabe at my github <https://github.com/evandrosouza-developer/ps2tomsxUSB>

THANKS

Solution