

# CSCI 200: Foundational Programming Concepts & Design



Exam I Review

# 1. What is the result?



a)  $2 + 3 * 4 - 6$

b)  $5 + 11 / 3$

c)  $11 \% 3 * 4$

d)  $(2 + 1) * 3 - 1$

## 2. Create boolean test conditions



- a) myHeight is greater than 2
- b) y is odd and less than 10
- c) At least one of x or y is 3
- d) t is between 2.1 and 2.3 inclusive

# 3. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 12;

    if( (x >= 2) || (x != 17) )
        cout << x << endl;
    else
        cout << "Have a good day" << endl;

    return 0;
}
```

# 4. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 1;

    if( (x >= 2) || (x != 17) )
        cout << x << endl;
    else
        cout << "Have a good day" << endl;

    return 0;
}
```

# 5. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 17;

    if( (x >= 2) && (x != 17) )
        cout << x << endl;
    else
        cout << "Have a good day" << endl;

    return 0;
}
```

## 6. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 11, y = 5;

    int answer;
    answer = x / y;
    cout << answer << endl;

    return 0;
}
```

# 7. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 9, y = 2;

    cout << x / y << endl;
    cout << (double)x / (double)y << endl;
    cout << (double)x / y << endl;
    cout << x / (double)y << endl;

    return 0;
}
```



# 8. What is the output?



```
#include <iostream>

using namespace std;

int main() {
    int x = 5, y = 10;

    y = x++;
    cout << x << " " << y << endl;

    y = ++x;
    cout << x << " " << y << endl;

    return 0;
}
```

# 9. Find the Errors



```
#include <iostream>

using namespace std

int main() {
    int x = 6;
    double y = 2.5;
    z = 1;
    cin << z;
    if( x = y )
        cout << "x and y match";
    else
        cout << "x and y do not match";

    return 0;
}
```

# 10. Write if/else code



- a) Write a series of if statements (use only if) that will output a student's letter grade based on the input. Assume the input (already received) is called examScore and that the value of examScore is greater than 70 and less than 100.
  
- b) Write an if block (if and else if) that will output a student's letter grade based on the input. Assume the input (already received) is called examScore and that the value of examScore is greater than 70 and less than 100.

# 11. Write Loop code



- a) Write a snippet of code that prints all odd numbers between 0 and X (inclusive), where X is given by the user. Use a while loop.
- b) Write a snippet of code that prints all odd numbers between 0 and X (inclusive), where X is given by the user. Use a for loop.

# 12. Rewrite as a switch



```
if( (rank == 1) || (rank == 2) )
    cout << "Lower division" << endl;
else {
    if( (rank == 3) || (rank == 4) )
        cout << "Upper division" << endl;
    else {
        if( rank == 5 )
            cout << "Graduate student" << endl;
        else
            cout << "Invalid rank" << endl;
    }
}
```

# 13. True or False



- a) The statement “x++” adds one to x.
- b) A semi-colon is needed at the end of a while code block.
- c) Once a constant variable has been created, it cannot be changed.
- d) Boolean variables store the values always true, always false, or sometimes true.

# 14. Rewrite as a for loop



a)

```
int i = 2;
while( i <= 18 ) {
    cout << "*";
    i += 3;
}
```

b) What is the output?

# 15. What is the output?



```
int number = 0;
int sum = 0;
int limit = 20;

while( number > limit ) {
    sum += number;
    number += 2;
}

cout << sum << endl;
```



# 16. What is the output?



```
int number = 100;
int sum = 0;
int limit = 20;

while( number > limit ) {
    sum += number;
    number += 2;
}

cout << sum << endl;
```

# 17. What is the output?



```
int number = 0;
int sum = 0;
int limit = 20;

while( number < limit ) {
    sum += number;
    number += 2;
}

cout << sum << endl;
```

# 18. What is the output?



```
for( int i = 0; i < 4; i++ ) {  
    for( int j = i; j < 6; j++ )  
        cout << "*";  
    cout << endl;  
}
```

# 19. Random Numbers



- Write a program that prints 10 random numbers between 1 and 100. Use an appropriate seed.

# 20. True or False



- a) void functions return a value.
- b) Function prototypes do not require parameter names.

# 21. What is printed?



```
void my_func( int x, int y ) {  
    x = 52;  
    y = 7;  
}  
  
int main() {  
    int x = 0;  
    int y = 0;  
    my_func( x, y );  
    cout << "x = " << x << endl;  
    cout << "y = " << y << endl;  
    return 0;  
}
```

## 22. What is printed?



```
int my_function( double a, double b, double c ) {  
    a = 2 * b;  
    b = 15 + c;  
    c = 3 * a;  
    return (a + b + c);  
}
```

```
int main() {  
    double a = 1;  
    double b = 2;  
    double c = 3;  
    double d = my_function( a, b, c );  
    cout << "d = " << d << endl;  
    return 0;  
}
```

## 23. Which are legal statements?



```
void func_A( int x, int y, int z );
```

```
int func_B( int x, double y );
```

- a) `cout << func_A( 5, 4, 3 ) << endl;`
- b) `cout << func_B( 5, 4.0 ) << endl;`
- c) `func_A( 5, 4 );`
- d) `func_A( 5, 4.7, 3 );`
- e) `int x = func_B( 5, 6 );`
- f) `int y = func_A( 5, 4, 3 );`



# 24. Write Function Prototypes



- a) Write a function prototype with the name “cool\_func” that has no parameters and does not return a value.
- b) Write a function prototype with the name “hot\_func” that has no parameters and returns a double.
- c) Write a function prototype with the name “neutral\_func” that returns an integer and whose parameters in order are an integer named foo, a double named bar, and a character named baz.

# 25. Write a Function



- Write a function that calculates and returns the area of a square for whole numbers.

# 26. Find the errors



```
#include <iostream>

using namespace std;

int main() {
    int 7;
    add_one( x );
    cout >> "7 plus one is " << x << endl;
    return 0;
}

void add_one( int x ) {
    ++x;
}
```

# 27. Memory Time



- With Two's Complement and Floating Point Binary Representation, what does the leading bit correspond to?
- What does this do to the number of integers that can be stored?

# 28. Data Type Modifiers



- What affect to the allowable values of a standard `int` data type do the following modifiers have?
  - `unsigned long long int`
  - `long long int`
- What's the difference between the two?

# 29. Data Type Modifiers



- What is the output of the following code?

```
unsigned short int q = -1;  
cout << "q is: " << q << endl;
```

- a) -1
  - b) 65535
  - c) Compiler Error
  - d) Runtime Error
- 
- Why?

# 30. Building



- When compiling our C++ code into a binary object file, the object file has a larger file size than the C++ file. Why?

# 31. Makefiles



- What advantages to the build process does a Makefile provide?
- Why do we separate out the compile and link steps of our build process?