




QuantumACES.jl: design noise characterisation experiments for quantum computers

Evan T. Hockings ^{1,2}

¹ School of Physics, The University of Sydney, Sydney, NSW 2006, Australia ² ARC Centre of Excellence for Engineered Quantum Systems

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

QuantumACES.jl is a Julia ([Bezanson et al., 2017](#)) package for designing, simulating, and performing scalable Pauli noise characterisation experiments for quantum computers. Noise in quantum devices is the key obstacle to large-scale quantum computation. Consequently, quantum computers will require fault-tolerant architectures that replace physical qubits and operations with redundantly-encoded logical equivalents, which entails regularly measuring the parity checks of quantum error correcting codes ([Aliferis, 2013](#); [Gottesman, 2010](#); [Shor, 1996](#)). Detailed characterisation of the noise in prototype quantum computers can demonstrate correct device performance and identify poorly functioning qubits and operations. It can also enable noise-aware decoding of quantum error correcting codes by calibrating the decoder prior on which physical configurations of errors are more and less likely ([Chen et al., 2022](#); [Higgott et al., 2023](#); [Sundaresan et al., 2023](#); [Tiurev et al., 2023](#); [Tuckett et al., 2020](#)).

QuantumACES.jl uses the framework of averaged circuit eigenvalue sampling (ACES) ([Flammia, 2022](#)) to design experiments that characterise Pauli noise in stabiliser circuits, following the theory and protocol outlined in ([Hockings et al., 2024](#)). Stabiliser circuits are a restricted class of quantum circuits that admit efficient classical simulation ([Aaronson & Gottesman, 2004](#); [Gottesman, 1997](#)), including with Pauli noise. Quantum noise is tailored into Pauli noise by techniques such as Pauli frame randomisation ([Knill, 2005](#)), randomised compiling ([Wallman & Emerson, 2016](#)), or quantum error correction itself ([Beale et al., 2018](#)), and the theory of quantum error correction and fault tolerance generally relies on modelling noise as Pauli noise ([Terhal, 2015](#)).

QuantumACES.jl contains routines for designing optimised designs for noise characterisation experiments, given an arbitrary stabiliser circuit and Pauli noise model, using functions that precisely predict the performance of these experimental designs. It has built-in circuits and noise models and also allows users to define their own. These noise characterisation experiments are simulated with the open-source Python package Stim ([Gidney, 2021](#)), a fast simulator for stabiliser circuits with Pauli noise.

In a typical fault-tolerant quantum computing architecture, the bulk of the physical qubits and gate operations are dedicated to performing the syndrome extraction circuits that measure the parity checks of quantum error correcting codes. These syndrome extraction circuits, which are stabiliser circuits, are therefore the key target for noise characterisation experiments. QuantumACES.jl is tailored to characterising Pauli noise in syndrome extraction circuits, particularly for topological quantum error correcting codes such as the surface code ([Bravyi & Kitaev, 1998](#); [Dennis et al., 2002](#); [Fowler et al., 2012](#); [Kitaev, 2003](#)). It leverages the fact that the simple structures of the syndrome extraction circuits of topological quantum codes remain similar across code sizes, enabling the optimised experimental design for the syndrome extraction circuit of a small-scale code to be transferred to syndrome extraction circuits of larger-scale versions of the same code. QuantumACES.jl is capable of calculating and precisely

44 fitting the performance scaling of these experimental designs as a function of the code size,
45 enabling performance predictions at scales where explicit calculation becomes intractable.

46 Moreover, QuantumACES.jl makes it easy to simulate memory experiments for its syndrome
47 extraction circuits with Stim, and supports decoding these experiments with the open-source
48 Python packages PyMatching (Higgott, 2022; Higgott & Gidney, 2025) and BeliefMatch-
49 ing (Higgott et al., 2023). It also contains an interface with the open-source Python package
50 Qiskit (Javadi-Abhari et al., 2024), enabling the export of experimental designs and circuits to
51 Qiskit circuits which can then be implemented on quantum devices to characterise noise in
52 real quantum hardware.

53 Statement of need

54 The utility of detailed and scalable Pauli noise characterisation methods grows as experimental
55 progress pushes quantum devices towards scales of hundreds of qubits and initial demon-
56 strations of fault tolerance. QuantumACES.jl enables noise characterisation in this context,
57 as demonstrated in (Hockings et al., 2024). While there are several software packages for
58 benchmarking and noise characterisation, there are no open-source packages capable of detailed
59 and scalable Pauli noise characterisation of quantum devices. Forest-Benchmarking (Combes et
60 al., 2019), is an open-source Python package containing many routines for quantum character-
61 isation, verification, and validation (QCVV), but its detailed noise characterisation techniques
62 are not scalable. Gate set tomography (GST) (Nielsen et al., 2021), is a principled and
63 extremely detailed noise characterisation protocol implemented by the open-source Python
64 package pyGSTi (Nielsen et al., 2022), but it is limited to characterising extremely small
65 numbers of qubits. Cycle error reconstruction (CER) (Carignan-Dugas et al., 2023) is the noise
66 characterisation protocol whose capabilities are most similar to ACES, but it is implemented
67 by the commercial software True-Q (Beale et al., 2020).

68 Acknowledgements

69 This work was supported by the Australian Research Council Centre of Excellence for Engineered
70 Quantum Systems (CE170100009), the U.S. Army Research Office (W911NF-21-1-0001,
71 W911NF-23-S-0004), and the Unitary Foundation.

72 References

- 73 Aaronson, S., & Gottesman, D. (2004). Improved simulation of stabilizer circuits. *Physical*
74 *Review A*, 70(5), 052328. <https://doi.org/10.1103/PhysRevA.70.052328>
- 75 Aliferis, P. (2013). Introduction to quantum fault tolerance. In D. A. Lidar & T. A. Brun
76 (Eds.), *Quantum Error Correction* (pp. 126–160). Cambridge University Press. <https://doi.org/10.1017/CBO9781139034807.007>
- 77 Beale, S. J., Boone, K., Carignan-Dugas, A., Chytros, A., Dahlen, D., Dawkins, H., Emerson,
78 J., Ferracin, S., Frey, V., Hincks, I., Hufnagel, D., Iyer, P., Jain, A., Kolbush, J., Ospadov,
79 E., Pino, J. L., Qassim, H., Saunders, J., Skanes-Norman, J., ... Wright, E. (2020). *True-Q*.
80 Zenodo. <https://doi.org/10.5281/zenodo.3945249>
- 81 Beale, S. J., Wallman, J. J., Gutiérrez, M., Brown, K. R., & Laflamme, R. (2018). Coherence
82 in quantum error-correcting codes. *Physical Review Letters*, 121(19), 190501. <https://doi.org/10.1103/PhysRevLett.121.190501>
- 83 Bezanson, J., Edelman, A., Karpinski, S., & Shah, V. B. (2017). Julia: A fresh approach to
84 numerical computing. *SIAM Review*, 59(1), 65–98. <https://doi.org/10.1137/141000671>

- 87 Bravyi, S. B., & Kitaev, A. Y. (1998). Quantum codes on a lattice with boundary. *arXiv*
88 *Preprint*. <https://arxiv.org/abs/quant-ph/9811052>
- 89 Carignan-Dugas, A., Dahlen, D., Hincks, I., Ospadov, E., Beale, S. J., Ferracin, S., Skanes-
90 Norman, J., Emerson, J., & Wallman, J. J. (2023). The error reconstruction and compiled
91 calibration of quantum computing cycles. *arXiv Preprint*. <https://arxiv.org/abs/2303.17714>
- 92 Chen, E. H., Yoder, T. J., Kim, Y., Sundaresan, N., Srinivasan, S., Li, M., Córcoles, A.
93 D., Cross, A. W., & Takita, M. (2022). Calibrated decoders for experimental quantum
94 error correction. *Physical Review Letters*, 128(11), 110504. [https://doi.org/10.1103/](https://doi.org/10.1103/PhysRevLett.128.110504)
95 [PhysRevLett.128.110504](https://doi.org/10.1103/PhysRevLett.128.110504)
- 96 Combes, J., Gulshen, K. V., Harrigan, M. P., Karalekas, P. J., Silva, M. P. da, Alam, M. S.,
97 Brown, A. F., Caldwell, S., Capelluto, L. C., Crooks, G. E., Girshovich, D., Johnson, B.
98 R., Peterson, E. C., Polloreno, A. M., Rubin, N. C., Ryan, C. A., Staley, A. N., Tezak,
99 N. A., & Valery, J. A. (2019). *Forest benchmarking: QCVV using PyQuil*. Zenodo.
100 <https://doi.org/10.5281/zenodo.3455848>
- 101 Dennis, E., Kitaev, A., Landahl, A., & Preskill, J. (2002). Topological quantum memory.
102 *Journal of Mathematical Physics*, 43(9), 4452–4505. <https://doi.org/10.1063/1.1499754>
- 103 Flammia, S. T. (2022). Averaged circuit eigenvalue sampling. *17th Conference on the Theory*
104 *of Quantum Computation, Communication and Cryptography (TQC 2022)*, 232, 4:1–4:10.
105 <https://doi.org/10.4230/LIPIcs.TQC.2022.4>
- 106 Fowler, A. G., Mariantoni, M., Martinis, J. M., & Cleland, A. N. (2012). Surface codes:
107 Towards practical large-scale quantum computation. *Physical Review A*, 86(3), 032324.
108 <https://doi.org/10.1103/PhysRevA.86.032324>
- 109 Gidney, C. (2021). Stim: A fast stabilizer circuit simulator. *Quantum*, 5, 497. <https://doi.org/10.22331/q-2021-07-06-497>
- 111 Gottesman, D. (1997). *Stabilizer codes and quantum error correction* [PhD thesis, California
112 Institute of Technology]. <https://doi.org/10.7907/rzr7-dt72>
- 113 Gottesman, D. (2010). An introduction to quantum error correction and fault-tolerant
114 quantum computation. In S. Lomonaco (Ed.), *Quantum information science and its*
115 *contributions to mathematics* (Vol. 68, pp. 13–58). American Mathematical Society.
116 <https://doi.org/10.1090/psapm/068>
- 117 Higgott, O. (2022). PyMatching: A Python package for decoding quantum codes with
118 minimum-weight perfect matching. *ACM Transactions on Quantum Computing*, 3(3),
119 16:1–16:16. <https://doi.org/10.1145/3505637>
- 120 Higgott, O., Bohdanowicz, T. C., Kubica, A., Flammia, S. T., & Campbell, E. T. (2023).
121 Improved decoding of circuit noise and fragile boundaries of tailored surface codes. *Physical*
122 *Review X*, 13(3), 031007. <https://doi.org/10.1103/PhysRevX.13.031007>
- 123 Higgott, O., & Gidney, C. (2025). Sparse blossom: Correcting a million errors per core
124 second with minimum-weight matching. *Quantum*, 9, 1600. [https://doi.org/10.22331/](https://doi.org/10.22331/q-2025-01-20-1600)
125 [q-2025-01-20-1600](https://doi.org/10.22331/q-2025-01-20-1600)
- 126 Hockings, E. T., Doherty, A. C., & Harper, R. (2024). Scalable noise characterisation of
127 syndrome extraction circuits with averaged circuit eigenvalue sampling. *arXiv Preprint*.
128 <https://arxiv.org/abs/2404.06545>
- 129 Javadi-Abhari, A., Treinish, M., Krsulich, K., Wood, C. J., Lishman, J., Gacon, J., Martiel, S.,
130 Nation, P. D., Bishop, L. S., Cross, A. W., Johnson, B. R., & Gambetta, J. M. (2024).
131 Quantum computing with Qiskit. *arXiv Preprint*. <https://arxiv.org/abs/2405.08810>
- 132 Kitaev, A. Y. (2003). Fault-tolerant quantum computation by anyons. *Annals of Physics*,
133 303(1), 2–30. [https://doi.org/10.1016/S0003-4916\(02\)00018-0](https://doi.org/10.1016/S0003-4916(02)00018-0)

- 134 Knill, E. (2005). Quantum computing with realistically noisy devices. *Nature*, 434(7029),
135 39–44. <https://doi.org/10.1038/nature03350>
- 136 Nielsen, E., Gamble, J. K., Rudinger, K., Scholten, T., Young, K., & Blume-Kohout, R. (2021).
137 Gate set tomography. *Quantum*, 5, 557. <https://doi.org/10.22331/q-2021-10-05-557>
- 138 Nielsen, E., Seritan, S., Proctor, T., Rudinger, K., Young, K., Russo, A., Blume-Kohout, R.,
139 Kelly, R. P., Gamble, J. K., & Saldyt, L. (2022). *pyGSTi*. Zenodo. <https://doi.org/10.5281/zenodo.594712>
140
- 141 Shor, P. W. (1996). Fault-tolerant quantum computation. *Proceedings of 37th Conference on*
142 *Foundations of Computer Science*, 56–65. <https://doi.org/10.1109/SFCS.1996.548464>
- 143 Sundaresan, N., Yoder, T. J., Kim, Y., Li, M., Chen, E. H., Harper, G., Thorbeck, T., Cross, A.
144 W., Córcoles, A. D., & Takita, M. (2023). Demonstrating multi-round subsystem quantum
145 error correction using matching and maximum likelihood decoders. *Nature Communications*,
146 14(1), 2852. <https://doi.org/10.1038/s41467-023-38247-5>
- 147 Terhal, B. M. (2015). Quantum error correction for quantum memories. *Reviews of Modern*
148 *Physics*, 87(2), 307–346. <https://doi.org/10.1103/RevModPhys.87.307>
- 149 Tiurev, K., Derks, P.-J. H. S., Roffe, J., Eisert, J., & Reiner, J.-M. (2023). Correcting
150 non-independent and non-identically distributed errors with surface codes. *Quantum*, 7,
151 1123. <https://doi.org/10.22331/q-2023-09-26-1123>
- 152 Tuckett, D. K., Bartlett, S. D., Flammia, S. T., & Brown, B. J. (2020). Fault-tolerant
153 thresholds for the surface code in excess of 5% under biased noise. *Physical Review Letters*,
154 124(13), 130501. <https://doi.org/10.1103/PhysRevLett.124.130501>
- 155 Wallman, J. J., & Emerson, J. (2016). Noise tailoring for scalable quantum computation
156 via randomized compiling. *Physical Review A*, 94(5), 052325. <https://doi.org/10.1103/PhysRevA.94.052325>
157