BridgeFinder
Finding Research Collaborators Across Communities at UIUC

Evan Lin Eric Liu
University of Illinois Urbana-Champaign

CS 470 Mid-Semester Report, October 2026

Abstract

Students who want research experience often know an instructor but few researchers outside that instructor's circle. BridgeFinder helps them find related researchers and see who might connect them. We have built a three-screen prototype, analyzed UIUC publications from 2015 to 2024, and gathered feedback from four students. Our historical test finds that BridgeFinder predicts more later collaborations than topic-only ranking but fewer than triadic closure. We therefore plan to test whether students find its suggestions relevant, unfamiliar, and useful for contacting someone.

1 Objective

A student who enjoyed a computing class might want to apply those skills in biology or agriculture. UIUC lists 2,574 professor-titled faculty across 110 departments [14], far too many to browse. Searching for papers can reveal relevant names, but it does not tell the student whom they could approach or how to start a conversation.

BridgeFinder helps UIUC undergraduate and early-stage graduate students explore research beyond their existing contacts. A student chooses a familiar researcher, sees suggestions outside that person's collaboration group, and opens a card with topics, papers, and a possible introduction route. The starting researcher's work stands in for the student's interests, so the student needs no publications of their own.

The problem is hard because relevance, novelty, and reachability pull in different directions. People who share a co-author with a familiar researcher are easy to find and easy to reach, but they belong to the circle the student already knows. People farther away are new, yet few of them work on related topics, and the student has no publications that could describe their interests. BridgeFinder must find the few distant researchers who are relevant and still reachable through people a student could ask.

So far we contribute a working three-view prototype, a historical test on 49,651 UIUC papers that shows where new cross-group collaborations form, and a first round of student feedback with the design changes it produced. A student study will test whether the suggestions help students choose someone to contact.

2 Related Work

Researcher search. Illinois Experts [15] collects institutional profiles and publications, helping students check expertise. A profile helps assess a known researcher, while our task asks whom else to approach from a familiar person's network. Google Scholar [11] supports following topics through papers and author profiles. Those records still leave the student to work out a possible route of contact. BridgeFinder combines the research match with that route.

Referral chains. ReferralWeb [6] built a social network from names that appear together in Web documents, including co-authored papers, and let users search for experts together with the chain of people linking them. Showing the chain turns a list of experts into a way to reach one. Searches start from the user's own name, so the user must already appear in the network, and results stay close to them. BridgeFinder starts from a familiar researcher because students rarely appear in the graph, and it deliberately skips anyone within two hops.

Literature maps. Connected Papers [12] gives a visual overview of related papers, useful when entering an unfamiliar area. Its map describes relationships between papers. ResearchRabbit [13] supports continued exploration from paper collections, but our contact task requires a route between people. We adapt visual exploration to researchers and possible introductions.

Link prediction. Liben-Nowell and Kleinberg [7] compare ways to predict future links from network structure. Shared-contact counts provide a simple, explainable baseline, but favor people already nearby. We compare with this triadic-closure baseline to test whether our suggestions beyond shared contacts offer useful alternatives.

Cross-domain recommendation. Tang et al. [10] learn topics associated with cross-field collaboration and rank authors using random walks through author and topic nodes. This can capture complementary expertise, but relies on publication histories to represent authors. BridgeFinder serves students without papers by using a familiar researcher's topics as their interest proxy. It

uses a fixed topic-and-path score and shows a possible introduction route. Our score does not learn relationships between topics across fields.

Network theory. Granovetter [5] explains how weak ties can carry information beyond close circles. Burt [3] explains the advantage of connecting separate groups. These ideas motivate looking beyond familiar collaborators. Neither establishes that an observed co-authorship route will lead to a useful introduction for a student.

3 Course Concepts and Network Analysis

3.1 Graph and communities

Brokerage involves connecting people across groups that have few ties to one another. We use this course concept to suggest researchers outside a familiar person's collaboration group. Nodes are UIUC authors from OpenAlex [9] papers. An edge joins two authors who wrote together, weighted by their number of joint papers.

On October 28, 2026 (UTC), we exhausted all 515 pages of the OpenAlex query for UIUC institution `I157725225` and publication years 2015–2024. Of 102,947 works, we retained 49,651 with at least two distinct authors whose authorship records on that paper listed UIUC. We omit external authors. Table 1 describes the 2015–2019 training graph.

Table 1. Training co-authorship graph from 2015–2019 papers.

Measure	Dataset
Authors	19,389
Edges	78,281
Communities	842
Modularity	0.884
Modularity in largest component	0.879

We use Louvain [2] to find communities with many collaborations inside each group. It seeks high *modularity*, meaning more within-group edge weight than expected from node strengths. Girvan–Newman [4] recomputes edge betweenness after every edge it removes, which is impractical for 78,281 edges, while Louvain partitions this graph in a few seconds.

Disconnected pieces can inflate modularity, but within the largest component, which holds 87% of authors, the same partition still scores 0.879. Collaboration therefore forms dense groups joined by few ties, the separation that brokers span. Communities are numbered groups, not verified departments.

3.2 Choosing suggestions

Following the proposal, candidates must be in another community and at least three hops from the starting researcher. One hop is one co-authorship edge. This excludes existing collaborators and people who already share a co-author. Triadic closure, the alternative covered in class, would suggest exactly those shared-contact people. It predicts ties well but keeps the student inside the familiar circle, so we use it as a baseline instead. Candidates must also be reachable so we can show a route.

The ranking combines topic overlap with a bonus for introduction paths, as shown below.

$$\mathrm{Score}(u, v) = S(u, v) + 0.5\frac{c_3(u, v)}{1 + c_3(u, v)}. \tag{1}$$

S is the number of shared topics divided by the number of distinct topics across both researchers, or zero if either topic set is empty. Each researcher has up to ten topics from their 2015–2019 papers. c_3 counts paths $u \to a \to b \to v$ with all four people distinct. Path counts and shortest routes ignore edge weights. The bonus stays below 0.5, and its saturation gives half of it to the first path because one route is enough to ask for an introduction. More distant candidates remain eligible without that bonus. The coefficient and saturation are fixed choices, not learned probabilities.

On real data the path bonus dominates. All 500 suggestions in the demo are exactly three hops away, and the bonus supplies 68% of their score, so the ranking favors people reachable through many short routes over the closest topic match. These routes pass through brokers. Their intermediaries have a median Burt constraint [3] of 0.12, against 0.47 for the median author in the largest component, so their collaborators rarely work with one another.

Without the network, the app would lose its group boundary, distance rule, and introduction routes and become a topic search tool. The resulting suggestions extend beyond shared contacts, although the graph does not tell us whether an introduction would be welcome.

4 Design and Implementation

The prototype takes the student through three views.

1. Researchers. The student searches 50 starting researchers by name or topic. The proposal let students pick several instructors, but one starting researcher keeps each route readable. We chose highly connected authors across large communities so every choice has ten valid suggestions. The landing page explains the steps and defines a researcher card. As in profile search [15], it provides an entry point without requiring a student profile.

2. Network. A map shows the selected researcher, suggestions, and intermediaries, colored by community (Figure 1). Solid lines show observed co-authorships. Orange dashed lines show suggested connections. This borrows visual exploration from literature maps [12, 13] while focusing on people. The proposal planned a campus-wide community map, but students found the full graph hard




Figure 1. Network view for Naiman A. Khan (large blue node). Dashed lines lead to the ten suggestions. Solid lines are observed co-authorships, including the intermediaries on each route. Colors mark communities.

to follow (Section 5), so the map now shows only this neighborhood.

3. Suggestions. Selecting a name or dashed line opens a card with an observed shortest route, topics, and example papers. We put the route first to show whom a student might approach. An optional explanation shows the ranking score. Students can edit, copy, or download an outreach draft. The app does not send email. Figure 2 shows the route at the top of a card.

Because the path bonus dominates the score, a suggestion can have little topic overlap. The topics and papers below the route let students judge relevance themselves, and the study's relevance ratings will show whether the bonus should be reduced.

The app, historical test, and study cards share one ranking implementation. Recommendations are computed in Python and displayed in D3. The core flow works on desktop and mobile, including keyboard navigation, and has been browser-tested for all 50 starting researchers.

5 Users and Feedback

Our target users want research opportunities but have few contacts beyond their classes or department. We gathered feedback from four students in individual sessions. The two graduate students were a Computer Science student and a Master of Computer Science student researching computational biology. One undergraduate studied Electrical and Computer Engineering, and the other studied Food Systems.

We gave students minimal context and asked them to work through the app. They gave feedback as they encountered problems. The undergraduates match our student entry point, while the graduate students add perspectives from computational research and its applications. The proposal aimed for about ten testers per round. Four sessions were enough to surface the problems below before a broader study [8], but not to estimate usability across campus. We made four changes in response.

Getting started. One student trying to find a relevant professor did not understand that they first needed to select a researcher to enter the graph. We added instructions on the landing page explaining that students should choose a starting researcher, explore a suggestion, and then review its route. The page now explains that the starting person's publications guide the suggestions.

Understanding the interface. Students found the interface unintuitive, prompting an overhaul with simpler layouts and clearly named views. They were also unsure what a card meant. The landing page now defines a researcher card as a profile with topics, example papers, and a possible introduction route. The map legend distinguishes observed collaborations from suggestions.

Readable map. The graph showed too many nodes and was difficult to follow. We narrowed the display to the selected researcher, suggestions, and people along their routes. Community colors help distinguish groups without showing the entire campus graph.

Correct labels. Some tags in the original design did not match the researchers shown. We corrected the profile labeling and distinguish inferred research areas from collaboration groups. These labels do not claim verified departmental appointments.

We have not yet retested these changes with students. The study in Section 6.2 will show whether they help.

6 Evaluation

6.1 Historical prediction

We used 2015–2019 papers to build the graph, communities, and topic profiles, then checked for new cross-community co-authorships in 2020–2024. Community labels stay fixed from training. We evaluated 3,492 starting researchers with at least one new cross-community tie to another training-graph author. That tie could be two hops away, more distant, or disconnected in training. Researchers without such future ties are excluded.

All methods rank training-graph authors in another community and exclude existing collaborators. **Topic-Only** uses BridgeFinder's reachable candidate pool at distance three or more. **Triadic closure** ranks two-hop candidates by their number of shared co-authors, without additional weighting. Those scores would be zero in our more distant pool. All methods predict the same future ties, comparing discovery strategies with different candidate pools.




Figure 2. Detail of Victoria J. Vieira-Potter's researcher card. The route connects Naiman A. Khan through Ruopeng An and Kelly Scott Swanson to the suggested researcher. Topics and papers appear below this detail. The route is observed in publications, not a confirmed introduction.

Precision at ten, or **P@10**, measures how many of each researcher's first ten suggestions became collaborators in the later period. We divide hits by ten even when fewer suggestions are available, then average across starting researchers. This matches the proposal's test of whether a shortlist includes people who later worked together.

Table 2. Prediction of new 2020–2024 cross-community ties. Higher is better.

Method	P@10
Topic-Only	0.0079
Triadic closure	0.0287
BridgeFinder	0.0131

Table 2 shows that BridgeFinder predicts more later ties than Topic-Only (0.0131 vs 0.0079), but fewer than Triadic closure (0.0287). It therefore does not meet the proposal's goal of outperforming both baselines. The data still support looking past shared contacts. Of 8,916 new cross-community ties, only 22% joined authors who already shared a co-author, while 67% joined authors three or more hops apart, inside BridgeFinder's candidate pool. These comparisons do not isolate distance from scoring. The student study will test whether the suggestions are useful for discovery despite lower historical prediction than triadic closure.

6.2 Planned student study

We will recruit 15 students, aiming for three each from CS, ECE, Bioengineering, Crop Sciences, and Information Sciences. This adds backgrounds beyond those in our first feedback round, but the study remains exploratory.

Each student will first state a research interest, then choose a starting researcher, open a suggestion and outreach draft, and explain the route and dashed line without coaching. A facilitator will record task completion and whether the student identifies the intermediaries and distinguishes suggestions from existing ties.

For the card comparison, students will choose the closest match to their interest from five starting researchers and rate up to 15 shuffled cards, five per method. Method labels are hidden. Shared candidates appear once and count for each selecting method. All cards use the same fields and shortest-path procedure. Closure cards show two-hop routes, while BridgeFinder and Topic-Only show routes of three or more hops. Unreachable candidates are excluded. We will collect the following measures.

- **Relevant discovery.** Students will rate relevance to their stated interest and novelty to themselves on scales from 1 to 7. Higher ratings mean a better research match or a less familiar suggestion. For BridgeFinder, we target means of at least 5 and a 25-percentage-point gain over triadic closure in cards rated at least 5 on both. Topic-Only is a second comparison.
- **Willingness to contact.** Students will rate how realistic contact feels given the route on a scale from 1 to 7. This checks whether they see a practical next step. For BridgeFinder, we target a mean of at least 5 and improvement over Topic-Only. Topic-Only draws on the same candidates without the path bonus, so this comparison asks whether favoring well-connected candidates makes contact feel more realistic. Triadic closure suggests people who share a co-author, so we report it for reference without a target.
- **Usability.** At least 12 of 15 students should complete the task and explain the line types correctly without help. The ten-item System Usability Scale will assess ease of using the interactive app. We target a mean of 80/100, above typical scores in published SUS norms [1].

We will compare methods using participant averages, not treat individual cards as independent responses. The rating and analysis tools are implemented. We have not yet run the study.

7 Limitations and Next Steps

Co-authorship cannot confirm an introduction or mentoring availability. Our dataset omits external and informal ties, and OpenAlex does not capture every publication. The demo offers 50 starting researchers, and the card study offers five, so some students may not find a suitable starting point. A researcher's topics may also be a poor proxy for a student's interests.

Two thirds of new cross-group collaborations joined people three or more hops apart, so looking past shared contacts targets where most of them form. Triadic closure still predicts better, and BridgeFinder's score leans on network position more than topic match. In November, the student study will test whether its suggestions are relevant, new, and worth acting on. Any ranking changes, such as a smaller path bonus, will use separate validation data.

Contributions and AI Use

Evan Lin worked on data collection, prediction tests, and the map. Eric Liu worked on scoring, citation analysis, study tools, and formative sessions. Both contributed to the report. Claude assisted with early development and drafting. OpenAI Codex assisted with checks, tests, and revision.

References

[1] A. Bangor, P. T. Kortum, and J. T. Miller. An empirical evaluation of the System Usability Scale. *International Journal of Human–Computer Interaction*, 24(6):574–594, 2008.

[2] V. D. Blondel, J.-L. Guillaume, R. Lambiotte, and E. Lefebvre. Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10):P10008, 2008.

[3] R. S. Burt. *Structural Holes: The Social Structure of Competition*. Harvard University Press, Cambridge, MA, 1992.

[4] M. Girvan and M. E. J. Newman. Community structure in social and biological networks. *Proceedings of the National Academy of Sciences*, 99(12):7821–7826, 2002.

[5] M. S. Granovetter. The strength of weak ties. *American Journal of Sociology*, 78(6):1360–1380, 1973.

[6] H. Kautz, B. Selman, and M. Shah. Referral Web: Combining social networks and collaborative filtering. *Communications of the ACM*, 40(3):63–65, 1997.

[7] D. Liben-Nowell and J. Kleinberg. The link-prediction problem for social networks. *Journal of the American Society for Information Science and Technology*, 58(7):1019–1031, 2007.

[8] J. Nielsen. *Usability Engineering*. Morgan Kaufmann, San Francisco, CA, 1993.

[9] J. Priem, H. Piwowar, and R. Orr. OpenAlex: A fully-open index of scholarly works, authors, venues, institutions, and concepts. *arXiv preprint arXiv:2205.01833*, 2022.

[10] J. Tang, S. Wu, J. Sun, and H. Su. Cross-domain collaboration recommendation. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '12)*, pages 1285–1293, 2012.

[11] Google. Google Scholar: About. n.d. `https://scholar.google.com/intl/en/scholar/about.html`.

[12] Connected Papers. Connected Papers: Explore connected papers in a visual graph. n.d. `https://www.connectedpapers.com/`.

[13] ResearchRabbit. ResearchRabbit: Literature discovery. n.d. `https://www.researchrabbit.ai/`.

[14] University of Illinois Board of Trustees. Academic and administrative appointments (Gray Book), February 2024. `https://bot.uillinois.edu/resources/gray_book/`.

[15] University of Illinois. Illinois Experts: Research and scholarship at UIUC. n.d. `https://experts.illinois.edu/`.