BridgeFinder: Discovering Cross-Community Research Collaborators at UIUC

Evan Lin Eric Liu
University of Illinois Urbana-Champaign

CS 470 Mid-Semester Report, October 2026

Abstract

Students seeking research mentors often know an instructor but lack a route into another research community. BridgeFinder uses a weighted UIUC co-authorship graph to recommend researchers outside a seed instructor's community and explain possible introductions. The challenge is balancing topical relevance with network diversity while avoiding claims that a missing co-authorship proves a social gap. We have built an OpenAlex ingestion pipeline, two real-data corpora, a three-screen web prototype, temporal backtests, a citation analysis, and a formative study with five students. The archived scaled backtest gives Full BridgeFinder P@5 of 0.0364 versus 0.0283 for Adamic–Adar, but misses our proposed improvement thresholds. A citation comparison finds a mean ratio of 1.053 ($p = 0.0601$), providing no significant evidence of a cross-community advantage. Feedback led to a faculty-seed entry point, an explicit missing-tie legend, and prominent introduction paths. We distinguish the implemented demonstration from the offline model and specify the remaining work before a comparative user study.

1 Problem, objective, and contribution

A student who enjoyed a computing course may want to apply those skills in biology or agriculture but know neither whom to approach nor who could introduce them. Keyword search supplies names; an existing co-author network supplies routes, but tends to keep exploration close to familiar groups. Our objective is to help UIUC undergraduate and early-stage graduate students find a relevant researcher outside a familiar instructor's collaboration community and understand a plausible next step toward contact.

The problem is challenging for three reasons. Students may have no publications from which to build a personal profile. Topical similarity alone can return familiar researchers, while network distance alone can return irrelevant ones. Finally, published co-authorship is an incomplete proxy for acquaintance, trust, and willingness to mentor. BridgeFinder therefore combines topical overlap with community boundaries and brokerage features, while treating paths as suggestions to verify rather than guaranteed introductions.

Our contributions at midterm are (1) a weighted graph pipeline with a temporally separated evaluation on two UIUC datasets; (2) a working seed–map–recommendation interface; (3) qualitative feedback linked to concrete design changes; and (4) preliminary results and a comparative evaluation plan. These establish feasibility, not improved mentoring outcomes or causal effects of brokerage.

2 Related work and design implications

Structural holes and weak ties. Granovetter explains how weak ties connect otherwise separated social circles [6]; Burt relates brokerage to access to nonredundant information and ideas [2, 3]. These theories motivate exploration beyond a student's immediate group. Their strength is explaining why diverse contacts can matter; their limitation here is that co-authorship data does not measure tie strength or prove that a suggested edge creates useful brokerage. We operationalize community boundaries as a testable proxy rather than claiming a direct measurement of social opportunity.

Academic discovery tools. Illinois Experts [11] and Google Scholar provide useful profile and publication search. Connected Papers and ResearchRabbit support visual literature exploration through relationships among papers. Their strength is fast discovery of expertise or related literature; their limitation for our task is that their central workflow does not explain a student-to-faculty introduction chain. BridgeFinder adapts visual graph exploration to people and makes an intermediate contact explicit. We do not claim that these systems lack all relational features.

Collaboration prediction. Liben-Nowell and Kleinberg [7] show how local network measures predict future links. Adamic–Adar rewards shared neighbors and is an interpretable, inexpensive baseline, but can favor familiar neighborhoods. Tang et al. [10] address cross-domain collaboration recommendation, demonstrating that topical and relational evidence can be combined. Its strength is making cross-domain matching explicit; its task and model do not directly establish whether a student can act on a displayed introduction. We compare against topic-only and local-topology models, and evaluate actionability

separately.

Organizational context. Dahlander and McFarland [4] study tie formation and persistence in a research organization. The longitudinal evidence motivates treating institutional context and intellectual similarity as important. Its limitation for our design is that an observational explanation is not itself an interactive discovery workflow. Our interface exposes candidate explanations; the evaluation must still test whether students find them useful.

3 Course concepts and network analysis

3.1 Graph construction and temporal scope

We use OpenAlex [9] works dated 2015–2024 associated with UIUC's ROR identifier `047426m28`. Nodes are author identifiers with UIUC affiliation on harvested works. Each retained paper contains at least two UIUC-affiliated authors; external collaborators are omitted. The 5,000-work harvest yields 2,493 such papers and 5,396 author records; the 25,000-work harvest yields 13,229 papers and 16,604 author records. These capped harvests are samples, not a campus census.

For retained UIUC authors A_p on paper p, the undirected edge weight is

$$w_{ij} = \sum_{p:\, i,j \in A_p} \frac{1}{|A_p| - 1}.$$

Fractional weighting limits the contribution of each large team without discarding it. The backtest includes large teams (up to 70 and 92 retained authors in the two corpora); the separate citation script filters to at most 25 retained authors. Thus the two analyses do not use identical graph construction. Training uses 2015–2019 papers, evaluation uses 2020–2024 papers, and backtest topics are each author's ten most frequent training-paper topics. Authors with no training edges are outside the prediction population.

3.2 Communities, brokerage, and routing

We use weighted Louvain modularity optimization [1] to identify collaboration communities, rather than assuming that departments are communities. Modularity compares within-group edge weight with a strength-preserving null model:

$$Q = \frac{1}{2W} \sum_{ij} \left(w_{ij} - \frac{s_i s_j}{2W} \right) \mathbf{1}[c_i = c_j].$$

Here $s_i = \sum_j w_{ij}$ and $W = \sum_{i<j} w_{ij}$. Girvan–Newman [5], an alternative covered in community discovery, repeatedly removes high-betweenness edges and offers an interpretable hierarchy, but repeated shortest-path computations are expensive. Louvain is a practical choice for repeated analysis of thousands of authors; its resolution limit and stochastic partitions remain limitations. We do not treat its output as verified disciplinary labels.

The pilot training graph contains 3,642 nodes and 16,408 edges; the scaled graph contains 9,042 nodes and 36,748 edges. The backtest partitions the union of all nontrivial connected components, not just the largest component. A validation run found 346 pilot communities with $Q \approx 0.950$. This high modularity indicates strong separation of observed collaboration groups, but disconnected components can inflate it. It does not establish that all groups are socially isolated or that crossing them is useful. The graph structure motivates both cross-community filtering and an explicit distinction between reachable and unreachable candidates.

For candidate v, Burt autonomy is $H(v) = \max(0, 1 - C_v)$, with

$$C_v = \sum_{j \in N(v)} \left(p_{vj} + \sum_{q \in N(v)} p_{vq} p_{qj} \right)^2, \quad p_{ij} = \frac{w_{ij}}{\sum_k w_{ik}}.$$

The implementation assigns $H = 0$ to degree-zero/one nodes. This feature measures the candidate's existing neighborhood, not the marginal benefit of a new edge. Boundary spanning toward seed u is $B(v, u) = |N(v) \cap C(u)|/|N(v)|$, where $C(u)$ now denotes the set of nodes in u's community.

Candidates are non-neighbors in another community. A distance-two candidate has a shared co-author who could be asked about an introduction. Distance three implies two intermediaries; no discovered short path calls for cold outreach. The student-to-seed anchor is user supplied and is not an observed graph edge. These ideas connect structural holes, triadic closure, community discovery, and small-world navigation from the course. Our computation is centralized graph analysis, not an implementation of decentralized local search, and graph distance does not measure sociological tie strength.

3.3 Offline score and ablation

Let S be Jaccard overlap of training-topic sets. The backtest ranks candidates by

$$\Phi(u, v) = 0.60S + 0.12H + 0.12B + 0.16P. \qquad (1)$$

$P = 1$ for two-hop candidates, 0.5 for candidates with a simple three-edge path and no two-hop connection, and 0.1 otherwise. The final case includes longer paths and disconnected components; it is not a reachability probability. These fixed heuristic weights prioritize relevance. A Topic+Path ablation uses $S + 0.5c_3/(1 + c_3)$, where c_3 is the number of simple three-edge paths. Comparing the ablation with the full model tests whether autonomy and boundary spanning add value beyond topic and route information.




Figure 1: Implemented interaction flow. This schematic describes controls and navigation, not a screenshot or measured researcher profile. Dashed links illustrate missing co-authorships; they are not validated opportunities.

4 Design and implementation

4.1 A demonstrable core flow

The implementation separates expensive graph preparation from browser interaction. `fetch_openalex.py` produces processed datasets; `backtest.py` and `citation_impact.py` evaluate them; `web/prepare_web_data.py` exports precomputed recommendations. A static HTTP server serves `web/index.html` and `data.json`; D3 v7 renders the graph. No account or publication history is required from the student.

Figure 1 connects the student problem to implemented controls. First, selecting a familiar instructor addresses the publication cold start; the generator chooses up to 50 high-degree seeds with coverage of the eight largest communities. These are automatically selected author records, not a manually verified faculty directory. Second, the map makes the community context visible, adapting literature graph exploration to people. It samples leaders from the eight largest communities and draws missing links between community leaders. Such dashed links are illustrative and are not filtered by topic overlap. Clicking an eligible node changes the seed; dashed-link filtering of recommendations is not implemented. Third, cards put the introduction before topic details and show autonomy as a positive gauge, translating an opaque structural measure into an explanation. An outreach modal supplies a template, but does not send messages.

4.2 Scope and fidelity of the prototype

The web generator currently uses all years and stored author topics, with a different demonstration score:

$$\Phi_{\text{web}} = 0.35S + 0.25H + 0.25B + 0.15P_{\text{web}},$$

where $P_{\text{web}} = 0.5$ for two-hop candidates and 0.1 otherwise. Consequently, offline improvements for Eq. 1 cannot be attributed to the displayed ranking. Aligning these implementations is required before a study comparing that model's interface.

A shared co-author is data-backed for two-hop cards. Other cards insert a generic institutional liaison and label the route "3-Hop" without computing a three-hop path or verifying an appointment. That label must not be interpreted as an observed introduction. Community colors and department names are heuristic labels, with community indices mapped modulo eight; author titles and affiliations also need verification. These are substantive prototype limitations, not evidence of actual mentoring access. Before participant deployment, we will replace unsupported routes with an explicit "no verified route" state, verify seed identities, and unify the score. The core navigation can be demonstrated now; the social assertions require this additional work.

5 Users and formative feedback

5.1 Population and sampling rationale

Our primary users are UIUC undergraduate and early-stage graduate students seeking research outside their current department. They are a better initial test population than established faculty because cold start and unfamiliar contact routes are central to the problem. Recruitment through ACM student groups, course peers, and interdisciplinary student channels is feasible but introduces convenience-sampling bias.

The authors report five completed individual, 30-minute think-aloud sessions: three CS/CE undergraduate juniors/seniors and two graduate students from Bioengineering and Information Sciences. This mix includes both computing students seeking applications and students in potential destination disciplines. Five sessions are useful for finding formative interaction problems [8]; they are not sufficient to estimate population usability or compare recommendation quality statistically. We do not infer a fixed percentage of problems discovered from the sample size.

5.2 Feedback-to-design trace

The following are author-reported qualitative observations; no participant quotes, issue frequencies, or quantitative usability scores are claimed.

Entry point. Students without publications could not use themselves as a seed. The interface now starts with a searchable faculty grid and department-style filters, enabling an instructor to serve as the anchor. A subsequent test should measure whether students can identify a familiar, correctly labeled seed without help.

Meaning of dashed links. Participants interpreted dashed lines as weak existing collaborations. The map now explicitly distinguishes observed co-authorship from a missing-tie structural-hole example. The next round should ask participants to explain the legend in their own

Table 1: Archived backtest outputs in `prototype/results/`. These are saved-run results, not deterministic guarantees.

	Pilot		Scaled	
Model	P@5	NDCG@10	P@5	NDCG@10
Preferential attach.	.0011	.0011	.0081	.0125
Betweenness	.0022	.0192	.0076	.0109
Topic-Only	.0076	.0342	.0201	.0406
Adamic–Adar	.0076	.0279	.0283	.0459
Topic+Path	.0216	.0697	.0333	.0630
Full BridgeFinder	.0195	.0671	.0364	.0705

words; successful navigation alone would not demonstrate comprehension.

Action before explanation. Participants looked for who could introduce them before reading topic details, and a low constraint value appeared to mean a poor candidate. The revised cards place the introduction first and express constraint through an autonomy gauge. The next round should test route comprehension and whether the gauge is mistaken for a success probability.

These changes are visible in the current interface, but they do not demonstrate that the reported problems have been resolved. Anonymized session notes and a repeat walk-through would strengthen the audit trail; the repository currently contains neither session-level notes nor completed comparative-study responses.

6 Evaluation: evidence and measurement plan

6.1 Temporal prediction on real data

The backtest predicts new 2020–2024 cross-community co-authorships using only 2015–2019 edges and topic profiles. Seeds must have at least one such future tie with an eligible training node. All methods rank the same non-neighbor, cross-community candidates across retained components. Conditioning on future-positive seeds excludes inactive researchers and makes these results more favorable than an all-student deployment population.

Baselines isolate alternative explanations: preferential attachment tests popularity; sampled global betweenness tests centrality alone; Topic-Only tests topical matching; Adamic–Adar tests common-neighbor evidence. Topic+Path is the simpler ablation. Metrics are macro-averaged over eligible seeds. P@k is the fraction of the top k candidates who become collaborators, reflecting shortlist efficiency. R@10 is the fraction of a seed's eligible future collaborators retrieved, measuring coverage. Binary-relevance NDCG@10 discounts hits by $1/\log_2(r+1)$ and normalizes against the ideal ranking, measuring whether useful names appear early.

Table 1 suggests useful signal beyond common neighbors. On the scaled corpus, Full BridgeFinder improves P@5 by 1.29× and NDCG@10 by 0.0246 over Adamic–Adar. Against our proposed success criteria of 2× P@5 and +0.05 NDCG@10, both scaled targets are missed. On the pilot, the P@5 target is met (2.57×) but the NDCG gain is only 0.0392. These thresholds are project targets, not a documented preregistration. Topic+Path wins on the pilot while the full model wins on the scaled corpus; this is mixed evidence for the extra structural features, not proof that network density causes the difference. Absolute precision remains low: most suggested researchers do not become observed co-authors.

Reproducibility and uncertainty. Louvain sets seed 42, but sampled betweenness has no fixed seed and score ties inherit set iteration order. Exact rankings and metrics can vary across processes or dependency versions. The archived files omit participant/seed-level uncertainty and run metadata. Current validation uses Python 3.12, NetworkX 3.7, and SciPy 1.18.1. A fresh run with `PYTHONHASHSEED=0` evaluated 185 pilot and 1,386 scaled seeds. Full-model P@5/NDCG@10 were 0.0205/0.0678 (pilot) and 0.0365/0.0713 (scaled), versus Adamic–Adar 0.0065/0.0317 and 0.0294/0.0467. This preserves the qualitative comparison but confirms that archived numbers are not exact reproduction targets. Before tuning weights, fix tie-breaking and random seeds, retain per-seed metrics, use a separate validation interval, and report paired bootstrap intervals over seeds. Overlapping collaboration neighborhoods limit the independence assumption even then.

6.2 Citation impact: a separate observational test

The citation script builds a pre-2020 graph after excluding papers with more than 25 retained UIUC authors. A later paper is cross-community when its known training authors span at least two communities, within-community when exactly one is represented, and unclassified when none is represented. Authors absent from training do not determine its category, so partially observed teams may be misclassified.

The scaled analysis includes 6,231 evaluation papers: 1,071 cross-community, 4,183 within-community, and 977 unclassified. Cross-community mean citations are 64.86 (SD 241.34), versus 61.60 (SD 119.92); medians are 36 and 37. The mean ratio is 1.053, with two-sided Mann–Whitney $U = 2{,}156{,}737$ and $p = 0.0601$. Our success target is a ratio above 1.10 and $p < 0.05$ against within-community papers. Neither criterion is met. Mann–Whitney tests a distributional difference, not specifically a difference in means. Year, field, team size, and repeated authors are uncontrolled, so these results establish neither a causal benefit nor absence of all benefit from brokerage.

6.3 Planned comparative user evaluation

We plan an exploratory within-subject study with 15 students, recruiting three from each of CS, ECE, Bioengineering, Crop Sciences, and Information Sciences. This

deliberately broadens the computing-heavy formative sample and tests cross-field comprehension, although it is not representative of all UIUC students. Obtain consent, use pseudonymous identifiers, and allow withdrawal. Participants should first attempt the seed–map–card task, then rate five candidates per method (BridgeFinder, Adamic–Adar, Topic-Only) for a matched seed. Shuffle method-hidden cards, handle repeated candidates consistently, and counterbalance order. The goal is method blinding, not an unverified claim of double blinding.

Relevance and novelty. Seven-point relevance and novelty ratings test whether structural diversity preserves fit while surfacing unfamiliar names. Targets are mean ratings of at least 5/7 for each, compared with both baselines. The primary joint outcome is each participant's fraction of cards rated relevance ≥ 5 and novelty ≥ 5; target a 25-percentage-point gain over Adamic–Adar. Report paired differences and confidence intervals, with a paired test at $\alpha = 0.05$ for this single primary comparison. Treat other comparisons as exploratory and apply Holm correction within their declared family. Do not treat 225 card ratings as 225 independent participants.

Actionability and usability. Seven-point actionability ratings test whether the explanation supports a plausible next step; target at least 5/7 and improvement over Topic-Only. Record unaided task completion and whether participants correctly distinguish observed ties from suggested routes, targeting at least 12 of 15 successful completions and correct explanations. Administer the standard ten-item System Usability Scale after the interactive task; score it using the standard alternating-item transformation, targeting mean SUS $\geq 80/100$. SUS is compared with that fixed target, not a claim that static-card baseline systems have been usability-tested.

Implementation gates. Card generation, a rating interface, and an analyzer exist, but collection is not yet ready end to end. The interface exports `evaluator_id` and verbose rating keys; the analyzer expects `participant_id`, `relevance`, `novelty`, and `actionability`. The interface loads the complete card bundle rather than a chosen seed's 15 cards, and supplies default ratings for unanswered cards during export. The analyzer summarizes the joint outcome but does not test it; SUS collection/scoring is absent. Before recruitment, align schemas, preserve unanswered ratings as missing, restrict each session to the assigned cards, verify pseudonymous IDs, add SUS and the primary paired comparison, and validate the complete export-to-analysis route. No comparative human result is reported at midterm.

7 Discussion and next steps

BridgeFinder makes network structure part of both candidate selection and explanation. Removing it would remove cross-community filtering, autonomy, and shared-contact explanations, leaving topic search. The present evidence supports a feasible prototype and modest historical ranking gains; it does not establish better mentoring outcomes, usable institutional routes, or a significant citation advantage.

The formative sample is small and self-selected; missing session notes limit independent verification. The graph omits informal relationships, external collaborators, and unpublished work. Harvest caps, large-team cliques, modularity resolution, and heuristic department labels affect who is visible. The web demonstration differs from the evaluated model, and its institutional routes must be corrected before real outreach. These limitations guide the next iteration rather than being treated as confirmed benefits.

In early November, unify the model and display semantics, verify seed identities, and complete the study collection gates. In mid-November, run the 15-person evaluation and report participant-level outcomes, including failures and uncertainty. In late November, revise the interface from observed comprehension errors and tune weights using a held-out validation period. In December, rerun the locked evaluation, document remaining biases, and prepare the final report and demonstration. User feedback and future collaboration precision answer different questions; both are necessary before recommending deployment.

Contributions and AI assistance

Evan Lin: ingestion, backtest pipeline, and campus map. Eric Liu: brokerage score, citation analysis, study tooling, and formative sessions. Both authors contributed to the report. The existing project used Claude for debugging, layout, and typesetting. OpenAI Codex assisted with this rubric audit, code-to-report checks, evaluation reruns, and editing. No participant responses or quotations were generated for this revision.

References

[1] V. D. Blondel, J.-L. Guillaume, R. Lambiotte, and E. Lefebvre. Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10):P10008, 2008.

[2] R. S. Burt. *Structural Holes: The Social Structure of Competition*. Harvard University Press, Cambridge, MA, 1992.

[3] R. S. Burt. Structural holes and good ideas. *American Journal of Sociology*, 110(2):349–399, 2004.

[4] L. Dahlander and D. A. McFarland. Ties that last: Tie formation and persistence in research organizations, 1988–2003. *Administrative Science Quarterly*, 58(1):69–110, 2013.

[5] M. Girvan and M. E. J. Newman. Community structure in social and biological networks. *Proceedings of the National Academy of Sciences*, 99(12):7821–7826, 2002.

[6] M. S. Granovetter. The strength of weak ties. *American Journal of Sociology*, 78(6):1360–1380, 1973.

[7] D. Liben-Nowell and J. Kleinberg. The link-prediction problem for social networks. *Journal of the American Society for Information Science and Technology*, 58(7):1019–1031, 2007.

[8] J. Nielsen. *Usability Engineering*. Morgan Kaufmann, San Francisco, CA, 1993.

[9] J. Priem, H. Piwowar, and R. Orr. Openalex: A fully-open index of scholarly works, authors, venues, institutions, and concepts. *arXiv preprint arXiv:2205.01833*, 2022.

[10] J. Tang, S. Wu, J. Sun, and H. Su. Cross-domain collaboration recommendation. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '12)*, pages 1285–1293, 2012.

[11] University of Illinois. Illinois experts: Research and scholarship at UIUC. https://experts.illinois.edu/, 2024.