

EFX₀ Allocations with at Most Three Relevant Goods: A Short Proof by Exchange Cycles

Evan Lin

University of Illinois Urbana-Champaign

Abstract. An allocation of indivisible goods is EFX₀ if no agent envies another agent’s bundle after removing any single good from it, even one the envious agent values at zero. We give a short proof that every instance with nonnegative additive valuations in which each agent positively values at most three goods has a complete EFX₀ allocation, in which moreover all bundles but at most one have at most two goods, and a polynomial-time algorithm, Draft and Exchange (DE), that computes one with at most $4n$ exchanges. The heart of the proof is an *Improvement Lemma*: a valid state from which no free agent can absorb the leftover goods is Pareto-dominated by another valid state, reached by one exchange along a cycle or a path of agents. Existence, and the shape for agents that value exactly three goods and are balanced, were machine-checked in Lean in previous work, by a much longer construction. The new proof, derived independently twice and refereed once with no error found (by an independent AI agent; there has been no human peer review), is machine-checked in Lean over the natural numbers, together with the algorithm and its bound of $4n$ exchanges; it was also checked by computer on millions of states.

Keywords: Fair division · Indivisible goods · EFX · Exchange cycles

1 Introduction

Agents N ($|N| = n \geq 1$) share a set M of m indivisible goods with nonnegative additive valuations $v_i(S) = \sum_{g \in S} v_i(g)$. An allocation X assigns every good to exactly one agent, who receives the bundle X_i ; no good is left out (allocations are *complete*). It is EFX₀ if

$$v_i(X_i) \geq v_i(X_j \setminus \{h\}) \quad \text{for all } i \neq j \text{ and all } h \in X_j,$$

and EFX asks this only for goods h with $v_i(h) > 0$ [4]. So EFX₀ implies EFX, and the two coincide for positive values. *Under EFX₀, if X_j contains a good that i values at 0, then i must not envy X_j at all.* Whether complete EFX allocations always exist for additive valuations is open; they are known to exist in special cases, among them three agents [5] or three types [7], $m \leq n + 3$ [15], four agents and at most nine goods [3], goods

valued by at most two agents [1,6,16,8], and hypergraphs of girth at least four [9] (Table 1 in Appendix F). Let $R_i = \{g : v_i(g) > 0\}$. If $|R_i| \leq 2$ for all i , serial dictatorship gives EFX_0 [13]. For $|R_i| \leq 4$, Viswanathan and Mehta [17] announce ordinary EFX, with a proof sketch; their algorithm gives the goods nobody values to an arbitrary agent, which can break EFX_0 .

Theorem 1 (existence and shape). *Every instance with $n \geq 1$ agents and nonnegative additive valuations in which every agent positively values at most three goods has a complete EFX_0 allocation in which all bundles but at most one have at most two goods. In particular this holds when every agent values exactly three goods and is balanced (values none of them more than the other two together).*

Theorem 2 (algorithm). *Algorithm DE (Section 5) computes such an allocation with at most n peeling steps and at most $4n$ exchanges, each taking time polynomial in n and m ; on real values, a comparison of two sums of at most two values of one agent counts as one step, as in [10].*

Previous work and status. Theorem 1 (existence, and the shape for agents that value exactly three goods and are balanced) was proved in previous work [10] with a construction, K3ALG, whose proof uses blocks of a draft, leaders, an owner test and one rotation; existence and that shape are machine-checked in Lean 4 for values in any linearly ordered cancellative commutative monoid, and K3ALG with its operation bound over $\mathbb{N}$ (over ordered values in a comparison model) [10,12]. This paper gives a much shorter proof. Its core, the Improvement Lemma (Theorem 4), was derived independently twice, by two different arguments [11]. It was refereed once, with no error found, by an independent AI agent (a separate session of our coding assistant, given only the written proof); there has been no human peer review. Every step has been checked by computer as described in Section 6, and it is machine-checked in Lean 4. A long version with every proof in the body, a worked example with a figure, and pseudocode is [paper/k3-simple/long.pdf](#) in [11]. So are soundness (Theorem 3), DE with at most $4n$ exchanges, and the shape in general (over $\mathbb{N}$; not the running time).

2 Preliminaries

The *threat* of a nonempty set B to agent i is $\theta_i(B) = v_i(B) - \min_{h \in B} v_i(h)$, and $\theta_i(\emptyset) = 0$; agent i is *safe* in X if $v_i(X_i) \geq \theta_i(X_j)$ for all $j \neq i$, so X

is EFX₀ iff every agent is safe. A good is *alone* if it is the only good of its bundle. When $|R_i| = 3$, we name i 's goods so that $v_i(a_i) \geq v_i(b_i) \geq v_i(c_i) > 0$, ties broken by index, and write $a_i \succ_i b_i \succ_i c_i$. Agent i is *balanced* if $v_i(a_i) \leq v_i(b_i) + v_i(c_i)$, *strictly* if the inequality is strict. Proofs of this section are in Appendix A.

Lemma 1 (threats). (a) $\theta_i(B) = 0$ if $|B| \leq 1$; (b) $\theta_i(B) \leq v_i(B \cap R_i)$; (c) $\theta_i(\{g, h\}) = \max(v_i(g), v_i(h))$.

Lemma 2 (safety). Let i be balanced with $|R_i| = 3$, and X an allocation. (a) If $b_i, c_i \in X_i$, i is safe. (b) Let $y \in X_i \cap R_i$ or $y = \perp$, and $G_y = \{g \in R_i : g \succ_i y\}$ ($G_\perp = R_i$). If no bundle X_j , $j \neq i$, $|X_j| \geq 2$, contains a good of G_y , then i is safe, unless $y = a_i$ and some X_j , $j \neq i$, $|X_j| \geq 3$, contains b_i and c_i .

Lemma 3 (peeling). Let $i \in N$ and $P \subseteq M$ with $|P| \leq 1$ and $v_i(P) \geq v_i(M \setminus P)$. If the instance without i and P has an EFX₀ allocation Z , then Z with $X_i = P$ is EFX₀.

Rule R1: with G the remaining goods and p agent i 's favourite good of G , agent i leaves with $P = \emptyset$ if it values no good of G , and with $P = \{p\}$ if $v_i(G \setminus \{p\}) \leq v_i(p)$.

Lemma 4 (when R1 applies to nobody). If i values at most three goods of G and R1 does not apply to i , then i values exactly three goods of G and is strictly balanced with respect to them.

3 States and Soundness

In the *core case* every agent values exactly three goods and is strictly balanced; goods valued by nobody may exist. A *state* Y gives each agent i a holding $Y_i \in \{\emptyset, \{a_i\}, \{b_i\}, \{c_i\}, \{b_i, c_i\}\}$, pairwise disjoint. U is the set of *pair holders* ($Y_i = \{b_i, c_i\}$); $J = M \setminus \bigcup_i Y_i$ is the set of *leftover* goods; for $i \notin U$ with $|Y_i| = 1$ we write $Y_i = \{y_i\}$. The *utility* $u_i(Y)$ is 4, 3, 2, 1, 0 for the pair, $\{a_i\}$, $\{b_i\}$, $\{c_i\}$, $\emptyset$; Y' *Pareto-dominates* Y if $u_i(Y') \geq u_i(Y)$ for all i , strictly for some i .

- The *needs* are $N_i = \emptyset$ for $i \in U$, $N_i = R_i$ if $Y_i = \emptyset$, and $N_i = \{g \in R_i : g \succ_i y_i\}$ otherwise; $NA = \bigcup_i N_i$. No agent needs its own good. (N is the set of agents; N_i , with a subscript, are the needs of agent i .)
- Y is *valid* if every $g \in NA$ is the only good of some agent ($Y_j = \{g\}$; then $j \notin U$).

- An agent $i \notin U$ is *free* if $Y_i = \emptyset$ or $y_i \notin NA$; F is the set of free agents.
- The *need digraph* D has the agents outside U as vertices and an arc $j \rightarrow j'$ when j holds a single good $y_j \in N_{j'}$. It has no loops.
- Agent x is *exposed* for o if $x \neq o$, $x \notin U$, $Y_x = \{a_x\}$ and $b_x, c_x \in J \cup Y_o$; E_o is the set of these agents.
- Agent o is a *valid absorber* with set H if $o \in F \cup U$, (A1) $\{b_x, c_x\} \cap J \neq \emptyset$ for every $x \in E_o$, and (A2) $H \subseteq J$ meets every $\{b_x, c_x\} \cap J$ ($x \in E_o$) and $|H| \leq |F \setminus \{o\}|$. Y is *completable* if some agent is a valid absorber.
- The *completion* with o and H : each good of H goes to a different free agent other than o ; o receives $X_o = Y_o \cup (J \setminus H)$; every other agent i keeps $X_i = Y_i$, or $X_i = Y_i \cup \{h\}$ if it received $h \in H$.

Theorem 3 (soundness). *If Y is valid and o is a valid absorber with set H , the completion is EFX_0 , and only X_o can have more than two goods.*

The proof (Appendix B) shows that needed goods stay alone, and that no agent $x \neq o$, $x \notin U$, holding only a_x finds b_x and c_x in X_o : otherwise $b_x, c_x \in J \cup Y_o$, so $x \in E_o$, and H took one of them out of X_o . Lemma 2 then applies to every agent.

Lemma 5. (Draft) *If the agents, in any order, each take the first of a_i, b_i, c_i not yet taken (or nothing), the result is a valid state. Now let Y be valid and Y' a state. (F1) If $u_i(Y') \geq u_i(Y)$, then $N'_i \subseteq N_i$. (F2) Every agent outside $U \cup F$ has an out-arc in D . (Transfer) If a state Y' has $u_i(Y') \geq u_i(Y)$ for all i , strictly for some, and every $g \in NA$ is the only good of some agent in Y' , then Y' is valid and Pareto-dominates Y .*

Proof. (Draft) A good that i needs was taken before i 's turn, alone, by an earlier agent, and holdings do not change. (F1) If Y'_i is the pair, $N'_i = \emptyset$; if $Y'_i = \{g'\}$, then Y_i is $\emptyset$ or a single good ranked at most as high as g' , so every good ranked above g' is in N_i ; if $Y'_i = \emptyset$, then $Y_i = \emptyset$. (F2) Such a j holds $y_j \in NA$, so some j' needs y_j ; $j' \neq j$, and $j' \notin U$ since pair holders need nothing. (Transfer) By (F1), $NA' \subseteq NA$. $\square$

4 The Improvement Lemma

Theorem 4 (Improvement Lemma). *In the core case, let Y be valid, with no free agent a valid absorber and some agent not in U . Then some valid state Pareto-dominates Y , obtained by one need cycle, pair chain or exchange cycle, found in polynomial time.*

If Y is not completable, the hypotheses hold (if $U = N$, every agent is a valid absorber with $H = \emptyset$, as exposed agents are outside U). So every valid state that no valid state dominates is completable. In the proof, Y is valid.

Lemma 6 (need cycle; pair chain). (a) If D has a cycle, Y is dominated by a valid state. (b) If some $x \notin U$ has $Y_x = \{a_x\}$ and $b_x, c_x \in J$, Y is dominated by a valid state.

Proof. (a) Let $j_0 \rightarrow \dots \rightarrow j_{k-1} \rightarrow j_0$ be a cycle ($k \geq 2$); its agents hold single goods. Let each j_{t+1} take y_{j_t} (indices mod k). The goods are permuted, each j_{t+1} receives a good it needs, and a needed good held by j_t is now held alone by j_{t+1} ; others are unchanged. Transfer applies. (b) Walk $j_0 = x$, j_{t+1} = an out-neighbour of j_t , while one exists. A repeat gives a cycle: use (a). Otherwise the walk stops at j_k with no out-arc. Let x take $\{b_x, c_x\}$ and j_t take $y_{j_{t-1}}$ for $1 \leq t \leq k$ ($y_{j_0} = a_x$); the old good of j_k , if any, becomes leftover. Holdings stay disjoint (b_x, c_x were leftover), x goes from 3 to 4, and each j_t , $t \geq 1$, gets a needed good. Leftover goods are not needed (validity); y_{j_t} ($t < k$) moves to j_{t+1} alone; and $j_k \notin U$ has no out-arc, so $j_k \in F$ by (F2) and its old good is not needed. Transfer applies. $\square$

From now on assume **(P)**: no $x \notin U$ with $Y_x = \{a_x\}$ has $b_x, c_x \in J$.

Lemma 7. Assume (P). (a) If $o \in F$ holds nothing, $E_o = \emptyset$ and o is a valid absorber with $H = \emptyset$. (b) If $o \in F$ holds y_o , every $x \in E_o$ has $\{b_x, c_x\} = \{y_o, h_x\}$ with $h_x \in J$; with $H_o = \{h_x : x \in E_o\}$, o is a valid absorber iff $|H_o| \leq |F| - 1$, and then with $H = H_o$. (c) An agent x lies in E_o for at most one free o holding a good, so h_x depends only on x . (d) If $F = \emptyset$ and $U \neq N$, D has a cycle.

Proof. (a) $x \in E_o$ would have $b_x, c_x \in J$, against (P). (b) $b_x, c_x \in J \cup \{y_o\}$, not both in J , and $b_x \neq c_x$; so one is y_o and the other is leftover. Then $\{b_x, c_x\} \cap J = \{h_x\}$, and H meets all of these iff $H \supseteq H_o$; and $|F \setminus \{o\}| = |F| - 1$. (c) If $x \in E_o \cap E_{o'}$, $o \neq o'$, then $\{b_x, c_x\} = \{y_o, y_{o'}\}$ has no leftover good, against (b). (d) Every agent outside U has an out-arc by (F2), and there is one. $\square$

The *exchange digraph* D^+ (under (P)) adds to D an *exposure arc* $o \rightarrow x$, labelled h_x , for every $o \in F$ holding a good and every $x \in E_o$. Heads of exposure arcs hold their tops and need nothing; heads of need arcs need a good; so the head determines the kind of arc. The *exchange* along a

cycle $(w_0, \dots, w_{k-1})$ of D^+ ($k \geq 2$, indices mod k) lets w_{t+1} take its pair $\{y_{w_t}, h_{w_{t+1}}\}$ if $w_t \rightarrow w_{t+1}$ is an exposure arc, and y_{w_t} alone if it is a need arc; agents off the cycle keep their holdings. Every cycle agent holds a single good and has one predecessor, so this is well defined.

Lemma 8 (exchange cycle). *Assume (P). If the exposure arcs of a cycle C of D^+ have distinct labels, the exchange along C is valid and Pareto-dominates Y ; its new pair holders are the heads of the exposure arcs.*

Proof. Each y_{w_t} moves to w_{t+1} only; the labels are leftover and distinct; agents off C keep other goods. So holdings are disjoint. Exposure heads go from 3 to 4; need heads receive a needed good; others are unchanged. If $g \in NA$ is held by j alone and $j = w_t \in C$, then $w_t \notin F$, so $w_t \rightarrow w_{t+1}$ is a need arc and w_{t+1} holds g alone; if $j \notin C$, j keeps g . Transfer applies. $\square$

Lemma 9 (an exchange cycle exists). *Assume (P), $F \neq \emptyset$, no free agent holds nothing, and $|H_o| \geq |F|$ for all $o \in F$. Then D^+ has a cycle whose exposure arcs have distinct labels.*

Proof. List $F = \{o_1, \dots, o_f\}$ and pick $q_{o_i} \in H_{o_i} \setminus \{q_{o_1}, \dots, q_{o_{i-1}}\}$, possible since $|H_{o_i}| \geq f > i - 1$. Let $x_o \in E_o$ have protecting good q_o . Define $\sigma(o) = x_o$ for $o \in F$, and $\sigma(j)$ = an out-neighbour in D for $j \notin U \cup F$ (F2). Then $\sigma(j) \notin U$, $\sigma(j) \neq j$, and $j \rightarrow \sigma(j)$ is an arc of D^+ . Iterating σ from any agent outside U repeats an agent and gives a cycle; its exposure arcs $o \rightarrow x_o$ carry the distinct labels h_o . $\square$

Proof (of Theorem 4). If (P) fails, Lemma 6(b). If $F = \emptyset$, Lemma 7(d) gives a cycle of D , and Lemma 6(a). Otherwise no free agent absorbs, so none holds nothing and $|H_o| \geq |F|$ for all $o \in F$ (Lemma 7(a,b)); Lemmas 9 and 8. Each step is a walk or a greedy choice. $\square$

5 The Algorithm Draft and Exchange

Algorithm DE. 1. Peel. While at least two agents remain and rule R1 applies to one of them, it leaves with its set P . If one agent remains, it takes all remaining goods; stop. **2. Draft.** The remaining agents, in index order, take the first of a_i, b_i, c_i not yet taken, or nothing. **3. Exchange.** Repeat: if (P) fails, apply the pair chain (or need cycle) of Lemma 6(b); else, if every agent holds its pair, or a free agent holds nothing, or a free o has $|H_o| \leq |F| - 1$, stop with that absorber (any agent if all hold pairs;

$H = \emptyset, \emptyset, H_o$ respectively); else, if $F = \emptyset$, apply a need cycle; else apply the exchange cycle of Lemma 9. **4. Complete** with the absorber o and H .

Theorem 5. *On every instance with $|R_i| \leq 3$ for all i , DE returns a complete EFX₀ allocation in which all bundles but at most one have at most two goods, after at most n peels and $4n$ exchanges.*

Proof. By Lemma 3 and induction on the peels, it suffices that the allocation of the residual instance is EFX₀; with one agent this is trivial. Otherwise, by Lemma 4, we are in the core case. The draft is valid (Lemma 5). Each exchange keeps validity and raises $\sum_i u_i \in [0, 4n]$ by at least 1 (Lemmas 6, 7(d), 8, 9, as in the proof of Theorem 4), so there are at most $4n$. At the stop, o is a valid absorber with H (Lemma 7, or, if every agent holds its pair, the remark after Theorem 4), and the completion is EFX₀ with only X_o large (Theorem 3). Peeled agents get at most one good. $\square$

Theorems 1 and 2 follow; each iteration needs one pass over agents and goods, so DE takes $O(n(n+m))$ steps after reading the input (not formalized; on real values, in the comparison model of Section 1). The absorber test is applied only under (P), where it is a count; in general it would ask for a smallest hitting set.

Example. Goods $g_0, \dots, g_9$; agents $x_1, x'_1, x_2, x'_2, o_1, o_2$ rank $(g_0, g_4, g_6), (g_1, g_4, g_7), (g_2, g_5, g_8), (g_3, g_5, g_9), (g_2, g_3, g_4), (g_0, g_1, g_5)$ (values 4, 3, 2, say). Nobody is peeled; the draft gives the x 's their tops, o_1 its $c = g_4$ and o_2 its $c = g_5$. Then $NA = \{g_0, \dots, g_3\}$, $J = \{g_6, \dots, g_9\}$, $F = \{o_1, o_2\}$, $H_{o_1} = \{g_6, g_7\}$ (from x_1, x'_1) and $H_{o_2} = \{g_8, g_9\}$: no free agent absorbs. There is no need cycle, pair chain, or cycle of D^+ with one exposure arc, and each of the four valid states that dominate this one gives pairs to two agents. DE picks $q_{o_1} = g_6$, $q_{o_2} = g_8$ and exchanges along $o_1 \rightarrow x_1 \rightarrow o_2 \rightarrow x_2 \rightarrow o_1$ (Figure 1): x_1 takes $\{g_4, g_6\}$, o_2 takes g_0 , x_2 takes $\{g_5, g_8\}$, o_1 takes g_2 . Now $NA = \emptyset$, $J = \{g_7, g_9\}$, and x'_1 absorbs with $H = \emptyset$: $X_{x'_1} = \{g_1, g_7, g_9\}$, an EFX₀ allocation. One-arc exchanges are the rotations of K3ALG [10]; the single-move local search gets stuck here [11]. A state with no free absorber and no such short move needs $n \geq 6$ and $m \geq 8$, both attained (a written proof, not refereed), and on a family of rings every exchange cycle needed k exposure arcs in our computations for $k \leq 5$ (not proved; Appendix C).




Fig. 1. The exchange digraph of the drafted state of the example. Double circles: free agents. Dashed: exposure arcs (labelled by the protecting good); solid: need arcs (labelled by the good that moves). Black: the cycle chosen by DE.

6 Verification Status, Evidence and Conclusion

The Improvement Lemma, soundness and DE (correctness, shape, at most $4n$ exchanges, peeling included) are machine-checked in Lean 4 over $\mathbb{N}$ ([11], `lean/EFX/K3DE*.lean`; standard axioms only; the formal statements, written by the same AI assistant, are not independently reviewed). The Improvement Lemma was found twice independently: the proof above and a “rainbow walk” ([11], `k3/simplify/po/hall/NOTES.md` and `po/potential/NOTES.md`). One referee, an independent AI agent given only the written proof, found no error (`po/referee/README.md`); there has been no human peer review; its four presentation fixes are applied (explicit completion and owner constraint; h_x well defined; Lemma 6(a) when $F = \emptyset$; test wording). Three implementations (the two proofs as code, and the referee’s, written from the text alone) assert every claim of the proofs, with raw EFX₀ checks of the outputs, on millions of valid states and runs, without failure (Appendix E). Our script `paper/k3-simple/examples/check_examples.py` rechecks every example and runs DE, peeling included, on 40,000 random instances (Appendix E). The shape cannot be improved in the obvious ways: some core instances need a bundle of three goods, and some need four (Appendix D). EFX₀ with four relevant goods per agent is open (for EFX, see [17]); so are a better bound than $4n$ exchanges, and the least size of the large bundle.

Acknowledgments. The proofs, code and the Lean formalizations were developed with the assistance of AI coding agents (Claude Code); this paper was also drafted with their assistance.

References

1. Afshinmehr, M., Ashuri, A., Mahmoudkhan, P., Mehlhorn, K., Shahrezaei, A.M.: EFX allocations exist on multi-graphs. arXiv preprint arXiv:2606.18665 (2026), accepted at the 27th ACM Conference on Economics and Computation (EC 2026)
2. Akrami, H., Mayorov, A., Mehlhorn, K., Srinivas, S., Weidenbach, C.: A counterexample to EFX $n \geq 3$ agents, $m \geq n + 5$ items, submodular valuations via SAT-solving. arXiv preprint arXiv:2604.18216 (2026)
3. Alkassar, E., Fouz, M., Mehlhorn, K.: Complete EFX allocations exist for four additive agents and up to nine goods. arXiv preprint arXiv:2608.08590 (2026)
4. Amanatidis, G., Birmas, G., Filos-Ratsikas, A., Voudouris, A.A.: Fair division of indivisible goods: A survey. In: Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence (IJCAI-22). pp. 5385–5393 (2022). <https://doi.org/10.24963/ijcai.2022/756>, arXiv:2202.07551
5. Chaudhury, B.R., Garg, J., Mehlhorn, K.: EFX exists for three agents. Journal of the ACM **71**(1), 4:1–4:27 (2024). <https://doi.org/10.1145/3616009>, conference version in Proc. 21st ACM Conference on Economics and Computation (EC 2020), pp. 1–19; full version arXiv:2002.05119
6. Christodoulou, G., Fiat, A., Koutsoupias, E., Sgouritsa, A.: Envy-freeness up to any good allocations on graphs. Mathematics of Operations Research (2026). <https://doi.org/10.1287/moor.2025.0915>, conference version: “Fair Allocation in Graphs”, in Proc. 24th ACM Conference on Economics and Computation (EC 2023), pp. 473–488
7. HV, V.P., Ghosal, P., Nimbhorkar, P., Varma, N.: EFX exists for three types of agents. In: Proceedings of the 26th ACM Conference on Economics and Computation (EC 2025). pp. 101–128. ACM (2025). <https://doi.org/10.1145/3736252.3742509>, arXiv:2410.13580
8. Kaviani, A., Seddighin, M., Shahrezaei, A.: Almost envy-free allocation of indivisible goods: A tale of two valuations. In: Web and Internet Economics (WINE 2024). pp. 261–276. Lecture Notes in Computer Science, Springer (2026). https://doi.org/10.1007/978-3-032-08560-3_15, full version arXiv:2407.05139
9. Lianas, T., Sgouritsa, A., Sotiriou, M.M.: EFX allocation in (multi)hypergraphs. Proceedings of the AAAI Conference on Artificial Intelligence **40**(20), 17102–17110 (2026). <https://doi.org/10.1609/aaai.v40i20.38759>, AAAI-26; arXiv:2608.03171
10. Lin, E.: EFX₀ allocations with at most three relevant goods: Existence and a verified polynomial-time algorithm. Manuscript (CS 580 course project report), folder `paper/k3` of the repository `efx0-three-goods`, <https://github.com/evanlin23/efx0-three-goods> (2026)
11. Lin, E.: `efx0-three-goods`, branch `proof/k3-simplify`: notes, tests and referee report for the short proof. GitHub repository, branch `proof/k3-simplify`, commit `bdff404`, <https://github.com/evanlin23/efx0-three-goods> (2026)
12. Lin, E.: `efx0-three-goods`: EFX₀ with at most three relevant goods per agent (proofs, certificates, Lean formalization). GitHub repository, commit `fa08f55`, <https://github.com/evanlin23/efx0-three-goods> (2026)
13. Lin, E., Osterhaus, G.: Strong EFX allocations for 2-relevant agents: Lean 4 formalization. GitHub repository `mrd-efx`, tag `v1.2.0` (commit `fa42aa1`, 23 September 2026), <https://github.com/evanlin23/mrd-efx> (2026)
14. Mackenzie, S., Suzuki, M.: Counterexamples to EFX for submodular and subadditive valuations. arXiv preprint arXiv:2605.06451 (2026)

15. Mahara, R.: Extension of additive valuations to general valuations on the existence of EFX. *Mathematics of Operations Research* **49**(2), 1263–1277 (2024). <https://doi.org/10.1287/moor.2022.0044>, conference version in Proc. 29th Annual European Symposium on Algorithms (ESA 2021), LIPIcs 204, 66:1–66:15; arXiv:2107.09901
16. Sgouritsa, A., Sotiriou, M.M.: On the existence of EFX allocations in multigraphs. arXiv preprint arXiv:2502.09777 (2025), extended abstract, without the bipartite case, in Proc. 24th International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2025), pp. 2735–2737
17. Viswanathan, M., Mehta, R.: On the existence of EFX under picky or non-differentiative agents. In: Proceedings of the 23rd International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2024). pp. 2534–2536 (2024). <https://doi.org/10.65109/osos1146>, extended abstract

A Proofs for Section 2

Proof (of Lemma 1). (a) $\theta_i(\{h\}) = 0$. (b) The minimum is at least 0 and $v_i(B) = v_i(B \cap R_i)$. (c) $v_i(g) + v_i(h) - \min(v_i(g), v_i(h))$. $\square$

Proof (of Lemma 2). Fix $j \neq i$; if $|X_j| \leq 1$, $\theta_i(X_j) = 0$. Let $|X_j| \geq 2$ and $T = X_j \cap R_i$, so $\theta_i(X_j) \leq v_i(T)$. (a) $T \subseteq \{a_i\}$, and $v_i(a_i) \leq v_i(b_i) + v_i(c_i) \leq v_i(X_i)$. (b) If $y = \perp$, $T \subseteq G_\perp$ is empty. Otherwise each $g \in T$ is neither in G_y nor y , so $y \succ_i g$ and $v_i(g) \leq v_i(y) \leq v_i(X_i)$; this settles $|T| \leq 1$. If $|T| \geq 2$, then $y = a_i$ and $T = \{b_i, c_i\}$; if $|X_j| = 2$, $\theta_i(X_j) = v_i(b_i) \leq v_i(a_i)$ by Lemma 1(c); if $|X_j| \geq 3$ we are in the exception. $\square$

Proof (of Lemma 3). Every other bundle lies in $M \setminus P$, so its threat to i is at most $v_i(M \setminus P) \leq v_i(P)$. The bundle P has at most one good, so its threat is 0. Other constraints are those of Z . $\square$

Proof (of Lemma 4). R1 fails, so $v_i(p) > 0$ and $v_i(G \setminus \{p\}) > v_i(p)$. With at most two valued goods, $v_i(G \setminus \{p\})$ would be the value of at most one good, at most $v_i(p)$. So i values three goods, $p = a_i$, and $v_i(b_i) + v_i(c_i) > v_i(a_i)$. $\square$

If $|R_i| \leq 2$ for all agents, serial dictatorship with the last agent taking the rest is EFX₀: each pick satisfies R1 (Lemma 3, induction).

B Proof of Theorem 3

Proof. Sizes. A free agent other than o holds at most one good and receives at most one; a pair holder has two goods; other agents keep one good. So only X_o can have three or more goods. *(N) Needed goods stay alone.* For $g \in NA$, validity gives $Y_j = \{g\}$; $j \notin U \cup F$, so $j \neq o$ and j receives no good of H ; so $X_j = \{g\}$. *(OC)* No $x \neq o$, $x \notin U$, $Y_x = \{a_x\}$, has $b_x, c_x \in X_o$: otherwise $b_x, c_x \in Y_o \cup J$, so $x \in E_o$, and by (A2) H contains a leftover good of $\{b_x, c_x\}$, which went to another agent and is not in Y_o , hence not in X_o . *Safety.* Agents are balanced. If $i \in U$, Lemma 2(a). If $i \notin U$, apply Lemma 2(b) with $y = y_i$ (or $\perp$): $G_y = N_i \subseteq NA$, so its goods are alone by (N). In the exception, $y_i = a_i$ and b_i, c_i lie in a bundle of at least three goods, which is X_o with $o \neq i$; (OC) excludes this. $\square$

The proof uses only validity, the definition of a valid absorber, and balance of pair holders.

C Short Moves and Large Exchanges

A *short move* is a need cycle, a pair chain, or an exchange along a cycle of D^+ with one exposure arc. The rotation of K3ALG [10] and K3S [11] is a short move: an agent k exposed for r takes its pair and its top travels along a need chain to r .

Proposition 1 ([11], `po/potential/NOTES.md`, **Lemma 3; written, not refereed**). *In the core case, let Y be valid, with no free valid absorber, $U \neq N$, and no short move. Then $|F| \geq 2$, $n \geq 6$ and $m \geq 8$ (and $n \geq 9$, $m \geq 12$ if $|F| \geq 3$). The bounds $n \geq 6$ and $m \geq 8$ are attained.*

Proof. (P) holds (no pair chain) and D is acyclic (no need cycle), so every walk along need arcs ends at a free agent (F2). By Lemma 7, $F \neq \emptyset$, every free agent holds a good, $|H_o| \geq |F|$ for $o \in F$, and the sets E_o are disjoint with $|E_o| \geq |H_o|$. Every agent holds a good. If $F = \{o\}$, some $x \in E_o$ walks along need arcs to o , and $o \rightarrow x \rightarrow \dots \rightarrow o$ is a short move. If $F = \{o_1, o_2\}$: walks from E_{o_1} cannot end at o_1 (short move), so they end at o_2 ; one of the at least two agents of E_{o_1} is not o_2 , so a need arc enters o_2 , o_2 needs a good, and $o_2 \notin E_{o_1}$. So E_{o_1} , and symmetrically E_{o_2} , hold at least two non-free agents: $n \geq 6$, and $m \geq n + |J| \geq 6 + 2$. If $|F| = k \geq 3$, the E_o hold at least k^2 agents, at most k of them free: $n \geq k^2$, $m \geq k^2 + k$. The example of Section 5 has $n = 6$; the state with rankings $o_1: (g_4, g_5, g_0)$, $o_2: (g_6, g_7, g_1)$, $x_1: (g_4, g_1, g_2)$, $x'_1: (g_5, g_3, g_1)$, $x_2: (g_6, g_0, g_2)$, $x'_2: (g_7, g_3, g_0)$, where o_1 holds g_0 , o_2 holds g_1 and the x 's their tops, has $n = 6$, $m = 8$ (checked by our script). $\square$

In the notes' family of rings with k free agents (each needing the roots of a binary need tree whose leaves are exposed for the previous free agent), every cycle of D^+ with distinct labels has exactly k exposure arcs; this was checked by computer for $k \leq 5$ (notes) and $k \leq 4$ (our script), not proved.

D Limits of the Shape

Lemma 10 (cases of safety). *Let $R_i = \{a, b, c\}$ with $v_i(a) > v_i(b) > v_i(c) > 0$ and $v_i(a) < v_i(b) + v_i(c)$. Agent i is safe in X iff (T) i holds a , and also b or c , or b and c are not together in a bundle of at least three goods; or (BC) i holds b and c ; or (B) i holds b and a is alone; or (C) i holds c , and a and b are alone; or (E) a, b, c are all alone.*

Proof. Write x for $v_i(x)$: $0 < c < b < a < b+c < a+c < a+b < a+b+c$. Let $S = X_i \cap R_i$ and, for $j \neq i$, $T = X_j \cap R_i$; $\theta_i(X_j)$ is 0 if $T = \emptyset$ or $|X_j| = 1$, $v_i(T)$ if $X_j \not\subseteq R_i$, and the larger value if $X_j = T$ has two goods. If S contains a and another good, every threat is at most $b < a+c$: safe (T). If $S = \{b, c\}$, every threat is at most $a < b+c$: safe (P). If $S = \{a\}$, the threat is $b+c > a$ exactly when b, c share a bundle of at least three goods (it then has a good outside R_i), and at most b otherwise: (T). If $S = \{b\}$: if a is not alone its bundle has threat at least $a > b$; if a is alone the remaining threat is at most c : (B). If $S = \{c\}$: a must be alone, and b too (its bundle otherwise has threat at least $b > c$): (C). If $S = \emptyset$: any bundle of two or more goods meeting R_i has positive threat: (E). Conversely each case is one of these safe situations. $\square$

Proposition 2 (limits of the shape). *With values as in Lemma 10 for every agent: (a) if agents 0, 1, 2 rank $g_0 \succ g_1 \succ p_i$, with p_i valued only by i , no EFX₀ allocation has all bundles of at most two goods, and $\{g_0\}, \{g_1\}, \{p_0, p_1, p_2\}$ is EFX₀ in any order; (b) if agents 0, 1, 2, 3 rank $g_0 \succ g_2 \succ p_0$, $g_0 \succ g_2 \succ p_1$, $g_1 \succ g_2 \succ p_2$, $g_1 \succ g_2 \succ p_3$, every EFX₀ allocation has sizes 4, 1, 1, 1, and one exists.*

Proof. (a) Bundles of at most two goods have sizes 2, 2, 1: one good is alone. Two agents do not hold g_0 ; (T) fails for them, and (C), (E) need two alone goods; so both are in (BC) or (B) and hold g_1 : impossible. The stated allocation is (T), (B), (C). (b) Each top g_0, g_1 has a different *loser*, an agent ranking it first without holding it. A loser is safe only by (BC) or (B), holding g_2 , or by (C) or (E), with g_2 alone. Both cannot hold g_2 , so g_2 is alone and (BC) is impossible; then each loser needs its top alone too. So g_0, g_1, g_2 are alone in three bundles, and the fourth is $\{p_0, \dots, p_3\}$. Giving g_0, g_2, g_1 and the p_i to agents 0, 1, 2, 3 is EFX₀ (cases T, B, T, C). $\square$

Our script confirms both parts by listing all allocations.

E Evidence in Detail

The tests ([11]; k3/simplify/po/hall/, po/potential/, po/referee/) are evidence, not proof; values 4, 3, 2 suffice for distinct strictly balanced values by Lemma 10, and the referee also used real values. *First proof as code*: every valid state of every ranking profile with $n = 2$ ($m \leq 6$), $n = 3$ ($m \leq 7$), $n = 4$ ($m = 5$): 1,693,750 states, 269,028 not completable, each improved; 183,484 sampled states; one completion per completable

state checked EFX_0 ; all 774,248 Pareto-optimal states completable; DE’s loop on 44,971 profiles. *Second proof as code*: about 15.5 million valid states (every profile with $n = 2, m \leq 6$; $n = 3, m \leq 7$; $n = 4, m \leq 6$; random $n \leq 8$; cores $n = 5, 6$). *Referee*: 2,006,886 profiles (every profile with $n = 2, m \leq 6$; $n = 3, m \leq 7$; $n = 4, m = 5, 6$), 30,700 cores ($n = 5$), 200,000 random ($n \leq 9$), 273,805 states, 1,130,775 completions, 65,816 rejection-sampled states (with need cycles), 3,000 rings ($k \leq 9, n \leq 304$), 300,000 real-valued instances with peeling. *This paper’s script* (independent): the example, the instances of Appendices C and D, the first rows of the first set (cross-checked with `hall.py`), and DE on 40,000 random instances ($n \leq 9$; ties, top-heavy agents, goods nobody values): all EFX_0 with at most one bundle of more than two goods, at most 8 exchanges. No test failed.

F Related Work

For monotone valuations that are not additive, EFX allocations need not exist [2,14]. A 3-relevant instance with no complete EFX_0 allocation would refute the additive EFX conjecture (perturb all values by a small $\varepsilon > 0$; compare [5]), but perturbing destroys the relevance structure.

Table 1. Existence results for complete allocations under restrictions. *Version cited:* the published version where one exists, else arXiv. ^aGoods nobody values go to an arbitrary agent. ^bIncludes additive. ^cExtended abstract with a proof sketch. ^dAn AAMAS 2025 extended abstract has the degree and girth conditions. ^eAccepted at EC 2026. ^fExistence; the shape for exactly three balanced goods; K3ALG over $\mathbb{N}$.

Result	Restriction (agents, goods, who values what)	Notion	Complete	Valuations	Algorithm	Version cited
[5]	$n = 3$	EFX ₀	yes	additive	pseudo-polynomial	JACM 2024
[7]	at most three distinct valuations	EFX ₀	yes	additive	no bound stated	EC 2025
[15]	$m \leq n + 3$	EFX ₀	yes	monotone	none stated	MOR 2024
[3]	$n = 4, m \leq 9$	EFX ₀	yes	additive	none stated	arXiv
[6]	graphs: at most two valuers per good, two agents share at most one good	EFX ₀	yes	monotone	polynomial time	MOR 2026 (EC 2023)
[1]	multigraphs: at most two valuers per good	EFX ₀	yes	cancelable ^b	polynomial time	arXiv ^e
[16]	multigraphs: bipartite, or at most $\lceil n/4 \rceil - 1$ neighbours per agent, or girth at least six (non-parallel edges)	EFX ₀	yes	monotone	not efficient (stated)	arXiv ^d
[8]	at most two valuers per good, $v_i(g) \in \{0, v_g\}$	EFX ₀	yes	restricted additive	no time bound stated	WINE 2024
[9]	hypergraphs of girth at least four (a good joins its valuers)	EFX ₀	yes	monotone	polynomial time	AAAI 2026
[17]	at most four relevant goods per agent	EFX	yes ^a	additive	polynomial time, announced	AAMAS 2024 ^c
[13]	at most two relevant goods per agent	EFX ₀	yes	additive; monotone	serial dictatorship; Lean-checked	GitHub, v1.2.0
[10]	at most three relevant goods per agent	EFX ₀	yes	additive	polynomial time; Lean-checked ^f	manuscript
this paper	at most three relevant goods per agent; any number of valuers per good	EFX ₀	yes	additive	polynomial time, at most $4n$ exchanges	this paper