CYS 335

Total points 23/25

write you name and student number

The respondent's email (**s0k0j4m3s@gmail.com**) was recorded on submission of this form.

✗ Student Number: * ···/1

20231392 ✗

✓ What are the characteristics of signature based IDS? * 1/1

- (●) Most are based on simple pattern matching algorithms ✓
- ( ) It is programmed to interpret a certain series of packets
- ( ) It models the normal usage of network as a noise characterization
- ( ) Anything distinct from the noise is assumed to be intrusion activity

✓ What is a key advantage of anomaly-based IDS? * 1/1

- ( ) It is very effective at detecting known attacks.
- (•) It can detect novel or zero-day attacks. ✓
- ( ) It generates very few false positives.
- ( ) It is easy to configure and maintain.

✓ What are two main types of IDS signatures? * 1/1

- ( ) Network based and File based
- (•) Context based and Content based ✓
- ( ) Active and Reactive
- ( ) None of the above

✓ When a NIDS is pulling all traffic from the network so that it can be processed, it must be run in what mode? *1/1

- ( ) Traffic collector
- ( ) Monitor
- (•) Promiscuous ✓
- ( ) Analysis

✓ What are the characteristics of anomaly based IDS? * 1/1

- (●) It models the normal usage of network as a noise characterization ✓
- ( ) It doesn't detect novel attacks
- ( ) Anything distinct from the noise is not assumed to be intrusion activity
- ( ) It detects based on signature

✓ How does an Intrusion Prevention System (IPS) differ from an IDS? * 1/1

- ( ) An IPS only monitors network traffic, while an IDS can both monitor and block malicious traffic.
- (●) An IPS can actively block malicious traffic, while an IDS can only generate alerts ✓
- ( ) An IDS can encrypt network traffic, while an IPS cannot.
- ( ) An IPS can automatically patch vulnerabilities, while an IDS cannot.

✓ What are the drawbacks of the host based IDS? * 1/1

- (●) Unselective logging of messages may increase the audit burdens ✓
- ( ) Selective logging runs the risk of missed attacks
- ( ) They are very fast to detect
- ( ) They have to be programmed for new patterns

✗ Name: * ···/1

James Soko ✗

✓ What is a false negative in the context of an IDS? * 1/1

- ○ An IDS incorrectly identifies legitimate traffic as malicious.
- ◉ An IDS fails to detect malicious traffic and allows it to pass. ✓
- ○ An IDS generates too many alerts, overwhelming security personnel.
- ○ An IDS is unable to monitor network traffic.

✓ What is the major drawback of anomaly detection IDS? * 1/1

- ○ These are very slow at detection
- ◉ It generates many false alarms ✓
- ○ It doesn't detect novel attacks
- ○ None of the mentioned

✓ What are characteristics of Network based IDS? * 1/1

- (●) They look for attack signatures in network traffic ✓
- ( ) Filter decides which traffic will not be discarded or passed
- ( ) It is programmed to interpret a certain series of packet
- ( ) It models the normal usage of network as a noise characterization

✓ What is a padded cell in the context of intrusion detection? * 1/1

- ( ) A type of network firewall.
- (●) A decoy system used to lure attackers. ✓
- ( ) A system for automatically patching vulnerabilities.
- ( ) A device that encrypts network traffic.

✓ Hostile activity that does not match an IDS signature and goes undetected is called a false positive. *1/1

- ( ) True
- (●) False ✓

✓ What are the different ways to classify an IDS? * 1/1

- ○ Level based
- ○ Network & Zone based
- ◉ Host & Network based ✓
- ○ Zone based

✓ Which of the following is the primary function of an Intrusion Detection System (IDS)? *1/1

- ○ To actively block malicious traffic
- ◉ To monitor network traffic and alert on suspicious activity ✓
- ○ To encrypt all network traffic
- ○ To automatically patch vulnerabilities

✓ You want to examine activity on a small server, but have no other actions taken. Which should you implement? *1/1

- ◉ -HIDS ✓
- ○ -NIDS
- ○ -HIPS
- ○ -NIPS

✓ What are the characteristics of Host based IDS? * 1/1

- ○ The host operating system logs in the audit information
- ○ Logs includes logins, file opens and program executions
- ○ Logs are analysed to detect tails of intrusion
- ◉ All of the mentioned ✓

✓ Which of the following is an example of an IPS? * 1/1

- ◉ Snort ✓
- ○ Wireshark
- ○ Nmap
- ○ Metasploit

✓ Your boss would like to implement a device that would monitor traffic and turn off processes and reconfigure permissions as necessary. Which tool would you use for this task? *1/1

- ○ A firewall
- ○ A sniffer
- ○ A passive HIDS
- ◉ An active HIDS ✓

✓ What is one difference between the misuse model and the anomaly IDS models? 1/1

- ( ) Misuse model require knowledge of normal activity, whereas the anomaly model does not
- (•) Anomaly models require knowledge of normal activity, whereas the misuse model does not ✓
- ( ) Anomaly models are based on patterns of suspicious activity
- ( ) Anomaly model-based systems suffer from many false positives

✓ What do the letters TCP stand for? * 1/1

- ( ) Trade Control Protocol
- ( ) Transfer Centre Protocol
- (•) Transmission Control Protocol ✓
- ( ) Transfer Control Protocol

✓ An action that violates a specific policy and is detected is the result of: * 1/1

- ( ) An anomaly detection model
- ( ) An IPS
- (•) A misuse detection model ✓
- ( ) Analysis Engine

✓ Which reflects a ping of death? * 1/1

- (●) A large ICMP packet ✓
- ( ) Ports scanning of ICMP packets
- ( ) DOS attacking using ICMP
- ( ) A series of runt ICMP packets

✓ Which is an open source IDS/IPS? * 1/1

- ( ) Nmap
- ( ) SIEM
- (●) Snort ✓
- ( ) Tcpdumb

This content is neither created nor endorsed by Google. - Contact form owner - Terms of Service - Privacy Policy

Does this form look suspicious? Report

Google Forms