Capstone Checkpoint 4.1 decomposed w/reasoning

Oracle, vector, and hybrid experiment comparison. Generated 2026-09-15 08:05 EDT.

13	4	247	19	0
Included runs	Configurations	Question-runs	Questions	Legacy runs excluded

Summary

The highest observed mean quality score was 0.763 for vs_k7_md_decomposed_query across 4 run(s). Quality assigns 1 to pass, 0.5 to partial, and 0 to fail.

The highest observed mean designated-source recall was 89.9% for vs_k7_markdown_base. Article recall is recomputed from the required and retrieved article names in every CSV.

The highest task-family attention score was 62.5 for Exhaustive list or time filter under vs_k7_md_decomposed_query. Attention is 100 x (1 - grouped quality), so higher values identify larger observed improvement opportunities.

Answer outcomes



Configuration	Runs	Cases	Pass	Partial	Fail	Quality	Run SD	Article recall	Full source coverage	Mean context
oracle_markdown_base	3	57	73.7%	0.0%	26.3%	0.737	0.043	n/a	n/a	102.0k
vs_k7_markdown_base	3	57	71.9%	7.0%	21.1%	0.754	0.033	89.9%	78.9%	207.1k
vs_k5_md_decomposed_query	3	57	71.9%	3.5%	24.6%	0.737	0.037	84.8%	73.7%	180.7k

Configuration	Runs	Cases	Pass	Partial	Fail	Quality	Run SD	Article recall	Full source coverage	Mean context
vs_k7_md_decomposed_query	4	76	73.7%	5.3%	21.1%	0.763	0.037	89.6%	80.3%	240.5k

Percentages aggregate all question-runs within a configuration. Run SD is the standard deviation of mean quality across repeated runs.

Retrieval diagnostics

Designated-source coverage



The analyzer recomputes recall after removing only final .txt and .html suffixes. This corrects historical .html.txt versus .html mismatches. Designated-source recall is diagnostic: alternative retrieved articles may still contain sufficient evidence.

Outcome and source-coverage combinations

Configuration	Pass, full	Pass, incomplete	Non-pass, full	Non-pass, missing
vs_k5_md_decomposed_query	31	10	11	5
vs_k7_markdown_base	35	6	10	6
vs_k7_md_decomposed_query	47	9	14	6

A non-pass result with full designated-source recall points toward answer synthesis, context noise, table interpretation, or judge behavior. A non-pass result with a missing designated source is consistent with a retrieval recall problem, but manual review is still required.

Per-question comparison

Cells show the mean quality score for each question and configuration across repeated runs.

	oracle_markdown_base	vs_k7_markdown_base	vs_k5_md_decomposed_query	vs_k7_md_decomposed_query
GT01	**1.00**	**1.00**	**1.00**	**1.00**
GT02	**1.00**	**0.83**	**1.00**	**0.88**
GT03	**0.00**	**0.00**	**0.00**	**0.00**
GT04	**1.00**	**1.00**	**1.00**	**1.00**
GT05	**1.00**	**1.00**	**1.00**	**1.00**
GT06	**1.00**	**1.00**	**1.00**	**1.00**
GT07	**0.33**	**1.00**	**0.33**	**0.88**
GT08	**0.00**	**0.33**	**0.33**	**0.38**
GT09	**1.00**	**1.00**	**1.00**	**1.00**
GT10	**0.00**	**0.00**	**0.00**	**0.00**
GT11	**0.00**	**0.00**	**0.00**	**0.00**
GT12	**0.67**	**1.00**	**1.00**	**1.00**
GT13	**1.00**	**0.83**	**0.83**	**1.00**
GT14	**1.00**	**1.00**	**1.00**	**1.00**
GT15	**1.00**	**1.00**	**1.00**	**1.00**
GT16	**1.00**	**0.33**	**0.67**	**0.38**
GT17	**1.00**	**1.00**	**1.00**	**1.00**
GT18	**1.00**	**1.00**	**1.00**	**1.00**
GT19	**1.00**	**1.00**	**0.83**	**1.00**

Fail (0) Partial (0.5) Pass (1)

Question	oracle_markdown_base	vs_k7_markdown_base	vs_k5_md_decomposed_query	vs_k7_md_decomposed_query
GT01	1.000	1.000	1.000	1.000
GT02	1.000	0.833	1.000	0.875
GT03	0.000	0.000	0.000	0.000
GT04	1.000	1.000	1.000	1.000
GT05	1.000	1.000	1.000	1.000
GT06	1.000	1.000	1.000	1.000
GT07	0.333	1.000	0.333	0.875
GT08	0.000	0.333	0.333	0.375
GT09	1.000	1.000	1.000	1.000
GT10	0.000	0.000	0.000	0.000
GT11	0.000	0.000	0.000	0.000
GT12	0.667	1.000	1.000	1.000
GT13	1.000	0.833	0.833	1.000
GT14	1.000	1.000	1.000	1.000
GT15	1.000	1.000	1.000	1.000
GT16	1.000	0.333	0.667	0.375
GT17	1.000	1.000	1.000	1.000
GT18	1.000	1.000	1.000	1.000
GT19	1.000	1.000	0.833	1.000

Per-question article recall

Fraction of each question's designated source articles that appeared in the retrieved set (retriever configurations only). 1.00 = every gold article retrieved; lower values mark a retrieval miss — usually a multi-source question.

Question	vs_k7_markdown_base	vs_k5_md_decomposed_query	vs_k7_md_decomposed_query
GT01	100.0%	100.0%	100.0%

Question	vs_k7_markdown_base	vs_k5_md_decomposed_query	vs_k7_md_decomposed_query
GT02	100.0%	100.0%	100.0%
GT03	33.3%	11.1%	16.7%
GT04	100.0%	100.0%	100.0%
GT05	100.0%	100.0%	100.0%
GT06	100.0%	100.0%	100.0%
GT07	100.0%	100.0%	100.0%
GT08	100.0%	100.0%	100.0%
GT09	50.0%	100.0%	100.0%
GT10	100.0%	100.0%	100.0%
GT11	100.0%	100.0%	100.0%
GT12	100.0%	66.7%	91.7%
GT13	100.0%	100.0%	100.0%
GT14	75.0%	83.3%	81.2%
GT15	100.0%	83.3%	100.0%
GT16	50.0%	50.0%	62.5%
GT17	100.0%	66.7%	50.0%
GT18	100.0%	66.7%	100.0%
GT19	100.0%	83.3%	100.0%

Performance by task type

The 18 original category labels are consolidated into five task families so each group contains multiple questions. The attention score ranks observed improvement opportunities for the strongest retrieval configuration; it is not a statistical significance test.



Task family	Questions	Baseline quality	Attention	Fail	Oracle quality	Oracle gap	Article recall
Exhaustive list or time filter	5	0.375	62.5	60.0%	0.267	-0.108	83.3%
Evidence selection or explanation	3	0.750	25.0	16.7%	0.667	-0.083	100.0%
Entity relationship or historical synthesis	6	0.896	10.4	8.3%	0.944	+0.049	80.9%
Cross-table quantitative reasoning	2	1.000	0.0	0.0%	1.000	+0.000	100.0%
Direct fact or table lookup	3	1.000	0.0	0.0%	1.000	+0.000	100.0%

Baseline quality and failure rate use vs_k7_md_decomposed_query. Oracle gap equals oracle quality minus baseline quality: a large positive gap is consistent with a retrieval or context-selection opportunity, while low oracle quality indicates that the difficulty persists even when the designated articles are supplied.

Performance by source scope

Source scope groups questions by the number of designated articles. It tests whether the number of sources, rather than the reasoning operation, explains performance.

	oracle_markdown_base	vs_k7_markdown_base	vs_k5_md_decomposed_query	vs_k7_md_decomposed_query
1 article	**0.667**	**0.727**	**0.682**	**0.739**
2 articles	**1.000**	**0.867**	**0.900**	**0.875**
3+ articles	**0.556**	**0.667**	**0.667**	**0.667**

Source scope	Configuration	Questions	Question-runs	Pass	Partial	Fail	Quality	Article recall
1 article	oracle_markdown_base	11	33	66.7%	0.0%	33.3%	0.667	n/a
2 articles	oracle_markdown_base	5	15	100.0%	0.0%	0.0%	1.000	n/a
3+ articles	oracle_markdown_base	3	9	55.6%	0.0%	44.4%	0.556	n/a
1 article	vs_k7_markdown_base	11	33	69.7%	6.1%	24.2%	0.727	100.0%
2 articles	vs_k7_markdown_base	5	15	80.0%	13.3%	6.7%	0.867	80.0%
3+ articles	vs_k7_markdown_base	3	9	66.7%	0.0%	33.3%	0.667	69.4%
1 article	vs_k5_md_decomposed_query	11	33	66.7%	3.0%	30.3%	0.682	97.0%
2 articles	vs_k5_md_decomposed_query	5	15	86.7%	6.7%	6.7%	0.900	76.7%
3+ articles	vs_k5_md_decomposed_query	3	9	66.7%	0.0%	33.3%	0.667	53.7%
1 article	vs_k7_md_decomposed_query	11	44	70.5%	6.8%	22.7%	0.739	100.0%
2 articles	vs_k7_md_decomposed_query	5	20	85.0%	5.0%	10.0%	0.875	82.5%
3+ articles	vs_k7_md_decomposed_query	3	12	66.7%	0.0%	33.3%	0.667	63.2%

Question-runs are repeated measurements of the listed unique questions. Source-scope groups remain small and mix different task families, so this view should be used as a diagnostic rather than a general performance estimate.

Run-to-run variability

Each dot is one run; the larger dot is the configuration mean.



Run	Configuration	Cases	Pass	Partial	Fail	Quality	Article recall	Full source coverage
magical_curry	oracle_markdown_base	19	15	0	4	0.789	n/a	n/a
loving_cerf	oracle_markdown_base	19	13	0	6	0.684	n/a	n/a
zen_andreessen	oracle_markdown_base	19	14	0	5	0.737	n/a	n/a
zealous_ritchie	vs_k7_markdown_base	19	14	1	4	0.763	89.9%	78.9%
relaxed_musk	vs_k7_markdown_base	19	12	3	4	0.711	89.9%	78.9%
elastic_adleman	vs_k7_markdown_base	19	15	0	4	0.789	89.9%	78.9%
loving_torvalds	vs_k5_md_decomposed_query	19	15	0	4	0.789	82.5%	73.7%
magical_kernighan	vs_k5_md_decomposed_query	19	13	1	5	0.711	86.4%	73.7%
mystifying_dijkstra	vs_k5_md_decomposed_query	19	13	1	5	0.711	85.5%	73.7%
practical_adleman	vs_k7_md_decomposed_query	19	15	1	3	0.816	88.2%	78.9%
pensive_shannon	vs_k7_md_decomposed_query	19	13	1	5	0.711	93.9%	89.5%
admiring_matsumoto	vs_k7_md_decomposed_query	19	14	1	4	0.763	88.2%	78.9%

Run	Configuration	Cases	Pass	Partial	Fail	Quality	Article recall	Full source coverage
amazing_gosling	vs_k7_md_decomposed_query	19	14	1	4	0.763	88.2%	73.7%

Methodology and limitations

Scoring

Pass is assigned 1, partial is assigned 0.5, and fail is assigned 0. The quality score is the arithmetic mean across the applicable question-runs. Pass, partial, and fail percentages are also reported separately so the weighted score does not hide the underlying verdicts.

Task-family attention

The attention score is 100 multiplied by one minus grouped quality. A score of 66 means that the group lost 66% of the available quality points under the selected retrieval baseline. It is a prioritization aid, not an estimate of population-wide failure risk. Task-family and source-scope results must be read with their unique-question counts because the evaluation set contains only 19 questions.

Configuration grouping

Runs are grouped by a CSV experiment_name or config_name when one is present. If no explicit name is present, grouping falls back to evaluation mode, context source, retriever kind and label, Top K, hybrid weights, answer model, and judge model. RAGAS-generated filenames identify individual runs but do not define configurations.

Framework compatibility

Legacy oracle runs stored under pass_fail_only directories are excluded by default because they could not produce partial verdicts. Use --include-binary-oracle only for a labeled historical appendix, not for a direct three-level score comparison.

Interpretation limits

An LLM produced the answers and another LLM applied the rubric, so repeated runs can vary. Article recall measures coverage of designated ground-truth sources, not every possible supporting source. Full article recall does not prove that the model used the evidence correctly, and missing a designated source does not prove the context was insufficient when another article contains equivalent evidence. Differences between configurations should be interpreted together with run counts and per-question behavior.

Included experiment files

Run file
experiments/admiring_matsumoto.csv
experiments/amazing_gosling.csv
experiments/elastic_adleman.csv
experiments/loving_cerf.csv
experiments/loving_torvalds.csv
experiments/magical_curry.csv
experiments/magical_kernighan.csv
experiments/mystifying_dijkstra.csv
experiments/pensive_shannon.csv
experiments/practical_adleman.csv
experiments/relaxed_musk.csv

Run file
experiments/zealous_ritchie.csv
experiments/zen_andreessen.csv

Excluded files

Run file	Reason
datasets/wikipedia_GT_advanced_inputs.csv	missing columns: ['score']
datasets/wikipedia_GT_oracle_inputs.csv	duplicate of datasets/wikipedia_GT_advanced_inputs.csv
datasets/wikipedia_GT_retrieval_inputs.csv	duplicate of datasets/wikipedia_GT_advanced_inputs.csv