

```

/* The following code example is taken from the book
 * "The C++ Standard Library – A Tutorial and Reference, 2nd Edition"
 * by Nicolai M. Josuttis, Addison-Wesley, 2012
 *
 * (C) Copyright Nicolai M. Josuttis 2012.
 * Permission to copy, use, modify, sell and distribute this software
 * is granted provided this copyright notice appears in all copies.
 * This software is provided "as is" without express or implied
 * warranty, and with no claim as to its suitability for any purpose.
 */
#include "algotstuff.hpp"
using namespace std;

int main()
{
    vector<int> coll1;
    list<int> coll2;

    INSERT_ELEMENTS(coll1,1,9);
    PRINT_ELEMENTS(coll1,"coll1:  ");

    // square each element
    transform (coll1.cbegin(), coll1.cend(),           // first source range
               coll1.cbegin(),                          // second source range
               coll1.begin(),                          // destination range
               multiplies<int>());                      // operation
    PRINT_ELEMENTS(coll1,"squared: ");

    // add each element traversed forward with each element traversed backward
    // and insert result into coll2
    transform (coll1.cbegin(), coll1.cend(),           // first source range
               coll1.crbegin(),                        // second source range
               back_inserter(coll2),                  // destination range
               plus<int>());                          // operation
    PRINT_ELEMENTS(coll2,"coll2:  ");

    // print differences of two corresponding elements
    cout << "diff:  ";
    transform (coll1.cbegin(), coll1.cend(),           // first source range
               coll2.cbegin(),                        // second source range
               ostream_iterator<int>(cout, " "),      // destination range
               minus<int>());                          // operation
    cout << endl;
}

```