```
/* The following code example is taken from the book
 * "The C++ Standard Library - A Tutorial and Reference, 2nd Edition"
 * by Nicolai M. Josuttis, Addison-Wesley, 2012
 * (C) Copyright Nicolai M. Josuttis 2012.
 st Permission to copy, use, modify, sell and distribute this software
* is granted provided this copyright notice appears in all copies.
* This software is provided "as is" without express or implied
 * warranty, and with no claim as to its suitability for any purpose.
#ifndef ICSTRING HPP
#define ICSTRING HPP
#include <string>
#include <iostream>
#include <cctype>
// replace functions of the standard char traits char
// so that strings behave in a case-insensitive way
struct ignorecase_traits : public std::char_traits<char> {
    // return whether c1 and c2 are equal
    static bool eq(const char& c1, const char& c2) {
        return std::toupper(c1) == std::toupper(c2);
    // return whether c1 is less than c2
    static bool lt(const char& cl, const char& c2) {
        return std::toupper(c1) < std::toupper(c2);
    // compare up to n characters of s1 and s2
    static int compare(const char* s1, const char* s2,
                         std::size t n) {
        for (std::size t i=0; i < n; ++i) {
            if (!eq(s1[i], s2[i])) {
                 return lt(s1[i], s2[i])?-1:1;
        return 0;
    // search c in s
    static const char* find(const char* s, std::size_t n,
                              const char& c) {
        for (std::size_t i=0; i<n; ++i) {
    if (eq(s[i],c)) {
                 return &(s[i]);
        return 0:
}:
// define a special type for such strings
typedef std::basic_string<char, ignorecase_traits> icstring;
// define an output operator
// because the traits type is different from that for std::ostream
inline
```

```
std::ostream& operator << (std::ostream& strm, const icstring& s)
{
    // simply convert the icstring into a normal string
    return strm << std::string(s.data(), s.length());
}
#endif // ICSTRING_HPP</pre>
```