```
/* The following code example is taken from the book
 * "The C++ Standard Library - A Tutorial and Reference, 2nd Edition"
 * by Nicolai M. Josuttis, Addison-Wesley, 2012
 * (C) Copyright Nicolai M. Josuttis 2012.
 * Permission to copy, use, modify, sell and distribute this software * is granted provided this copyright notice appears in all copies. * This software is provided "as is" without express or implied
 * warranty, and with no claim as to its suitability for any purpose.
 */
#include <iostream>
#include <list>
#include <algorithm>
#include <iterator>
#include "print.hpp"
using namespace std;
class IntSequence {
  private:
    int value;
  public:
    // constructor
    IntSequence (int initialValue)
     : value(initialValue) {
    // "function call"
int operator() () {
         return value++;
};
int main()
     list <int> coll;
    IntSequence seq(1);
                             // integral sequence starting with 1
    // insert values from 1 to 4
     // - pass function object by reference
             so that it will continue with 5
    generate_n \langle back_insert_iterator \langle list \langle int \rangle \rangle,
                  int, IntSequence&>(back inserter(coll),
                                         4,
                                                  // number of elements
                                         seq);
                                                  // generates values
    PRINT ELEMENTS (coll):
    // insert values from 42 to 45
    generate_n (back_inserter(coll),
                                                  // start
                                                  // number of elements
// generates values
                   IntSequence (42));
    PRINT ELEMENTS (col1);
    // continue with first sequence
    // - pass function object by value
             so that it will continue with 5 again
    generate n (back inserter(coll),
                                            // start
```

```
4,  // number of elements seq);  // generates values PRINT_ELEMENTS(coll);

// continue with first sequence again generate_n (back_inserter(coll),  // start  // number of elements seq);  // generates values PRINT_ELEMENTS(coll);
}
```