

Bundled Crossings Revisited

Steven Chaplick, Thomas C. van Dijk, Myroslav Kryven,
Alexander Wolff

Julius-Maximilians-Universität Würzburg, Germany

Ji-won Park

KAIST, Daejeon, Republic of Korea

Alexander Ravsky

Pidstryhach Institute for Applied Problems of Mechanics and Mathematics,

Nat. Acad. Sciences of Ukraine, Lviv, Ukraine


Motivation

Ideally drawings of graphs should avoid crossings ...

Motivation

Ideally drawings of graphs should avoid crossings ...

Planar graphs can be drawn without crossings




Motivation

Ideally drawings of graphs should avoid crossings ...

Planar graphs can be drawn without crossings



but many graphs cannot be drawn without crossings.



Motivation

Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.



Classical problem in Graph Drawing:
How to minimize the number of crossings?



Motivation

Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.

Classical problem in Graph Drawing:
How to minimize the number of crossings?





Motivation

Ideally drawings of graphs should avoid crossings ...

Planar graphs can be drawn without crossings

but many graphs cannot be drawn without crossings.



Classical problem in Graph Drawing:
How to minimize the number of crossings?



Motivation

Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.

Classical problem in Graph Drawing:
How to minimize the number of crossings?





Motivation

Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.

Classical problem in Graph Drawing:
How to minimize the number of crossings?


Lots of different variants.



Motivation




Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.

Classical problem in Graph Drawing:
How to minimize the number of crossings?



Lots of different variants.
Our main result concerns
simple circular layouts.


simple
avoids:



Motivation


Ideally drawings of graphs should avoid crossings ...
Planar graphs can be drawn without crossings
but many graphs cannot be drawn without crossings.

Classical problem in Graph Drawing:
How to minimize the number of crossings?





Lots of different variants.
Our main result concerns
simple circular layouts.


simple avoids:

Two diagrams illustrating graph layouts. The left diagram shows a simple layout with two vertices and two edges that do not cross. The right diagram shows a non-simple layout with two vertices and two edges that cross each other.

This talk concerns *bundled crossings*, def'd next.




Motivation




There is an FPT algorithm for deciding whether a graph admits a circular layout with k crossings. [Bannister, Eppstein '14]

Motivation




[Holten '06]

Bundle the
drawing




There is an FPT algorithm for deciding whether a graph admits a circular layout with k crossings.[Bannister, Eppstein '14]

Motivation




[Holten '06]

Bundle the
drawing



There is an FPT algorithm for deciding whether a graph admits a circular layout with k crossings. [Bannister, Eppstein '14]

Motivation




[Holten '06]

Bundle the
drawing



F: [Fink et al. '16]


A: [Alam et al. '16]



Minimize crossings of bundles instead of edges!


There is an FPT algorithm for deciding whether a graph admits a circular layout with k crossings. [Bannister, Eppstein '14]

Motivation



[Holten '06]

Bundle the
drawing



F: [Fink et al. '16]

A: [Alam et al. '16]


Minimize crossings of bundles instead of edges!

gen. layouts: NP-c for fixed [F] and variable [A] embeddings.

fixed embedding: 10-apx for circular, and $O(1)$ -apx for gen. layouts [F]


There is an FPT algorithm for deciding whether a graph admits a circular layout with k crossings. [Bannister, Eppstein '14]

Motivation



[Holten '06]

Bundle the
drawing



F: [Fink et al. '16]

A: [Alam et al. '16]

Minimize crossings of bundles instead of edges!

gen. layouts: NP-c for fixed [F] and variable [A] embeddings.


fixed embedding: 10-apx for circular, and $O(1)$ -apx for gen. layouts [F]

Ques.

Is there an FPT algorithm for deciding whether a graph admits a circular layout with k **bundled crossings**? [A]

Bundled Crossing


A **bundle** is a set of pieces of edges that travel in parallel in the drawing.



Bundled Crossing

A **bundle** is a set of pieces of edges that travel in parallel in the drawing.


Outer edges of a bundle are called **frame edges**



Bundled Crossing

A **bundle** is a set of pieces of edges that travel in parallel in the drawing.

Outer edges of a bundle are called **frame edges**




Bundled Crossing

A **bundle** is a set of pieces of edges that travel in parallel in the drawing.

Outer edges of a bundle are called **frame edges**

A **bundled crossing** is a set of crossings inside the **region** bounded by the frame edges.




Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .

Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .

Thm. Deciding whether $bc^\circ(G) = k$ is FPT in k .



resolves an open problem of [Alam et al. 2016]



Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .

Thm. Deciding whether $bc^\circ(G) = k$ is FPT in k .

└ resolves an open problem of [Alam et al. 2016]

Remark on simple vs. non-simple: consider $K_{3,3}$



Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .



Thm. Deciding whether $bc^\circ(G) = k$ is FPT in k .

└ resolves an open problem of [Alam et al. 2016]

Remark on simple vs. non-simple: consider $K_{3,3}$

Non-simple \rightsquigarrow orientable graph genus [Alam et al. 2016]

... more on this soon



Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .

Thm. Deciding whether $bc^\circ(G) = k$ is FPT in k .

↳ resolves an open problem of [Alam et al. 2016]

Other results (not covered in this talk, see the paper!):

Bundled Crossing Minimization

Def. For a given graph G
the circular bundled crossing number $bc^\circ(G)$ of G is
the minimum number of bundled crossings
over all possible bundlings
of all possible simple circular layouts of G .

resolves open
problem of
[Fink et al.;
2016]

Thm. Deciding whether $bc^\circ(G) = k$ is FPT in k .

↳ resolves an open problem of [Alam et al. 2016]


Other results (not covered in this talk, see the paper!):

Thm. For general layouts, on inputs (G, k) , deciding whether G has a simple drawing with k bundled crossings is NPc. For non-simple, this is FPT in k (via genus).

Obs. For circular layouts, on inputs (G, k) , deciding whether G has a (non-simple) circular drawing with k bundled crossings is FPT in k (via genus).


Structure of a drawing

Consider a drawing
with k bundled crossings
and observe that:




Structure of a drawing

Consider a drawing
with k bundled crossings
and observe that:




- At most k bundled crossings \implies at most $4k$ frame edges.

Structure of a drawing



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**


Structure of a drawing



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**

Structure of a drawing


Consider a drawing
with k bundled crossings
and observe that:



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**

Structure of a drawing


Consider a drawing
with k bundled crossings
and observe that:



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**
- and subdivide the surface into **regions**.

Structure of a drawing


Consider a drawing with k bundled crossings and observe that:



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**
- and subdivide the surface into **regions**.
- Other edges/vertices of the graph partitioned into these regions.

Structure of a drawing


Consider a drawing with k bundled crossings and observe that:



- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**
- and subdivide the surface into **regions**.
- Other edges/vertices of the graph partitioned into these regions.
- The graph induced by edges inside a single region has a special outerplanar drawing.

Structure of a drawing

What if a region has
a bridge and a tunnel
corresponding to
the same bundled crossing?




- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**
- and subdivide the surface into **regions**.
- Other edges/vertices of the graph partitioned into these regions.
- The graph induced by edges inside a single region has a special outerplanar drawing.

Structure of a drawing

What if a region has a bridge and a tunnel corresponding to the same bundled crossing?

Lem. Each region is a topological disk.




- At most k bundled crossings \implies at most $4k$ frame edges.
- We can “lift” the drawing onto a **surface of genus k**
- and subdivide the surface into **regions**.
- Other edges/vertices of the graph partitioned into these regions.
- The graph induced by edges inside a single region has a special outerplanar drawing.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a **good** outerplanar drawing.

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .




- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a **good** outerplanar drawing.

MSO₂

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .



But what is MSO_2 again?


- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a **good** outerplanar drawing.

MSO_2

The Algorithm

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .



But what is MSO_2 again?

- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a **good** outerplanar drawing.

MSO_2

Monadic Second Order Logic (MSO₂)

PARTITION($E; E_0, \dots, E_\gamma$) =

$$(\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg (e \in E_i \wedge e \in E_j) \right) \right].$$

Monadic Second Order Logic (MSO₂)

PARTITION($E; E_0, \dots, E_\gamma$) =

$$(\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg(e \in E_i \wedge e \in E_j) \right) \right].$$

Thm (Courcelle): If a property P is expressed as $\varphi \in \text{MSO}_2$, then for every graph G with treewidth at most t , P can be tested in time $O(f(t, |\varphi|)(n + m))$ for a computable function f .

Monadic Second Order Logic (MSO₂)

PARTITION($E; E_0, \dots, E_\gamma$) =

$$(\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg(e \in E_i \wedge e \in E_j) \right) \right].$$

Thm (Courcelle): If a property P is expressed as $\varphi \in \text{MSO}_2$, then for every graph G with **treewidth** at most t , P can be tested in time $O(f(t, |\varphi|)(n + m))$ for a computable function f .

Monadic Second Order Logic (MSO₂)

$$\text{PARTITION}(E; E_0, \dots, E_\gamma) =$$
$$(\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg(e \in E_i \wedge e \in E_j) \right) \right].$$

Thm (Courcelle): If a property P is expressed as $\varphi \in \text{MSO}_2$, then for every graph G with **treewidth** at most t , P can be tested in time $O(f(t, |\varphi|)(n + m))$ for a computable function f .

↓

Since our regions induce outerplanar graphs, we have treewidth at most $8k + 2$ where k is the number of bundled crossings.

Monadic Second Order Logic (MSO₂)

$$\text{PARTITION}(E; E_0, \dots, E_\gamma) = \\ (\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg(e \in E_i \wedge e \in E_j) \right) \right].$$

Thm (Courcelle): If a property P is expressed as $\varphi \in \text{MSO}_2$, then for every graph G with treewidth at most t , P can be tested in time $O(f(t, |\varphi|)(n + m))$ for a computable function f .

But, what about?

- Test graphs in each region for a *good* outerplanar drawing.

Monadic Second Order Logic (MSO₂)

$$\text{PARTITION}(E; E_0, \dots, E_\gamma) = \\ (\forall e \in E) \left[\left(\bigvee_{i=0}^{\gamma} e \in E_i \right) \wedge \left(\bigwedge_{i \neq j} \neg(e \in E_i \wedge e \in E_j) \right) \right].$$

Thm (Courcelle): If a property P is expressed as $\varphi \in \text{MSO}_2$, then for every graph G with treewidth at most t , P can be tested in time $O(f(t, |\varphi|)(n + m))$ for a computable function f .

But, what about?

- Test graphs in each region for a *good* outerplanar drawing.

This can be stated in MSO₂ via a mechanism of *MSO-definition schemes*, and the *Backwards Translation Theorem* [Courcelle, Engelfriet; 2012]

Monadic Second Order Logic (MSO₂)

Theorem 7.10 (Backwards Translation Theorem) Let \mathcal{D} be a k -copying C_r MS-definition scheme of type $\mathcal{R} \rightarrow \mathcal{R}'$ with parameters \mathcal{W} . Let \mathcal{X} be a finite set of set variables and $\mathcal{Y} = \{y_i\}_{i \in \mathbb{N}}$ be a set of first-order variables. For every $\beta \in C_r\text{MS}(\mathcal{R}', \mathcal{X} \cup \mathcal{Y})$ and $\mathbf{i} \in \mathbb{N}$, one can construct a formula $\beta_{\mathbf{i}}^{\mathcal{D}} \in C_r\text{MS}(\mathcal{R}, \mathcal{W} \cup \mathcal{X}^{(k)} \cup \mathcal{Y})$ such that for every $S \in \text{STR}^c(\mathcal{R})$, every \mathcal{W} -assignment γ , every $\mathcal{X}^{(k)}$ -assignment η , and every \mathcal{Y} -assignment μ , all of them in S , we have:

$(S, \gamma \cup \eta \cup \mu) \models \beta_{\mathbf{i}}^{\mathcal{D}}$ if and only if
 $\hat{\mathcal{D}}(S, \gamma)$ is defined,
 $\eta^{[k]} \cup \mu_{\mathbf{i}}$ is a \mathcal{Y} -assignment in $\hat{\mathcal{D}}(S, \gamma)$, and
 $(\hat{\mathcal{D}}(S, \gamma), \eta^{[k]} \cup \mu_{\mathbf{i}}) \models \beta$.

The quantifier-height of $\beta_{\mathbf{i}}^{\mathcal{D}}$ is at most $k \cdot qh(\beta) + qh(\mathcal{D}) + 1$. □


This can be stated in MSO₂ via a mechanism of *MSO-definition schemes*, and the *Backwards Translation Theorem* [Courcelle, Engelfriet; 2012]

Testing whether $bc^\circ = k$

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .

Runtime:



- Guess the drawing of at most $4k$ frame edges and their bundling.
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a *good* outerplanar drawing.


Testing whether $bc^\circ = k$

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .

Runtime:

$$2^{O(k^2)}$$



- Guess the drawing of at most $4k$ frame edges and their bundling. $2^{O(k^2)}$
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions.
 - Test graphs in each region for a *good* outerplanar drawing.


Testing whether $bc^\circ = k$

Thm.

Deciding whether $bc^\circ(G) = k$ is FPT in k .

Runtime:

$$2^{O(k^2)} f(k) (|V| + |E|)$$




- Guess the drawing of at most $4k$ frame edges and their bundling. $2^{O(k^2)}$
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions. MSO_2
 - Test graphs in each region for a *good* outerplanar drawing.

Testing whether $bc^\circ = k$

Recall that for correctness of the algorithm we need to show that

Thm. Each region is a topological disk.




- Guess the drawing of at most $4k$ frame edges and their bundling. $2^{O(k^2)}$
- Construct a **surface of genus k** and a subdivision into **regions**.
 - Map the edges of the graph to the guessed frame edges.
 - Partition the edges and vertices into the regions. MSO_2
 - Test graphs in each region for a *good* outerplanar drawing.

A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.

Proof.




Stick to the right!

A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.


Proof.



A region is a topological disk

Lem. Each region is a topological disk.

Proof.




A region is a topological disk

Lem. Each region is a topological disk.

Proof.


hurray!



A region is a topological disk

Lem. Each region is a topological disk.

Proof.



A region is a topological disk


Lem. Each region is a topological disk.

Proof.

Cannot
be completed!



follows from [Arroyo,
Bensmail, Richter; 2018]



A region is a topological disk


Lem. Each region is a topological disk.

Proof.

Cannot
be completed!



follows from [Arroyo,
Bensmail, Richter; 2018]



A region is a topological disk


Lem. Each region is a topological disk.

Proof.

Cannot
be completed!



follows from [Arroyo,
Bensmail, Richter; 2018]



Open Questions

We have provided an FPT algorithm for deciding whether $bc^\circ(G) = k$.

Since our algorithm is based on MSO_2 the runtime is

Open Questions

We have provided an FPT algorithm for deciding whether $bc^\circ(G) = k$.

Since our algorithm is based on MSO_2 the runtime is



$$(k) \times (|V| + |E|)$$

Open Questions

We have provided an FPT algorithm for deciding whether $bc^\circ(G) = k$.

Since our algorithm is based on MSO_2 the runtime is



$$(k) \times (|V| + |E|)$$

Question 1

Is there a faster FPT algorithm for deciding whether $bc^\circ(G) = k$?

Open Questions

We have provided an FPT algorithm for deciding whether $bc^\circ(G) = k$.

Since our algorithm is based on MSO_2 the runtime is



$$(k) \times (|V| + |E|)$$

Question 1

Is there a faster FPT algorithm for deciding whether $bc^\circ(G) = k$?

Question 2

Is deciding whether $bc^\circ(G) = k$ NP-hard?

Open Questions

We have provided an FPT algorithm for deciding whether $bc^\circ(G) = k$.

Since our algorithm is based on MSO_2 the runtime is



$$(k) \times (|V| + |E|)$$

Question 1

Is there a faster FPT algorithm for deciding whether $bc^\circ(G) = k$?

Question 2

Is deciding whether $bc^\circ(G) = k$ NP-hard?

Question 3

Is bundle crossing min. also FPT for general simple layouts?