

```
DROP TABLE QIngredientIngredientOrder
DROP TABLE QMenuIngredient
DROP TABLE QMenuOrder
DROP TABLE Pickup
DROP TABLE Delivery
DROP TABLE PhoneOrder
DROP TABLE WalkInOrder
DROP TABLE OrderOnly
DROP TABLE OrderPayRecord
DROP TABLE InStoreShift
DROP TABLE DriverShift
DROP TABLE InstoreStaff
DROP TABLE DriverStaff
DROP TABLE BankDetails
DROP TABLE InstorePay
DROP TABLE DriverPay
DROP TABLE CPhone
DROP TABLE Customer
DROP TABLE IngredientOrder
DROP TABLE Supplier
DROP TABLE Ingredient
DROP TABLE MenuItem
go
```

```
-- Create the MenuItem table
```

```
CREATE TABLE MenuItem (
    ItemCode VARCHAR(10) NOT NULL PRIMARY KEY,
    Name VARCHAR(50),
    Size VARCHAR(20),
    Description TEXT,
    Price DECIMAL(10, 2)
);
go
```

```
-- Create the Ingredient table
```

```
CREATE TABLE Ingredient (
    IngredientCode VARCHAR(10) NOT NULL PRIMARY KEY,
    Name VARCHAR(50),
    Type VARCHAR(20),
    Description TEXT,
    CurrentStockLevel VARCHAR(20),
    SuggestedStockLevel VARCHAR(20),
    ReorderLevel VARCHAR(20)
);
go
```

```
-- Create the Supplier table
```

```
CREATE TABLE Supplier (
    SupplierID VARCHAR(10) NOT NULL PRIMARY KEY,
    Name VARCHAR(50),
    Phone VARCHAR(20),
    Street VARCHAR(20),
    City VARCHAR(10),
    Postcode VARCHAR(4),
    Email VARCHAR(30)
);
go
```

```
-- Create the IngredientOrder table
```

```

CREATE TABLE IngredientOrder (
    IngredientOrderNo VARCHAR(10) NOT NULL PRIMARY KEY,
    TotalAmount DECIMAL(10, 2),
    DateIssued Date,
    DateSupplied Date,
    Status VARCHAR(50),
    Description TEXT,
    SupplierID VARCHAR(10),
    FOREIGN Key (SupplierID) REFERENCES Supplier(SupplierID) ON UPDATE CASCADE ON
DELETE NO ACTION
);
go

-- Create the Customer table
CREATE TABLE Customer (
    CustomerID VARCHAR(10) NOT NULL PRIMARY KEY,
    FirstName VARCHAR(20),
    LastName VARCHAR(10),
    Street VARCHAR(20),
    City VARCHAR(10),
    Postcode VARCHAR(4),

);
go

-- Create the CPhone table
CREATE TABLE CPhone (
    Phone VARCHAR(14) PRIMARY KEY,
    CustomerID VARCHAR(10),
    FOREIGN KEY (CustomerID) REFERENCES Customer(CustomerID) ON UPDATE CASCADE ON
DELETE CASCADE
);
go

-- Create the DriverPay table
CREATE TABLE DriverPay (
    RecordID VARCHAR(10) NOT NULL PRIMARY KEY,
    GrossPay DECIMAL(10, 2),
    TaxWithheld DECIMAL(10, 2),
    TotalAmountPaid DECIMAL(10, 2),
    PaymentDate DATE,
    PayPeriodStartDate DATE,
    PayPeriodEndDate DATE,
    PaidDeliveryRate DECIMAL(10, 2),
    DeliveriesPay DECIMAL(10, 2)

);
go

-- Create the InStorePay table
CREATE TABLE InStorePay (
    RecordID VARCHAR(10) NOT NULL PRIMARY KEY,
    GrossPay DECIMAL(10, 2),
    TaxWithheld DECIMAL(10, 2),
    TotalAmountPaid DECIMAL(10, 2),
    PaymentDate DATE,
    PayPeriodStartDate DATE,
    PayPeriodEndDate DATE,
    PaidHourlyRate DECIMAL(10, 2),
    HoursPaid INT

```

```

);
go

-- Create the BankDetails table
CREATE TABLE BankDetails (
    BSB VARCHAR(15) PRIMARY KEY,
    AcName VARCHAR(25)
);
go

-- Create the DriverStaff table
CREATE TABLE DriverStaff (
    StaffID VARCHAR(10) NOT NULL PRIMARY KEY,
    FirstName VARCHAR(20),
    LastName VARCHAR(10),
    Street VARCHAR(20),
    City VARCHAR(10),
    Postcode VARCHAR(4),
    TaxFileNo CHAR(9) ,
    BSB VARCHAR(15),
    AccNo VARCHAR(15),
    Status VARCHAR(50) DEFAULT 'Active',
    Description VARCHAR(20) DEFAULT 'Full-time' ,
    DriverLicNo VARCHAR(15),
    RatePerDelivery DECIMAL(10, 2),
    UNIQUE (TaxFileNo, DriverLicNo),
    FOREIGN KEY (BSB) REFERENCES BankDetails(BSB) ON UPDATE CASCADE ON DELETE
CASCADE
);
go

-- Create the InStoreStaff table
CREATE TABLE InStoreStaff (
    StaffID VARCHAR(10) NOT NULL PRIMARY KEY,
    FirstName VARCHAR(20),
    LastName VARCHAR(10),
    Street VARCHAR(20),
    City VARCHAR(10),
    Postcode VARCHAR(4),
    TaxFileNo CHAR(9),
    BSB VARCHAR(15),
    AccNo VARCHAR(15),
    HourlyRate DECIMAL(10, 2),
    Status VARCHAR(50) DEFAULT 'Active',
    Description VARCHAR(20) DEFAULT 'Full-time',
    UNIQUE (TaxFileNo),
    FOREIGN KEY (BSB) REFERENCES BankDetails(BSB) ON UPDATE CASCADE ON DELETE
CASCADE
);
go

-- Create the DriverShift table
CREATE TABLE DriverShift (
    ShiftID VARCHAR(10) NOT NULL PRIMARY KEY,
    StaffID VARCHAR(10),
    RecordID VARCHAR(10),
    StartDateTime DATETIME,
    EndDateTime DATETIME,
    DeliveriesNum INT,

```

```

        FOREIGN KEY (StaffID) REFERENCES DriverStaff(StaffID) ON UPDATE CASCADE ON
DELETE NO ACTION,
        FOREIGN KEY (RecordID) REFERENCES DriverPay(RecordID) ON UPDATE CASCADE ON
DELETE NO ACTION
    );
go

```

-- Create the InStoreShift table

```

CREATE TABLE InStoreShift (
    ShiftID VARCHAR(10) NOT NULL PRIMARY KEY,
    StaffID VARCHAR(10),
    RecordID VARCHAR(10),
    StartDateTime DATETIME,
    EndDateTime DATETIME,
    WorkHourNum INT,
    FOREIGN KEY (StaffID) REFERENCES InStoreStaff(StaffID) ON UPDATE CASCADE ON
DELETE NO ACTION,
    FOREIGN KEY (RecordID) REFERENCES InStorePay(RecordID) ON UPDATE CASCADE ON
DELETE NO ACTION
);
go

```

-- Create the OrderPayRecord table

```

CREATE TABLE OrderPayRecord (
    PaymentApprovalNo VARCHAR(10) PRIMARY KEY,
    PaymentMethod VARCHAR(255),
    TotalAmountDue DECIMAL(10, 2)
);
go

```

-- Create the OrderOnly table

```

CREATE TABLE OrderOnly (
    OrderID VARCHAR(10) NOT NULL PRIMARY KEY,
    OrderDateTime DATETIME,
    PaymentApprovalNo VARCHAR(10),
    Status VARCHAR(50) DEFAULT 'Delivered',
    CustomerID VARCHAR(10),
    StaffID VARCHAR(10),
    FOREIGN KEY (CustomerID) REFERENCES Customer(CustomerID) ON UPDATE CASCADE ON
DELETE CASCADE,
    FOREIGN KEY (StaffID) REFERENCES InStoreStaff(StaffID) ON UPDATE CASCADE ON
DELETE CASCADE,
    FOREIGN KEY (PaymentApprovalNo) REFERENCES OrderPayRecord(PaymentApprovalNo) ON
UPDATE CASCADE ON DELETE CASCADE
);
go

```

-- Create the WalkInOrder table

```

CREATE TABLE WalkInOrder (
    OrderID VARCHAR(10) PRIMARY KEY,
    WalkInTime DATETIME,
    FOREIGN KEY (OrderID) REFERENCES OrderOnly(OrderID) ON UPDATE CASCADE ON DELETE
NO ACTION
);
go

```

-- Create the PhoneOrder table

```

CREATE TABLE PhoneOrder (
    OrderID VARCHAR(10) PRIMARY KEY,

```

```

        PhoneStartTime DATETIME,
        PhoneEndTime DATETIME,
        FOREIGN KEY (OrderID) REFERENCES OrderOnly(OrderID) ON UPDATE CASCADE ON DELETE
NO ACTION
);
go

```

-- Create the Delivery table

```

CREATE TABLE Delivery (
    OrderID VARCHAR(10) PRIMARY KEY,
    DeliveryAddress VARCHAR(100),
    DeliveryTime DATETIME,
    ShiftID VARCHAR(10),
    FOREIGN KEY (OrderID) REFERENCES PhoneOrder(OrderID) ON UPDATE CASCADE ON
DELETE NO ACTION,
    FOREIGN KEY (ShiftID) REFERENCES DriverShift(ShiftID) ON UPDATE NO ACTION ON
DELETE NO ACTION,
);
go

```

-- Create the Pickup table

```

CREATE TABLE Pickup (
    OrderID VARCHAR(10) PRIMARY KEY,
    PickupTime DATETIME,
    FOREIGN KEY (OrderID) REFERENCES PhoneOrder(OrderID) ON UPDATE CASCADE ON
DELETE CASCADE
);
go

```

-- Create the QMenuOrder table

```

CREATE TABLE QMenuOrder (
    OrderID VARCHAR(10),
    ItemCode VARCHAR(10),
    Quantity INT,
    PRIMARY KEY (OrderID, ItemCode),
    FOREIGN KEY (OrderID) REFERENCES OrderOnly(OrderID) ON UPDATE CASCADE ON DELETE
NO ACTION,
    FOREIGN KEY (ItemCode) REFERENCES MenuItem(ItemCode) ON UPDATE CASCADE ON
DELETE NO ACTION
);
go

```

-- Create the QMenuIngredient table

```

CREATE TABLE QMenuIngredient (
    ItemCode VARCHAR(10),
    IngredientCode VARCHAR(10),
    Quantity INT,
    PRIMARY KEY (ItemCode, IngredientCode),
    FOREIGN KEY (ItemCode) REFERENCES MenuItem(ItemCode) ON UPDATE CASCADE ON
DELETE NO ACTION,
    FOREIGN KEY (IngredientCode) REFERENCES Ingredient(IngredientCode) ON UPDATE
CASCADE ON DELETE NO ACTION
);
go

```

-- Create the QIngredientIngredientOrder table

```

CREATE TABLE QIngredientIngredientOrder (
    IngredientCode VARCHAR(10),
    IngredientOrderNo VARCHAR(10),

```

```

    Price DECIMAL(10, 2),
    Quantity INT,
    PRIMARY KEY (IngredientCode, IngredientOrderNo),
    FOREIGN KEY (IngredientCode) REFERENCES Ingredient(IngredientCode) ON UPDATE
CASCADE ON DELETE NO ACTION,
    FOREIGN KEY (IngredientOrderNo) REFERENCES IngredientOrder(IngredientOrderNo)
ON UPDATE CASCADE ON DELETE NO ACTION,

```

```

);
go

```

```

--INSERT INTO table VALUES('','','','');
--Insert data into MenuItem table
INSERT INTO MenuItem VALUES ('MENU001', 'Ultimate Cheese Lover's', '14 inch', 'Large
Pizza', '23.95');
INSERT INTO MenuItem VALUES ('MENU002', 'Supreme', '12 inch', 'Medium Pizza', '19.85');
INSERT INTO MenuItem VALUES ('MENU003', 'Hawaiian', '12 inch', 'Medium
Pizza', '18.95');
INSERT INTO MenuItem VALUES ('MENU004', 'MeatLover's', '16 inch', 'Extra Large
pizza', '25.95');
INSERT INTO MenuItem VALUES ('MENU005', 'BBQ Chicken', '10 inch', 'Small
pizza', '15.95');
INSERT INTO MenuItem VALUES ('MENU006', 'Pepperoni Lover's', '14 inch', 'Large
Pizza', '22.95');
INSERT INTO MenuItem VALUES ('MENU007', 'Veggie Lover's', '14 inch', 'Large
Pizza', '22.95');
go

```

```

--Insert data into Ingredient table
INSERT INTO Ingredient VALUES
('IN001', 'Garlic', 'Vegetable', 'Fresh', '7.5kg', '10kg', '3kg');
INSERT INTO Ingredient VALUES
('IN002', 'Mushroom', 'Vegetable', 'Fresh', '10kg', '8kg', '3kg');
INSERT INTO Ingredient VALUES ('IN003', 'GreenBell
Pepper', 'Vegetable', 'Fresh', '10kg', '7.5kg', '3kg');
INSERT INTO Ingredient VALUES
('IN004', 'Onion', 'Vegetable', 'Fresh', '10kg', '8kg', '3kg');
INSERT INTO Ingredient VALUES
('IN005', 'Pineapple', 'Fruit', 'Frozen', '10kg', '5kg', '3kg');
INSERT INTO Ingredient VALUES ('IN006', 'Chicken', 'Meat', 'Chicken
Breast', '10kg', '6kg', '3kg');
INSERT INTO Ingredient VALUES ('IN007', 'Pork', 'Meat', 'Pork
Belly', '15kg', '10kg', '3kg');
INSERT INTO Ingredient VALUES ('IN008', 'Sausage', 'Processed Meat', 'Beef
Sausage', '10kg', '10kg', '3kg');
INSERT INTO Ingredient VALUES ('IN009', 'Ham', 'Processed Meat', 'Champagne Leg
Ham', '15kg', '10kg', '3kg');
INSERT INTO Ingredient VALUES ('IN010', 'Pepperoni', 'Processed Meat', 'Small
pepperoni', '10kg', '5kg', '3kg');
INSERT INTO Ingredient VALUES ('IN011', 'Cheese', 'Contain
Dairy', 'Mozzarella', '10kg', '8kg', '3kg');
INSERT INTO Ingredient VALUES ('IN012', 'Italian Sauce', 'Pizza Sauce', 'Bazil &
Oregano sause', '10kg', '7kg', '3kg');
INSERT INTO Ingredient VALUES ('IN013', 'Creamy Garlic Sauce', 'Pizza
Sauce', 'Contains Dairy', '10kg', '9kg', '3kg');
INSERT INTO Ingredient VALUES ('IN014', 'Pizza Dough', 'Pizza Base', 'Gluten
Free', '20kg', '10kg', '3kg');
go

```

----Insert data into Supplier table

```
INSERT INTO Supplier VALUES ('SUPP1001', 'MaryButchers', '0123123123', 'Hunter
Street', 'Newcastle', '2300', 'marybutchers@gmail.com');
INSERT INTO Supplier VALUES ('SUPP1002', 'BidFood', '0400444222', 'King
Street', 'Newcastle', '2300', 'bidfood@gmail.com');
INSERT INTO Supplier VALUES ('SUPP2000', 'FoodBomb', '0291988452', 'Glebe
Roas', 'Newcastle', '2308', 'foodbomb@gmail.com');
INSERT INTO Supplier VALUES ('SUPP2001', 'FoodnDairy', '023005445', 'Bull
Street', 'Newcastle', '2300', 'foodndairy@gmail.com');
INSERT INTO Supplier VALUES ('SUPP2002', 'Bibica', '0562125621', 'Tydlad
Street', 'Newcastle', '2299', 'bibica@gmail.com');
INSERT INTO Supplier VALUES ('SUPP2003', 'HunterFood', '045612896', 'Tyrrell
Street', 'Newcastle', '2300', 'hunterfood@gmail.com');
INSERT INTO Supplier VALUES ('SUPP2004', 'MocoFood', '0453289562', 'Union
Street', 'Newcastle', '2300', 'mocomoco@gmail.com');
go
```

--Insert data into IngredientOrder table

```
INSERT INTO IngredientOrder VALUES ('INOR1100', 129.90, '2023-09-10', '2023-09-20',
'Delivered', 'On time delivery', 'SUPP1001');
INSERT INTO IngredientOrder VALUES ('INOR1200', 150.00, '2023-08-10', '2023-08-25',
'Delivered', null, 'SUPP1002');
INSERT INTO IngredientOrder VALUES ('INOR1300', 170.25, '2023-10-01', '2023-10-15',
'Delivered', null, 'SUPP1001');
INSERT INTO IngredientOrder VALUES ('INOR2100', 80.90, '2023-10-08', '2023-10-16',
'Delivered', 'Slightly late', 'SUPP2004');
INSERT INTO IngredientOrder VALUES ('INOR2200', 145.50, '2023-10-15', '2023-10-25',
'Delivered', 'Deliveried late', 'SUPP2002');
INSERT INTO IngredientOrder VALUES ('INOR2300', 120.75, '2023-10-10', '2023-10-24',
'In Progress', null, 'SUPP2002');
go
```

-- Insert data into the Customer table

```
INSERT INTO Customer VALUES ('CUST001', 'Mary', 'Smith', '123 Hunter Street',
'Newcastle', '2300');
INSERT INTO Customer VALUES ('CUST002', 'Nick', 'Lomma', '456 Elm Avenue',
'Sydney', '2000');
INSERT INTO Customer VALUES ('CUST003', 'Paul', 'Brown', '789 Oak Road',
'Melbourne', '3000');
INSERT INTO Customer VALUES ('CUST004', 'Lisa', 'Chou', '101 Pine Lane',
'Brisbane', '4220');
INSERT INTO Customer VALUES ('CUST005', 'Michael', 'Lee', '222 Cedar Street',
'Perth', '6203');
go
```

-- Insert data into the CPhone table

```
INSERT INTO CPhone VALUES ('0423589456', 'CUST001');
INSERT INTO CPhone VALUES ('0123568459', 'CUST002');
INSERT INTO CPhone VALUES ('0125126563', 'CUST003');
INSERT INTO CPhone VALUES ('0148623259', 'CUST004');
INSERT INTO CPhone VALUES ('0259245621', 'CUST005');
go
```

-- Insert data into the DriverPay table

```
INSERT INTO DriverPay VALUES ('DP001', 2050.00, 460.00, 1520.00, '2023-08-10',
'2023-08-01', '2023-08-25', 120.00, 1590.00);
INSERT INTO DriverPay VALUES ('DP002', 1550.00, 360.00, 1460.00, '2023-10-15',
'2023-10-01', '2023-10-30', 90.00, 1450.00);
```

```

INSERT INTO DriverPay VALUES ('DP003', 1250.00, 450.00, 1860.00, '2023-09-17',
'2023-08-15', '2023-09-25', 100.00, 1630.00);
INSERT INTO DriverPay VALUES ('DP004', 1990.00, 390.00, 1520.00, '2023-06-12',
'2023-05-26', '2023-06-20', 195.00, 1425.00);
INSERT INTO DriverPay VALUES ('DP005', 2250.00, 520.00, 1580.00, '2023-11-02',
'2023-10-16', '2023-11-15', 80.00, 1675.00);
go

```

```

-- Insert data into the InStorePay table
INSERT INTO InStorePay VALUES ('IP001', 2510.00, 300.00, 1625.00, '2023-08-12',
'2023-08-03', '2023-08-15', 20.00, 80);
INSERT INTO InStorePay VALUES ('IP002', 1406.00, 253.00, 1230.00, '2023-10-12',
'2023-10-01', '2023-10-15', 19.00, 70);
INSERT INTO InStorePay VALUES ('IP003', 1600.00, 452.00, 1280.00, '2023-09-10',
'2023-08-25', '2023-09-15', 20.25, 67);
INSERT INTO InStorePay VALUES ('IP004', 1550.00, 125.00, 1240.00, '2023-07-12',
'2023-06-26', '2023-07-31', 18.75, 74);
INSERT INTO InStorePay VALUES ('IP005', 1452.00, 450.00, 1500.00, '2023-11-12',
'2023-10-16', '2023-11-30', 17.50, 74);
go

```

```

-- Insert data into the BankDetails table
INSERT INTO BankDetails VALUES ('123-456', 'John Smith');
INSERT INTO BankDetails VALUES ('789-012', 'Alice Johnson');
INSERT INTO BankDetails VALUES ('345-678', 'David Brown');
INSERT INTO BankDetails VALUES ('901-234', 'Sarah Davis');
INSERT INTO BankDetails VALUES ('567-890', 'Michael Wilson');
go

```

```

-- Insert data into the DriverStaff table
INSERT INTO DriverStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, Description, DriverLicNo, RatePerDelivery) VALUES ('DS001',
'John', 'Smith', '150 Cinre Street', 'Brisbane', '5962', '2632785', '123-456',
'1234567890', 'Part-time', 'DL751023', 5.50);
INSERT INTO DriverStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, Description, DriverLicNo, RatePerDelivery) VALUES ('DS002',
'Alice', 'Johnson', '89A Inue Avenue', 'Sydney', '2000', '245985230', '789-012',
'9876543210', 'Part-time', 'DL752015', 4.00);
INSERT INTO DriverStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, DriverLicNo, RatePerDelivery) VALUES ('DS003', 'David',
'Brown', '14B Danfin Street', 'Newcastle', '3000', '562123148', '345-678',
'5432167890', 'DL423658', 4.25);
INSERT INTO DriverStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, DriverLicNo, RatePerDelivery) VALUES ('DS004', 'Sarah',
'Davis', '52 Gine Street', 'Sydney', '4000', '245698745', '901-234', '2109876540',
'DL210987', 5.75);
INSERT INTO DriverStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, DriverLicNo, RatePerDelivery) VALUES ('DS005', 'Michael',
'Wilson', '33 Huneit Road', 'Adelaide', '6000', '125623456', '567-890',
'6543217890', 'DL654321', 4.50);
go

```

```

-- Insert data into the InStoreStaff table
INSERT INTO InStoreStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, HourlyRate) VALUES ('ISS001', 'John', 'Smith', '123 Dervin
Street', 'Newcastle', '2300', '123456789', '123-456', '1234567890', 20.00);
INSERT INTO InStoreStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, HourlyRate, Description) VALUES ('ISS002', 'Alice',
'Johnson', '456 Elm Street', 'Sydney', '2000', '987654321', '789-012',

```



```
'9876543210', 18.50, 'Part-time');
INSERT INTO InStoreStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, HourlyRate) VALUES ('ISS003', 'David', 'Brown', '74 Oak
Road', 'Melbourne', '3000', '543216789', '345-678', '5432167890', 21.00);
INSERT INTO InStoreStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, HourlyRate, Description) VALUES ('ISS004', 'Sarah', 'Davis',
'101 Inien Lane', 'Brisbane', '4000', '210987654', '901-234', '2109876540',
19.75, 'Part-time');
INSERT INTO InStoreStaff (StaffID, FirstName, LastName, Street, City, Postcode,
TaxFileNo, BSB, AccNo, HourlyRate) VALUES ('ISS005', 'Michael', 'Wilson', '52 Aunit
Street', 'Perth', '6000', '654321789', '567-890', '6543217890', 22.50);
go
```

```
-- Insert data into the DriverShift table
INSERT INTO DriverShift VALUES ('DSH001', 'DS001', 'DP001', '2023-10-12 08:00:00',
'2023-10-12 12:00:00', 13);
INSERT INTO DriverShift VALUES ('DSH002', 'DS002', 'DP002', '2023-10-12 11:30:00',
'2023-10-12 15:30:00', 17);
INSERT INTO DriverShift VALUES ('DSH003', 'DS003', 'DP003', '2023-10-12 08:30:00',
'2023-10-12 14:50:00', 7);
INSERT INTO DriverShift VALUES ('DSH004', 'DS004', 'DP004', '2023-10-12 13:00:00',
'2023-10-12 17:00:00', 10);
INSERT INTO DriverShift VALUES ('DSH005', 'DS005', 'DP005', '2023-10-12 10:00:00',
'2023-10-12 15:30:00', 14);
go
```

```
-- Insert data into the InStoreShift table
INSERT INTO InStoreShift VALUES ('ISHI001', 'ISS001', 'IP001', '2023-10-12
10:00:00', '2023-10-12 18:00:00', 8);
INSERT INTO InStoreShift VALUES ('ISHI002', 'ISS002', 'IP002', '2023-10-11
10:30:00', '2023-10-12 15:30:00', 7);
INSERT INTO InStoreShift VALUES ('ISHI003', 'ISS003', 'IP003', '2023-10-11
09:30:00', '2023-10-12 17:30:00', 8);
INSERT INTO InStoreShift VALUES ('ISHI004', 'ISS004', 'IP004', '2023-10-12
13:00:00', '2023-10-12 17:00:00', 4);
INSERT INTO InStoreShift VALUES ('ISHI005', 'ISS005', 'IP005', '2023-10-12
11:00:00', '2023-10-12 18:00:00', 7);
go
```

```
-- Insert data into the OrderPayRecord table
INSERT INTO OrderPayRecord VALUES ('PAY001', 'Cash', 50.75);
INSERT INTO OrderPayRecord VALUES ('PAY002', 'Cash', 63.90);
INSERT INTO OrderPayRecord VALUES ('PAY003', 'Credit Card', 50.25);
INSERT INTO OrderPayRecord VALUES ('PAY004', 'Credit Card', 59.00);
INSERT INTO OrderPayRecord VALUES ('PAY005', 'Credit Card', 80.95);
INSERT INTO OrderPayRecord VALUES ('PAY006', 'Cash', 40.75);
INSERT INTO OrderPayRecord VALUES ('PAY007', 'Cash', 50.00);
INSERT INTO OrderPayRecord VALUES ('PAY008', 'Debit Card', 80.25);
INSERT INTO OrderPayRecord VALUES ('PAY009', 'Cash', 50.00);
INSERT INTO OrderPayRecord VALUES ('PAY010', 'Cash', 70.05);
INSERT INTO OrderPayRecord VALUES ('PAY011', 'Credit Card', 69.55);
INSERT INTO OrderPayRecord VALUES ('PAY012', 'Cash', 60.65);
INSERT INTO OrderPayRecord VALUES ('PAY013', 'Debit Card', 54.75);
INSERT INTO OrderPayRecord VALUES ('PAY014', 'Debit Card', 35.50);
INSERT INTO OrderPayRecord VALUES ('PAY015', 'Credit Card', 70.55);
go
```

```
-- Insert data into the OrderOnly table
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
```

```

CustomerID, StaffID) VALUES ('ORD001', '2023-10-12 12:05:00', 'PAY001',
'Processing', 'CUST001', 'ISS001');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD002', '2023-10-13 20:00:00', 'PAY002', 'CUST002', 'ISS002');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD003', '2023-10-13 12:11:00', 'PAY003',
'Processing', 'CUST003', 'ISS003');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD004', '2023-10-13 11:30:00', 'PAY004', 'CUST004', 'ISS004');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD005', '2023-10-14 19:30:00', 'PAY005',
'Processing', 'CUST005', 'ISS005');

```

```

INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD006', '2023-10-13 10:42:00', 'PAY006',
'Processing', 'CUST001', 'ISS001');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD007', '2023-10-12 14:41:00', 'PAY007', 'CUST002', 'ISS002');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD008', '2023-10-14 11:00:00', 'PAY008',
'Processing', 'CUST003', 'ISS003');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD009', '2023-10-14 13:25:00', 'PAY009', 'CUST004', 'ISS004');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD010', '2023-10-15 19:30:00', 'PAY010',
'Processing', 'CUST005', 'ISS005');

```

```

INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD0011', '2023-10-12 11:45:00', 'PAY011', 'CUST001', 'ISS001');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD0012', '2023-10-13 15:40:00', 'PAY012', 'CUST002', 'ISS002');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD0013', '2023-10-13 12:01:00', 'PAY013',
'Processing', 'CUST003', 'ISS003');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, CustomerID,
StaffID) VALUES ('ORD0014', '2023-10-13 14:30:00', 'PAY014', 'CUST004', 'ISS004');
INSERT INTO OrderOnly (OrderID, OrderDateTime, PaymentApprovalNo, Status,
CustomerID, StaffID) VALUES ('ORD0015', '2023-10-14 20:35:00', 'PAY015',
'Processing', 'CUST005', 'ISS005');
go

```

```

-- Insert data into the WalkInOrder table
INSERT INTO WalkInOrder VALUES ('ORD001', '2023-10-12 11:55:00');
INSERT INTO WalkInOrder VALUES ('ORD002', '2023-10-13 19:55:00');
INSERT INTO WalkInOrder VALUES ('ORD003', '2023-10-13 12:05:00');
INSERT INTO WalkInOrder VALUES ('ORD004', '2023-10-13 11:20:00');
INSERT INTO WalkInOrder VALUES ('ORD005', '2023-10-14 19:27:00');
go

```

```

-- Insert data into the PhoneOrder table
INSERT INTO PhoneOrder VALUES ('ORD006', '2023-10-13 10:38:00', '2023-10-13
10:45:00');
INSERT INTO PhoneOrder VALUES ('ORD007', '2023-10-12 14:35:00', '2023-10-12
14:45:00');
INSERT INTO PhoneOrder VALUES ('ORD008', '2023-10-14 10:45:00', '2023-10-14
11:00:00');
INSERT INTO PhoneOrder VALUES ('ORD009', '2023-10-14 13:15:00', '2023-10-14
13:28:00');
INSERT INTO PhoneOrder VALUES ('ORD010', '2023-10-15 19:20:00', '2023-10-15

```

```

19:35:00');

INSERT INTO PhoneOrder VALUES ('ORD0011', '2023-10-13 11:38:00', '2023-10-13
11:45:00');
INSERT INTO PhoneOrder VALUES ('ORD0012', '2023-10-12 15:35:00', '2023-10-12
15:45:00');
INSERT INTO PhoneOrder VALUES ('ORD0013', '2023-10-14 11:45:00', '2023-10-14
12:00:00');
INSERT INTO PhoneOrder VALUES ('ORD0014', '2023-10-14 14:15:00', '2023-10-14
14:28:00');
INSERT INTO PhoneOrder VALUES ('ORD0015', '2023-10-15 20:20:00', '2023-10-15
20:35:00');
go

-- Insert data into the Delivery table
INSERT INTO Delivery VALUES ('ORD0011', '123 Elm Street, Newcastle', '2023-10-15
12:30:00', 'DSH001');
INSERT INTO Delivery VALUES ('ORD0012', '456 Oak Road, Newcastle', '2023-10-16
16:00:00', 'DSH002');
INSERT INTO Delivery VALUES ('ORD0013', '789 Pine Lane, Newcastle', '2023-10-17
12:20:00', 'DSH003');
INSERT INTO Delivery VALUES ('ORD0014', '101 Cedar Street, Newcastle', '2023-10-18
15:00:00', 'DSH004');
INSERT INTO Delivery VALUES ('ORD0015', '222 Birch Avenue, Newcastle', '2023-10-19
20:50:00', 'DSH005');
go

-- Insert data into the Pickup table
INSERT INTO Pickup VALUES ('ORD006', '2023-10-13 11:10:00');
INSERT INTO Pickup VALUES ('ORD007', '2023-10-12 15:00:00');
INSERT INTO Pickup VALUES ('ORD008', '2023-10-14 11:45:00');
INSERT INTO Pickup VALUES ('ORD009', '2023-10-14 14:30:00');
INSERT INTO Pickup VALUES ('ORD010', '2023-10-15 20:05:00');
go

-- Insert data into the QMenuOrder table
INSERT INTO QMenuOrder VALUES ('ORD001', 'MENU007', 1);
INSERT INTO QMenuOrder VALUES ('ORD001', 'MENU002', 1);
INSERT INTO QMenuOrder VALUES ('ORD002', 'MENU003', 1);
INSERT INTO QMenuOrder VALUES ('ORD002', 'MENU006', 1);
INSERT INTO QMenuOrder VALUES ('ORD002', 'MENU005', 1);
INSERT INTO QMenuOrder VALUES ('ORD003', 'MENU006', 1);
INSERT INTO QMenuOrder VALUES ('ORD004', 'MENU005', 3);
INSERT INTO QMenuOrder VALUES ('ORD005', 'MENU002', 1);
INSERT INTO QMenuOrder VALUES ('ORD006', 'MENU004', 2);
INSERT INTO QMenuOrder VALUES ('ORD007', 'MENU003', 4);
INSERT INTO QMenuOrder VALUES ('ORD008', 'MENU002', 1);
INSERT INTO QMenuOrder VALUES ('ORD008', 'MENU001', 1);
INSERT INTO QMenuOrder VALUES ('ORD009', 'MENU002', 3);
INSERT INTO QMenuOrder VALUES ('ORD010', 'MENU004', 3);
INSERT INTO QMenuOrder VALUES ('ORD0011', 'MENU004', 2);
INSERT INTO QMenuOrder VALUES ('ORD0012', 'MENU004', 1);
INSERT INTO QMenuOrder VALUES ('ORD0013', 'MENU003', 2);
INSERT INTO QMenuOrder VALUES ('ORD0013', 'MENU001', 1);
INSERT INTO QMenuOrder VALUES ('ORD0014', 'MENU003', 2);
INSERT INTO QMenuOrder VALUES ('ORD0015', 'MENU005', 1);
INSERT INTO QMenuOrder VALUES ('ORD0015', 'MENU006', 1);
INSERT INTO QMenuOrder VALUES ('ORD0015', 'MENU001', 1);
go

```

```

-- Insert data into the QMenuIngredient table
INSERT INTO QMenuIngredient VALUES ('MENU001', 'IN001', 2);
INSERT INTO QMenuIngredient VALUES ('MENU001', 'IN011', 1);
INSERT INTO QMenuIngredient VALUES ('MENU002', 'IN002', 2);
INSERT INTO QMenuIngredient VALUES ('MENU002', 'IN003', 1);
INSERT INTO QMenuIngredient VALUES ('MENU002', 'IN012', 4);
INSERT INTO QMenuIngredient VALUES ('MENU003', 'IN014', 1);
INSERT INTO QMenuIngredient VALUES ('MENU003', 'IN005', 2);
INSERT INTO QMenuIngredient VALUES ('MENU003', 'IN012', 2);
INSERT INTO QMenuIngredient VALUES ('MENU004', 'IN006', 3);
INSERT INTO QMenuIngredient VALUES ('MENU004', 'IN010', 2);
INSERT INTO QMenuIngredient VALUES ('MENU004', 'IN014', 5);
INSERT INTO QMenuIngredient VALUES ('MENU005', 'IN006', 2);
INSERT INTO QMenuIngredient VALUES ('MENU005', 'IN005', 1);
INSERT INTO QMenuIngredient VALUES ('MENU006', 'IN005', 3);
INSERT INTO QMenuIngredient VALUES ('MENU007', 'IN010', 2);
INSERT INTO QMenuIngredient VALUES ('MENU007', 'IN013', 1);
go

-- Insert data into the QIngredientIngredientOrder table
INSERT INTO QIngredientIngredientOrder VALUES ('IN001', 'INOR1100', 12.50, 5);
INSERT INTO QIngredientIngredientOrder VALUES ('IN002', 'INOR1100', 8.75, 3);
INSERT INTO QIngredientIngredientOrder VALUES ('IN003', 'INOR1200', 6.20, 4);
INSERT INTO QIngredientIngredientOrder VALUES ('IN004', 'INOR1200', 9.10, 2);
INSERT INTO QIngredientIngredientOrder VALUES ('IN005', 'INOR1300', 14.00, 6);
INSERT INTO QIngredientIngredientOrder VALUES ('IN006', 'INOR2100', 7.50, 4);
INSERT INTO QIngredientIngredientOrder VALUES ('IN007', 'INOR2100', 10.25, 3);
INSERT INTO QIngredientIngredientOrder VALUES ('IN008', 'INOR2200', 5.60, 5);
INSERT INTO QIngredientIngredientOrder VALUES ('IN009', 'INOR2200', 12.75, 2);
INSERT INTO QIngredientIngredientOrder VALUES ('IN010', 'INOR2300', 8.30, 4);
go

SELECT * FROM MenuItem
SELECT * FROM Ingredient
SELECT * FROM Supplier
SELECT * FROM IngredientOrder
SELECT * FROM Customer
SELECT * FROM CPhone
SELECT * FROM DriverPay
SELECT * FROM InStorePay
SELECT * FROM BankDetails
SELECT * FROM DriverStaff
SELECT * FROM InStoreStaff
SELECT * FROM DriverShift
SELECT * FROM InstoreShift
SELECT * FROM OrderPayrecord
SELECT * FROM OrderOnly
SELECT * FROM WalkInOrder
SELECT * FROM PhoneOrder
SELECT * FROM Delivery
SELECT * FROM Pickup
SELECT * FROM QMenuOrder
SELECT * FROM QMenuIngredient
SELECT * FROM QIngredientIngredientOrder
go

-- Implement Queries
-- Q.1 For an instore staff with id number ISS001,

```

```
-- print his/her first name, last name, and hourly payment rate.
SELECT FirstName, LastName, HourlyRate
FROM InStoreStaff
WHERE StaffID = 'ISS001';
```

```
-- Q.2 List all the shift details of a delivery staff with first name JOHN and last
name SMITH
-- between date 2023-10-12 and 2023-10-20
SELECT SH.ShiftID, SH.StaffID, SH.RecordID, SH.StartDateTime, SH.EndDateTime,
SH.DeliveriesNum
FROM DriverStaff s
JOIN DriverShift SH
ON sh.staffID = s.staffID
WHERE S.FirstName = 'John' AND S.LastName = 'Smith'
AND SH.StartDateTime >= '2023-10-12 00:00:00'
AND SH.EndDateTime <= '2023-10-20 23:59:59';
```

```
-- Q.3 List all the order details of the orders that are made by a walk-in customer
-- with first name Lisa and last name Chou between date 2023-10-10 and 2023-10-20.
SELECT W.WalkInTime, O.OrderDateTime, O.Status, P.PaymentMethod, P.TotalAmountDue
FROM OrderOnly O
JOIN WalkInOrder W
ON W.OrderID = O.OrderID
JOIN Customer C
ON C.CustomerID = O.CustomerID
JOIN OrderPayRecord P
ON P.PaymentApprovalNo = O.PaymentApprovalNo
WHERE C.FirstName = 'Lisa' AND C.LastName = 'Chou'
AND O.OrderDateTime BETWEEN '2023-10-10 00:00:00' AND '2023-10-20 23:59:59'
```

```
-- Q.4 List the names of the menu items that are ordered in the current year. Note
the
-- current year is the current year that is decided by the system.
SELECT DISTINCT M.Name
FROM MenuItem M
JOIN QMenuOrder Q ON M.ItemCode = Q.ItemCode
JOIN OrderOnly O ON O.OrderID = Q.OrderID
WHERE YEAR(O.OrderDateTime) = YEAR(CURRENT_TIMESTAMP)
```

```
-- Q.5 List the name(s) of the ingredient(s) that was/were supplied by the supplier
-- with supplier ID SUPP1001 on date 2023-09-20
SELECT DISTINCT I.Name
FROM Ingredient I
JOIN QIngredientIngredientOrder Q
ON Q.IngredientCode = I.IngredientCode
JOIN IngredientOrder O
ON O.IngredientOrderNo = Q.IngredientOrderNo
WHERE O.SupplierID = 'SUPP1001'
AND O.DateSupplied = '2023-09-20';
```