

XEvent-B User Manual

Thai Son Hoang and Dana Dghaym

ECS, University of Southampton

{T.S.Hoang, dd4g12} at ecs dot soton dot ac dot uk

Version 0.0.2

(for feature version 0.0.6)

Wednesday 17th May, 2017

1 Event-B XText Front-end Overview

The Event-B XText Front-end provides new XEvent-B constructs (XMachines and XContexts) which are text files which are automatically translated into the corresponding Rodin Event-B constructs (i.e., Machine and Context) accordingly. Facility for translating from Rodin Event-B components to XEvent-B components can be invoked manually. The overall process can be seen in Figure 1.




Figure 1: Overview of XEvent-B and Rodin Event-B Constructs

2 Getting Started

2.1 Installation

2.1.1 Setup

- Before installing the Event-B XText Front-end feature, you need to add the XText update site (<http://download.eclipse.org/modeling/tmf/xtext/updates/composite/releases/>) as an additional software site (see Figure 2).




Figure 2: Adding XText Update Site

- The Event-B XText front-end feature is available from the main Rodin update site (under “Editors” category). There are two versions of the feature, *Event-B XText* providing facilities for working with Event-B XText Front-end, and the *Event-B XText (SDK)* is the feature including source code for software developers (see Figure 3).

2.1.2 Release Notes

0.0.5

- Event-B XText Documentations (0.0.1): Documentation plug-in (Initial version).

0.0.4

- Updated plug-in dependency for the feature

0.0.3

- Event-B XText Context (0.0.3):
 - Issue #3: Single-line comment after the element, multi-line comment before the element




Figure 3: Adding XText Update Site

- Event-B XText Context IDE (0.0.2): Regenerated
- Event-B XText ContextUI IDE (0.0.2): Regenerated
- Event-B XText Machine (0.0.3):
 - Issue #3: Single-line comment after the element, multi-line comment before the element.
 - Issue #5: Event terminator using 'end' keyword instead of ';'
- Event-B XText Machine IDE (0.0.2) Regenerated
- Event-B XText Machine UI IDE (0.0.2) Regenerated

0.0.2

- Event-B XText Common (0.0.2):
 - Added transient value service for XContext and XMachine.
- Event-B XText Context (0.0.2):
 - Added formatter (used for auto-indentation).
- Event-B XText Machine (0.0.2):
 - Added formatter (used for auto-indentation).
- Event-B XText UI (0.0.1): Initial version
 - Added context menu for converting machines and contexts to XText.

0.0.1 Initial version contains the following plug-ins:

- Event-B XText Branding (0.0.1) Initial version: Branding information
- Event-B XText Common (0.0.1) Initial version: Common facilities
- Event-B XText Context (0.0.1) Initial version: Core support for Event-B contexts
- Event-B XText Context IDE (0.0.1) Initial version: IDE for Event-B contexts
- Event-B XText Context UI (0.0.1) Initial version: UI for Event-B contexts
- Event-B XText Machine (0.0.1) Initial version: Core support for Event-B machines
- Event-B XText Machine IDE (0.0.1) Initial version: IDE for Event-B machines
- Event-B XText Machine UI (0.0.1) Initial version: UI for Event-B machines

2.1.3 **IMPORTANT**

- Currently, Event-B XText front-end ONLY supports “standard” Event-B machines and contexts.
- Since the XContexts and XMachines are compiled to the Rodin files, the corresponding Rodin contexts and machines will be **OVER-WRITTEN**. Any changes in the Rodin files will not be lost.
- **DO NOT USE** the Event-B XText Front-end if you use modelling plug-ins such as *iUML-B* state-machines and class-diagrams, as the additional modelling elements will be over-written.

2.1.4 **Known Issues**

- Converting to XText: Currently, the “extended” attribute of events are not serialised.

2.1.5 **Configuration**

Event-B Explorer By default, XContext files (extension .bucx) and XMachines files (extension .bumx) are not display in the *Event-B Explorer*. To enable this, select *Customize view* for *Event-B Explorer* and uncheck the option *All files and folders*.

2.2 **Basic Tutorial**

This tutorial provides a step-by-step walk-through working with XEvent-B constructs. This tutorial also available as Cheatsheets with the Rodin Platform ([Help/Cheat Sheets/Event-B XText Cheatsheets](#)/[Event-B XText Basic Tutorial](#)).

2.2.1 Task 1. Customise the Event-B Explorer

Introduction The purpose of this task is to customise the Event-B Explorer so that XEvent-B constructs are visible.

Step 1. Disable the filter on “All files and folders” Select “Customize View” of Event-B Explorer View. Make sure that “All files and folders” from the dialog is **Unchecked**.

Conclusion Since the filter on “All files and folders” is now disabled, there might be other files and folders than XEvent-B constructs will also be visible in the Event-B Explorer.

2.2.2 Task 2. Create an Event-B Project

Introduction The purpose of this task is to create an Event-B project for the XEvent-B constructs.

Step 1. Create a new Event-B Project Create a new Event-B Project named “Club” using the *New Event-B Project* wizard (see Figure 4).




Figure 4: Create Event-B Project called “Club”

Conclusion By now, the project “Club” should be visible in the Event-B Explorer.

2.2.3 Task 3. Create a simple XContext coursesCtx.bucx

Introduction The purpose of this task is to create a simple XContext within the newly created project.

Step 1. Create a new XContext coursesCtx.bucx Create a new XContext named “coursesCtx.bucx” using the *New File wizard* (see Figure 5).

Important: A pop-up dialog will be displayed asking to convert the “Club” project to XText project, please answer **Yes** (see Figure 6).




Figure 5: Create an XContext called “coursesCtx.bucx”




Figure 6: Convert “Club” to XText project

Step 2. Set the content of courseCtx.bucx Set the content of “coursesCtx.bucx” as follows.

```

context coursesCtx

sets CRS

constants m

axioms

@axm0_1: "finite(CRS)"

@axm0_2: "m ∈ N1" 

@thm0_1: "0 < m" theorem

end

```

Important: In order to typeset Event-B mathematical symbol, e.g., N_1 , one can use content assist. For example, typing NAT and invoking content assist (e.g., on Mac OS **Ctrl+Space**), a dropdown list will appear with options for typesetting N_1 and N_1 (See Figure 7).




Figure 7: Type-setting N_1 using Content Assist

Step 3. Auto-format the code Automatically format the content of “coursesCtx.bucx” using short-cut (e.g., on Mac OS: **Cmd+Shift+F**).

Step 4. Save the file Save the file “coursesCtx.bucx”.

Conclusion By now, the XContext “coursesCtx.bucx” and the corresponding Rodin Context “coursesCtx” should be visible in the Event-B Explorer (see Figure 8).




Figure 8: The final XContext coursesCtx.bucx

2.2.4 Task 4. Create a simple XMachine m0.bumx

Introduction The purpose of this task is to create a simple XMachine within the newly created project.

Step 1. Create a new XMachine m0.bumx Create a new XMachine named “m0.bumx” using the New File wizard (see Figure 9). The newly created file should be opened automatically in an XMachine editor.




Figure 9: Type-setting N_1 using Content Assist

Step 2. Set the content of m0.bumx Set the content of "m0.bumx" as follows.

```

machine m0

variables crs

invariants

@inv0_1: "crs ∈ ℙ(CRS)"

@thm0_2: "finite(crs)" theorem

@inv0_2: "card(crs) ≤ m"

@DLF: "(card(crs) ≠ m) ∨ (∃ cs : cs ⊆ crs ∧ cs ≠ ∅)"

events

INITIALISATION

begin

@act0_1: "crs := ∅"

end

OpenCourses

when

@grd0_1: "card(crs) ≠ m"

@thm0_3: "crs ≠ CRS" theorem

then

@act0_1: "crs :| crs ⊂ crs' ∧ card(crs') ≤ m"

end

CloseCourses anticipated

any cs where

@grd0_1: "cs ⊆ crs"

@grd0_2: "cs ≠ ∅"

then
```

@act0_1: "crs := crs \ cs"

end

end

Step 3. Auto-format the code Automatically format the content of “m0.bumx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “m0.bumx”.

Step 5. Add missing “sees” clause In the compiled Rodin Machine m0, there are several errors, due to the fact that **m0** refers to the sets and constants of the context courseCtx. **Add the missing “sees” clause** after the “machine” clause

sees courseCtx

(Note: One can use *Content Assist* after typing the “sees” keyword to select the context, see Figure 10).




Figure 10: Content Assist for adding Sees clause

Step 6. Save the file again Save the file "m0.bumx" again.

Conclusion By now, the XMachine “m0.bumx” and the corresponding Rodin Machine “m0” (without any error) should be visible in the Event-B Explorer (see Figure 11).




Figure 11: XMachine m0.bucx

2.2.5 Task 5. Create extended XContexts

Introduction The purpose of this task is to create some more extended XContexts within the “Club” project.

Task 5.1. Create a simple XContext membersCtx.bucx **Introduction**
The purpose of this sub-task is to create a simple XContext “membersCtx.bucx” within the “Club” project.

Step 1. Create a new XContext membersCtx.bucx **Create a new XContext** named “membersCtx.bucx” using the *New File* wizard (see Figure 12).




Figure 12: Create membersCtx.bucx

Step 2. Set the content of membersCtx.bucx Set the content of “membersCtx.bucx” as follows.

```

context membersCtx
sets MEM
axioms
  @axm0_1: "finite(MEM)"
end

```

Step 3. Auto-format the code Automatically format the content of “membersCtx.bucx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “membersCtx.bucx”.

Conclusion By now, the XContext “membersCtx.bucx” and the corresponding Rodin Context “membersCtx” should be visible in the Event-B Explorer (see Figure 13).




Figure 13: XContext membersCtx.bucx

Task 5.2. Create an extended XContext participantsCtx.bucx **Introduction** The purpose of this sub-task is to create an extended XContext “participantsCtx.bucx” within the “Club” project.

Step 1. Create a new XContext participantsCtx.bucx Create a new XContext named “participantsCtx.bucx” using the *New File wizard* (see Figure 14).




Figure 14: Create participantsCtx.bucx

Step 2. Set the content of participantsCtx.bucx Set the content of “participantsCtx.bucx” as follows.

```

context participantsCtx

extends membersCtx

constants PRTCPT

axioms

    @axm1_2: "PRTCPT ∈ ℙ(MEM)"

    @thm1_1: "finite(PRTCPT)" theorem

end

```

Step 3. Auto-format the code Automatically format the content of “participantsCtx.bucx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “participantsCtx.bucx”.

Conclusion By now, the XContext “participantsCtx.bucx” and the corresponding Rodin Context “participantsCtx” should be visible in the Event-B Explorer (see Figure 15).

Task 5.3. Create an extended XContext instructorsCtx.bucx **Introduction** The purpose of this sub-task is to create an extended XContext “instructorsCtx.bucx” within the “Club” project.




Figure 15: XContext participantsCtx.bucx

Step 1. Create a new XContext instructorsCtx.bucx Create a new XContext named “instructorsCtx.bucx” using the *New File wizard* (see Figure 16).




Figure 16: Create instructorsCtx.bucx

Step 2. Set the content of instructorsCtx.bucx Set the content of “instructorsCtx.bucx” as follows.

```

context instructorsCtx

extends membersCtx coursesCtx

constants INSTR instrs
  
```

axioms

```

@axm1_3: "INSTR ∈ ℙ(MEM)"

@axm1_4: "instrs ∈ CRS → INSTR"

end

```

Step 3. Auto-format the code Automatically format the content of “instructorsCtx.bucx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “instructorsCtx.bucx”.

Conclusion By now, the XContext “instructorsCtx.bucx” and the corresponding Rodin Context “instructorsCtx” should be visible in the Event-B Explorer (see Figure).




Figure 17: XContext instructorsCtx.bucx

2.2.6 Task 6. Create refined XMachines

Introduction The purpose of this task is to create some more refined XMachines within the “Club” project.

Task 6.1. Create a refined XMachine m1.bumx **Introduction** The purpose of this sub-task is to create a refined XMachine “m1.bumx” within the “Club” project.

Step 1. Create a new XMachine m1.bumx **Create a new XMachine** named “m1.bumx” using the *New File wizard* (see Figure 18. The newly created file should be opened automatically in an XMachine editor.




Figure 18: Create m1.bumx

Step 2. Set the content of m1.bumx Set the content of “m1.bumx” as follows.

```

machine m1

refines m0

sees instructorsCtx participantsCtx

variables crs prtcpts

invariants

    @inv1_1: "prtcpts ∈ crs ↔ PRTCPT"

    @inv1_2: "∀ c ∈ crs ⇒ instrs(c) ⊂ prtcpts[{c}]"

variant "(crs × PRTCPT) \ prtcpts"

events

    INITIALISATION extended

    begin

        @act1_2: "prtcpts := ∅"

    end

    OPENCOURSES extended

```

```

refines OpenCourses

when

@thm1_2: "dom(prtcpts) ⊆ crs" theorem

end

CloseCourses extended anticipated

refines CloseCourses

begin

@act1_2: "prtcpts := cs ⇐ prtcpts"

end

Register convergent

any p c where

@grd1_1: "p ∈ PRTCPT"

@grd1_2: "c ∈ crs"

@grd1_3: "p ≠ instrs(c)"

@grd1_4: "c ↦ p ≠ prtcpts"

then

@act1_1: "prtcpts := prtcpts ∪ {c ↦ p}"

end

end

```

Step 3. Auto-format the code Automatically format the content of “m1.bumx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “m1.bumx”.

Conclusion By now, the XMachine “m1.bumx” and the corresponding Rodin Machine “m1” should be visible in the Event-B Explorer (see Figure 19).

Task 6.2. Create a refined XMachine m2.bumx **Introduction** The purpose of this sub-task is to create a refined XMachine “m2.bumx” within the “Club” project.




Figure 19: XMachine m1.bumx

Step 1. Create a new XMachine m2.bumx Create a new XMachine named “m2.bumx” using the *New File wizard* (see Figure 20). The newly created file should be opened automatically in an XMachine editor.




Figure 20: Create m2.bumx

Step 2. Set the content of m2.bumx Set the content of “m2.bumx” as follows.

```
machine m2

refines m1

sees instructorsCtx participantsCtx
```

```

variables atnds

invariants

@inv2_1: "atnds ∈ CRS → ℙ(PRTCPT)"

@inv2_2: "crs = dom(atnds)"

@inv2_3: "∀ c · c ∈ crs ⇒ prtcpts[{c}] = atnds(c)"

@thm2_1: "finite(atnds)" theorem

variant "card(atnds)"

events

INITIALISATION

begin

@act2_1: "atnds := ∅"

end

OpenCourse

refines OpenCourses

any c where

@grd2_1: "c ∉ dom(atnds)"

@grd2_2: "card(atnds) ≠ m"

@thm2_2: "card(crs) ≠ m" theorem

with

@crs': "crs' = crs ∪ {c}"

then

@act2_1: "atnds(c) := ∅"

end

CloseCourse convergent

refines CloseCourses

```

```

any c where
  @grd2_1: "c ∈ dom(atnds)"

with
  @cs: "cs = {c}"

then
  @act1_2: "atnds := {c} ⊲ atnds"

end

Register convergent

refines Register

any p c where
  @grd2_1: "p ∈ PRTCPT"
  @grd2_2: "p ≠ instrs(c)"
  @grd2_3: "c ∈ dom(atnds)"
  @grd2_4: "p ∉ atnds(c)"

@thm2_3: "atnds(c) = prtcpts[{c}]" theorem

then
  @act2_1: "atnds(c) := atnds(c) ∪ {p}"

end

```

Step 3. Auto-format the code Automatically format the content of “m2.bumx” by using short-cut (e.g., on Mac OS: Cmd+Shift+F).

Step 4. Save the file Save the file “m2.bumx”.

Conclusion By now, the XMachine “m2.bucx” and the corresponding Rodin Machine “m2” should be visible in the Event-B Explorer (see Figure 21).




Figure 21: XMachine m2.bumx

3 Concepts

3.1 XText Projects

Each project containing XEvent-B constructs must be set to be XText project. An XText project has an associated XContext and XMachine builders that can compile XEvent-B source files into Rodin files as they are changed. The builders can be turned off via the preferences, either workspace-wise or project-wise (see Figure 22).




Figure 22: XContext Preference

The XText projects must be organised such that all XEvent-B constructs have the project as the source container.

3.2 XEvent-B Builders

The XEvent-B Builders, i.e., XContext builder and XMachine builder, build XEvent-B constructs, i.e., XContext and XMachine using their own compiler. If they are enabled, the XEvent-B builders are run everytime an individual XEvent-B file is saved. Problems detected by the XEvent-B builders are classified as either warnings or errors. Compile-time errors are always reported as errors by the XEvent-B builders and in the presence of errors, no new Rodin files are created or updated, i.e., the XEvent-B builders do not produce any new Rodin file content.

3.3 Content Assist

Content assist are available for typesetting keywords and Event-B mathematical symbols. The short-cut for invoking content assist is **Ctrl+Space**. Figure 23 shows an example for content assist with keywords. For Event-B mathematical




Figure 23: Keyword Content Assist

symbols, the key combination is defined by the Rodin Keyboard plug-in.

4 Tasks

4.1 Creating XEvent-B Files

New XEvent-B files can be create via the *New File wizard* with appropriate file extensions. The file extension for XContext is **bucx** and for XMachine is **bumx**. The syntax of XContext and XMachine can be seen in Section 5.2 and Section 5.3, respectively.

4.2 Typesetting Event-B Mathematical Symbols

Event-B mathematical symbols in predicates, expressions, and assignments are typeset using Content Assist. The definition of the character combinations is

defined in the Rodin Keyboard plug-in.

5 Reference

5.1 Common Syntax

```
ML_COMMENT ::= /* STRING */

SL_COMMENT ::= // SL_STRING

ID ::= [^] (LETTER | _) {LETTER | DIGIT | _}

XLABEL ::= @STRING:
```

5.2 XContext Syntax

```
XCONTEXT ::=

    [ ML_COMMENT | SL_COMMENT ]

    context ID

    [extends ID { ID }]

    [sets XSET {XSET}]

    [constants XCONSTANT { XCONSTANT }]

    [axioms XAXIOM {XAXIOM}]

    end

XSET ::=

    XSET_NO_COMMENT |
    XSET_ML_COMMENT |
    XSET_SL_COMMENT

XSET_NO_COMMENT ::= ID

XSET_ML_COMMENT ::= ML_COMMENT ID

XSET_SL_COMMENT ::= ID ML_COMMENT

XCONSTANT ::=
```

```

XCONSTANT_NO_COMMENT |  

XCONSANT_ML_COMMENT |  

XCONSTANT_SL_COMMENT  

XCONSTANT_NO_COMMENT ::= ID  

XCONSTANT_ML_COMMENT ::= ML_COMMENT ID  

XCONSTANT_SL_COMMENT ::= ID ML_COMMENT  

XAXIOM ::=  

XAXIOM_NO_COMMENT |  

XAXIOM_ML_COMMENT |  

XAXIOM_SL_COMMENT  

XAXIOM_NO_COMMENT ::= XLABEL "XPREDICATE" [theorem]  

XAXIOM_ML_COMMENT ::= ML_COMMENT XLABEL "XPREDICATE" [theorem]  

XAXIOM_SL_COMMENT ::= XLABEL "XPREDICATE" [theorem] SL_COMMENT

```

5.3 XMachine syntax

```

XMACHINE ::= [ ML_COMMENT | SL_COMMENT ]  

machine ID  

[refines ID  

[sees ID { ID }]  

[variables XVARIABLE {XVARIABLE}]  

[invariants XINVARIANT { XINVARIANT }]  

[variant XARIANT]  

[events XEVENT { XEVENT }]  

end  

XVARIABLE ::=

```

```

XVARIABLE_NO_COMMENT |  

XVARIABLE_ML_COMMENT |  

XVARIABLE_SL_COMMENT  

XVARIABLE_NO_COMMENT ::= ID  

XVARIABLE_ML_COMMENT ::= ML_COMMENT ID  

XVARIABLE_SL_COMMENT ::= ID SL_COMMENT  

XINVARIANT ::=  

XINVARIANT_NO_COMMENT  

XINVARIANT_ML_COMMENT  

XINVARIANT_SL_COMMENT  

XINVARIANT_NO_COMMENT ::=  

XLABEL "XPREDICATE" [theorem]  

XINVARIANT_ML_COMMENT ::=  

ML_COMMENT XLABEL "XPREDICATE" [theorem]  

XINVARIANT_SL_COMMENT ::=  

XLABEL "XPREDICATE" [theorem] SL_COMMENT  

XEVENT ::=  

XEVENT_NO_COMMENT  

XEVENT_ML_COMMENT  

XEVENT_SL_COMMENT  

XEVENT_NO_COMMENT ::=  

ID  

([extended] & [ordinary | convergent | anticipated])  

[refines ID { ID }]  

[

```

```

[with XWITNESS { XWITNESS }]

begin XACTION { XACTION }

|
when XGUARD { XGUARD }

[with XWITNESS { XWITNESS }]

[then XACTION { XACTION }]

|
any XPARAMETER { XPARAMETER }

where XGUARD { XGUARD }

[with XWITNESS { XWITNESS }]

[then XACTION { XACTION }]

]

end

XEVENT_ML_COMMENT ::=

ML_COMMENT

ID

([extended] & [ordinary | convergent | anticipated])

[refines ID { ID }]

[
[with XWITNESS { XWITNESS }]

begin XACTION { XACTION }

|
when XGUARD { XGUARD }

[with XWITNESS { XWITNESS }]

[then XACTION { XACTION }]

```

```

|
any XPARAMETER { XPARAMETER }
where XGUARD { XGUARD }
[with XWITNESS { XWITNESS }]
[then XACTION { XACTION }]
]

end

XEVENT_SL_COMMENT ::=

ID
([extended] & [ordinary | convergent | anticipated])
[refines ID { ID }]

SL_COMMENT

[
[with XWITNESS { XWITNESS }]
begin XACTION { XACTION }
|
when XGUARD { XGUARD }
[with XWITNESS { XWITNESS }]
[then XACTION { XACTION }]
|
any XPARAMETER { XPARAMETER }
where XGUARD { XGUARD }
[with XWITNESS { XWITNESS }]
[then XACTION { XACTION }]
]

```

```

end

XWITNESS ::=

    XWITNESS_NO_COMMENT |
    XWITNESS_ML_COMMENT |
    XWITNESS_SL_COMMENT |

    XWITNESS_NO_COMMENT ::= XLABEL "XPREDICATE"
    XWITNESS_ML_COMMENT ::= ML_COMMENT XLABEL "XPREDICATE"
    XWITNESS_SL_COMMENT ::= XLABEL "XPREDICATE" SL_COMMENT

XPARAMETER ::=

    XPARAMETER_NO_COMMENT |
    XPARAMETER_ML_COMMENT |
    XPARAMETER_SL_COMMENT |

    XPARAMETER_NO_COMMENT ::= ID
    XPARAMETER_ML_COMMENT ::= ML_COMMENT ID
    XPARAMETER_SL_COMMENT ::= ID SL_COMMENT

XGUARD ::=

    XGUARD_NO_COMMENT |
    XGUARD_ML_COMMENT |
    XGUARD_SL_COMMENT |

    XGUARD_NO_COMMENT ::=

        XLABEL "XPREDICATE" [theorem]

    XGUARD_ML_COMMENT ::=

        ML_COMMENT XLABEL "XPREDICATE" [theorem]

    XGUARD_SL_COMMENT ::=

        XLABEL "XPREDICATE" [theorem] SL_COMMENT

```

```

XACTION ::=

    XACTION_NO_COMMENT |

    XACTION_ML_COMMENT |

    XACTION_SL_COMMENT

XACTION_NO_COMMENT ::= XLABEL "XASSIGNMENT" [theorem]

XACTION_ML_COMMENT ::= ML_COMMENT XLABEL "XASSIGNMENT"

XACTION_SL_COMMENT ::= XLABEL "XASSIGNMENT" SL_COMMENT

```

5.4 Preferences

5.4.1 XContext Preferences

The following XContext preferences can be set on the the XContext preference page and its sub-pages.

Option	Description	Default
Compiler is activated	Compiler is activated or deactivated	Activated

Table 1: XContext Compiler Preferences

Compiler

Syntax Coloring

5.4.2 XMachine Preferences

The following XMachine preferences can be set on the XMachine preference page and its sub-pages.

Compiler

Syntax Coloring

5.5 XEvent-B Editors

5.5.1 XEvent-B Content Assist

In the XContext and XMachine editors press **Ctrl+Space** on code to complete. This opens a list of available code completions. Some tips for using code assist are listed in the following paragraph:

Option	Description	Default
Comment	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Green White None Platform dependent
Default	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
Invalid Symbol	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
Keyword	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Purple White Bold Platform dependent
Number	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Gray White None Platform dependent
Punctuation character	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
String	Color Background Style (Italic, Bold, Underline, Strike through) Font	Blue White None Platform dependent
Task Tag	Color Background Style (Italic, Bold, Underline, Strike through) Font	Light Blue White Bold Platform dependent

Table 2: XContext Syntax Coloring Preferences

Option	Description	Default
Compiler is activated	Compiler is activated or deactivated	Activated

Table 3: XMachine Compiler Preferences

Option	Description	Default
Comment	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Green White None Platform dependent
Default	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
Invalid Symbol	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
Keyword	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Purple White Bold Platform dependent
Number	Color Background Style (Italic, Bold, Underline, Strike through) Font	Dark Gray White None Platform dependent
Punctuation character	Color Background Style (Italic, Bold, Underline, Strike through) Font	Black White None Platform dependent
String	Color Background Style (Italic, Bold, Underline, Strike through) Font	Blue White None Platform dependent
Task Tag	Color Background Style (Italic, Bold, Underline, Strike through) Font	Light Blue White Bold Platform dependent

Table 4: XMachine Syntax Coloring Preferences

- You can use the mouse or the keyboard (Up Arrow, Down Arrow, Page Up, Page Down, Home, End, Enter) to navigate and select lines in the list.
- Clicking or pressing Enter on a selected line in the list inserts the selection into the editor.




Figure 24: Content Assist for adding Sees clause

5.5.2 XEvent-B Formatter

In the XContent and XMachine editors press **Ctrl+Shift+F** on code to format it. If no selection is set then the entire source is formatted otherwise only the selection will be.

6 Legal

6.1 RODIN Software User Agreement

June 1st, 2006

6.1.1 Usage Of Content

THE RODIN PROJECT MAKES AVAILABLE SOFTWARE, DOCUMENTATION, INFORMATION AND/OR OTHER MATERIALS FOR OPEN SOURCE PROJECTS (COLLECTIVELY "CONTENT"). USE OF THE CONTENT IS GOVERNED BY THE TERMS AND CONDITIONS OF THIS AGREEMENT AND/OR THE TERMS AND CONDITIONS OF LICENSE AGREEMENTS OR NOTICES INDICATED OR REFERENCED BELOW. BY USING THE CONTENT, YOU AGREE THAT YOUR USE OF THE CONTENT IS GOVERNED BY THIS AGREEMENT AND/OR THE TERMS AND CONDITIONS OF ANY APPLICABLE LICENSE AGREEMENTS OR NOTICES

INDICATED OR REFERENCED BELOW. IF YOU DO NOT AGREE TO THE TERMS AND CONDITIONS OF THIS AGREEMENT AND THE TERMS AND CONDITIONS OF ANY APPLICABLE LICENSE AGREEMENTS OR NOTICES INDICATED OR REFERENCED BELOW, THEN YOU MAY NOT USE THE CONTENT.

6.1.2 Applicable Licences

Unless otherwise indicated, all Content made available by the CODA project is provided to you under the terms and conditions of one of the following licences. Unless otherwise indicated, all Content made available by the Rodin Project is provided to you under the terms and conditions of the Eclipse Public License Version 1.0 (“EPL”). A copy of the EPL is provided with this Content and is also available at <http://www.eclipse.org/legal/epl-v10.html>. For purposes of the EPL, “Program” will mean the Content.

Content includes, but is not limited to, source code, object code, documentation and other files maintained in the Rodin SourceForge CVS repository (“Repository”) in CVS modules (“Modules”) and made available as downloadable archives (“Downloads”).

- Content may be structured and packaged into modules to facilitate delivering, extending, and upgrading the Content. Typical modules may include plug-ins (“Plug-ins”), plug-in fragments (“Fragments”), and features (“Features”).
- Each Plug-in or Fragment may be packaged as a sub-directory or JAR (JavaTM ARchive) in a directory named “plugins”.
- A Feature is a bundle of one or more Plug-ins and/or Fragments and associated material. Each Feature may be packaged as a sub-directory in a directory named “features”. Within a Feature, files named “feature.xml” may contain a list of the names and version numbers of the Plug-ins and/or Fragments associated with that Feature.
- Features may also include other Features (“Included Features”). Within a Feature, files named “feature.xml” may contain a list of the names and version numbers of Included Features.

The terms and conditions governing Plug-ins and Fragments should be contained in files named “about.html” (“Abouts”). The terms and conditions governing Features and Included Features should be contained in files named “license.html” (“Feature Licenses”). Abouts and Feature Licenses may be located in any directory of a Download or Module including, but not limited to the following locations:

- The top-level (root) directory
- Plug-in and Fragment directories
- Inside Plug-ins and Fragments packaged as JARs
- Sub-directories of the directory named “src” of certain Plug-ins
- Feature directories

Note: if a Feature made available by the Rodin Project is installed using the Eclipse Update Manager, you must agree to a license (“Feature Update License”) during the installation process. If the Feature contains Included Features, the Feature Update License should either provide you with the terms and conditions governing the Included Features or inform you where you can locate them. Feature Update Licenses may be found in the “license” property of files named “feature.properties” found within a Feature. Such Abouts, Feature Licenses, and Feature Update Licenses contain the terms and conditions (or references to such terms and conditions) that govern your use of the associated Content in that directory.

THE ABOUTS, FEATURE LICENSES, AND FEATURE UPDATE LICENSES MAY REFER TO THE EPL OR OTHER LICENSE AGREEMENTS, NOTICES OR TERMS AND CONDITIONS. SOME OF THESE OTHER LICENSE AGREEMENTS MAY INCLUDE (BUT ARE NOT LIMITED TO):

- Common Public License Version 1.0 (available at <http://www.eclipse.org/legal/cpl-v10.html>)
- Apache Software License 1.1 (available at <http://www.apache.org/licenses/LICENSE>)
- Apache Software License 2.0 (available at <http://www.apache.org/licenses/LICENSE-2.0>)
- IBM Public License 1.0 (available at <http://oss.software.ibm.com/developerworksopensource/license10.html>)
- Metro Link Public License 1.00 (available at <http://www.opengroup.org/openmotif/supporters/metrolink/license.html>)
- Mozilla Public License Version 1.1 (available at <http://www.mozilla.org/MPL/MPL-1.1.html>)

IT IS YOUR OBLIGATION TO READ AND ACCEPT ALL SUCH TERMS AND CONDITIONS PRIOR TO USE OF THE CONTENT. If no About, Feature License, or Feature Update License is provided, please contact the Rodin Project to determine what terms and conditions govern that particular Content.

6.1.3 Cryptography

Content may contain encryption software. The country in which you are currently may have restrictions on the import, possession, and use, and/or re-export to another country, of encryption software. BEFORE using any encryption software, please check the country’s laws, regulations and policies concerning the import, possession, or use, and re-export of encryption software, to see if this is permitted.

- Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.