

# A Sample Document for the Usages of **lstEventB** Package

Thai Son Hoang  
ECS, University of Southampton  
<T dot S dot Hoang at ecs dot soton dot ac dot uk>

March 28, 2021

For convenient, we define macro `\EventB` for Event-B.

We start first with some inline Event-B code by embedding them using a pair of `|`, for example `|@grd1: SNSR = FALSE|` gives `@grd1: SNSR = FALSE`. Any Event-B formulae including Unicode symbols will be typeset using the `bsymb` package accordingly.

ASCII	Symbols	Explanation
<code>!:</code>	$\in$	Set membership
<code>/:</code>	$\notin$	Set non-membership
<code>&lt;:</code>	$\subseteq$	Subset
<code>/&lt;:</code>	$\not\subseteq$	Not a subset
<code>&lt;&lt;:</code>	$\subset$	Proper subset
<code>/&lt;&lt;:</code>	$\not\subset$	Not a proper subset
<code>!finite</code>	finite	Finite
<code>!partition</code>	partition	Partition

Table 1: Set predicates

ASCII	Symbols	Explanation
<code>!BOOL</code>	BOOL	BOOL set
<code>!TRUE</code>	TRUE	TRUE
<code>!FALSE</code>	FALSE	FALSE
<code>!bool</code>	bool	bool predicate

Table 2: BOOL and bool

More complete piece of code (including the Unicode symbols) can be typeset using the `EventBcode` environment. Below is the typesetting of an Event-B machine.

---

ASCII	Symbols	Explanation
<code>!INT</code>	$\mathbb{Z}$	Set of integer numbers
<code>!NAT</code>	$\mathbb{N}$	Set of natural numbers
<code>!NAT1</code>	$\mathbb{N}_1$	Set of positive natural numbers
<code>!min</code>	min	Minimum
<code>!max</code>	max	Maximum
<code>-</code>	$-$	Difference
<code>*</code>	$*$	Product
<code>!/</code>	$\div$	Quotient
<code>!mod</code>	mod	Remainder
<code>..</code>	$..$	Interval

Table 3: Numbers

ASCII	Symbols	Explanation
<code>&gt;</code>	$>$	Greater
<code>&lt;</code>	$<$	Less
<code>&gt;=</code>	$\geq$	Greater or equal
<code>&lt;=</code>	$\leq$	Less or equal

Table 4: Number predicates

ASCII	Symbols	Explanation
<code>&lt;-&gt;</code>	$\leftrightarrow$	Relations
<code>!dom</code>	dom	Domain
<code>!ran</code>	ran	Range
<code>&lt;&lt;-&gt;</code>	$\Leftrightarrow$	Total relations
<code>&lt;-&gt;&gt;</code>	$\Rrightarrow$	Surjective relations
<code>&lt;&lt;-&gt;&gt;</code>	$\Leftrightarrow$	Total surjective relations
<code>!circ</code>	$\circ$	Backward composition
<code>!id</code>	id	Identity
<code>&lt; </code>	$\triangleleft$	Domain restriction
<code>&lt;&lt; </code>	$\triangleleft$	Domain subtraction
<code> &gt;</code>	$\triangleright$	Range restriction
<code> &gt;&gt;</code>	$\triangleright$	Range subtraction
<code>~</code>	$\sim$	Inverse
<code>&lt;+</code>	$\Leftarrow$	Overriding
<code>&gt;&lt;</code>	$\otimes$	Direct product
<code>  </code>	$\parallel$	Parallel product
<code>!prj1</code>	$\text{prj}_1$	First projection
<code>!prj2</code>	$\text{prj}_2$	Second projection

Table 5: Relations

ASCII	Symbols	Explanation
$\leftrightarrow$	$\leftrightarrow$	Partial functions
$\rightarrow$	$\rightarrow$	Total functions
$\rightarrowtail$	$\rightarrowtail$	Partial injections
$\hookrightarrow$	$\hookrightarrow$	Total injections
$\twoheadrightarrow$	$\twoheadrightarrow$	Partial surjections
$\twoheadrightarrow$	$\twoheadrightarrow$	Total surjections
$\rightarrowtail$	$\rightarrowtail$	Bijections
$\lambda$	$\lambda$	Lambda abstraction

Table 6: Functions

ASCII	Symbols	Explanation
$:=$	$:=$	Becomes equal to
$::$	$:\in$	Choice from a set
$: $	$: $	Choice by predicate

Table 7: Functions

```

1 machine Sensor_m0_SNSR
2 variables
3   SNSR
4 invariants
5   theorem @thm0.1: SNSR  $\in$  BOOL
6 events
7
8   INITIALISATION
9   begin
10     @act1: SNSR := FALSE
11   end
12
13   SNSR_on
14   when
15     @grd1: SNSR = FALSE
16   then
17     @act1: SNSR := TRUE
18   end
19
20   SNSR_off
21   when
22     @grd1: SNSR = TRUE
23   then
24     @act1: SNSR := FALSE
25   end
26
27 end

```

---

One can change the different colour options. For example, `\EventBSetKeywordColour{blue!50!black}` will change the keyword colour to dark blue. (This has effects only when

---

```

1 machine Sensor_m0_SNSR
2 variables

```

```

3 SNSR
4 invariants
5 theorem @thm0.1: SNSR  $\in$  BOOL

```

---

One can include external file containing Event-B code using the `\EventBinputlisting` command. For example the following is the result of including the code in the file `Sensor_m1_DEP.bumx` using `\EventBinputlisting{Sensor_m1_DEP.bumx}`.

```

1 machine Sensor_m1_DEP
2 refines Sensor_m0_SNSR
3 variables
4 SNSR
5 DEP
6 invariants
7 @inv0.1: DEP  $\in$   $\mathbb{N}$ 
8 events
9
10 INITIALISATION extended
11 begin
12 @act2: DEP := 0
13 end
14
15 SNSR_on extends SNSR_on
16 end
17
18 SNSR_off extends SNSR_off
19 begin
20 @act2: DEP := DEP + 1
21 end
22
23 end

```

---

More specifically, one can specify more details on the inclusion, e.g., the ranges, as the following example `\EventBinputlisting[firstline=16,lastline=20]{Sensor_m2_snsr.bumx}` gives

```

1 @inv1.1: Snsr_01 = TRUE  $\Rightarrow$  SNSR = TRUE
2
3 @inv1.2: Snsr_10 = TRUE  $\Rightarrow$  SNSR = FALSE
4
5 @inv1.3: Snsr_01 = FALSE  $\vee$  Snsr_10 = FALSE

```

---

```

1 machine Sensor_m3_Ctrl
2
3 refines
4
5 Sensor_m2_Snsr
6
7 variables

```

---

```

8
9  SNSR
10
11  DEP
12
13  Snsr_01
14
15  Snsr_10
16
17  ctrl_snsr
18
19  ctrl_dep
20
21  ctrl_snsr_01
22
23  ctrl_snsr_10
24
25  invariants
26
27  @inv2.1:
28  Snsr_01 = FALSE  $\wedge$  Snsr_10 = FALSE  $\wedge$  ctrl_snsr_01 = FALSE  $\wedge$  ctrl_snsr_10 = FALSE  $\Rightarrow$ 
    ctrl_snsr = SNSR
29
30  @inv2.2: ctrl_dep  $\in \mathbb{N}$ 
31
32  @inv2.3: Snsr_10 = FALSE  $\wedge$  ctrl_snsr_10 = FALSE  $\Rightarrow$  ctrl_dep = DEP
33
34  @inv2.4: Snsr_10 = TRUE  $\vee$  ctrl_snsr_10 = TRUE  $\Rightarrow$  ctrl_dep = DEP - 1
35
36  @inv2.5: ctrl_snsr_01 = TRUE  $\Rightarrow$  SNSR = TRUE
37
38  @inv2.6: ctrl_snsr_10 = TRUE  $\Rightarrow$  SNSR = FALSE
39
40  @inv2.7: ctrl_snsr_01 = TRUE  $\Rightarrow$  Snsr_01 = FALSE
41
42  @inv2.8: ctrl_snsr_10 = TRUE  $\Rightarrow$  Snsr_10 = FALSE
43
44  events
45
46  INITIALISATION extends INITIALISATION
47  begin
48    @act5: ctrl_snsr := FALSE
49    @act6: ctrl_dep := 0
50    @act7: ctrl_snsr_01 := FALSE
51    @act8: ctrl_snsr_10 := FALSE
52  end
53
54  SNSR_on extends SNSR_on
55  when
56    @grd3: ctrl_snsr_10 = FALSE
57  end
58
59  SNSR_off extends SNSR_off
60  when
61    @grd3: ctrl_snsr_01 = FALSE
62  end

```

```
63
64 ctrl_Senses_Snsr_01 extends ctrl_Senses_Snsr_01
65 begin
66   @act2: ctrl_snsr_01 := TRUE
67 end
68
69 ctrl_Senses_Snsr_10 extends ctrl_Senses_Snsr_10
70 begin
71   @act2: ctrl_snsr_10 := TRUE
72 end
73
74 ctrl_on
75 when
76   @grd1: ctrl_snsr_01 = TRUE
77 then
78   @act1: ctrl_snsr_01 := FALSE
79   @act2: ctrl_snsr := TRUE
80 end
81
82 ctrl_off
83 when
84   @grd1: ctrl_snsr_10 = TRUE
85 then
86   @act1: ctrl_snsr_10 := FALSE
87   @act2: ctrl_snsr := FALSE
88   @act3: ctrl_dep := ctrl_dep + 1
89 end
90
91 end
```