COVID-19 subject UPHS-1650

2021-06-23


The table below provides a summary of subject samples for which sequencing data is available. The experiments column shows the number of sequencing experiments performed for each specimen. Experiment specific analyses are shown at the end of this report. Lineages are called with the Pangolin software tool (Rambaut et al 2020) for genomes with > 90% sequence coverage.

Table 1. Sample summary.

Experiment	Туре	Genomes	Sample type	Sample date	Largest contig (KD)	Lineage	Reference read coverage	Reference read coverage (>= 5 reads)
VSP2951-1	single experiment	NA	NA	2021-05-16	29.80	B.1.1.7	99.8%	99.8%

Variants shared across samples

The heat map below shows how variants (reference genome /home/common/SARS-CoV-2-Philadelphia/Wuhan-Hu-1) are shared across subject samples where the percent variance is colored. Variants are called if a variant position is covered by 5 or more reads, the alternative base is found in > 50% of read pairs and the variant yields a PHRED score > 20. Gray tiles denote positions where the variant was not the major variant or no variants were found. The relative base compositions of each experiment used to calculate tiles are shown in the following plot where the total number of position reads are shown atop of each plot.




NA 2021-05-16

2021-05-16
1824
1448
3288
2657
3600
2891
2881
320
2688
608
4438
5448
1999
3655
4930
4261
5500
7653
9516
4794
2534
1801
186
2992
3114
4228
4561
2618
5140
9557
8858
8438
5424
6513
2709
1844
1844
1982
591
590
590
1409
228
VSP2951-1
92
P2
δ
•


Analyses of individual experiments and composite results

VSP2951-1 | 2021-05-16 | NA | UPHS-1650 | genomes | single experiment


The plot below shows the number of reads covering each nucleotide position in the reference genome. Variants are shown as colored dots along the bottom of the plot and are color coded according by variant types: gray - transgenic, green - silent, gold - missense, red - nonsense, black - indel.



Excerpt from plot above focusing on reads coverage from 0 to 50 NT.



The longest five assembled contigs are shown below colored by their edit distance to the reference genome.



Software environment

Software/R package	Version				
R	3.4.0				
bwa	0.7.17-r1198-dirty				
samtools	1.10 Using htslib 1.10				
bcftools	1.10.2-34-g1a12af0-dirty Using htslib $1.10.2-57-gf58a6f3$				
pangolin	3.1.3				
genbankr	1.4.0				
optparse	1.6.0				
forcats	0.3.0				
stringr	1.4.0				
dplyr	0.8.1				
purrr	0.2.5				
readr	1.1.1				
tidyr	0.8.1				
tibble	2.1.2				
ggplot2	3.3.3				
tidyverse	1.2.1				
ShortRead	1.34.2				
GenomicAlignments	1.12.2				
${\bf Summarized Experiment}$	1.6.5				
DelayedArray	0.2.7				
matrixStats	0.54.0				
Biobase	2.36.2				
Rsamtools	1.28.0				
GenomicRanges	1.28.6				
GenomeInfoDb	1.12.3				
Biostrings	2.44.2				
XVector	0.16.0				
IRanges	2.10.5				
S4Vectors	0.14.7				
BiocParallel	1.10.1				
BiocGenerics	0.22.1				