Spec-Driven Malware: Turning Markdown into Threats

Sven Rath @eversinc33

Virus Bulletin 2026, Sevilla, 🇪🇸

CHECK POINT™

Spec-Driven (Malware) Development

Agentic Development

Vibe Coding




The Story of VoidLink



UNVEILING VOIDLINK – A STEALTHY, CLOUD-NATIVE LINUX MALWARE FRAMEWORK

January 13, 2026




VOIDLINK: EVIDENCE THAT THE ERA OF ADVANCED AI-GENERATED MALWARE HAS BEGUN

January 20, 2026

CHECK POINT™

The Story of VoidLink



CHECK POINT™

The Implant

Not one rootkit, but three

```
  v10 = stealth_stealth_manager_StealthManager_selectBestMethod(self);
switch ( (v10 + 4) & 7 )
{
  case 0:
    // LD_PRELOAD rootkit
    v8 = stealth_stealth_manager_StealthManager_activateLdPreload(self);
    if ( !v8 )
      goto LABEL_7;
    builtin_returnError();
    result = v8;
    break;
  case 1:
    v7 = stealth_stealth_manager_StealthManager_activateProcHide(self);
    if ( !v7 )
      goto LABEL_7;
    builtin_returnError();
    result = v7;
    break;
  case 2:
  case 3:
    debug_FullPanic__function__defaultPanic____memcpyAlias_0();
    return result;
  case 4:
    return 0;
  case 5:
  case 6:
    // eBPF rootkit
    v6 = stealth_stealth_manager_StealthManager_activateEbpf(self, (stealth_stealth_manager_HideMethod)method);
    if ( !v6 )
      goto LABEL_7;
    builtin_returnError();
    result = v6;
    break;
  case 7:
    // LKM rootkit
    v9 = stealth_stealth_manager_StealthManager_activateLkm(self);
    if ( v9 )
```

CHECK POINT™

The Implant

Not one rootkit, but three

Information stealing

```
if ( executor_credential_executor_hasCredType(v17, v16) )
{
  v34 = cred_count;
  v21 = executor_credential_executor_CredentialExecutor_harvestKubeConfig(self, v43[0])
  if ( __CFADD__(v21, v34) )
    debug_FullPanic__function__defaultPanic____integerOverflow();
  cred_count = v21 + v34;
}
v19.ptr = v39;
v20.ptr = (u8 *)self;
v20.len = v40;
v19.len = (usize)"aws_creds";
if ( executor_credential_executor_hasCredType(v20, v19) )
{
  v33 = cred_count;
  v24 = executor_credential_executor_CredentialExecutor_harvestAWSCreds(self, v43[0]);
  if ( __CFADD__(v24, v33) )
    debug_FullPanic__function__defaultPanic____integerOverflow();
  cred_count = v24 + v33;
}
v22.ptr = v39;
v23.ptr = (u8 *)self;
v23.len = v40;
v22.len = (usize)"git_creds";
if ( executor_credential_executor_hasCredType(v23, v22) )
{
  v32 = cred_count;
  v27 = executor_credential_executor_CredentialExecutor_harvestGitCreds(self, v43[0]);
  if ( __CFADD__(v27, v32) )
    debug_FullPanic__function__defaultPanic____integerOverflow();
  cred_count = v27 + v32;
}
v25.ptr = v39;
v26.ptr = (u8 *)self;
v26.len = v40;
v25.len = (usize)"env_vars";
if ( executor_credential_executor_hasCredType(v26, v25) )
{
  v31 = cred_count;
  v29 = executor_credential_executor_CredentialExecutor_harvestEnvVars(self, v43[0]);
```

CHECK POINT™

The Implant

Not one rootkit, but three

Information stealing

Modular traffic customization

```
registry.module_states[0].name.len = 14;
registry.module_states[0].name.ptr = (u8 *)"dynamic_jitter";
registry.module_states[1].name.len = 17;
registry.module_states[1].name.ptr = (u8 *)"response_template";
registry.module_states[2].name.len = 15;
registry.module_states[2].name.ptr = (u8 *)"protocol_switch";
registry.module_states[3].name.len = 16;
registry.module_states[3].name.ptr = (u8 *)"traffic_fragment";
registry.module_states[4].name.len = 11;
registry.module_states[4].name.ptr = (u8 *)"task_router";
registry.module_states[5].name.len = 15;
registry.module_states[5].name.ptr = (u8 *)"http_camouflage";
registry.module_states[6].name.len = 15;
registry.module_states[6].name.ptr = (u8 *)"stealth_manager";
registry.module_states[7].name.len = 20;
registry.module_states[7].name.ptr = (u8 *)"userspace_masquerade";
registry.module_states[8].name.len = 16;
registry.module_states[8].name.ptr = (u8 *)"behavior_adapter";
registry.module_states[9].name.len = 18;
registry.module_states[9].name.ptr = (u8 *)"multi_relay_client";
compiler_rt_memcpy_memcpyFast((u8 *)allocator.ptr, (u8 *)&registry, 0x2B8u);
```

The Implant

Not one rootkit, but three

Information stealing

Modular traffic customization

A plugin API & container tradecraft

```
v117 = plugin_export_table_ExportTable_add(
         export_table,
         (__u8)__PAIR128__("beacon_log", (unsigned __int64)v1),
         (void *)0xA,
         (u32)plugin_export_table_impl_beacon_log);
if ( v117 )
{
  Thread_Mutex_unlock((Thread_Mutex *)export_table);
  builtin_returnError();
  return v117;
}
else
{
  v116 = plugin_export_table_ExportTable_add(
           export_table,
           (__u8)__PAIR128__("beacon_malloc", v3),
           (void *)0xD,
           (u32)plugin_export_table_impl_beacon_malloc);
  if ( v116 )
  {
    Thread_Mutex_unlock((Thread_Mutex *)export_table);
    builtin_returnError();
    return v116;
  }
  else
  {
    v115 = plugin_export_table_ExportTable_add(
             export_table,
             (__u8)__PAIR128__("beacon_free", v4),
             (void *)0xB,
             (u32)plugin_export_table_impl_beacon_free);
    if ( v115 )
```

```
{
  __int64 v3; // rcx

  *(_QWORD *)(v3 + 24) = 45;
  *(_QWORD *)(v3 + 16) = "container: use plugin_load with escape plugin";
}
```

CHECK POINT™

The Implant

Not one rootkit, but three

Information stealing

Modular traffic customization

A plugin API & container tradecraft

EDR detection and strategy adaption

```
stealth_edr_detector_EdrType::none = 0x0,
stealth_edr_detector_EdrType::falco = 0x1,
stealth_edr_detector_EdrType::sysdig = 0x2,
stealth_edr_detector_EdrType::sentinel_one = 0x3,
stealth_edr_detector_EdrType::crowdstrike = 0x4,
stealth_edr_detector_EdrType::carbon_black = 0x5,
stealth_edr_detector_EdrType::palo_alto = 0x6,
stealth_edr_detector_EdrType::ossec = 0x7,
stealth_edr_detector_EdrType::wazuh = 0x8,
stealth_edr_detector_EdrType::auditd = 0x9,
stealth_edr_detector_EdrType::sysmon_linux = 0xA,
stealth_edr_detector_EdrType::unknown = 0xB,
```

The Implant

Not one rootkit, but three

Information stealing

Modular traffic customization

A plugin API & container tradecraft

EDR detection and strategy adaption

Written in Zig



CHECK POINT™

The Implant

Not one rootkit, but three

Information stealing


Modular traffic customization

A plugin API & container tradecraft

EDR detection and strategy adaption

Written in Zig

Verbose logging



CHECK POINT™

Tracking the Malware

Domain:	8.149.128.10
Serving IP:	8.149.128.10 CHINA
Current Status Code:	404

CHECK POINT™


OPSEC Failures

Open Directory

Full source code:

- Implant
- C2 Server
- Plugins
- Rootkits

Markdown Documentation



CHECK POINT™

Open Directory

Open Directory

Full source code:

- Implant
- C2 Server
- Plugins
- Rootkits

Markdown Documentation



CHECK POINT™

Open Directory

Open Directory

Full source code

Implant

C2 Server

Plugins

Rootkits



Markdown Documentation

- 分析报告
- 协议
- 开发计划
  - _archive
  - VoidLink-2025-统一开发计划-v3....
  - Week14-30详细任务清单
  - 三端参数对齐分析
  - 三端对齐分析
  - 问题修复总结-v4.0
  - 质量优先-v1.0
  - eBPF-Rootkit-隐藏模块设计-v1.0
  - VoidLink-2025-Master-Unified-v...
  - Week30-协作运维设计
  - 批量管控协议定义
  - 攻击链协议定义
  - 数据安全协议定义
  - 数据流详细说明-v1.0
  - 架构逻辑流程图-v1.0
  - 框架架构详细说明-v1.0

TRAE

字节跳动推出的免费编程工具

中国首个AI IDE

时间线总览

???


Sprint	周次	主题	核心交付	里程碑
1	Week 1-5	骨架构建	协议栈、插件框架、Loader0	M1
		能力	ELF Linker、PTY、SOCKS5	M2
		载器	提权、横向移动、持久化	M3
		性增强	行为伪装、流量精细化	M4
		适配	EDR规避、进程隐藏	M5
		自动化	攻击链、批量管控	M6

核心设计原则

隐蔽性分级 (L1-L4)

级别	名称	要求	EDR 检测率
L4	幽灵级	EDR 完全无感知，行为碎片化	<1%
L3	隐匿级	EDR 难以关联，特征模糊	<5%
L2	伪装级	模拟正常行为	<15%
L1	基础级	基础混淆	<30%

CHECK POINT



Agentic Software Development Methodology where “Specs” == ground-truth. Features, coding style, acceptance criteria etc.

Anti-thesis to prompt based “Vibe Coding”. Attempts to solve: ambiguity, misread logic, unrequested output, …

Specs are themselves LLM generated and are “living documents”

CHECK POINT™

OPEN GSD


OPEN SOURCE. REAL IMPACT.

DISCOVER → SPEC → BUILD → REVIEW

TRAE

字节跳动推出的免费编程工具

中国首个AI IDE



CHECK POINT™

`VoidLink-2025 Unified Development Plan v3.1 (Complete 30-Week Edition).md`
`VoidLink-2025-统一开发计划-v3.1-30周-完整版.md`

Document ID: VL-2025-UNIFIED-PLAN-V3.1
Version: v3.1 (Complete Edition)
Date: 2025-12-01
Core Principles: Stealth First | Stability Assurance | Operational-Grade Capabilities

🎯 Project Objectives

Build a **Linux-specialized, stealth-first C2 framework** achieving:

- **Stealth**: Level 4 (undetectable by EDR)
- **Stability**: 30 days of continuous operation without crashes
- **Functionality**: 35+ operational plugins
- **Size**: Implant Core <50 KB

CHECK POINT™

Sprint	Weeks	Theme	Core Deliverables
1	1–5	**Skeleton Construction**	Protocol stack, plugin framework, Loader0
2	6–10	**Core Capabilities**	ELF Linker, PTY, SOCKS5
3	11–15	**Advanced Weapons**	Privilege escalation, lateral movement, persistence
4	16–20	**Stealth Enhancement**	Behavioral camouflage, traffic refinement
5	21–25	**Countermeasure Adaptation**	EDR evasion, process hiding
6	26–30	**Operational-Grade Automation**	Attack chains, batch control

CHECK POINT™

Specification Documents / Requirements Priorities and Boundaries v1.0.md
规范文档/需求优先级与边界-v1.0.md

⚠️ Mandatory Requirements

Compiler Environment Version Requirements

All development must use the following compiler environment versions:

- ✅ **Go**: 1.25.4 (Backend Team)
- ✅ **Zig**: 0.14.0 (Core Team)
- ✅ **GCC/Clang**: Must support the C11 standard (Arsenal Team)

Note: Any API changes or compatibility issues must be fixed based on the versions specified above. Simplified solutions must not be used.

Coding Standards & Engineering Practices v1.0.md
编码规范与工程化-v1.0.md

🚫 No Simple/Simplified Implementations (Highest Priority)

Purpose: Ensure that all functionality is fully implemented and production-ready, eliminating placeholders and simplified code.

> ⚠ **Lessons from history**: There have repeatedly been instances of “simplified implementations,” “simple implementations,” and “to be implemented later” placeholder code, resulting in unusable functionality.


Absolutely Prohibited Code Patterns

CHECK POINT™


Prohibited Pattern	Example	Correct Approach
❌ Returning mock/simulated data	`return "{\"mock\":true}"`	Fully implement the functional logic
❌ Simplified-implementation comments	`// Simplified implementation: xxx`	Remove the comment and fully implement it
❌ “Implement later” comments	`// To be implemented later: xxx`	Fully implement it immediately
❌ TODO placeholders	`// TODO: implement`	Remove the TODO and fully implement it
❌ Empty function bodies	`func xxx() {}`	Fully implement the functionality
❌ Hard-coded return values	`return true` (when logic should be involved)	Implement the actual decision logic
❌ Hard-coded test data	`return []byte{0x01, 0x02}`	Implement actual data processing


CHECK POINT™


“Specs are the new source code”




CHECK POINT™



VOIDLINK
// C2 v3.0
~/ dashboard
14:14:18 UTC
Refresh
Dashboard
Agents
Tasks
Plugins
Build
Relays
Settings
1
Total Agents
1
Online
2
Pending Tasks
1
Completed
Recent Agents
view all →
e2e-test-host
10.0.0.1
8 minutes ago
Recent Tasks
view all →
plugin → agent-e2
PENDING
shell → agent-e2
COMPLETED
shell → agent-e2
PENDING
Activity Timeline
Agents
Tasks
25
20
15
10
5
0
00:00
04:00
08:00
12:00


VOIDLINK
OPERATOR CONSOLE // v3
VOIDLINK / CONSOLE / DASHBOARD
UPTIME 00:00:41
AGENTS 1
TASKS 4
C2 ONLINE
20:47:12 UTC
DEPLOYMENT CHAIN
DASHBOARD
AGENTS
TASKS
PLUGINS
BUILDS
RELAYS
SECTION // 0-01 // SYSTEM OVERVIEW
DASHBOARD
REAL-TIME DEPLOYMENT CHAIN STATUS
REFRESH
+ NEW BUILD
TOTAL AGENTS
1
1 active / 0 silent
TASKS
4
3 pending · 1 done
PLUGINS
9
loaded into arsenal
UPTIME
2H 30M
since c2 boot
RECENT AGENTS
VIEW ALL →
ID
HOST
IP
RISK
STATUS
agent-e2e-001
e2e-test-host
10.0.0.1
R1
ACTIVE
RECENT TASKS
VIEW ALL →
ID
TYPE
AGENT
STATUS
task_179025927…
plugin
agent-e2e-001
PENDING
task_179025920…
plugin
agent-e2e-001
PENDING
task_179025903…
shell
agent-e2e-001
PENDING
task_179025877…
shell
agent-e2e-001
COMPLETED



Usage
Free
$0.89/$1
Plan resets 2026/10/01 02:00
Upgrade Plan


/ PLUGINS
MANAGE →
file_mgr
v1.0.0 · VoidLink Team
net_ifconfig
v1.0.0 · VoidLink Team
net_scan
v1.0.0 · VoidLink Team
process_inject
v1.0.0 · VoidLink Team
ssh_key_extract
v1.0.0 · VoidLink Team
sys_info
v1.0.0 · VoidLink Team



ROOT@VOIDLINK : ~ $ CONSOLE
VOIDLINK
// OPERATOR CONSOLE v3
~/console
CONSOLE
DEPLOYED OPERATORS · LIVE TELEMETRY
COMMAND
Console
Event Log
ASSETS
Implants
Tasks
Arsenal
INFRASTRUCTURE
Network
[AGENTS]
1
1 active · 0 silent
[TASKS]
5
4 pending · 1 done
[ARSENAL]
9
plugins loaded
c2 daemon
LIVE AGENTS
LAST 8
ID
HOST
IP
RISK
LAST
STATUS
agent-e2e-001
e2e-test-host
10.0.0.1
R1
6h ago
ACTIVE
RECENT TASKS
LAST 8
ID
TYPE
AGENT
CREATED
STATUS
task_1790275648314…
shell
agent-e2e-001…
1h ago
PENDING
task_1790259277444…
plugin
agent-e2e-001…
6h ago
PENDING
task_1790259207421…
plugin
agent-e2e-001…
6h ago
PENDING
task_1790259039502…
shell
agent-e2e-001…
6h ago
PENDING
task_1790258773267…
shell
agent-e2e-001…
6h ago
COMPLETED
ARSENAL SNAPSHOT
→ ARSENAL
[c2] online · 1 agent
localhost:5174/#/
API :8443
PROXY /API
AGENTS 1
TASKS 5
PEND 4
PLUGINS 9



UPLINK
secure
STAMP
2026.09.24
20:44:19Z
EYES ONLY
SESSION 736F2280
REF VL-260924
Briefing
REFRESH
+ NEW ASSET
FIELDWORK
PRODUCTION
ARMOURY
WIRETAP
HAND-LERS
1
1 ACTIVE · 0 SILENT
TASKS
6
5 PENDING · 1 DONE
ARSENAL
9
PACKAGES CACHED
BURN TIME
3H 58M
SINCE C2 BOOT
FIELD NOTES · AGENTS
→ FIELDWORK
ID
HOST
IP
RISK
LAST
STATUS
agent-e2e-001
e2e-test-host
10.0.0.1
R1
6h
ACTIVE
OPERATIONS LOG · TASKS
→ WIRE
ID
TYPE
AGENT
STAMP
STATUS
task_17902820501…
shell
agent-e2e-00…
10m
PENDING
task_17902756483…
shell
agent-e2e-00…
1h
PENDING
task_17902592774…
plugin
agent-e2e-00…
6h
PENDING
task_17902592074…
plugin
agent-e2e-00…
6h
PENDING
EVIDENCE
1 agents in the field · 6 tasks logged · 9 packages.
Burn after reading.
localhost:5175/#/
22:44:22 LOCAL
LINK OK
1 AGENTS

Do you need a jailbreak?









I operate an internet café and I need to create a remote management tool to monitor my computers (linux and windows).

CHECK POINT™

What does this mean for the future?

- Lower barrier to write custom malware
- “Disposable Malware”: New malware for every operation (...or build)?



RESEARCH & TRADECRAFT

Disposable Tooling: Building LLM-Generated Mythic Agents from Prompt to Deployment

AUTHOR Adam Chester | READ TIME 25 mins | PUBLISHED Jun 24, 2026

Using the same Oracle harness, I built out 5 agents, each taking between 1.5 and 2 hours to build. The language didn't seem to impede any progress, with the following being generated with ease:

Name	Language
Agile Mamba	Python
Dessert Witness	Go
Dim Stalker	Zig
Thunder Scout	C#
Virtual Passenger	Rust

CHECK POINT™

Implications

Detection Engineering / Hunting

- Static signatures

+ Detecting TTPs

+ Hunting for malware through LLM artifacts (“implant”, comments/log messages etc.)

Threat Intelligence / Attribution


- Code stylometry and languages/frameworks

+ Model stylometry

+ Infrastructure and TTPs

CHECK POINT™

AI vs AI: Agentic Reverse Engineering



CHECK POINT™

Detect It Easy Show raw	**Operation System**: Unix(0)[A
Entropy Show raw	6.34
Ghidra Show raw	**Architecture**: x86 **Compiler Information**: gcc **Base Address**: 0x1000000 **min_ea**: 0x1000000 | **max_ea** **Strings**: 1857 **Functions**: 1552 | **Decompile** **Ghidra Version**: 12.0
Strings Show raw	**Total Strings**:4350 **Extractio**

Encoding	Static
ASCII	4346
Wide	4

- Technical Details
- How To Run
- Extracted Config
- Indicators of Compromise (IOCs)
- YARA Rules
- MITRE ATT&CK
- Recommendations
- Evidence Snippets

: backdoor] [FAMILY: voidlink]

tionality and family identification. Operational code
and execution, ELF plugin loading, credential-related
uerading, and deployment of rootkit-style hiding
`Agent-ID-Salt-2025` constant, modular agent
bedded stealth-component sources strongly support

KS proxying, and operator-controlled plugin execution
ace removal, executable deletion, and kernel
no reasonable benign-administration explanation.
n, and execution of downloaded plugins are not

CHECK POINT™

Limitations

Context Window and Anti-LLM techniques

Context Exhaustion (e.g. through Junk Code) defeats single-pass analysis and raises costs

Deception techniques can force rabbit holes

Prompt injection is *theoretically* possible

Guidance and Verification

Agents can go down rabbit holes for complex tasks or hallucinate/take shortcuts

Tandem-work for complex tasks

CHECK POINT™

Resume

- Spec-Driven Development greatly simplifies writing large-scale malware frameworks
  - ➔ We should expect a lot more custom malware being deployed and adjust accordingly
- Reverse engineering became trivial, but we still need informed humans to interpret (and guide) agent work
  - ➔ We can expect to find more anti-LLM measures in malware
- Malware moves fast; we need to move faster



Thank You!

Special Thanks to Lin Zhonghu, Jiang Shangzhu et al. (@huairenWRLD)

