

S5750E(R2) Dual Stack 10G Ethernet Routing Fiber Switch



S5750E-16F-SI-R



S5750E-28F-SI-D



S5750E-52F-SI-R

■ Product Overview

S5750E(R2) series next-generation 10G stackable routing switch has advanced hardware and software architecture design. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features such as VSF, IEEE 802.3at optional. It is ideal for aggregation or access layer as its high performance, availability and reliability.

■ Key Features and Benefits

➤ Performance and Scalability

With high switching capacity, S5750E(R2) series support wire-speed L2/L3 forwarding and high routing performance for IPv4 and IPv6 protocols.

The 10 Gigabit Ethernet connectivity of S5750E(R2) is accomplished via a hot-pluggable 10 Gigabit SFP+ transceiver which supports distance up to 300 meters over multimode fiber and 10 to 40km over single-mode fiber(The distance depends the optical module chosen).

S5750E(R2) series fiber switches support AC+12VDC RPS power supplies.

➤ VSF(Virtual Switch Framework)

Virtual Switch Framework can virtualize multiple DCN switches into one logical device, achieving the sharing of information and data tables between different switches. The performance and ports density of virtualized device are greatly enlarged by times under VSF. VSF also simplifies management work for network administrator and provides more reliability.

➤ Rich L3 Features

S5750E(R2) series delivers high-performance, hardware based IP routing.RIP, OSPF and BGP provide dynamic routing by exchanging routing information with other Layer 3 switches and routers. With S5750E(R2) series, customers could easily achieve Policy based Route(PBR), which is important when they need multi exit application.

➤ Strong Multicast

© 2017 Yunke China Information Inc All rights reserved. This document is DCN Public Information
All specifications are subject to change without further notice. All features with * mark will be available by firmware upgrade.

S5750E(R2) series supports abundant multicast features. In Layer 2, such as IGMPv1/v2/v3 snooping and fast leave. L3 multicast protocols such as IGMPv1/v2/v3. With Multicast VLAN Register (MVR), multicast receiver/sender control and illegal multicast source detect functions; S5750E(R2) series provides great application experience for customer.

➤ Easy High Reliability network

MRPP is Multi-layer Ring Protection Protocol, which is DCN's private fast Ethernet ring protocol. Comparing to spanning tree protocol, it has advantages of fast convergence, simple protocol calculation, less system resources cost and so on, which can improve the reliability of Ethernet network operation.

➤ Comprehensive QoS

With 8 queues per port, S5750E(R2) series enable differentiated management of up to 8 traffic types. The traffic is prioritized according to IEEE802.1p, DSCP, IP precedence and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video.

S5750E(R2) series also supports Bi-directional rate-limiting, per port or traffic class, preserves network bandwidth and allows full control of network resources.

➤ Enhanced Security

IEEE 802.1X port-based access control and MAC-based access control ensure all users are authorized before being granted access to the network.

Ingress/Egress Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on L2/L3/L4 headers information. And for some services are based on time, the product can support time based ACL to match the requirement.

Secure Shell (SSH) encrypts network management information via Telnet providing secure network management.

RADIUS Authentication enables centralized control of the switch and restricts unauthorized users from altering the configuration of the switch.

➤ Abundant IPv6 Support

S5750E(R2) series supports IPv6 switching and routing based on hardware for maximum performance. With increased network devices growing the need for larger addressing and higher security become critical, S5750E(R2) series will be a right product to meet this requirement.

➤ Green-Energy

Temperature monitoring, alarming, automatic cooling, energy saving features are realized on S5750E(R2). According to the temperature monitoring, Fan speed can be adjusted or stopped to reduce energy consumption and noise.

■ Specification

Item	S5750E-16F-SI-R	S5750E-28F-SI-D	S5750E-52F-SI-R
Physical port	8 x 100/1000Base-X (SFP) + 4 x GE Combo(RJ45/SFP) + 4 x 10GbE (SFP+)	16 x 100/1000Base-X (SFP) + 8x GE Combo(GT/SFP) + 4 x 10GE(SFP+)	48 x 100/1000Base-X (SFP) + 4 x 10GbE (SFP+)
Management port	1 x RJ45 Ethernet Management port		

	1x Console port		
	1x USB2.0 interface		
Performance			
Switching Capacity	112Gbps	128Gbps	176Gbps
Throughput	83Mpps	95Mpps	131Mpps
Jumbo Frame	10K	10K	10K
MAC Address	16K	16K	16K
ARP Table	4K	4K	4K
Routing Table	1K	1K	1K
ACL Table	1K	1K	1K
Physical			
Dimension (W*H*D)	330mm x 44mm x 230mm	440mm x 44mm x 240mm	440mm*44mm*320mm
Relative Humidity	10%~90% non-condensing, storage 95%		
Temperature	Working 0°C~50°C, storage -40°C~70°C		
Power Supply	AC:100~240VAC, 50~60Hz + 12VDC RPS	AC:100~240VAC, 50~60Hz + 48V DC	AC:100~240VAC, 50~60Hz + 12VDC RPS
Power Consumption	<22W	<34W	<60W
Main Features			
L1, L2 Features	IEEE802.3(10Base-T), IEEE802.3u(100Base-TX), IEEE802.3z(1000BASE-X), IEEE802.3ab(1000Base-T), IEEE802.3ae(10GBase), IEEE802.3x, IEEE802.3ak(10GBASE-CX4)		
	Port loopback detection		
	LLDP and LLDP-MED		
	UDLD		
	802.3ad LACP, max 128 group trunks with max 8 ports for each trunk		
	LACP load balance		
	N:1 Port Mirroring		
	RSPAN		
	ERSPAN		
	IEEE802.1d(STP)		
	IEEE802.1w(RSTP)		
	IEEE802.1s(MSTP)		
	Root Guard		
	BPDU Guard		
	BPDU Tunnel		
802.1Q, 4K VLAN			
MAC VLAN, Vlan VLAN, PVLAN, Protocol VLAN, Multicast VLAN			
QinQ, Flexible QinQ			
GVRP			
N:1 VLAN Translation			
Broadcast / Multicast / Unicast Storm Control			

	IGMP v1/v2/v3 Snooping and L2 Query ND Snooping MLDv1/v2 Snooping Port Security Flow Control: HOL, IEEE802.3x Bandwidth Control
L3 Features	Static Routing,RIPv1/v2,OSPFv2,BGP4 OSPFv3, BGP4+ OSPF multiple process LPM Routing Policy-based Routing(PBR) for IPv4 and IPv6 VRRP URPF, ECMP BFD IGMP v1/v2/v3, IGMP Proxy, Static Multicast Route Multicast Receive Control Illegal Multicast Source Detect ARP Guard, Local ARP proxy, Proxy ARP, ARP Binding, Gratuitous ARP, ARP Limit Anti ARP Cheat, Anti ARP Scan DNS Client, DNS Relay GRE Tunnel
IPv6	6to4 Tunnel, Configured Tunnel, ISATAP Tunnel, GRE Tunnel ICMPv6,ND,DNSv6 IPv6 LPM Routing,IPv6 Policy-based Routing(PBR) IPv6 VRRPv3,IPv6 URPF,IPv6 RA RIPng,OSPFv3,BGP4+ MLD Snooping,IPv6 Multicast VLAN MLDv1/v2, IPv6 Any Cast RP, IPv6 ACL, IPv6 QoS
QoS	8 Queues SWRR, SP, WRR, WDRR, SWDRR Traffic Classification Based on 802.1p COS, ToS, DiffServ DSCP, ACL, port number Traffic Policing PRI Mark/Remark
ACL	IP ACL ,MAC ACL,IP-MAC ACL Standard and Expanded ACL Based on source/destination IP or MAC, IP Protocol, TCP/UDP port, DSCP, ToS, IP Precedence), VLAN, Tag/Untag, CoS Redirect and statistics Rules can be configured to port, VLAN, VLAN routing interfaces Time Ranged ACL

Security	802.1x AAA
	Port, MAC based authentication
	Accounting based on time length and traffic
	Guest VLAN and auto VLAN
	RADIUS for IPv4 and IPv6
	TACACS+ for IPv4 and IPv6
	MAB
DHCPv4/v6	DHCP Server/Client for IPv4/IPv6
Traffic Monitor	DHCP Relay/Option 82
	DHCP Snooping/Option 82
Traffic Monitor	sFlow Traffic Analysis
Security Network Management	CLI, WEB, Telnet, SNMPv1/v2c/v3 through IPv4 and IPv6
	Syslog and external Syslog Server
	HTTP SSL
	SNMP MIB, SNMP TRAP
	FTP/TFTP
	SNTP/NTP
	RMOM 1,2,3,9
	Authentication by Radius/TACACS
	SSH v1/v2
	Dual firmware images/ Configuration files
	802.3ah OAM, 802.1ag OAM
Data Center Features	VSF(Virtual Switch Framework)

The contents marked with “*” need future upgrade or are under development

■ Order Information

Product	Description
S5750E-16F-SI-R	10G Ethernet Routing Switch, 8 x 100/1000Base-X (SFP) + 4 x GE Combo(RJ45/SFP) + 4 x 10GbE (SFP+), AC + 12VDC RPS power supply
S5750E-28F-SI-D	10G Ethernet Routing Switch, 16 x 100/1000Base-X (SFP) + 8 x GE Combo(RJ45/SFP) + 4 x 10GbE (SFP+), AC + 48V DC power supply
S5750E-52F-SI-R	10G Ethernet Routing Switch, 48 x 100/1000Base-X (SFP) + 4 x 10GbE (SFP+), AC + 12VDC RPS power supply
AOC-SFPX-10M	AOC cable with 2 10G(SFP+) modules, 10m, suitable for SFP+ ports on same model of switch, can be used for VSF
DAC-SFPX-3M	DAC cable with 2 10G(SFP+) modules, 3m, suitable for SFP+ ports on same model of switch, can be used for VSF

■ Contact us

For more detail information about DCN product, contact:

URL: <http://www.DCNglobal.com>

Email: sales@DCNglobal.com

Address: Digital Technology Plaza, NO.9 Shangdi 9th Street, Haidian District, Beijing, China