

Łukasiewicz Public Announcement Logic

Non-classical Dynamic Epistemic Logics

Umberto Rivieccio
UFRN

Introduction: DEL

- **Dynamic logics** are language expansions of modal logic designed to reason about change, and widely applied in computer science.
- Dynamic **epistemic** logic (DEL) models changes affecting the cognitive state of agents.
- We focus here on changes that do not concern facts of the world but rather cognitive states (e.g., public announcements).
- Logical consequence in DEL can be difficult to treat (from a syntactic as well as semantic point of view), e.g. because it is not substitution-invariant.

Introduction: DEL

- Recent work of Alessandra Palmigiano and collaborators tackles the above problems using **display calculi** to axiomatize systems of DEL and **duality theory** to study their semantics.
- Alessandra & co. propose a uniform methodology for developing DEL in a number of **non-classical settings**, which can be useful for different applications.
- In this talk I will report on the algebraic and duality-theoretic aspects of this ongoing enterprise.

Epistemic updates

- Epistemic change is represented in DEL as a transformation from a (relational, algebraic) model representing the current situation to a new model that represents the situation after some **epistemic action** has occurred.
- The update on the epistemic state of agents caused by an action is known as **epistemic update**.
- Epistemic updates are formalized
 - on Kripke-style models via (pseudo-) **co-products** and **sub-models**,
 - on algebras via (pseudo-) **products** and **quotients**.

Epistemic Action and Knowledge

- The logic EAK was introduced by A. Baltag, L.S. Moss and S. Solecki (1999) to deal with “Public Announcements, Common Knowledge and Private Suspicions”.
- The language of EAK is that of modal logic (S5) expanded with **dynamic operators** $\langle \alpha \rangle$ and $[\alpha]$, where α is an **action structure**.
- The intended meaning of $\langle \alpha \rangle \varphi$ is: the action α can be executed, and after execution φ holds.
- Dually, $[\alpha] \varphi$ means: if the action α can be executed, then after execution φ holds.

Epistemic Action and Knowledge

Language of (classical, single-agent) EAK

$$\varphi ::= p \in \mathbf{Var} \mid \neg\varphi \mid \varphi \vee \varphi \mid \dots \mid \Diamond\varphi \mid \Box\varphi \mid \langle\alpha\rangle\varphi \mid [\alpha]\varphi,$$

where α is an **action structure**:

$$\alpha = (K, k, R_\alpha, Pre_\alpha : K \rightarrow Fm).$$

Epistemic Action and Knowledge

Language of (classical, single-agent) EAK

$$\varphi ::= p \in \mathbf{Var} \mid \neg\varphi \mid \varphi \vee \varphi \mid \dots \mid \Diamond\varphi \mid \Box\varphi \mid \langle\alpha\rangle\varphi \mid [\alpha]\varphi,$$

where α is an **action structure**:

$$\alpha = (K, k, R_\alpha, Pre_\alpha : K \rightarrow Fm).$$

Kripke semantics

For $M = (W, R, v)$, define

$$M, w \Vdash \langle\alpha\rangle\varphi \quad \text{iff} \quad M, w \Vdash Pre(\alpha) \text{ and } M^\alpha, w \Vdash \varphi$$

$$M, w \Vdash [\alpha]\varphi \quad \text{iff} \quad \text{if } M, w \Vdash Pre(\alpha), \text{ then } M^\alpha, w \Vdash \varphi$$

where M^α is the **updated model**, after execution of α .

Epistemic Action and Knowledge

Intermediate model (pseudo coproduct)

Given $\alpha := (K, k, R_\alpha, Pre_\alpha : K \rightarrow Fm)$ and $M = (W, R, v)$, let

$$\coprod_\alpha M := (\coprod_K W, R \times R_\alpha, \coprod_K v)$$

- $\coprod_K W \cong W \times K$
- $(w, j)(R \times R_\alpha)(u, i) \quad \text{iff} \quad wRu \text{ and } jR_\alpha i$
- $(\coprod_K v)(p) := \coprod_K v(p).$

Epistemic Action and Knowledge

Intermediate model (pseudo coproduct)

Given $\alpha := (K, k, R_\alpha, Pre_\alpha : K \rightarrow Fm)$ and $M = (W, R, v)$, let

$$\coprod_\alpha M := (\coprod_K W, R \times R_\alpha, \coprod_K v)$$

- $\coprod_K W \cong W \times K$
- $(w, j)(R \times R_\alpha)(u, i) \quad \text{iff} \quad wRu \text{ and } jR_\alpha i$
- $(\coprod_K v)(p) := \coprod_K v(p).$

The second step, M^α

M^α is the submodel of $\coprod_\alpha M$ with domain

$$W^\alpha := \{(w, j) \mid M, w \Vdash Pre_\alpha(j)\}.$$

Axiomatization

EAK is axiomatized by

- the axioms and rules of modal logic (S5) plus the following axioms:


- 1 $\langle \alpha \rangle p \leftrightarrow (Pre(\alpha) \wedge p)$ where $p \in \text{Var}$
- 2 $\langle \alpha \rangle \neg \varphi \leftrightarrow (Pre(\alpha) \wedge \neg \langle \alpha \rangle \varphi)$
- 3 $\langle \alpha \rangle (\varphi \vee \psi) \leftrightarrow (\langle \alpha \rangle \varphi \vee \langle \alpha \rangle \psi)$
- 4 $\langle \alpha \rangle \Diamond \varphi \leftrightarrow (Pre(\alpha) \wedge \bigvee \{ \Diamond \langle \alpha_i \rangle \varphi \mid kR_\alpha i \})$

where $\alpha = \alpha_k$ and $\alpha_i = (K, i, R_\alpha, Pre_\alpha)$ for each $i \in K$.

- The rule:

from $\emptyset \vdash \varphi \rightarrow \psi$ infer $\emptyset \vdash \langle \alpha \rangle \varphi \rightarrow \langle \alpha \rangle \psi$.

Methodology: dual characterizations



Methodology: dual characterizations

The above methodology can be uniformly applied to a variety of (non-classical) modal systems, including:

- Distributive lattice-based logics (classical, intuitionistic, positive modal logic).
- Paraconsistent modal logics (bilattices, N4-lattices).
- Substructural logics (finite-valued Łukasiewicz).

Methodology: dual characterizations

The above methodology can be uniformly applied to a variety of (non-classical) modal systems, including:

- Distributive lattice-based logics (classical, intuitionistic, positive modal logic).
- Paraconsistent modal logics (bilattices, N4-lattices).
- Substructural logics (finite-valued Łukasiewicz).

Results

- Hilbert-style axiomatizations
- Completeness w.r.t. to algebraic and relational models
- Display calculi.

Intermediate models as algebras

Let \mathbb{A} be a modal algebra and $\alpha = (K, k, R_\alpha, Pre_\alpha : K \rightarrow \mathbb{A})$ an action structure over \mathbb{A} .

Define

$$\prod_{\alpha} \mathbb{A} := (\mathbb{A}^K, \Diamond^{\prod_{\alpha} \mathbb{A}}, \Box^{\prod_{\alpha} \mathbb{A}})$$

where, for each $f : K \rightarrow \mathbb{A}$ and $j \in K$,

$$(\Diamond^{\prod_{\alpha} \mathbb{A}} f)(j) = \bigvee \{ \Diamond^{\mathbb{A}} f(i) \mid j R_{\alpha} i \}$$

$$(\Box^{\prod_{\alpha} \mathbb{A}} f)(j) = \bigwedge \{ \Box^{\mathbb{A}} f(i) \mid j R_{\alpha} i \}.$$

A similar definition can be given for (semi)lattices with operators, HAOs, modal bilattices etc.

The pseudo quotient

Let \mathbb{A} be a modal algebra and $\alpha = (K, k, R_\alpha, Pre_\alpha : K \rightarrow \mathbb{A})$ an action structure over \mathbb{A} .

Since $Pre_\alpha \in \prod_\alpha \mathbb{A}$, we let, for every $b, c \in \prod_\alpha \mathbb{A}$,

$$b \equiv_\alpha c \quad \text{iff} \quad b \wedge Pre_\alpha = c \wedge Pre_\alpha$$

and we have a Boolean algebra $\prod_\alpha \mathbb{A} / \equiv_\alpha$ on which we define, for any $[b] \in \prod_\alpha \mathbb{A} / \equiv_\alpha$,

$$\Diamond^\alpha [b] := [\Diamond^{\prod_\alpha \mathbb{A}} (Pre_\alpha \wedge b)]$$

$$\Box^\alpha [b] := [\Box^{\prod_\alpha \mathbb{A}} (Pre_\alpha \rightarrow b)].$$

The pseudo quotient

Remarks:

- We can define an injective map $\iota: [b] \mapsto b \wedge Pre_\alpha$ that embeds $\prod_\alpha \mathbb{A}/\equiv_\alpha$ into $\prod_\alpha \mathbb{A}$.
- If \mathbb{A} is a different algebra with operators (bilattice, MV), the relation $\{(b, c) \in A \times A \mid b \wedge Pre_\alpha = c \wedge Pre_\alpha\}$ may not be a congruence of the non-modal reduct of \mathbb{A} .
- A more widely applicable recipe: if the underlying non-modal logic \mathcal{L} is algebraizable, take the congruence $\theta(Fi_{\mathcal{L}}(Pre_\alpha))$ determined by the logical filter $Fi_{\mathcal{L}}(Pre_\alpha)$.
- To define $\diamond^\alpha, \square^\alpha$ we still need a uniform characterization of $\theta(Fi_{\mathcal{L}}(Pre_\alpha))$, for example

$$\{(b, c) \in A \times A \mid b \wedge (Pre_\alpha)^n = c \wedge (Pre_\alpha)^n\}$$

works for n -potent modal MV-algebras.

Algebraic semantics

For every algebraic model $M = (\mathbb{A}, v)$, where $v: \text{Var} \rightarrow \mathbb{A}$, the extension map $\llbracket \cdot \rrbracket_M : Fm \rightarrow \mathbb{A}$ is defined as:

$$\begin{aligned}
 \llbracket p \rrbracket_M &= v(p) \\
 \llbracket \varphi \spadesuit \psi \rrbracket_M &= \llbracket \varphi \rrbracket_M \spadesuit^{\mathbb{A}} \llbracket \psi \rrbracket_M & \spadesuit &\in \{\wedge, \vee, \rightarrow, \dots\} \\
 \llbracket \heartsuit \varphi \rrbracket_M &= \heartsuit^{\mathbb{A}} \llbracket \varphi \rrbracket_M & \heartsuit &\in \{\diamond, \square, \neg, \dots\} \\
 \llbracket \langle \alpha \rangle \varphi \rrbracket_M &= \llbracket Pre(\alpha_k) \rrbracket_M \wedge^{\mathbb{A}} \pi_k \circ \iota(\llbracket \varphi \rrbracket_{M^\alpha}) \\
 \llbracket [\alpha] \varphi \rrbracket_M &= \llbracket Pre(\alpha_k) \rrbracket_M \rightarrow^{\mathbb{A}} \pi_k \circ \iota(\llbracket \varphi \rrbracket_{M^\alpha}).
 \end{aligned}$$

Completeness results

- Soundness of the axioms is checked w.r.t. to algebraic models.
- Completeness is obtained using the interaction axioms to reduce EAK to its static fragment (e.g., modal logic S5).
- Soundness and completeness w.r.t. relational models follow by duality.
- Classical and intuitionistic EAK are also axiomatized by means of modular, cut-free display-style sequent calculi.

Further work

- Understand epistemic updates on algebras in the most general setting (role of Leibniz congruence, preservation of equations).
- Extend to other logics (e.g., positive modal logic, infinite-valued Łukasiewicz, logics of order).
- Study updates in a topological duality setting.
- Applications in non-classical reasoning (e.g., public announcements with lies).

References

- A. Kurz and A. Palmigiano. [Epistemic Updates on Algebras](#). Logical Methods in Computer Science, 9(4:17), 2013, 1–28.
- M. Ma, A. Palmigiano and M. Sadrzadeh. [Algebraic semantics and model completeness for Intuitionistic Public Announcement Logic](#). Annals of Pure and Applied Logic, 165 (2014), 963–995.
- U. Riveccio. [Bilattice public announcement logic](#). R. Goré, B. Kooi and A. Kurucz (eds.), Advances in Modal Logic, Vol. 10, College Publications, 2014, 459–477.
- Z. Bakhtiari and U. Riveccio. [Epistemic updates on bilattices](#). To appear on Proceedings of LORI 2015.
- L. Cabrer, U. Riveccio and R. Rodríguez. [Łukasiewicz Public Announcement Logic](#). In preparation.