

Pump Performance Datasheet

Customer	:	Quote number	:
Customer reference	:	Size	: IE 100x080x315
Item number	: Default	Stages	: 1
Service	:	Based on curve number	: OKH 117 022.10_3.0
Quantity	: 1	Date last saved	: 25 Sep 2025 11:02 AM

Operating Conditions		Liquid	
Flow, rated	: 500.0 USgpm	Liquid type	: Water
Differential head / pressure, rated (requested)	: 195.7 psi	Additional liquid description	:
Differential head / pressure, rated (actual)	: 198.4 psi	Solids diameter, max	: 0.00 mm
Suction pressure, rated / max	: 0.00 / 0.00 bar.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 20.00 deg C
Site Supply Frequency	: 60 Hz	Fluid density, rated / max	: 0.999 / 0.999 kg/dm3
Performance		Viscosity, rated	: 1.00 cSt
Speed criteria	: Synchronous	Vapor pressure, rated	: 0.00 bar.a
Speed, rated	: 3570 rpm	Material	
Impeller diameter, rated	: 269 mm	Material selected	: Standard
Impeller diameter, maximum	: 324 mm	Pressure Data	
Impeller diameter, minimum	: 268 mm	Maximum discharge pressure	: 14.72 bar.g
Efficiency	: 62.60 %	Maximum allowable working pressure	: N/A
NPSH required / margin required	: 3.33 / 0.00 m	Maximum allowable suction pressure	: N/A
Ns (imp. eye flow) / Nss (imp. eye flow)	: 815 / 11,659 US Units	Hydrostatic test pressure	: N/A
MCSF	: 167.2 USgpm	Driver & Power Data (@Max density)	
Head, maximum, rated diameter	: 213.5 psi	Driver sizing specification	: Rated power
Head rise to shutoff	: 8.99 %	Margin over specification	: 0.00 %
Flow, best eff. point	: 646.5 USgpm	Service factor	: 1.15 (used)
Flow ratio, rated / BEP	: 77.34 %	Power, hydraulic	: 42.57 kW
Diameter ratio (rated / max)	: 83.02 %	Power, rated	: 68.00 kW
Head ratio (rated dia / max dia)	: 62.15 %	Power, maximum, rated diameter	: 78.30 kW
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00	Minimum recommended motor rating	: 74.57 kW / 100 hp
Selection status	: Acceptable		

