

KS801 Pendent Fire Sprinkler Standard Response

UL Listed Pendent Series Fire Sprinkler Standard Response, 5mm
Glass Bulb, K5.6, 1/2" Connecting Thread.



Model: KS801

Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Pendent Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø5mm Standard Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

KS802 Pendent Fire Sprinkler Quick Response

KS802 Pendent Fire Sprinkler Quick Response UL Listed Pendent
Series Sprinkler, Quick Response, 3mm Glass Bulb, K5.6, 1/2"
Connecting Thread.



Pendent Series Fire Sprinkler

Model: KS802

Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Pendent Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø3mm Quick Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

KS803 Upright Fire Sprinkler Standard Response

UL Listed Upright Series Fire Sprinkler, Standard Response, 5mm
Glass Bulb, K5.6, 1/2" Connecting Thread.



Upright Series Fire Sprinkler

Model: KS803

Standard Coverage, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Upright Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø5mm Standard Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

KS804 Upright Fire Sprinkler Quick Response

UL Listed Upright Series Fire Sprinkler, Quick Response, 3mm Glass
Bulb, K5.6, 1/2" Connecting Thread.



Upright Series Fire Sprinkler

Model: KS804

Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Upright Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from 135°F/57°C, 155°F /68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø3mm Quick Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

KS805 Horizontal Sidewall Fire Sprinkler Standard Response

UL Listed Horizontal Sidewall Series Fire Sprinkler, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.



Horizontal Sidewall Series Fire Sprinkler

Model: KS805

Standard Coverage, Standard Response, 5mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Horizontal Sidewall Sprinklers are glass-bulb types designed for use in various commercial applications. The temperature range of 5mm and 3mm glass bulb is from 135°F/57°C, 155°F/68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø5mm Standard Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psig/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed

KS806 Horizontal Sidewall Fire Sprinkler Quick Response

UL Listed Horizontal Sidewall Series Fire Sprinkler Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.



Horizontal Sidewall Series Fire Sprinkler

Model: KS806

Standard Coverage, Quick Response, 3mm Glass Bulb, K5.6, 1/2" Connecting Thread.

UL Listed KSFCO Standard Coverage Horizontal Sidewall Sprinklers are glass-bulb types designed for use in various commercial applications.

KSFCO Horizontal Sidewall Sprinklers launched in year 2020 with standard response and quick response. The temperature range of 5mm and 3mm glass ball is from 135°F/57°C, 155°F/68°C, 175°F/79°C, 200°F/93°C up to 286°F/141°C.

Bulb Nominal Dia. & Response	Ø3mm Quick Response
Thread Size	NPT1/2" or BSPT1/2"
Nominal Orifice Size	1/2 Inch
Nominal K-Factor	5.6 (U.S.)/80 (metric)
Max. Working Pressure	175psi/1.2MPa (12bar)
Sprinkler Finish	Natural Brass, Chrome Finished or White Painting (RAL9010)
Nominal Temp. Rating °F (°C)	135°F/(57°C) 155°F/(68°C) 175°F/(79°C) 200°F/(93°C) 286°F/(141°C)
Listing and Approvals	UL Listed



FM Approval Water Flow Detector T-tap



UL/FM Water Flow Detector

Model	Nominal Pipe Size		Weight (kg)
KSWFD 2	2"	DN50	1.35
KSWFD 2.5	2.5"	DN65	1.35
KSWFD 3	3"	DN80	1.40
KSWFD 4	4"	DN100	1.45
KSWFD 6	6"	DN150	1.85
KSWFD 8	8"	DN200	2.42

- UL Listed, FM Approved.
- Rating Working Pressure: UL-Max 300PSI (2.1MPa)/ FM-Max 450PSI(3.1MPa)
- Flow Sensitivity Range for Signal: 4-10GPM (15.0-37.5L/min)
- Maximum Surge: 18FPS (5.5m/s)
- Contact Ratings: Two sets of SPDT (Form C)
10.1Amps at 125/250 VAC
2.0Amps at 24 VDC
- Operating Temperature Range: 40° F to 120°F (4.5°C to 49°C)
- Enclosure Rating: NEMA 4- suitable for indoor/outdoor use
- Conduit Entrances: Two opening for 1/2" conduit
One open, one knock-out type
- Compatible Pipe: Steel water pipe, schedule 10 through 40
- Service Use: Automatic Sprinkler: NFPA-13
One or Two Family Dwelling: NFPA-13D
Residential Occupancies up to 4 stories: NFPA-13R
National Fire Alarm Code: NFPA-72
- Warranty: 3 Years

Recessed Escutcheon White Painting

Recessed Escutcheon White Painting



Recessed Escutcheon White Painting for KSFCO Sprinklers

Code Number	Size	Color	Material
KS903	1/2"	White (RAL9010)	Mild Steel
KS904	3/4"	White (RAL9010)	Mild Steel

