

VIZM7.EX15240 - Fittings, Rubber Gasketed Certified for Canada

Fittings, Rubber Gasketed Certified for Canada

WEIFANG 100TONG CASTING CO LTD
1919 Airport South Rd
Weicheng District
Weifang, Shandong 261000 China

EX15240

Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (kPa)
XGQT01	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	2760
XGQT01	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	2070
XGQT01	Rolled	T3091-1993	6-1/2 OD	2070
XGQT01	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	2760
XGQT01	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	2070
XGQT01	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2068
XGQT01	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3448
XGQT01	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3448
XGQT01	Rolled	10	4	2758
XGQT01	Rolled, Cut	40	4	2758
XGQT01	Rolled	10	5, 6, 8, 10, 12	2068
XGQT01	Rolled, Cut	40	5, 6, 8, 10, 12	2068
XGQT01H	Rolled, cut	3507-SPP	60.5mm, 76.3mm, 89.1mm, 114.3mm	3450
XGQT01H	Rolled, cut	3507-SPP	139.8mm, 165.2mm	3102
XGQT01H	Rolled, cut	3507-SPP	216.3mm, 267.4mm, 318.5mm, 355.6mm, 406.4mm	2070
XGQT01H	Rolled, cut	3507-SPP	457.2mm, 508.0mm, 609.6mm	1723
XGQT01H	Rolled, cut	3562-40	60.5mm, 76.3mm, 89.1mm, 114.3mm	3450
XGQT01H	Rolled, cut	3562-40	139.8mm, 165.2mm	3102
XGQT01H	Rolled, cut	3562-40	216.3mm, 267.4mm, 318.5mm, 355.6mm, 406.4mm	2070

XGQT01H	Rolled, cut	3562-30	457.2mm, 508.0mm	1723
---------	-------------	---------	------------------	------

8/1/23, 21:10	VIZM7.EX15240 - Fittings, Rubber Gasketed Certified for Canada UL Product iQ			
XGQ101H	Rolled, cut	3562-20	609.6mm	1723
XGQT02H	Rolled	3507-SPP	355.6mm, 406.4mm, 457.2mm 508.0mm, 609.6mm	1723
XGQT02H	Rolled	3562-40	355.6mm, 406.4mm	1723
XGQT02H	Rolled, cut	3562-30	457.2mm, 508.0mm	1723
XGQT02H	Rolled	3562-20	609.6mm	1723
XGQT02D	Rolled	3576-10S	216.3mm, 267.4mm, 318.5mm	1723
XGQT02D	Rolled	3576-20S	216.3mm, 267.4mm, 318.5mm	1723
XGQT02D	Rolled	3588-10S	355.6mm, 406.4mm, 457.2mm, 508.0mm	1723
XGQT02D	Rolled	3588-20S	355.6mm, 406.4mm, 457.2mm, 508.0mm	1723
SS01	Rolled	3576-10S	60.5mm, 76.3mm, 89.1mm, 114.3mm, 139.8mm, 165.2mm	1723
SS01	Rolled	3576-20S	60.5mm, 76.3mm, 89.1mm, 114.3mm, 139.8mm, 165.2mm	1723
SS02	Rolled	3576-10S	216.3mm, 267.4mm, 318.5mm	1723
SS02	Rolled	3576-20S	216.3mm, 267.4mm, 318.5mm	1723
101T	Rolled	5	1, 1-1/4, 1-1/2, 2	2070
101T	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
101T	Rolled	10	1, 1-1/4, 1-1/2	3102
101T	Rolled, cut	40	1, 1-1/4, 1-1/2	3102
101T	Rolled	10	2, 2-1/2, 3, 4, 5, 6	2516
101T	Rolled, cut	40	2, 2-1/2, 3, 4, 5, 6	2516
101T	Rolled	EN10217-1	33.7mm, 42.4mm, 48.3mm	3102
101T	Rolled	EN10217-1	60.3mm, 73mm, 76.1mm, 88.9mm, 108mm, 114.3mm, 133mm, 139.7mm, 141.3mm, 159mm, 168.3mm	2516
101T	Rolled	ISO 4200 D	108mm, 114.3mm, 133mm, 139.7mm, 141.3mm, 159mm, 168.3mm	2516
101T	Rolled	ISO 4200 E	60.3mm, 73mm, 76.1mm, 88.9mm, 108mm, 114.3mm, 133mm, 139.7mm, 141.3mm, 159mm, 168.3mm	2516
101T	Rolled, cut	ISO 4200 F	33.7mm, 42.4mm, 48.3mm	3102
101T	Rolled, cut	ISO 4200 F	60.3mm, 73mm, 76.1mm, 88.9mm, 108mm, 114.3mm, 133mm, 139.7mm, 141.3mm, 159mm, 168.3mm	2516
101T	Cut	ISO 4200 G	33.7mm, 42.4mm, 48.3mm	3102
101T	Cut	ISO 4200 G	60.3mm, 73mm, 76.1mm, 88.9mm, 108mm, 114.3mm, 133mm, 139.7mm, 141.3mm, 159mm, 168.3mm	2516
101T	Rolled	T3091	165.1mm	2516

XGQT31	Rolled	5	1, 1-1/4, 1-1/2, 2	2070
XGQT31	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
XGQT31	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT31	Rolled	10	4, 5, 6, 8, 10	2070
XGQT31	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT31	Rolled, Cut	40	4, 5, 6, 8, 10, 12	2070
XGQT31	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	2070
XGQT31	Rolled, Cut	JIS G3452	216 mm	2070
XGQT31X	Roll	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
XGQT31X	Roll&cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	2070
XGQT31X	Roll	ISO4200 D	114.3mm, 139.7mm, 141.3mm, 159mm, 168.3mm, 219.1mm	2070
XGQT31X	Roll	EN10220	114.3mm, 139.7mm, 141.3mm, 159mm, 168.3mm, 219.1mm	2070
XGQT31X	Roll	ISO4200 E	60.3mm(2.9mm), 73.0mm(2.9mm), 76.1mm(2.9mm), 88.9mm(3.2mm), 108mm(3.6mm), 114.3mm(3.6mm), 139.7mm(4.0mm), 141.3mm(4.0mm), 159mm(4.5mm), 168.3mm(4.5mm), 219.1mm(6.3mm))	2070
XGQT31X	Roll	EN10220	60.3mm(2.9mm), 73.0mm(2.9mm), 76.1mm(2.9mm), 88.9mm(3.2mm), 108mm(3.6mm), 114.3mm(3.6mm), 139.7mm(4.0mm), 141.3mm(4.0mm), 159mm(4.5mm), 168.3mm(4.5mm), 219.1mm(6.3mm)	2070
XGQT31X	Roll&cut	ISO4200 F	33.7mm(3.2mm), 42.4mm(3.6mm), 48.3mm(3.6mm), 60.3mm(4.0mm), 73.0mm, 76.1mm(5.0mm), 88.9 mm(5.6mm), 108mm(6.3mm), 114.3mm(6.3mm), 139.7mm(6.3mm), 141.3mm(6.3mm), 159mm(7.1mm), 168.3mm(7.1mm), 219.1mm(8.0mm)	2070
XGQT31X	Roll&cut	EN10220	33.7mm(3.2mm), 42.4mm(3.6mm), 48.3mm(3.6mm), 60.3mm(4.0mm), 73.0mm, 76.1mm(5.0mm), 88.9 mm(5.6mm), 108mm(6.3mm), 114.3mm(6.3mm), 139.7mm(6.3mm), 141.3mm(6.3mm), 159mm(7.1mm), 168.3mm(7.1mm), 219.1mm(8.0mm)	2070
XGQT31X	Cut	ISO4200 G	33.7mm(4.5mm), 42.4mm(5.0mm), 48.3mm(5.0mm), 60.3mm(5.6mm), 73.0mm(7.1mm), 76.1mm(7.1mm), 88.9mm(8.0mm), 108mm(8.8mm), 114.3mm(8.8mm), 139.7mm(10.0mm), 141.3mm(10.0mm), 159mm(11.0mm), 168.3mm(11.0mm), 219.1mm(12.5mm)	2070
XGQT31X	Cut	EN10220	33.7mm(4.5mm), 42.4mm(5.0mm), 48.3mm(5.0mm), 60.3mm(5.6mm), 73.0mm(7.1mm), 76.1mm(7.1mm), 88.9mm(8.0mm), 108mm(8.8mm), 114.3mm(8.8mm), 139.7mm(10.0mm), 141.3mm(10.0mm), 159mm(11.0mm), 168.3mm(11.0mm), 219.1mm(12.5mm)	2070

XGQT31X	Roll	EN10217-1	33.7mm(2.6mm), 42.4mm(2.6mm), 48.3mm(2.6mm), 60.3mm(2.6mm), 73mm, 76.1mm(2.9mm), 88.9mm(2.9mm), 108mm(3.2mm), 114.3mm(3.2mm), 139.7mm(3.6mm), 141.3mm(3.6mm), 159mm(4.0mm), 168.3mm(4.0mm), 219.1mm(4.5mm)	2070
---------	------	-----------	--	------

			88.9 mm(2.9mm), 108mm(3.2mm), 114.3mm(3.2mm), 139.7mm(3.6mm), 141.3mm(3.6mm), 159mm(4.0mm), 168.3mm(4.0mm), 219.1mm(4.5mm)	
XGQT31X	Roll	EN10220	33.7mm(2.6mm), 42.4mm(2.6mm), 48.3mm(2.6mm), 60.3mm(2.6mm), 73mm, 76.1mm(2.9mm), 88.9 mm(2.9mm), 108mm(3.2mm), 114.3mm(3.2mm), 139.7mm(3.6mm), 141.3mm(3.6mm), 159mm(4.0mm), 168.3mm(4.0mm), 219.1mm(4.5mm)	2070
XGQT31X	Roll&cut	T17395	108mm(3.2mm), 159mm(4.0mm)	2070
XGQT31X	Roll&cut	T3091	76.1mm, 139.7mm, 165.1mm	2070
XGQT01P	Rolled	10	5	3448
XGQT01P	Rolled, Cut	40	5	3448
XGQT01P	Rolled	10	6, 8	3103
XGQT01P	Rolled, Cut	40	6, 8	3103
XGQT01P	Rolled	10	10, 12	2758
XGQT01P	Rolled, Cut	40	10, 12	2758
XGQT01P	Rolled, Cut	T3091	5-1/2OD	3448
XGQT01P	Rolled, Cut	T3091	6-1/2OD	3103
XGQT35	Rolled	5	2	2070
XGQT35	Rolled	10	2, 2-1/2, 3	2760
XGQT35	Rolled	10	4, 5, 6	2070
XGQT35	Rolled, Cut	40	2, 2-1/2, 3	2760
XGQT35	Rolled, Cut	40	4, 5, 6	2070
XGQT35	Rolled	GB/T 3091	2, 2-1/2, 3	2760
XGQT35	Rolled	GB/T 3091	4, 6-1/2OD	2070
XGQT35	Rolled	WGalweld 7	2, 2-1/2, 3, 4	2070
XGQT35	Rolled, Cut	GB/T 17395	5-1/2OD/4.5mm	2070
XGQT35	Rolled, Cut	GB/T 17395	3OD/4mm	2760
XGQT35	Rolled	GB/T 21835	6/4.5mm	2070
31A	Rolled	5	1-1/4, 1-1/2, 2	2070
31A	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2760
31A	Rolled	10	5, 6, 8, 10	2070
31A	Rolled Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2760
Rolled	Rolled Cut	40	5, 6, 8, 10, 12	2070
31A	Rolled	GB/T 3091	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2760

31A	Rolled	GB/T 3091	5-1/2OD, 6-1/2OD, 8	2070
-----	--------	-----------	---------------------	------

31A	Rolled	WGalweld /	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
31A	Rolled Cut	GB/T 17395	3OD/4mm, 4-1/4OD/4mm, 5-1/2OD/4.5mm, 6-1/4OD/5mm	2070
31A	Rolled Cut	JIS G3452	216.3mm, 267.4mm	2070
31A	Rolled	GB/T 21835	6/4.5mm, 10/6.3mm, 12/7.1mm	2070
31A	Roll	5	1	1206
31A	Roll	ISO4200 D	33.7mm(2.0mm)	1206
31A	Roll	EN10220	33.7mm(2.0mm)	1206
31A	Roll	ISO4200 E	33.7mm(2.3mm)	1206
31A	Roll	EN10220	33.7mm(2.3mm)	1206
31A	Roll&cut	ISO4200 F	33.7mm(3.2mm)	2760
31A	Roll&cut	EN10220	33.7mm(3.2mm)	2760
31A	Roll&cut	ISO4200 G	33.7mm(4.5mm)	2760
31A	Roll&cut	EN10220	33.7mm(4.5mm)	2760

Flexible coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (kPa)
XGQT02	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	2760
XGQT02	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	2070
XGQT02	Rolled	T3091-1993	6-1/2 OD	2070
XGQT02	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	2760
XGQT02	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	2070
XGQT02	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
XGQT02	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT02	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT02	Rolled	10	4	2760
XGQT02	Rolled, Cut	40	4	2760
XGQT02	Rolled	10	5, 6, 8, 10, 12	2070
XGQT02	Rolled, Cut	40	5, 6, 8, 10, 12	2070
XGQT32	Rolled	5	1, 1-1/4, 1-1/2, 2	2070
XGQT32	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	2070
XGQT32	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT32	Rolled	10	4, 5, 6, 8, 10	2070
XGQT32	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	3450
XGQT32	Rolled, Cut	40	4, 5, 6, 8, 10, 12	2070

XGQT32	Rolled, Cut	40	4, 5, 6, 8, 10, 12	2070
XGQT32	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	2070
XGQT32	Rolled, Cut	JIS G3452	216 mm, 267 mm, 318 mm	2070
XGQT02K	Rolled	10	2, 3, 4, 6	3450
XGQT02K	Rolled	10	8	2760
XGQT02K	Rolled	40	2, 3, 4, 6	3450
XGQT02K	Rolled	40	8, 10, 12	2760
XGQT02P	Rolled	10	5	3448
XGQT02P	Rolled, Cut	40	5	3448
XGQT02P	Rolled	10	6, 8	3103
XGQT02P	Rolled, Cut	40	6, 8	3103
XGQT02P	Rolled	10	10, 12	2758
XGQT02P	Rolled, Cut	40	10, 12	2758
XGQT02P	Rolled, Cut	T3091	5-1/2OD	3448
XGQT02P	Rolled, Cut	T3091	6-1/2OD	3103

Reducing Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (kPa)
XGQT02B	Rolled	T3091	2x1-1/2, 3 ODx1-1/2, 3 ODx2, 3x1-1/2, 3x2, 3x3 OD, 4x1-1/2, 4x2, 4x3 OD, 4x3, 6x3, 6x4, 8 / 6 mm x6	2070
XGQT02B	Rolled	T17395xT3091	2-1/2 / 4 mm x1-1/2, 2-1/2 / 4 mm x2	2070
XGQT02B	Rolled	T3091xT17395	3x2-1/2 / 4 mm, 4x2-1/2 / 4 mm	2070
XGQT02B	Rolled, Cut	T3091	3ODx2-1/2	2068
XGQT02B	Rolled	10	1-1/2x1-1/4; 2x1-1/2; 2-1/2x1-1/2, 2; 3x1-1/2, 2, 2-1/2; 4x1-1/2, 2, 2-1/2, 3	2068
XGQT02B	Rolled, Cut	40	1-1/2x1-1/4; 2x1-1/2; 2-1/2x1-1/2, 2; 3x1-1/2, 2, 2-1/2; 4x1-1/2, 2, 2-1/2, 3	2068

Flange adapter

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (kPa)
XGQT19	Rolled	T3091	2, 3 OD, 3, 4, 5-1/2OD, 6, 8 / 6 mm	2070
XGQT19	Rolled	T3091-1993	6-1/2 OD	2070

XGQT19	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm, 5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 / 6 mm	2070
XGQT19	Roll	10	10	1206
XGQT19	Roll	40	10	1206
XGQT19	Roll	ISO4200 D	273mm(5mm)	1206
XGQT19	Roll	EN10220	273mm(5mm)	1206
XGQT19	Roll	ISO4200 E	273mm(6.3mm)	1206
XGQT19	Roll	EN10220	273mm(6.3mm)	1206
XGQT19	Roll	ISO4200 F	273mm(10mm)	1206
XGQT19	Roll	EN10220	273mm(10mm)	1206
XGQT19	Roll	ISO4200 G	273mm(14.2mm)	1206
XGQT19	Roll	EN10220	273mm(14.2mm)	1206
XGQT19	Roll	EN10217-1	273mm(5mm)	1206
XGQT29	Rolled	10, 40	2, 2-1/2, 3, 4, 5, 6, 8	2070
XGQT29	Rolled	10, 40	10	1206

Side outlet

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (kPa)
XGQT03	Rolled	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2	2070
XGQT03	Rolled	T3091	5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	2070
XGQT03	Grooved	10, 40	2-1/2 x 1; 4 x 2-1/2, 3OD, 3	2070
XGQT03	Grooved	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3; 6-1/2OD x 4	2070
XGQT03S	Threaded	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2, 5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	2070
XGQT03S	Threaded	10, 40	2-1/2 x 1-1/4; 4 x 2-1/2, 3OD, 3	2070
XGQT03S	Threaded	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3	2070

XGQT03U	Threaded	T3091	1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/2x1/2, 1-1/2x3/4, 2x1/2, 2x3/4, 3 ODx1/2, 3 ODx3/4, 3 ODx1-1/4	2070
---------	----------	-------	--	------

XGQT03U	Threaded	T17395	2-1/2 / 4 mm x1/2, 2-1/2 / 4 mm x3/4	2070
XGQT03U	Threaded	10, 40	1-1/4x1; 1-1/2x1; 2x1; 2-1/2x1, 1-1/4; 3x1/2, 3/4, 1, 1-1/4; 4x1/2, 3/4, 1, 1-1/4	2070
XGQT03U	Threaded	ISO 4200 F	42.4mmx33.7mm;48.3mmx33.7mm	2070
XGQT03U	Threaded	ISO 4200 E	60.3mmx33.7mm;73mmx33.7mm;76.1mm x 33.7mm	2070
XGQT33	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2; 8 x 2, 2-1/2	2070
XGQT33S	Threaded	10, 40	2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1, 1-1/4, 1-1/2, 2, 2-1/2; 6 x 1- 1/4, 1-1/2, 2, 2-1/2	2070

All fitting models are suitable for use in dry pipe systems for temperatures to -40° F except for fitting models XGQT01H, XGQT02H, XGQT02D, SS01, SS02, 101T.

Models XGQT03S in the 2x1, 3 ODx1, 3x1, 4x1, 5x1 in. sizes are intended for direct connection to sprinklers.

Models XGQT03U and XGQT33S in the 1/2, 3/4 in. nominal outlet, and 2x1, 3 ODx1 in. sizes are intended for direct connection to sprinklers.

Models XGQT03, XGQT03S, XGQT03U, XGQT33 and XGQT33S in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Note:

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

T3091 refers to GB/T3091 ordinary steel pipe.

T3091-1993 refers to GB/T3091-1993 ordinary steel pipe.

GB/T 3091 refers to GB/T3091 ordinary steel pipe.

GB/T 17395 refers to GB/T 17395 steel ordinary pipe.

GB/T 21835 refers to GB/T 21835 ordinary steel pipe.

T17395 refers to GB/T17395 steel ordinary pipe

5 refers to ASME B36.10M ordinary steel pipe.

WGalweld 7 refers to Wuppermann Stahl GmbH, model WGalweld 7 (Galvanized) pipe, file number EX16421.

JIS G3452 refers to JIS G3452-2014 ordinary steel pipe.

3507-SPP refers to steel pipe manufactured in accordance with KS D 3507, grade SPP.

3562-20 refers to steel pipe manufactured in accordance with KS D 3562, Schedule 20.

3562-30 refers to steel pipe manufactured in accordance with KS D 3562, Schedule 30.

3562-40 refers to steel pipe manufactured in accordance with KS D 3562, Schedule 40.

3576-10S refers to steel pipe manufactured in accordance with KS D 3576, Schedule 10s.

3576-20S refers to steel pipe manufactured in accordance with KS D 3576, Schedule 20S.

3588-10S refers to steel pipe manufactured in accordance with KS D 3588, Schedule 10S.

3588-20S refers to steel pipe manufactured in accordance with KS D 3588, Schedule 20S.

EN10217-1 refers to steel pipe manufactured in accordance with DIN EN10217-1.

ISO 4200 D refers to Type D wall thickness pipe manufactured in accordance with ISO 4200.

ISO 4200 E refers to Type E wall thickness pipe manufactured in accordance with ISO 4200.

ISO 4200 F refers to Type F wall thickness pipe manufactured in accordance with ISO 4200.

ISO 4200 G refers to Type G wall thickness pipe manufactured in accordance with ISO 4200.

EN 10220 refers to steel pipe manufactured in accordance with EN10220

Trademark and/or Tradename:  ,  , 

Last Updated on 2022-12-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."