

Pipe Fittings

Product Description

<i>Model Designation</i>	<i>Fitting Description</i>	<i>Nominal Pipe Size, (inch)</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>Remarks</i>
XGQT03	90 Degree Elbow	60.3, 76.1, 88.9, 108, 114.3, 133, 139.7, 159, 165.1, 219.1	363 (2505)	d
XGQT04	45 Degree Elbow	60.3, 76.1, 88.9, 114.3, 139.7, 159, 165.1, 219.1	363 (2505)	d
XGQT07	Equal Tee	60.3, 76.1, 88.9, 108, 114.3, 139.7, 159, 165.1, 219.1	363 (2505)	d
XGQT08	Grooved Reducing Tee	88.9 x 60.3, 76.1 114.3 x 48.3, 60.3, 76.1, 88.9 139.7 x 76.1, 88.9, 114.3 159 x 114.3 165.1 x 76.1, 88.9, 114.3, 139.7 219.1 x 76.1, 88.9, 114.3, 159, 165.1	363 (2505)	d
XGQT08S	Threaded Reducing Tee	76.1 x 42.4, 48.3, 60.3 88.9 x 42.4, 48.3, 60.3, 76.1 114.3 x 42.4, 48.3, 60.3, 88.9 139.7 x 76.1, 88.9 165.1 x 48.3, 60.3, 76.1, 88.9, 114.3 219.1 x 76.1, 88.9	363 (2505)	a, b, c
XGQT09	Equal Cross	60.3, 76.1, 88.9, 114.3, 139.7, 165.1, 219.1	363 (2505)	d
XGQT16	End Cap	76.1, 88.9, 114.3, 139.7, 165.1, 219.1	363 (2505)	d
XGQT11	Concentric Reducer (Grooved Outlet)	60.3 x 48.3 76.1 x 33.7, 60.3 88.9 x 42.4, 60.3, 76.1 114.3 x 60.3, 76.1, 88.9 139.7 x 76.1, 88.9, 114.3 165.1 x 76.1, 88.9, 114.3, 139.7 219.1 x 76.1, 88.9, 114.3, 165.1	363 (2505)	d

XGQT11S	Concentric Reducer (Threaded Outlet)	60.3 x 42.4, 48.3 76.1 x 33.7, 42.4, 48.3, 60.3 88.9 x 33.7, 42.4, 48.3, 60.3, 76.1 114.3 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 165.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9, 114.3 219.1 x 76.1, 88.9	363 (2505)	a, b, c
XGQT05	22-1/2 Degree Elbow	114.3, 165.1, 219.1	363 (2505)	d
XGQT06	11-1/4 Degree Elbow	114.3, 165.1	363 (2505)	d
XGQT10	Grooved Reducing Cross	88.9 x 76.1 114.3 x 76.1, 88.9 165.1 x 76.1, 88.9, 114.3 219.1 x 114.3, 165.1	363 (2505)	d
XGQT10S	Threaded Reducing Cross	88.9 x 42.4, 48.3, 60.3, 76.1 114.3 x 48.3, 60.3, 76.1, 88.9 165.1 x 60.3, 76.1, 88.9, 114.3	363 (2505)	a, b, c
XGQT13 (1.6 MPa)	Flange Adapter (Grooved Outlet)	76.1, 108.0, 114.3, 133.0, 139.7, 159.0, 165.1, 216.3, 219.1	232 (1600)	e
XGQT13 (2.5 MPa)	Flange Adapter (Grooved Outlet)	60.3, 76.1, 88.9, 108.0, 114.3, 133.0, 139.7, 159.0, 165.1, 216.3, 219.1	363 (2500)	f

Remarks:

a. Threads per ANSI B1.20.1 - 1983

b. Threads per ISO 7-1

c. Threaded per DIN 2999

d. Available with Cut Grooves

e. PN16 flange per ISO 7005-1

f. PN25 flange per ISO 7005-1

Product Designation	Fitting Description	Nominal Pipe Size, DN	Rated Working Pressure, psi (kPa)	Remarks
90	90° Elbow	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c
90R	90° Reducing Elbow	20 x 15 25 x 15, 20 32 x 15, 20, 25 40 x 15, 20, 25, 32 50 x 15, 20, 25, 32, 40 65 x 15, 20, 25, 32, 40, 50 80 x 15, 20, 25, 32, 40, 50, 65 100 x 15, 20, 25, 32, 40, 50, 65, 80	175 (1205)	a, b, c
130	Equal Tee	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c

130R	Reducing Tee (Threaded Outlet)	20 x 15 25 x 15, 20 32 x 15, 20, 25 40 x 15, 20, 25, 32 50 x 15, 20, 25, 32, 40 65 x 15, 20, 25, 32, 40, 50 80 x 15, 20, 25, 32, 40, 50, 65 100 x 15, 20, 25, 32, 40, 50, 65, 80	175 (1205)	a, b, c
180	Equal Cross	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c
180R	Reducing Cross (Threaded Outlet)	20 x 15 25 x 15, 20 32 x 15, 20, 25 40 x 15, 20, 25, 32 50 x 15, 20, 25, 32, 40 65 x 15, 20, 25, 32, 40, 50 80 x 15, 20, 25, 32, 40, 50, 65 100 x 15, 20, 25, 32, 40, 50, 65, 80	175 (1205)	a, b, c
240	Concentric Reducer (Threaded Outlet)	20 x 15 25 x 15, 20 32 x 15, 20, 25 40 x 15, 20, 25, 32 50 x 15, 20, 25, 32, 40 65 x 15, 20, 25, 32, 40, 50 80 x 15, 20, 25, 32, 40, 50, 65 100 x 15, 20, 25, 32, 40, 50, 65, 80	175 (1205)	a, b, c
241	Bushing	20 x 15 25 x 15, 20 32 x 15, 20, 25 40 x 15, 20, 25, 32 50 x 15, 20, 25, 32, 40 65 x 15, 20, 25, 32, 40, 50 80 x 15, 20, 25, 32, 40, 50, 65 100 x 15, 20, 25, 32, 40, 50, 65, 80	175 (1205)	a, b, c
270	Straight Coupling	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c
280	Pipe Nipple	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c
291	Plug	15, 20, 25, 32, 40, 50, 65, 80, 100	175 (1205)	a, b, c

Remarks:

a. For use with NPT Threaded End Connections

b. For use with a Galvanized Finish

c. For use with a Black Painted Finish

Details

Category	Pipe Fittings
Class of Work	1920 - Coupling & Fitting, All Type

Company

Hebei Jianzhi Casting Group Co Ltd

Pang Zhuang Zi, Southeast of Yutian County, Tangshan City, Hebei Province 064100, China

China

Approval Standard FM 1920 - Pipe Couplings and Fittings for Aboveground Fire Protection Systems

Certification Type FM Approved

Listing Country China

<http://en.jianzhi-fitting.com>